

TYPE	M-NO.	GRINNELL FIG. NO.	PIPE SIZE RANGE	MAX. TEMP.(?F)	MAX.INSU. TH'K (IN)	REMARKS
FIG.-A	M-31	60				
FIG.-C	M-28	66		750		
FIG.-D	M-28	66		750		
FIG.-E	M-3	260	1/2"-30"	650		
FIG.-G	M-4	212	1/2"-24"	750		
FIG.-H	M-5	216	3"-42"	750		LOAD CAPACITY GREATER THAN FIG-G
FIG.-J	M-6	295	3/4"-24"	750	4	
FIG.-K	M-7	295H	6"-36"	750	4	LOAD CAPACITY GREATER THAN FIG-J
FIG.-L	M-8	295A	1 1/2"-10"	1050	4	
FIG.-M	M-9	224	4"-16"	1050	4	LOAD CAPACITY GREATER THAN FIG-L
FIG.-N	M-10	246	10"-24"	1075	6	LOAD CAPACITY GREATER THAN FIG-M
FIG.-Q	M-24	299	2"-24"	750		

NOTES :

1. DESIGNATION NUMBER DENOTE AS FOLLOWS :
62-4B- 5/8 -05 ~ 30D-J(T)
DENOTE TYPE NO. 
2. FOR WELDING SIZE, SEE M-28.
3. TURNBUCKLE SHALL BE USED IN ONE OF THE FOLLOWING CASES :
(a) DIM. "H" LARGER THAN 2000 MM
(b) THE UPPER PART FIG. -D IS IN HANGER COMBINATION.
4. IF FIG.-D IS CHOSEN COMBINATION WITHOUT TURNBUCKLE , A LEFT-HAND
THREADED WELDLESS EYE NUT SHALL BE USED.

中威工程顧問股份有限公司 CHUNG WEI ENGINEERING CONSULTING CO., LTD.						ENGINEERING STANDARD	
						HP6-DSD-A4-500-001	
BY	SHIH		CHK.	YANG		D-76	REV.
DATE	7/15/'24		APPR.	CHEN			1

DETAIL OF PIPE SUPPORT
TYPE-62
(2 OF 2)