

FOR STAINLESS STEEL

TEMP. °F

| CORRECTION FACTORS |       |       |       |       |       |       |       |       |       |       |       |
|--------------------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| TEMP.              | TP304 | TP316 | TP347 | TEMP. | TP304 | TP316 | TP347 | TEMP. | TP304 | TP316 | TP347 |
| -325 TO            |       |       |       | 750   | 1.60  | 0.99  | 1.13  | 1150  | 2.90  | 1.96  | 2.08  |
| 200                | 1.00  | 0.89  | 0.89  | 800   | 1.67  | 0.99  | 1.14  | 1200  | 3.70  | 2.45  | 3.33  |
| 300                | 1.11  | 0.93  | 0.98  | 850   | 1.72  | 1.01  | 1.16  | 1250  | 5.12  | 3.14  | 4.63  |
| 400                | 1.22  | 0.95  | 1.05  | 900   | 1.77  | 1.04  | 1.18  | 1300  | 6.80  | 4.16  | 6.17  |
| 500                | 1.33  | 0.97  | 1.10  | 950   | 1.83  | 1.10  | 1.20  | 1350  | 9.25  | 5.55  | 8.32  |
| 600                | 1.44  | 0.97  | 1.12  | 1000  | 1.89  | 1.19  | 1.23  | 1400  | 11.89 | 7.09  | 10.74 |
| 650                | 1.49  | 0.98  | 1.12  | 1050  | 1.96  | 1.36  | 1.27  | 1450  | 16.65 | 9.00  | 13.88 |
| 700                | 1.54  | 0.98  | 1.13  | 1100  | 2.22  | 1.60  | 1.33  | 1500  | 22.20 | 11.10 | 16.65 |

DIMENSION (mm)

| Y                                            |           | TRUNNION – NOMINAL PIPE SIZE |     |        |     |        |     |        |     |        |     |        |     |        |     |        |     | PAD TH'K MIN. "E" |     | DIM. "D" |  |
|----------------------------------------------|-----------|------------------------------|-----|--------|-----|--------|-----|--------|-----|--------|-----|--------|-----|--------|-----|--------|-----|-------------------|-----|----------|--|
|                                              |           | 2"                           |     | 3"     |     | 4"     |     | 6"     |     | 8"     |     | 10"    |     | 12"    |     | 14"    |     |                   |     |          |  |
|                                              |           | MIN. SCH. SAME AS HEADER     |     |        |     |        |     |        |     |        |     |        |     |        |     |        |     |                   |     |          |  |
|                                              |           | PAD REQUIREMENTS             |     |        |     |        |     |        |     |        |     |        |     |        |     |        |     |                   |     |          |  |
| NOM. PIPE SIZE                               | PIPE SCH. | NO PAD                       | PAD | NO PAD | PAD | NO PAD | PAD | NO PAD | PAD | NO PAD | PAD | NO PAD | PAD | NO PAD | PAD | NO PAD | PAD |                   |     |          |  |
| MOMENT CAPACITY OF ONE TRUNNION. (INCH–KIPS) |           |                              |     |        |     |        |     |        |     |        |     |        |     |        |     |        |     |                   |     |          |  |
| 3"                                           | 5S        | 1                            | 3   |        |     |        |     |        |     |        |     |        |     |        |     |        |     | 2.0               | 30  |          |  |
| 4"                                           | 5S        | 1                            | 2   | 2      | 5   |        |     |        |     |        |     |        |     |        |     |        |     | 2.0               | 40  |          |  |
| 6"                                           | 5S        | 1                            | 3   | 2      | 6   | 4      | 10  |        |     |        |     |        |     |        |     |        |     | 3.0               | 45  |          |  |
| 8"                                           | 5S        | 1                            | 3   | 2      | 5   | 3      | 9   | 7      | 20  |        |     |        |     |        |     |        |     | 3.0               | 60  |          |  |
| 10"                                          | 5S        |                              |     | 2      | 7   | 4      | 11  | 8      | 24  | 14     | 41  |        |     |        |     |        |     | 3.5               | 65  |          |  |
| 12"                                          | 5S        |                              |     | 2      | 8   | 5      | 14  | 11     | 30  | 18     | 51  | 28     | 79  |        |     |        |     | 4.0               | 75  |          |  |
| 14"                                          | 5S        |                              |     |        |     | 4      | 12  | 9      | 26  | 16     | 45  | 25     | 70  | 35     | 98  |        |     | 4.0               | 75  |          |  |
| 16"                                          | 5S        |                              |     |        |     | 4      | 12  | 10     | 27  | 16     | 46  | 25     | 71  | 35     | 100 | 42     | 120 | 4.0               | 85  |          |  |
| 18"                                          | 5S        |                              |     |        |     |        |     | 9      | 25  | 15     | 43  | 24     | 67  | 33     | 94  | 40     | 113 | 4.0               | 90  |          |  |
| 20"                                          | 5S        |                              |     |        |     |        |     | 10     | 29  | 18     | 50  | 27     | 77  | 39     | 108 | 47     | 131 | 5.0               | 100 |          |  |
| 24"                                          | 5S        |                              |     |        |     |        |     | 12     | 33  | 20     | 57  | 31     | 88  | 44     | 124 | 53     | 149 | 5.5               | 120 |          |  |
| 30"                                          | 5S        |                              |     |        |     |        |     |        |     | 22     | 62  | 34     | 97  | 48     | 136 | 58     | 164 | 6.5               | 145 |          |  |
| 3"                                           | 10S       | 2                            | 5   |        |     |        |     |        |     |        |     |        |     |        |     |        |     | 3.0               | 30  |          |  |
| 4"                                           | 10S       | 1                            | 4   | 3      | 9   |        |     |        |     |        |     |        |     |        |     |        |     | 3.0               | 40  |          |  |
| 6"                                           | 10S       | 1                            | 4   | 3      | 9   | 5      | 14  |        |     |        |     |        |     |        |     |        |     | 3.5               | 45  |          |  |
| 8"                                           | 10S       | 1                            | 4   | 3      | 9   | 5      | 14  | 11     | 31  |        |     |        |     |        |     |        |     | 4.0               | 60  |          |  |
| 10"                                          | 10S       |                              |     | 3      | 9   | 5      | 15  | 12     | 33  | 20     | 55  |        |     |        |     |        |     | 4.0               | 65  |          |  |
| 12"                                          | 10S       |                              |     | 3      | 10  | 6      | 16  | 12     | 34  | 21     | 58  | 32     | 90  |        |     |        |     | 4.5               | 75  |          |  |
| 14"                                          | 10S       |                              |     |        |     | 6      | 16  | 12     | 35  | 21     | 59  | 33     | 92  | 46     | 130 |        |     | 5.0               | 75  |          |  |
| 16"                                          | 10S       |                              |     |        |     | 5      | 15  | 12     | 33  | 20     | 55  | 30     | 86  | 43     | 121 | 52     | 146 | 5.0               | 85  |          |  |
| 18"                                          | 10S       |                              |     |        |     |        |     | 11     | 31  | 18     | 52  | 29     | 81  | 40     | 114 | 49     | 138 | 5.0               | 90  |          |  |
| 20"                                          | 10S       |                              |     |        |     |        |     | 13     | 37  | 22     | 62  | 34     | 96  | 48     | 135 | 58     | 163 | 5.5               | 100 |          |  |
| 24"                                          | 10S       |                              |     |        |     |        |     | 14     | 41  | 25     | 70  | 38     | 108 | 54     | 152 | 65     | 183 | 6.5               | 120 |          |  |
| 30"                                          | 10S       |                              |     |        |     |        |     |        |     | 31     | 87  | 48     | 135 | 67     | 189 | 81     | 228 | 8.0               | 145 |          |  |



中鼎工程股份有限公司

CTCI CORPORATION

DETAIL OF PIPE SUPPORT

TYPE-61

(3 OF 3)

ENGINEERING STANDARD

D7TS-701-E

D-74

REV.  
1

BY

CHK.

DATE

APPR.