

DIMENSION (mm)

MEMBER "M"	H (MAX.)	$\theta = 30^\circ$			$\theta = 45^\circ$		
		B	S	N	B	S	N
L75X75X9	950	135	$0.577H-8$	$1.155H + 92$	115	$H - 30$	$1.414H + 57$
C100X50X5	950	145	$0.577H-7$	$1.155H + 100$	120	$H - 31$	$1.414H + 55$
C125X65X6	1750	145	$0.577H+4$	$1.155H + 114$	130	$H - 33$	$1.414H + 41$
C150X75X9	1750	165	$0.577H+3$	$1.155H + 125$	140	$H - 36$	$1.414H + 47$
C180X75X7	1750	185	$0.577H+7$	$1.155H + 145$	150	$H - 32$	$1.414H + 60$
C200X90X8	1750	195	$0.577H+9$	$1.155H + 155$	160	$H - 36$	$1.414H + 56$

NOTES:

1. DESIGNATION NUMBER DENOTE AS FOLLOWS :

43-2B-L75-520A OR B-175

_____ MODIFY DIMENSION "Q" (IN mm) IF ANY
 _____ SEE NOTE 4
 _____ DENOTE DIMENSION "H" (IN mm)
 _____ DENOTE MEMBER "M"
 _____ DENOTE SUPPORTED LINE SIZE "N"
 _____ DENOTE TYPE NO.

2. THE TRUNNION SIZE MUST BE CHECKED BY SH'T D-72,73 & 74.

3. WHERE
- $H = K - \sqrt{R^2 - Q^2} - t - E - 30$

4. A: FOR
- $\theta = 30^\circ$
- , B: FOR
- $\theta = 45^\circ$

D-052M.DWG



中鼎工程股份有限公司
俊鼎機械廠股份有限公司

DETAIL OF PIPE SUPPORT

TYPE-43

(2 OF 2)

ENGINEERING STANDARD

STM-05.01

BY

CHK.

DATE

APPR.

D-52

REV.
1