

CORRECTION FACTORS											
TEMP. °C	TP304	TP316	TP347	TEMP. °C	TP304	TP316	TP347	TEMP. °C	TP304	TP316	TP347
-325 TO 93	1.00	0.89	0.89	399	1.60	0.99	1.13	621	2.90	1.96	2.08
				427	1.67	0.99	1.14	649	3.70	2.45	3.33
150	1.11	0.93	0.98	454	1.72	1.01	1.16	677	5.12	3.14	4.63
205	1.22	0.95	1.05	482	1.77	1.04	1.18	704	6.80	4.16	6.17
260	1.33	0.97	1.10	510	1.83	1.10	1.20	732	9.25	5.55	8.32
315	1.44	0.97	1.12	538	1.89	1.19	1.23	760	11.89	7.09	10.74
340	1.49	0.98	1.12	566	1.96	1.36	1.27	788	16.65	9.00	13.88
370	1.54	0.98	1.13	593	2.22	1.60	1.33	816	22.20	11.10	16.65

DIMENSION (mm), TABLE BELOW: 1 INCH-KIPS = 113 N-M

		TRUNNION — NOMINAL PIPE SIZE																PAD TH'K MIN. "E"		DIM. "D" mm
		2"		3"		4"		6"		8"		10"		12"		14"				
		MIN. SCH. SAME AS HEADER																		
Y		80		110		140		190		240		290		340		380				
NOM. PIPE SIZE	PIPE SCH.	PAD REQUIREMENTS																TH'K MIN.	DIM. "D" mm	
		NO PAD	PAD	NO PAD	PAD	NO PAD	PAD	NO PAD	PAD	NO PAD	PAD	NO PAD	PAD	NO PAD	PAD	NO PAD	PAD			
		MOMENT CAPACITY OF ONE TRUNNION. (INCH—KIPS)																		
3"	5S	1	3															2.0	30	
4"	5S	1	2	2	5													2.0	40	
6"	5S	1	3	2	6	4	10											3.0	45	
8"	5S	1	3	2	5	3	9	7	20									3.0	60	
10"	5S			2	7	4	11	8	24	14	41							3.5	65	
12"	5S			2	8	5	14	11	30	18	51	28	79					4.0	75	
14"	5S					4	12	9	26	16	45	25	70	35	98			4.0	75	
16"	5S					4	12	10	27	16	46	25	71	35	100	42	120	4.0	85	
18"	5S							9	25	15	43	24	67	33	94	40	113	4.0	90	
20"	5S							10	29	18	50	27	77	39	108	47	131	5.0	100	
24"	5S							12	33	20	57	31	88	44	124	53	149	5.5	120	
30"	5S									22	62	34	97	48	136	58	164	6.5	145	
3"	10S	2	5															3.0	30	
4"	10S	1	4	3	9													3.0	40	
6"	10S	1	4	3	9	5	14											3.5	45	
8"	10S	1	4	3	9	5	14	11	31									4.0	60	
10"	10S			3	9	5	15	12	33	20	55							4.0	65	
12"	10S			3	10	6	16	12	34	21	58	32	90					4.5	75	
14"	10S					6	16	12	35	21	59	33	92	46	130			5.0	75	
16"	10S					5	15	12	33	20	55	30	86	43	121	52	146	5.0	85	
18"	10S							11	31	18	52	29	81	40	114	49	138	5.0	90	
20"	10S							13	37	22	62	34	96	48	135	58	163	5.5	100	
24"	10S							14	41	25	70	38	108	54	152	65	183	6.5	120	
30"	10S									31	87	48	135	67	189	81	228	8.0	145	



中鼎工程股份有限公司
俊鼎機械廠股份有限公司

DETAIL OF PIPE SUPPORT

TYPE-61

(3 OF 3)

ENGINEERING STANDARD

STM-05.01

D-74

REV.
1

D-074M.DWG

BY

CHK.

DATE

APPR.