

Technical drawing of a steel beam-to-column connection. The beam is labeled "型鋼" (Steel). The column is labeled "1". The beam has a height of 5 and a width of 250. The column has a diameter of 5. The connection is shown in a side view with a cross-section of the column.

型鋼或水泥柱(樑)

50
50
75

100

5

250

2-φ13 鑽孔

配 (2) 或 (3)

1



件號	名 稱	規 格	材 質	數量	備 註
1	角 鋼	L50x50x6	A36	1	
2	螺栓連帽	M10x50L	A307-B 鍍鋅	2	適用於SS8B
3	擴展螺栓	EB2-M10-80L		2	適用於SS8E

說明:

1. 本結構管架適用於 1.1/2" (含)以下管線支撐
2. SS8B：使用螺栓連帽固定
SS8E：使用擴展螺栓固定
SS8W：使用焊接固定

3.稱呼代號: SS8 

圖面表示法

圖面表示法	
PLAN	SPOOL
 SS8W-400H	 NOTE: SHOWN ON THE LARGEST PIPE LINE.

NOTE: SHOWN ON THE
LARGEST PIPE LINE.

益高工程有限公司
E-KO ENGINEERING., LTD

STRUCTURE SUPPORT
結構管架

BY	CHK.	APP.	DATE	CONTRACT	DWG. NO. SS8	SH'T NO. 1 OF 1	REV. △
----	------	------	------	----------	------------------------	--------------------	-----------