

STANDARD BATTERY TEAM VAN LOADOUT

2" PVC / Rigid

- 2" PVC conduit — 5 sticks
- 2" PVC 90° elbows (bell) — 10
- 2" PVC couplers — 6
- 2" PVC male adapters — 20
- 2" lock rings — 20
- 2" plastic bushings — 20
- 2" weather sealing rings — 1 box
- 2" weather head — 1
- 12x12x6 PVC junction box — 3
- 8x8x4 PVC junction box — 3
- 6x6x4 PVC junction box — 3
- 2" PVC straps — 20–25
- 2" rigid conduit — 1 x 10-ft stick

3/4" EMT (Raintight)

- 3/4" EMT conduit — 15 sticks
- 3/4" male connectors — 50
- 3/4" couplers — 50
- 3/4" ground bushings — 50
- 3/4" LB conduit bodies — 20
- 3/4" LL conduit bodies — 10
- 3/4" LR conduit bodies — 10
- 3/4" T conduit bodies — 10
- 3/4" closed nipples — 20
- 3/4" standard nipples (non-closed) — 20

1" EMT (Raintight)

- 1" EMT conduit — 6 sticks
- 1" male adapters — 20
- 1" couplers — 10
- 1" ground bushings — 20
- 1" LB conduit bodies — 10
- 1" LL conduit bodies — 10
- 1" LR conduit bodies — 10
- 1" closed nipples — 10

Wire & Terminations

- 3/0 copper conductor — 150 ft
- Polaris lugs (3/0) — 30
- Wagos (comms) — 50
- Standard wire nuts — 100
- Grounding bars — 5
- Bonding bridges — 5
- Comms wire — 500 ft roll

THHN — #10

- Red — 2 × 1,000 ft rolls
- Black — 2 × 1,000 ft rolls
- Green — 2 × 1,000 ft rolls

THHN — #6

- Red — 500 ft
- Black — 500 ft
- White — 500 ft
- Green — 500 ft

THHN — #8

- Red — 500 ft
- Black — 500 ft
- White — 500 ft
- Green — 500 ft