

Preprocessing/Presolve

Preprocessing refers to elementary operations that can be used to strengthen/simplify a formulation.

- It is a phase between formulation and solution.
- It can greatly enhance the speed of algorithms.

Tightening bounds and variable fixing

For an example of bound tightening, consider the following IP formulation.

$$\begin{aligned} \max \quad & 2x_1 + x_2 - x_3 \\ & 5x_1 - 2x_2 + 8x_3 \leq 15 \\ & 8x_1 + 3x_2 - x_3 \geq 9 \\ & x_1 + x_2 + x_3 \leq 6 \\ & 0 \leq x_1 \leq 3 \\ & 0 \leq x_2 \leq 1 \\ & 1 \leq x_3 \\ & x_1, x_2, x_3 \text{ integer.} \end{aligned}$$

Isolate x_1 in the first constraint to improve its upper bound.

Isolate x_3 in the first constraint to improve its upper bound.

Isolate x_2 in the first constraint to improve its lower bound.

Isolate x_1 in the second constraint to improve its lower bound.

Observe that we must have $x_1 = 1$, so we can simplify the formulation:

$$\begin{aligned} \max \quad & 2 + x_2 - x_3 \\ & -2x_2 + 8x_3 \leq 10 \\ & 3x_2 - x_3 \geq 1 \\ & x_2 + x_3 \leq 5 \\ & 0 \leq x_2 \leq 1 \\ & 1 \leq x_3 \\ & x_2, x_3 \text{ integer.} \end{aligned}$$

Redundant constraints

Argue that the last constraint is redundant.

Rewrite the further simplified formulation.

Isolate x_3 in the first constraint and improve its bound.

Isolate x_2 in the second constraint and improve its bound.

What is the solution?

Simple observations used for bound tightening

Consider the set $S := \{x \in \mathbb{Z}^n \mid a^T x \leq b, l \leq x \leq u\}$, where we assume $l, u \in \mathbb{Z}^n$ and $0 \leq l \leq u$.

Assuming $a_1 > 0$, what is the best conceivable objective for $\max\{x_1 \mid x \in S\}$?

Assuming $a_1 < 0$, what is the best conceivable objective for $\min\{x_1 \mid x \in S\}$.

Proposition 1. Consider the set $S = \{x \in \mathbb{Z}_+^n \mid a^T x \leq b, l \leq x \leq u\}$, where $0 \leq l \leq u$.

1. Bound Tightening. If $a_1 > 0$, then x_1 is bounded above by:

And, if $a_1 < 0$, then x_1 is bounded below by:

2. Redundancy. The constraint $a^T x \leq b$ is redundant if:

3. Infeasibility. The set S is empty if:

Generating logical inequalities by “probing”

For 0-1 programs, it is often easy to generate (practically useful) “logical” or “boolean” constraints. For example, consider the following 0-1 set.

$$\begin{aligned}7x_1 + 3x_2 - 4x_3 - 2x_4 &\leq 1 \\-2x_1 + 7x_2 + 3x_3 + x_4 &\leq 6 \\-2x_2 - 3x_3 - 6x_4 &\leq -5 \\3x_1 - 2x_3 &\geq -1 \\x_1, x_2, x_3, x_4 &\text{ binary.}\end{aligned}$$

Looking at the first constraint, does setting $x_1 = 1$ imply anything?

Similarly, from the second constraint, can we conclude anything if $x_2 = 1$?

What about setting $x_4 = 0$ in the third constraint?

Anything from the fourth constraint?

Combining logical inequalities

Can we say anything about the relationship between x_1 and x_3 ?

What about between x_1 and x_2 ?

Now what can we say about x_4 ?

What does the constraint set look like after these simplifications?

Conflict graphs: used to store/generate logical inequalities

Introduced by Atamtürk, Nemhauser, and Savelsbergh in a 1998 EJOR paper.

A conflict graph $G = (V, E)$ for an IP with n binary variables has:

- $2n$ vertices: one for $x_i = 0$ and one for $x_i = 1$;
- an edge between two vertices if fixing the variables to associated values yields in a “conflict.”

Draw the conflict graph for the previous problem.

Any feasible solution to 0-1 program is.....in conflict graph.

Corollary:

The following two classes of valid inequalities were studied by Padberg (1973).

Proposition 2 (Clique inequalities). *If $C \subseteq V$ is a clique in a graph $G = (V, E)$, then the inequality $\sum_{i \in C} x_i \leq 1$ is valid for independent sets in G .*

Identify two cliques from the conflict graph that you drew and write the corresponding inequalities.

Proposition 3 (Odd-hole inequalities). *If $C \subseteq V$ induces an odd cycle in graph $G = (V, E)$, then the inequality $\sum_{i \in C} x_i \leq (|C| - 1)/2$ is valid for independent sets in G .*

Identify an odd hole (with $|C| \geq 5$) from the conflict graph and give the associated inequality.