

ALLEGHENY MILLWORK

HAZARD COMMUNICATION PROGRAM

Interior Finish Trades – Division 06: Rough & Finish
Carpentry/Architectural Millwork

Compliant with OSHA 29 CFR 1910.1200
OSHA Hazard Communication Standard (GHS Aligned)
Adopted by reference in construction under 29 CFR 1926.59

Program Administrator	
Date of Adoption	
Date of Last Review	

HAZARD COMMUNICATION PROGRAM

TABLE OF CONTENTS

Purpose.....	4
Scope	4
Division 06 Operations Covered	4
Substances Covered	5
Exemptions	5
Responsibilities	6
Safety Department/Program Administrator	6
Project Managers & Superintendents	6
Shop Manager & Field Supervisors	6
Employees.....	7
Purchasing	7
Safety Data Sheets (SDS)	8
The 16 Section GHS Aligned SDS Format	8
Access to SDS	9
Obtaining, Reviewing & Updating SDS	10
Hazardous Chemicals Typical to Division 06 Operations	11
Chemicals with Additional OSHA Standards	13
Labels & Other Forms of Warning	14
Required Elements on a Shipped Container Label (GHS).....	14
GHS Pictograms: Quick Reference.....	15
Workplace (Secondary) Container Labeling	16
Inspection & Replacement of Labels	17
Alternative Labeling Systems (Stationary Containers).....	17
Employee Information & Training	18
When Training is Provided.....	18
Content of Information (What Employees Must be Informed Of)	18
Content of Training (What Employees Must be Trained On)	18
Division 06: Specific Training Topics	19
Training Documentation	19
Multi-Employer Jobsites & Coordination with Other Trades.....	20
Information Allegheny Millwork Provides to Other Employers.....	20
Information Allegheny Millwork Obtains from Other Employers.....	20
Coordination Procedures.....	20
Non-Routine Tasks	21
Emergency Procedures.....	21

Recordkeeping	22
Program Evaluation	22
Hazardous Chemical Inventory.....	Appendix A
SDS Review Checklist (16 Section GHS Format)	Appendix B
SDS Request Letter Template.....	Appendix C
Hazard Communication Training Record	Appendix D

PURPOSE

This Hazard Communication Program has been developed by Allegheny Millwork to ensure that information concerning the identity and hazards of all hazardous chemicals present in the workplace is communicated to all employees who may be exposed under normal working conditions or in foreseeable emergencies. This program is intended to meet the requirements of the OSHA Hazard Communication Standard, 29 CFR 1910.1200, which is adopted by reference in construction under 29 CFR 1926.59.

The OSHA Hazard Communication Standard is aligned with the United Nations Globally Harmonized System of Classification and Labelling of Chemicals (GHS). Under the GHS aligned standard, chemical manufacturers and importers classify chemicals according to specified hazard criteria and convey hazard information through:

- Standardized container labels with a product identifier, signal word (“Danger” or “Warning”), hazard statement(s), precautionary statement(s), pictograms and supplier identification.
- Sixteen section Safety Data Sheets (SDS) in a standardized format.

This program establishes how Allegheny Millwork identified chemical hazards specific to Division 06 Interior Finish Carpentry & Architectural Millwork operations, maintains SDSs, labels workplace containers, trains employees and coordinates hazard information on multi-employer jobsites.

SCOPE

This program applies to all Allegheny Millwork employees, including shop fabricators, apprentices, project managers, superintendents, office personnel, as well as subcontractors and installers, who may enter the shop or jobsite areas, who may be exposed to hazardous chemicals during the course of their work.

This program covers all hazardous chemicals known to be present at Allegheny Millwork facilities and on jobsites where Division 06 work is performed, whether the chemicals are purchased, brought on site by other employers or generated by work operations (for example, wood dust, silica dust, welding fumes or decomposition products from heated finishes).

DIVISION 06 OPERATIONS COVERED

- Shop fabrication of architectural millwork, casework, paneling, wainscoting, stair parts, doors, and trim
- Application of stains, lacquers, sealers, topcoats, and touch-up finishes in shop finish rooms and spray booths
- Use of adhesives, contact cements, construction adhesives, edge-banding adhesives, and laminating adhesives
- On-site installation of architectural woodwork, casework, countertops, and related millwork
- Field-applied caulks, sealants, patching compounds, fillers, and touch-up finishes
- Cleanup and maintenance activities involving solvents, strippers, degreasers, and cleaners

- Housekeeping activities that generate or disturb hazardous substances (wood dust, silica dust from cement-based or stone materials, finishing-booth residues)

SUBSTANCES COVERED

- Purchased chemical products (finishes, adhesives, solvents, cleaners, fuels, lubricants, etc.)
- Chemicals brought onto Allegheny Millwork jobsites by other employers, to the extent our employees may be exposed
- Hazardous substances generated by work operations, including wood dust (certain species of which are classified as hazardous), respirable crystalline silica, welding fumes and thermal decomposition products

EXEMPTIONS

Consistent with 29 CFR 1910.1200(b), the following are *not* subject to this program:

- Hazardous waste regulated under the Resource Conservation and Recovery Act (RCRA)
- Tobacco or tobacco products
- Wood or wood particles that will not be processed (lumber intended only to be cut to length and installed); wood dust generated by cutting, sanding or machining operations is NOT exempt and is covered by this program
- Articles: Manufactured items that are formed to a specific shape, have end-use functions dependent on that shape and do not release more than very small quantities of a hazardous chemical under normal use
- Food, drugs, cosmetics or consumer products used in the workplace in the same manner and duration of exposure as normal consumer use

RESPONSIBILITIES

PROGRAM ADMINISTRATOR (SAFETY DEPARTMENT)

The Safety Department Program Administrator is the designated program coordinator with overall responsibility for this Hazard Communication Program.

The Program Administrator shall:

- Maintain and annually review this written program, and update it whenever operations, materials, or regulations change.
- Maintain the master list of hazardous chemicals used by Allegheny Millwork (Appendix A) and ensure that area-specific chemical lists are maintained at the shop and on each active jobsite.
- Obtain, maintain, and update Safety Data Sheets (SDSs) for every hazardous chemical on the master list. SDSs shall be stored in both electronic and hard-copy form.
- Review each incoming SDS for completeness against the 16-section GHS format (Section 4.0).
- Ensure that all shipping containers received are properly labeled with the six required GHS elements, and that workplace containers (including secondary/portable containers that are not for immediate use) are labeled in accordance with the section labeled “Labels & Other Forms of Warning”.
- Ensure initial and refresher training is delivered per the section labeled “Employee Information & Training” and maintain training records.
- Coordinate hazard information exchange with General Contractors, Controlling Contractors, and other trades on multi-employer jobsites.
- Clear all new chemical procurements before they are introduced to the shop or any jobsite.

PROJECT MANAGERS & SITE SUPERINTENDENTS

- Ensure the project-specific chemical inventory and SDS binder/electronic access are established for each jobsite before installation work begins.
- Verify that installers assigned to a project have received HazCom training and training on any project-specific chemicals.
- Coordinate with the General Contractor to receive hazard information about chemicals used by other trades that may expose Allegheny Millwork employees.
- Ensure that any chemicals brought to the jobsite by Allegheny Millwork are entered on the jobsite inventory and that the applicable SDSs travel with the materials.

SHOP MANAGER & FIELD SUPERVISORS

- Conduct and document pre-task briefings (toolbox talks) when a new chemical is introduced to a work area or when a non-routine task is assigned.
- Verify that container labels in their work area are legible and intact, and that workplace containers are labeled as required.
- Enforce the use of PPE and work practices identified on the SDS and label for each chemical in use.

- Report damaged labels, missing SDSs, or suspected overexposures to the Program Administrator.

EMPLOYEES

- Read container labels and the relevant SDS section before working with an unfamiliar chemical, and follow the precautions specified.
- Use the PPE, engineering controls, and work practices required for each chemical in use.
- Label every portable/secondary container that is not emptied at the end of the shift or that will be used by another employee.
- Participate in all required training.
- Report damaged, missing, or illegible labels, missing SDSs, spills, releases, and suspected overexposures to their supervisor.

PURCHASING

- Obtain an SDS with every initial shipment of a hazardous chemical. SDSs are to be provided to the Program Administrator within 10 working days of receipt.
- Do not accept shipments of hazardous chemicals that lack GHS-compliant labels.
- Notify the Program Administrator before introducing any new chemical into the Allegheny Millwork inventory.

SAFETY DATA SHEETS (SDS)

Allegheny Millwork maintains a current Safety Data Sheet for every hazardous chemical on the master list. SDSs are provided to the employer by the chemical manufacturer, importer, or distributor at no cost and must accompany or precede the initial shipment.

THE 16 SECTION GHS ALIGNED SDS FORMAT

Since June 1st, 2015, all SDSs must confirm to the 16 Section GHS Aligned Format required by 29 CFR 1910.1200(g) and Appendix D. The 16 Sections are:

#	Section Title	Content
1	Identification	Product identifier, manufacturer/supplier name and address, emergency phone number, recommended use & restrictions on use.
2	Hazard(s) Identification	GHS Classification, signal word, hazard statement(s), precautionary statement(s) & description of any hazards not otherwise classified.
3	Composition/Information on Ingredients	Chemical name, common names/synonyms, CAS number & concentration (or concentration range) for hazardous ingredients; trade secret claims where applicable.
4	First-Aid Measures	Required first-aid by route of exposure (inhalation, skin, eye, ingestion); most important symptoms/effects; indication of any immediate medical attention required.
5	Fire-Fighting Measures	Suitable and unsuitable extinguishing media, specific hazards arising from the chemical, special protective equipment & precautions for firefighters.
6	Accidental Release Measures	Personal precautions, PPE, emergency procedures, environmental precautions & methods & materials for containment & cleanup.
7	Handling & Storage	Precautions for safe handling & conditions for safe storage, including any incompatibilities.
8	Exposure Controls/Personal Protection	OSHA PEL, ACGIH TLV, other exposure limits; engineering controls & individual protection measures (PPE).
9	Physical & Chemical Properties	Appearance, odor, pH, melting/freezing point, boiling point, flash point, evaporation rate, flammability, vapor pressure, vapor density, relative density, solubility, partition coefficient, auto-ignition temperature, decomposition temperature, viscosity & other relevant properties.

#	Section Title	Content
10	Stability & Reactivity	Reactivity, chemical stability, possibility of hazardous reactions, conditions to avoid, incompatible materials, hazardous decomposition products.
11	Toxicological Information	Routes of exposure, related symptoms, acute & chronic effects, numerical measures of toxicity (e.g, LD ₅₀), carcinogenicity listings (NTP, IARC, OSHA).
12	Ecological Information (Non-Mandatory)	Ecotoxicity, persistence & degradability, bioaccumulative potential, mobility in soil & other adverse effects. OSHA does not enforce this section.
13	Disposal Considerations (Non-Mandatory)	Description of waste residues and information on safe handling and methods of disposal. OSHA does not enforce this section.
14	Transportation Information (Non-Mandatory)	UN number, UN proper shipping name, transport hazard class(es), packing group, environmental hazards, and special precautions. OSHA does not enforce this section.
15	Regulatory Information (Non-Mandatory)	Safety, health, and environmental regulations specific to the product. OSHA does not enforce this section.
16	Other Information	Date of preparation or last revision and any other information not covered elsewhere.

ACCESS TO SDSs

SDSs are readily accessible to every Allegheny Millwork employee during every work shift, without cost, barrier, or advance notice.

Access is provided as follows:

- **Shop:** A hard-copy SDS binder is maintained in the shop safety office and at each finishing station. The full SDS library is also accessible electronically from shop computers.
- **Jobsites:** A project-specific SDS binder is maintained in the Allegheny Millwork jobsite trailer or lead installer's vehicle, covering every chemical the crew brings on site. Jobsite SDSs are also available through the company's electronic SDS platform on crew mobile devices.
- **Electronic Access:** Where electronic access is used as the primary method, a reliable device with internet access and adequate battery/power is provided, and a backup hard-copy method is in place for use during outages or in areas without connectivity.

OBTAINING, REVIEWING & UPDATING SDSs

- Every initial shipment of a hazardous chemical must be accompanied or preceded by an SDS. If one is not received, Purchasing will use the SDS Request Letter (Appendix C) to obtain it from the supplier.
- The Program Administrator reviews each incoming SDS against the 16-section checklist (Appendix B) and requests clarification from the manufacturer for any incomplete SDS.
- Manufacturers are required to update an SDS within three months of becoming aware of new, significant hazard information. Allegheny Millwork incorporates updated SDSs into the library upon receipt and replaces any superseded copies.
- If an SDS cannot be obtained from a manufacturer or supplier despite reasonable efforts, a written complaint will be filed with the nearest OSHA Area Office.

HAZARDOUS CHEMICALS TYPICAL TO DIVISION 06 OPERATIONS

The table below identifies the categories of hazardous chemicals typically encountered in Interior Finish Carpentry and Architectural Millwork operations, along with the primary GHS hazard classifications and the most common routes of exposure and health effects. This table is provided as a training aid and general reference; it does not replace the chemical-specific information on the product SDS, which is always the authoritative source.

Material/Chemical Category	Typical Division 06 Use	Primary GHS Hazards	Main Routes & Effects
Solvent Based Stains, Lacquers, Sanding Sealers & Topcoats	Shop & Touch-Up Finishing of Architectural Woodwork & Casework	- Flammable Liquid (Cat 2-3) - Specific Target Organ Toxicity (STOT) SE/RE - Skin & Eye Irritation - Carcinogenicity (Certain Solvents)	- Inhalation of Vapors, Skin/Eye Contact - CNS Depression, Dermatitis, Respiratory Irritation
Water Based (waterborne) Stains, Lacquers & Topcoats	Shop & Field Finishing Where Solvent-Based systems are restricted	- Eye/Skin Irritation - Some Formulations contain preservatives that are sensitizers	- Skin/Eye contact - Inhalation of overspray mist - Irritation, sensitization
Conversion Varnishes, Catalyzed Lacquers & Polyurethane Coatings	High-wear Topcoats on Casework, Cabinetry & Architectural Panels	- Flammable Liquid - Respiratory & Skin Sensitization (isocyanates in some 2K polyurethanes) - Carcinogenicity category 2 (some formaldehyde-releasing systems)	- Inhalation of vapor/mist - Skin contact - Occupational asthma, dermatitis, long-term respiratory effects
Contact Cements & Solvent-Based Adhesives	Plastic Laminate Application, Edge Banding & Field Bonding	- Flammable Liquid (Cat 1-2) - STOT SE (CNS) - Aspiration Hazard	- Inhalation, Skin Contact - Dizziness, Headache - Flash Fire Risk near Ignition sources
Construction Adhesives, PL-Type Adhesives & Panel Adhesives	Field Installation of Paneling, Trim & Millwork Assemblies	- Flammable Aerosol or Liquid - Skin/Eye Irritation - STOT SE (Some Solvent-Bearing Products)	- Skin/Eye Contact - Inhalation - Irritation - Headache
PVA (Yellow/White) Wood Glues & Polyurethane Wood Glues	Shop Assembly of Millwork, Casework & Stair Parts	- PVA: Generally Low Hazard - Polyurethane Glues: Skin Sensitizer - Respiratory Sensitizer (isocyanate component)	- Skin Contact - Inhalation of Dust from Cured Product - Sensitization with Polyurethane Types

Material/Chemical Category	Typical Division 06 Use	Primary GHS Hazards	Main Routes & Effects
Silicone, Polyurethane & Acrylic-Latex Caulks & Sealants	Field Sealing of Millwork Joints, Countertop Seams & Wall Transitions	• Eye/Skin Irritation • Some Release Acetic Acid or Methanol During Cure (STOT SE)	• Skin/Eye/Respiratory Irritation During Cure
Wood Fillers, Patching Compounds & Touch-Up Putties	Shop & Field Repair of Millwork Defects, Nail Holes & Seams	• Flammable Liquid (solvent-based) • Eye/Skin Irritation • Some Contain Crystalline Silica Fillers	• Inhalation of Vapor or Dust • Skin Contact
Paint & Finish Strippers	Refinishing & Restoration of Existing Architectural Millwork	• Skin Corrosion • Carcinogenicity (Methylene Chloride-Based Strippers: Prohibited for Many Uses by EPA) • STOT SE	• Skin/Eye Contact • Inhalation • Severe Burns • CNS Depression • Cardiac Effects
Solvents & Cleaners (Mineral Spirits, Acetone, Lacquer Thinner, Denatured Alcohol, Naphtha)	Thinning, Cleanup of Spray Equipment, Surface Protection	• Flammable Liquid • Eye/Skin Irritation • STOT SE (CNS) • Aspiration Hazard	• Inhalation • Skin Contact • Defatting of Skin • Headache, Dizziness • Fire Risk
Wood Dust (Hardwood & Softwood)	Sawing, Routing, Sanding & Shaping of Lumber & Panel Goods	• Respirable Dust • IRC Group 1 Carcinogen for Hardwood Dust (Nasal Adenocarcinoma) • Skin/Respiratory Sensitizer for Certain Species	• Inhalation • Skin/Eye Contact • Sinonasal Cancer (Long-Term) • Asthma • Dermatitis, Irritation
Respirable Crystalline Silica Dust	Cutting, Drilling, Grinding or Polishing Engineered Stone, Natural Stone, Fiber-Cement, Cement Backer & Cast Trim	• Carcinogenicity Cat 1A • STOT RE (Lung)	• Inhalation • Silicosis • Lung Cancer • COPD • Kidney Disease (See Silica Program)
MDF, Particleboard & Certain Plywood	Cutting, Routing & Machining of Engineered Panel Products	• Wood Dust (As Above) Plus Potential Formaldehyde Off-Gassing During Machining of Urea-Formaldehyde - Bonded Panels • Carcinogenicity Cat 1A (Formaldehyde)	• Inhalation • Eye/Respiratory Irritation • Sensitization • Cancer Risk with Chronic Exposure

Material/Chemical Category	Typical Division 06 Use	Primary GHS Hazards	Main Routes & Effects
Compressed Gas Cylinders (Propane for Torches, CO ₂ /Argon for Welding, Pneumatic Air)	Shop Welding, Brazing & Pneumatic Tool Operation	- Compressed Gas - Flammable Gas (Propane) - Oxygen Asphyxiation Risk	Physical Hazards (Cylinder Rupture, Fire, Asphyxiation in Enclose Spaces)
Aerosol Propellants (Spray Lubricants, Cleaners, Touch-Up Aerosols)	Lubrication, Spot Cleaning & Small Area Touch-Up	- Flammable Aerosol - Gas Under Pressure - STOT SE	- Inhalation - Skin/Eye Contact - Explosion When Heated
Battery Electrolyte (Cordless Tool Batteries, Fork Truck Batteries)	Powered Hand Tools & Material Handling Equipment	- Lithium-Ion - Thermal Runaway/Fire Risk - Lead-Acid: Skin Corrosion (Sulfuric Acid)	- Thermal Injury - Chemical Burns

CHEMICALS WITH ADDITIONAL OSHA STANDARDS

Several hazardous chemicals commonly encountered in Division 06 work are also covered by substance/specific OSHA Standards that impose requirements beyond the Hazard Communication Standard. These include, but are not limited to:

- **Respirable Crystalline Silica:** 29 CFR 1926.1153 (construction). See the Allegheny Millwork Respirable Crystalline Silica Program
- **Formaldehyde:** 29 CFR 1910.1048 (applies where formaldehyde exposure can reasonably be expected, such as when machining certain composite wood panels).
- **Lead:** 29 CFR 1926.62 (may apply during removal or refinishing of painted historic millwork containing lead-based paint).
- **Asbestos:** 29 CFR 1926.1101 (may apply during demolition or renovation involving legacy asbestos-containing materials adjacent to millwork).
- **Methylene Chloride:** 29 CFR 1910.1052 (applies to certain paint/finish strippers; many consumer uses also restricted by EPA).

Where any of these standards apply, Allegheny Millwork complies with both the Hazard Communication Standard and the applicable substance-specific standard.

LABELS & OTHER FORMS OF WARNING

Chemical manufacturers, importers, and distributors are responsible for ensuring that every container of a hazardous chemical leaving their facility is labeled with the six GHS-required elements. Allegheny Millwork ensures that every container in our workplace remains labeled and that workplace containers into which chemicals are transferred are labeled in accordance with this section.

REQUIRED ELEMENTS ON A SHIPPED CONTAINER LABEL (GHS)

- **Product Identifier**: the name or number used on the label and cross-referenced to Section 1 of the SDS
- **Signal Word**: “Danger” (more severe) or “Warning” (less severe); only one signal word appears on a label
- **Hazard Statement(s)**: standardized phrases describing the nature of the hazard (e.g., “Highly flammable liquid and vapour,” “May cause cancer”)
- **Pictogram(s)**: one or more of the nine standard red-bordered diamond pictograms (flame, flame over circle, exploding bomb, corrosion, gas cylinder, skull and crossbones, exclamation mark, health hazard, environment)
- **Precautionary Statement(s)**: standardized phrases describing recommended measures to prevent or minimize adverse effects (prevention, response, storage, and disposal)
- Name, address & telephone number of the chemical manufacturer, importer, or other responsible party

GHS PICTORGRAMS: QUICK REFERENCE

The nine GHS pictograms commonly seen on Division 06 products are:

Pictogram Name	Pictogram Photo	Indicates	Examples in Millwork Use
Flame		• Flammable • Self-Reactive • Pyrophoric • Emits Flammable Gas • Organic Peroxide • Self-Heating	• Lacquer Thinner • Contact Cement • Acetone • Denatured Alcohol • Aerosols Sprays
Flame Over Circle		• Oxidizer	• Certain Catalysts & Peroxide Based Finish Hardeners
Exploding Bomb		• Explosive • Self-Reactive • Organic Peroxide	• Rare in Millwork • May Appear on Certain Peroxide Catalysts
Gas Cylinder		• Gas Under Pressure	• Propane • CO₂ • Argon • Pneumatic Air Cylinders
Corrosion		• Skin Corrosion/Burns • Eye Damage • Corrosive to Metals	• Paint Strippers • Battery Electrolyte • Strong Cleaners
Skull & Crossbones		• Acute Toxicity (Fatal or Toxic)	• Certain Methylene Chloride Strippers • Some Industrial Biocides

Pictogram Name	Pictogram Photo	Indicates	Examples in Millwork Use
Health Hazard		• Carcinogen • Mutagen • Reproductive Toxicity • Respiratory Sensitizer • Target-Organ Toxicity • Aspiration Toxicity	• Solvent-Based Finishes • Isocyanate Hardeners • Methylene Chloride • Formaldehyde Containing Products • Hardwood Dust
Exclamation Mark		• Irritant (Skin/Eye) • Skin Sensitizer • Acute Toxicity (harmful) • Narcotic Effects • Respiratory Tract Irritation	• Many Waterborne Finishes • Adhesives • Caulks • Cleaners
Environment (Non-Mandatory Under OSHA)		• Hazardous to Aquatic Environment	• Some Solvent-Based Coatings & Strippers

WORKPLACE (SECONDARY) CONTAINER LABELING

When a hazardous chemical is transferred from a labeled shipping container into a workplace container; for example, a spray cup, small finish jar, solvent squeeze bottle, or portable solvent can, the workplace container must be labeled as follows:

- If the container is for the IMMEDIATE USE of the employee who performed the transfer, AND the chemical will be used entirely during that work shift, AND the container remains in that employee's possession, no label is required.
- In ALL other cases (including any container left unattended, any container that may be used by another employee, any container retained at the end of the shift), the workplace container must bear either (a) a full GHS label or (b) product identifier plus words, pictures, symbols, or a combination thereof that provides general information on the hazards of the chemical.
- Allegheny Millwork's preferred workplace-container label format is a preprinted or hand-completed label that includes the product identifier and the GHS pictograms and signal word from the original label. These labels are stocked in the shop and in every jobsite trailer.
- Portable containers left unlabeled at the end of a shift must be either emptied and cleaned, or labeled, before the employee leaves the area.

INSPECTION & REPLACEMENT OF LABELS

- Shop Manager and Field Superintendents/Competent Persons inspect labels in their work areas weekly and before each new task.
- Damaged, faded, or illegible labels must be replaced immediately. Replacement label information is obtained from the product SDS or from the manufacturer.
- Existing labels on incoming shipping containers shall not be removed or defaced unless the container is immediately re-labeled with equivalent information.

ALTERNATIVE LABELING SYSTEMS (STATIONARY CONTAINERS)

For stationary process container, such as a dedicated solvent tank in the finish room, Allegheny Millwork may use signs, placards, process sheets, batch tickets, standard operating procedures or similar written materials in lieu of affixing a label directly to the container, provided the alternative conveys the same information as a label and is readily accessible to employees in the area throughout each work shift.

EMPLOYEE INFORMATION & TRAINING

Allegheny Millwork ensures that every employee who may be exposed to a hazardous chemical in the course of his or her work received effective information and training on hazardous chemicals in his or her work area. Training is provided at the time of initial assignment and whenever a new chemical hazard is introduced into the work area.

WHEN TRAINING IS PROVIDED

- Before initial assignment to any work area where hazardous chemicals are present (shop or jobsite)
- Whenever a new chemical hazard is introduced to the work area — defined as a chemical that presents a hazard type the employees have not previously been trained on
- Whenever Allegheny Millwork becomes aware of significant new hazard information for a chemical already in use
- Annually as a refresher, and more frequently if observation, inspection, or incident investigation indicates a need
- Before any non-routine task involving hazardous chemicals

CONTENT OF INFORMATION (WHAT EMPLOYEES MUST BE INFORMED OF)

- The requirements of the Hazard Communication Standard, 29 CFR 1910.1200
- Any operations in the employee's work area where hazardous chemicals are present
- The location and availability of this written program, the master and area-specific chemical lists, and the SDS library

CONTENT OF TRAINING (WHAT EMPLOYEES MUST BE TRAINED ON)

- Methods and observations employees can use to detect the presence or release of a hazardous chemical in the work area, including visual signs (dust clouds, vapor haze, pooled liquids, damaged containers), odor, and continuous or spot-monitoring devices used by Allegheny Millwork (where applicable)
- The physical hazards (fire, explosion, reactivity) and health hazards (acute, chronic, target organ, sensitization, carcinogenicity) of the chemicals in the work area, as well as any simple asphyxiation, combustible dust, or pyrophoric gas hazards
- Measures employees can take to protect themselves, including specific procedures Allegheny Millwork has implemented such as appropriate work practices, emergency procedures, and personal protective equipment
- The details of this Hazard Communication Program, including an explanation of the labeling system used on shipped and workplace containers, the 16-section SDS format, and how employees can obtain and use the appropriate hazard information

DIVISION 06: SPECIFIC TRAINING TOPICS

In addition to the required core content above, Allegheny Millwork HazCom training covers the following Division 06-specific topics:

- Solvent-based finishing: flash points, ignition sources, static control, grounding/bonding when transferring flammable liquids, spray-booth operation, and proper storage of rags (closed metal cans with self-closing lids)
- Two-component (2K) polyurethane, conversion varnish, and catalyzed systems: isocyanate and formaldehyde awareness, mixing precautions, pot life, and respiratory protection requirements
- Adhesives: contact-cement flash-fire risk, ventilation requirements, and skin protection
- Wood dust: hardwood vs. softwood hazards, the IARC carcinogen classification for hardwood dust, proper use of dust collection, and housekeeping (no compressed-air cleaning, no dry sweeping of accumulations where feasible)
- Respirable crystalline silica dust from engineered stone, fiber-cement, and cementitious substrates — cross-referenced to the Silica Program
- Finish strippers and methylene chloride awareness, including current EPA restrictions
- Compressed gases and aerosols: storage, transport, and use on jobsites

TRAINING DOCUMENTATION

Each training session is documented on the Hazard Communication Training Record (appendix D), including date, trainer name, topics covered and signatures of all attendees. Training records are retained by the Safety Department for the duration of employment, plus three (3) years.

MULTI-EMPLOYER JOBSITES & COORDINATION WITH OTHER TRADES

Allegheny Millwork installation crews routinely work on multi-employer construction sites alongside other trades. Under 29 CFR 1910.1200(e)(2), employers must ensure that hazard information is exchanged among all employers whose employees may be exposed to one another's hazardous chemicals.

INFORMATION ALLEGHENY MILLWORK PROVIDES TO OTHER EMPLOYERS

- A list of the hazardous chemicals Allegheny Millwork will bring to the jobsite, along with the corresponding SDSs
- The methods Allegheny Millwork uses to label workplace containers
- The precautionary measures other employers' employees should take to protect themselves from Allegheny Millwork chemicals, including recommended PPE and work restrictions during finishing or adhesive operations
- The location of Allegheny Millwork SDSs on the jobsite

INFORMATION ALLEGHENY MILLWORK OBTAINS FROM OTHER EMPLOYERS

- A list of hazardous chemicals that other trades will use in areas where Allegheny Millwork crews will be working
- Access to the other trade's SDSs, or copies where practical
- Notice of scheduled work that will generate hazardous airborne contaminants (concrete cutting, spray-applied fireproofing, welding, coating application by others) in areas that will be occupied by Allegheny Millwork crews

COORDINATION PROCEDURES

- The Project Manager or Field Supervisor participates in the General Contractor's pre-construction meeting and weekly safety coordination meetings and raises HazCom concerns whenever overlap is foreseeable.
- When another trade's chemicals or operations present an unavoidable exposure risk to Allegheny Millwork employees, the Field Supervisor either (a) requests isolation, rescheduling, or temporary evacuation of the area, or (b) implements additional controls (ventilation, respiratory protection, relocation) based on the exposure and the SDS.
- Allegheny Millwork notifies the General Contractor in advance of any shop-finishing, field-finishing, or adhesive-application work that will generate airborne contaminants affecting the shared workspace.

NON-ROUTINE TASKS

Before any employee is assigned to a non-routine task involving hazardous chemicals, the Superintendent/Competent Person and the Shop Manager, in coordination with the Program Administrator, shall provide task-specific information covering:

- The specific hazardous chemicals involved and their health and physical hazards
- Protective measures (engineering controls, work practices, PPE) required for the task
- Emergency procedures specific to the task
- The location of the applicable SDSs

Examples of non-routine tasks in Division 06 work include:

- Removal or refinishing of historic architectural woodwork that may bear lead-based paint or other legacy coatings
- Work in or adjacent to confined spaces (pump rooms, mechanical chases) where solvent vapors or spray mist may accumulate
- Use of a new finish system, adhesive, or cleaner that has not previously been used by the crew
- Cleanup of large spills of solvents, adhesives, or finishing products
- Tank or spray-booth entry for cleaning or maintenance
- Work requiring hot work (welding, brazing, torch cutting) near stored finishes or solvents

A written pre-task briefing shall be completed and signed by the supervisor and all participating employees before non-routine work begins, and retained with project records.

EMERGENCY PROCEDURES

Employees shall follow the procedures in the applicable SDS and the Allegheny Millwork Emergency Action Plan for any chemical emergency. The general sequence is:

- Protect yourself first: leave the area if conditions are not safe; do not attempt cleanup of spills or releases that exceed your training and available equipment.
- Alert others in the area and notify your supervisor immediately.
- For fires, activate the nearest fire alarm and call 911. Attempt extinguishment with a portable extinguisher only if the fire is incipient, you are trained, and you have a clear escape path.
- For injured or exposed persons, provide first aid per the SDS (Section 4) to the extent you are trained; call 911 for serious exposures; retrieve the SDS to accompany the injured person to medical treatment.
- Small, incidental spills of products routinely handled by the crew may be cleaned up by trained employees using the spill materials and PPE specified in SDS Section 6. Larger releases are treated as emergencies — evacuate, notify the supervisor, and contact emergency responders.

Flammable-solvent rags used in shop finishing operations present a spontaneous-combustion hazard and must be stored in a listed oily-waste safety can with a self-closing lid and emptied daily.

RECORDKEEPING

- Written Hazard Communication Program: the current version is maintained by the Safety Department; superseded versions are retained for reference.
- Master Chemical List & Area-Specific Chemical Lists (Appendix A): updated as chemicals are added or removed.
- Safety Data Sheets: retained for every hazardous chemical currently in use. Historical SDSs for discontinued chemicals are retained in accordance with 29 CFR 1910.1020 (30 years from the date the chemical was last used) if employee exposure records reference the chemical.
- Training Records (Appendix D): retained for the duration of employment plus three years.
- Non-Routine Task Briefings: retained with project files.
- SDS Request Letters (Appendix C) & Related Correspondence: retained until the SDS is received and filed.

PROGRAM EVALUATION

This Hazard Communication Program is reviewed and evaluated by the Safety Department at least annually. Review is also triggered by:

- Revisions to 29 CFR 1910.1200 or related OSHA standards
- Introduction of new product lines, finish systems, adhesives, or fabrication processes at Allegheny Millwork
- Changes to the chemical inventory that introduce new hazard classes
- Incident reports, near-miss reports, inspection findings, or employee feedback suggesting the program is not adequately protecting employees

The outcome of each review is documented and retained with this program.