



TOOLBOX TALK — WEEKLY SAFETY MEETING

Millwork | Carpentry | Interior Finishes | Material Handling

WEEK 49

Date: Supervisor:

Project / Job Name:

TOPIC: Lead Paint Awareness for Interior Renovation

OVERVIEW:

Lead-based paint was used in residential and commercial construction until 1978, when it was banned for consumer use. Buildings constructed before that year must be presumed to contain lead-based paint until tested and confirmed otherwise. When renovation, repair, or painting activities disturb lead-based

TALKING POINTS — Read to Crew:

1. Lead is a neurotoxin that accumulates in the body over time — primarily in the bones, blood, and soft tissues. There is no safe level of lead exposure. At low levels, lead causes cognitive impairment, memory problems, and mood disorders. At higher levels, it causes kidney damage, reproductive effects, and severe neurological damage. Children are significantly more susceptible
2. The EPA's Renovation, Repair, and Painting Rule requires that contractors working in pre-1978 buildings be EPA Lead-Safe Certified and use lead-safe work practices including containment, dust control, and cleanup procedures. If Allegheny Millwork is performing work in a pre-1978 building, the project should have an EPA Lead-Safe work plan in place. If you are not aware of one, ask your
3. The hazardous activities in renovation work include sanding painted surfaces, cutting or sawing through painted material, demolishing or removing painted components, and drilling into painted walls. Each of these activities can release significant quantities of lead dust. The correct controls are wet methods to suppress dust, HEPA vacuum collection, and respiratory protection with
4. Personal hygiene is a critical control for lead exposure. Lead dust on the hands is ingested when workers eat, drink, smoke, or touch their face. Before eating lunch, drinking water, or leaving the job site at the end of the day, wash hands and face thoroughly with soap and water. Do not take work clothing home to wash with family laundry — lead dust on clothing can contaminate other

DISCUSSION QUESTIONS — Ask Your Crew:

- Q1: Is this building subject to lead-safe work practice requirements? Has testing been done or assumed?
Q2: What personal hygiene facilities — soap, water, handwashing stations — do we have available for lead work?

KEY SAFETY POINTS:

- Buildings built before 1978 are assumed to contain lead until tested
- Never sand or disturb suspected lead-painted surfaces without proper precautions
- Use a HEPA vacuum for all cleanup — standard vacuums spread lead dust
- Wash hands and face before eating, drinking, or leaving the jobsite
- Lead exposure is tested via blood test — ask your employer about testing

Crew sign-in sheet on page 2 — all 30 crew members sign on the following page.



CREW SIGN-IN SHEET

WEEK 49

By signing, I confirm I attended this toolbox talk and understand the topic discussed.

#	PRINT NAME	SIGNATURE (click to sign in Acrobat)	#	PRINT NAME	SIGNATURE (click to sign in Acrobat)
01		click to sign	16		click to sign
02		click to sign	17		click to sign
03		click to sign	18		click to sign
04		click to sign	19		click to sign
05		click to sign	20		click to sign
06		click to sign	21		click to sign
07		click to sign	22		click to sign
08		click to sign	23		click to sign
09		click to sign	24		click to sign
10		click to sign	25		click to sign
11		click to sign	26		click to sign
12		click to sign	27		click to sign
13		click to sign	28		click to sign
14		click to sign	29		click to sign
15		click to sign	30		click to sign