

JavaScript Boolean Reference

[« Previous \(jsref_obj_array.asp\)](#)[Next Reference » \(jsref_obj_regexp.asp\)](#)

JavaScript Booleans

JavaScript booleans can have one of two values: **true** or **false**.

The Boolean() Function

You can use the Boolean() function to find out if an expression is true:

Example

```
Boolean(10 > 9)           // returns true
```

Try it Yourself » ([tryit.asp?filename=tryjsref_boolean_expression1](#))

Or even easier:

Example

```
(10 > 9)                  // also returns true  
10 > 9                    // also returns true
```

Try it Yourself » ([tryit.asp?filename=tryjsref_boolean_expression2](#))

For a tutorial about booleans, read our JavaScript Boolean Tutorial ([/js/js_booleans.asp](#)).

Boolean Properties

Property	Description
constructor (jsref_constructor_boolean.asp)	Returns the function that created JavaScript's Boolean prototype

prototype (jsref_prototype_boolean.asp)	Allows you to add properties and methods to the Boolean prototype
--	--

Boolean Methods

Method	Description
toString() (jsref_tostring_boolean.asp)	Converts a boolean value to a string, and returns the result
valueOf() (jsref_valueof_boolean.asp)	Returns the primitive value of a boolean

« [Previous \(jsref_obj_array.asp\)](#) [Next Reference » \(jsref_obj_regexp.asp\)](#)

Copyright 1999-2015 (/about/about_copyright.asp) by Refsnes Data. All Rights Reserved.