

Floyd-Warshall Algorithm

CS313E

What is Floyd-Warshall Algorithm ?


- The Floyd-Warshall algorithm is a **dynamic programming algorithm** formulation to solve the all-pairs shortest-paths problem on a directed graph $G = (V, E)$.
- The resulting algorithm, known as the *Floyd-Warshall algorithm*.
- In Floyds Algorithm, negative-weight edges may be present, but we assume that there are no negative-weight cycles.

The structure of a shortest path

- Consider a graph $G(V, E)$ with vertices V numbered 1 through N .
- Further consider a function $\text{shortest Path}(i, j, k)$ that returns the shortest possible path from i to j using vertices only from the set $\{1, 2, \dots, k\}$ as intermediate points along the way.
- Now, given this function, our goal is to find the shortest path from each i to each j using *any* vertex in $\{1, 2, \dots, N\}$.

Two possible cases:

- 1) k is not an intermediate vertex in shortest path from i to j . We keep the value of $\text{dist}[i][j]$ as it is.
- 2) k is an intermediate vertex in shortest path from i to j . We update the value of $\text{dist}[i][j]$ as $\text{dist}[i][k] + \text{dist}[k][j]$ if $\text{dist}[i][j] > \text{dist}[i][k] + \text{dist}[k][j]$



- First take the shortest path from i to k using intermediate vertices from the set $\{1, 2, \dots, k-1\}$
- Then take the shortest path from k to j using intermediate vertices from the set $\{1, 2, \dots, k-1\}$

$$d_{ij}^k = d_{ik}^{(k-1)} + d_{kj}^{(k-1)}$$

A recursive solution to the all-pairs shortest-paths problem

$$d_{ij}^{(k)} = \begin{cases} w_{ij} & \text{if } k = 0, \\ \min (d_{ij}^{(k-1)}, d_{ik}^{(k-1)} + d_{kj}^{(k-1)}) & \text{if } k \geq 1. \end{cases}$$

- This is a recursive formulation of shortest path to find the weight from vertex i to vertex j , for which all intermediate vertices are in the set $\{1, 2, \dots, k\}$.
- When $k = 0$, a path from vertex i to vertex j with no intermediate vertex numbered higher than 0 has no intermediate vertices at all.

Floyd-Warshall Algorithm

FLOYD-WARSHALL(W)

```
1   $n = W.rows$ 
2   $D^{(0)} = W$ 
3  for  $k = 1$  to  $n$ 
4      let  $D^{(k)} = (d_{ij}^{(k)})$  be a new  $n \times n$  matrix
5      for  $i = 1$  to  $n$ 
6          for  $j = 1$  to  $n$ 
7               $d_{ij}^{(k)} = \min(d_{ij}^{(k-1)}, d_{ik}^{(k-1)} + d_{kj}^{(k-1)})$ 
8  return  $D^{(n)}$ 
```

- **Time Complexity**

There are three loops. Each loop has constant complexities.

So, the time complexity of the Floyd-Warshall algorithm is **$O(n^3)$** .


Constructing a shortest path

- There are a variety of different methods for constructing shortest paths in the Floyd-Warshall algorithm.
- First One way is to compute the matrix D of shortest-path weights and then construct the predecessor matrix π from the D matrix.
- second one we can compute the predecessor matrix π while the algorithm computes the matrices D^k .

$$\pi_{ij}^{(k)} = \begin{cases} NIL & \text{if } i = j \text{ or } w_{ij} = \infty \\ i & \text{if } i \neq j \text{ and } w_{ij} < \infty \end{cases}$$

How Floyd-Warshall Algorithm Works?

- Let's take an example:
- Create a matrix D^0 of dimension $n \times n$ where n is the number of vertices. The row and the column are indexed as i and j respectively. i and j are the vertices of the graph. Each cell $D[i][j]$ is filled with the distance from the i^{th} vertex to the j^{th} vertex. If there is no path from i^{th} vertex to j^{th} vertex, the cell is left as infinity.



$$D^{(0)} = \begin{pmatrix} 0 & 3 & 8 & \infty & -4 \\ \infty & 0 & \infty & 1 & 7 \\ \infty & 4 & 0 & \infty & \infty \\ 2 & \infty & -5 & 0 & \infty \\ \infty & \infty & \infty & 6 & 0 \end{pmatrix}$$

$$\Pi^{(0)} = \begin{pmatrix} \text{NIL} & 1 & 1 & \text{NIL} & 1 \\ \text{NIL} & \text{NIL} & \text{NIL} & 2 & 2 \\ \text{NIL} & 3 & \text{NIL} & \text{NIL} & \text{NIL} \\ 4 & \text{NIL} & 4 & \text{NIL} & \text{NIL} \\ \text{NIL} & \text{NIL} & \text{NIL} & 5 & \text{NIL} \end{pmatrix}$$

Now, create a matrix D^1 using matrix D^0 . The elements in the first column and the first row are left as they are.


Let k be the intermediate vertex in the shortest path from source to destination. In this step, k is the first vertex. $D[i][j]$ is filled with

$(D[i][k] + D[k][j])$ if $(D[i][j] > D[i][k] + D[k][j])$.

That is, if the direct distance from the source to the destination is greater than the path through the vertex k , then the cell is filled with

$D[i][k] + D[k][j]$.

$$D^{(1)} = \begin{pmatrix} 0 & 3 & 8 & \infty & -4 \\ \infty & 0 & \infty & 1 & 7 \\ \infty & 4 & 0 & \infty & \infty \\ 2 & 5 & -5 & 0 & -2 \\ \infty & \infty & \infty & 6 & 0 \end{pmatrix} \quad \Pi^{(1)} = \begin{pmatrix} \text{NIL} & 1 & 1 & \text{NIL} & 1 \\ \text{NIL} & \text{NIL} & \text{NIL} & 2 & 2 \\ \text{NIL} & 3 & \text{NIL} & \text{NIL} & \text{NIL} \\ 4 & 1 & 4 & \text{NIL} & 1 \\ \text{NIL} & \text{NIL} & \text{NIL} & 5 & \text{NIL} \end{pmatrix}$$



For example:

$$D^0[4,2] = [4,1] + [1,2]$$

$$\infty = 2+3$$

$$\infty > 5$$

So, we are going to take 5 instead of

∞

Similarly, D^2 is also created.

$$D^{(2)} = \begin{pmatrix} 0 & 3 & 8 & 4 & -4 \\ \infty & 0 & \infty & 1 & 7 \\ \infty & 4 & 0 & 5 & 11 \\ 2 & 5 & -5 & 0 & -2 \\ \infty & \infty & \infty & 6 & 0 \end{pmatrix}$$

$$\Pi^{(2)} = \begin{pmatrix} \text{NIL} & 1 & 1 & 2 & 1 \\ \text{NIL} & \text{NIL} & \text{NIL} & 2 & 2 \\ \text{NIL} & 3 & \text{NIL} & 2 & 2 \\ 4 & 1 & 4 & \text{NIL} & 1 \\ \text{NIL} & \text{NIL} & \text{NIL} & 5 & \text{NIL} \end{pmatrix}$$

Similarly, D^3 and D^4 is also created.

$$D^{(3)} = \begin{pmatrix} 0 & 3 & 8 & 4 & -4 \\ \infty & 0 & \infty & 1 & 7 \\ \infty & 4 & 0 & 5 & 11 \\ 2 & -1 & -5 & 0 & -2 \\ \infty & \infty & \infty & 6 & 0 \end{pmatrix} \quad \Pi^{(3)} = \begin{pmatrix} \text{NIL} & 1 & 1 & 2 & 1 \\ \text{NIL} & \text{NIL} & \text{NIL} & 2 & 2 \\ \text{NIL} & 3 & \text{NIL} & 2 & 2 \\ 4 & 3 & 4 & \text{NIL} & 1 \\ \text{NIL} & \text{NIL} & \text{NIL} & 5 & \text{NIL} \end{pmatrix}$$

$$D^{(4)} = \begin{pmatrix} 0 & 3 & -1 & 4 & -4 \\ 3 & 0 & -4 & 1 & -1 \\ 7 & 4 & 0 & 5 & 3 \\ 2 & -1 & -5 & 0 & -2 \\ 8 & 5 & 1 & 6 & 0 \end{pmatrix}$$

$$\Pi^{(4)} = \begin{pmatrix} \text{NIL} & 1 & 4 & 2 & 1 \\ 4 & \text{NIL} & 4 & 2 & 1 \\ 4 & 3 & \text{NIL} & 2 & 1 \\ 4 & 3 & 4 & \text{NIL} & 1 \\ 4 & 3 & 4 & 5 & \text{NIL} \end{pmatrix}$$

D^5 gives the shortest path between each pair of vertices.

$$D^{(5)} = \begin{pmatrix} 0 & 1 & -3 & 2 & -4 \\ 3 & 0 & -4 & 1 & -1 \\ 7 & 4 & 0 & 5 & 3 \\ 2 & -1 & -5 & 0 & -2 \\ 8 & 5 & 1 & 6 & 0 \end{pmatrix} \quad \Pi^{(5)} = \begin{pmatrix} \text{NIL} & 3 & 4 & 5 & 1 \\ 4 & \text{NIL} & 4 & 2 & 1 \\ 4 & 3 & \text{NIL} & 2 & 1 \\ 4 & 3 & 4 & \text{NIL} & 1 \\ 4 & 3 & 4 & 5 & \text{NIL} \end{pmatrix}$$

Conclusion

- *Floyd-Warshall algorithm is a good way to solve all shortest path problems on a directed graph by using an intermediate vertex.*
- *Floyd-Warshall algorithm use a dynamic programing to solve all shortest path problems by take a sequence of decision.*

Reading and Visualization

- Cormen, Thomas H., Charles E. Leiserson, Ronald L. Rivest, and Clifford Stein. Introduction to algorithms. MIT press, 2009.
- Floyd-Warshall All-Pairs Shortest Path <https://www.cs.usfca.edu/~galles/visualization/Floyd.html>