

GeoPIXE Change Log

GeoPIXE-open-source

Note: For complex changes, tag the source file lines with: ;@month-year (e.g. ;@3-16).

10 June, 2026 (branch “main”)

1. ‘Dead_fraction’ weighting issue in some devices
 - a. These devices implement ‘get_dead_weight’ and ‘get_dead_weight_mode’:
 - i. FalconX, Fastcom MPA4, iXRF, Maia, MDAQ2.
 - ii. These all set ‘mode’ in ‘da_evt’ to 0,1,2.
 - iii. These behave correctly.
 - b. Default ‘mode’ in ‘da_evt’ set to -1
 - i. This causes ‘dead_fraction’ to be scaled down by ‘dwell’, when dwell present.
 - c. Devices that implement ‘get_dwell’:
 - i. AS MEX_H5, DAQ, FalconX, Fastcom MPA4, iXRF, Maia, Mdaq2, Midas, NSLS MCA, NSLS XFM_H5, Petra_P06_H5, PNC_CAT HDF
 - d. Of these, these do not implement ‘get_dead_weight_mode’ (so ‘mode’= -1)
 - i. AS MEX_H5, DAQ, Midas, NSLS MCA, NSLS XFM_H5, Petra_P06_H5, PNC_CAT HDF
 - e. Do any of these require returned ‘dead_fraction’ to be divided by ‘dwell’? In other words, do they accumulate dead time into ‘dead_fraction’ over event loop?
 - i. Yes: DAQ, Midas
 - ii. No: NSLS MCA
 - iii. Not sure: AS MEX_H5, NSLS XFM_H5, Petra_P06_H5, PNC_CAT HDF
 1. Probably No. Dead-time is not implemented yet.
 2. They should be implemented to return dead fraction.
 - f. The “Yes” devices should implement:
 - i. ‘get_dead_weight_mode’ and return ‘mode’=0
 - ii. ‘get_dead_weight’ and return weight = dwell map.
 - iii. With this done, the default ‘mode’= -1 in ‘da_evt’ should now not divide by dwell.
2. Main GeoPIXE
 - a. multiplicity_scale
 - i. The default value for ‘multiplicity’ should be n_elements(pactive), if multiplicity is not passed in as a value.
 - ii. Tagged line with “@6-26”
 - b. Da_evt
 - i. Remove divide by dwell map for ‘mode’= -1 case.
 - ii. Need to fix affected devices: DAQ, Midas.
 - iii. Tagged line with “@6-26”
 - c. Version 9.0b
3. DAQ device object
 - a. Add methods: ‘get_dead_weight_mode’ and return ‘mode’=0 and ‘get_dead_weight’ and return weight = dwell map.
 - b. Tagged line with “@6-26”
4. Midas device object
 - a. Add methods: ‘get_dead_weight_mode’ and return ‘mode’=0 and ‘get_dead_weight’ and return weight = dwell map.
 - b. Tagged line with “@6-26”

27 May, 2026 (branch “main”)

1. Main GeoPIXE
 - a. Evt

- i. Use new 'evt_fix_output' in template read (2D and 3D), 'charge-scan' event, 'finish' after event code, 'evt_set_evt_file' and 'evt_set_output_file'.
- b. evt_fix_output
 - i. Fix output filename to add ending for mode "cuts", "MPDA".
- c. Image_details
 - i. Added "All counts" mode, which was missing.
- d. Image_da_preview
 - i. Call 'read_da' with /silent.
- e. Read_da
 - i. Add keyword 'silent' and pass it on to 'read_mpdam' and 'read_da'.
 - ii. This stops infinite loop when this is called from 'image_da_preview' inside 'file_requester'.
- f. Version 9.0a

26 May, 2026 (branch "mbda")

1. Experimental side-branch "mbda" to trial a "MultiBack DA" (MBDA) method as a way to target background shape primarily. See branch "mbda" and this file there.
2. Conclusion: May be better to stick with MPDA and use it differently to track large variation in background shapes using suitable empirical endmembers set on extreme hot spots.

20-25 May, 2026 (branch "main")

1. Main GeoPIXE
 - a. Da_evt
 - i. Take care if log=0. Only use gprint and fix 'help, output=' lines.
 - ii. Especially in MPDA mode.
 - b. Read_da, Read_maia, throttle_q, read_buffer, geopixe_defaults, startup, read_mpdam, unstringify
 - i. Use 'gprint' instead of 'print', so errors get catch'ed.
 - c. Parallel_worker routines
 - i. Use 'gprintf' instead of 'printf', so errors get catch'ed.
 - d. Read_geopixe_image
 - i. Use 'gprintf' instead of 'printf', so errors get catch'ed.
 - e. Gprint
 - i. Add an error catch, to ignore print errors (e.g. in background process in cluster mode, when logging is disabled).
 - ii. Just count args that are not null to set 'narg' for case.
 - f. Gprintf, lun
 - i. Calls 'gprint, output=lun'.
 - g. Version 9.0a
2. Maia device
 - a. Replace all 'print' with 'gprint'
3. FalconX device
 - a. Replace all 'print' with 'gprint'

4. Log file option danger

- a. If logging to a Log file for cluster mode is disabled ('Cluster log 0' in 'geopixe.conf'), then any print to the stdout that is not handled via 'gprint' (which catches errors) will cause a fatal error and kill the spawned processes. No error message will be seen, and of course there is no log file to look at.
- b. If this happens, enable log mode. A helpful trick is to add a prefix to any lines printed by 'gprint', so you might identify lines printed in the log not by 'gprint'. Note this is complicated by any 'print' that uses 'format='.
- c. Then go looking for where (routines) these lines are printed from, and use 'gprint' there, instead of a simple 'print'.

- d. Remember that 'help' is print too.
- e. Disable logging to test that all is now working without error.
- f. **Note: Some device objects may still use 'print' and cannot be used with logging disabled.**
 - i. Each device would need to be corrected individually (replace 'print' with 'gprint').
 - ii. Also treat 'help' (e.g. output to string 's' and then 'gprint, s').

12 May, 2026

- 1. Include all source docx and tables, etc.

29 Apr - 5 May, 2026

- 1. Main GeoPIXE
 - a. Read_geopixe_image
 - i. Read 'energy_cal_file' was in wrong place. Now before read 'has_flux'.
 - b. Evt_start
 - i. Remove (*pp).energy_cal_file setting after sort.
 - ii. It needs to be passed to sort routines as an arg.
 - iii. Fixed for calls to da_evt, cut_avt, cube_evt, da_xstep_evt2, cut_xstep_evt, xanes_da_evt, xanes_single_da_evt, da_evt_stack, da_evt_tomo
 - c. Da_evt, _avt, cube_evt, da_xstep_evt2, cut_xstep_evt, xanes_da_evt, xanes_single_da_evt, da_evt_stack, da_evt_tomo
 - i. Add arg for 'energy_cal_file' and pass to 'image' struct.
 - d. Write_da, read_da, read_da_matrix
 - i. Now version -10
 - ii. Adds 'spec_file' (filename of the fitted spectrum) to the returned DA struct.
 - e. Calc_da_matrix2
 - i. Adds 'spec_file' (filename of the fitted spectrum) to the returned DA struct.
 - f. Image_da_preview
 - i. Now shows 'version' and 'spec_file' for a DA matrix file in the *File Requester*, under "Details" in the preview area.
 - g. Gimage
 - i. New menu "Load DA spectrum for refit" under "Process" to gather original SPEC file and PCM file to refit for a new DA matrix generation.
 - ii. These are sent top the *Spectrum Display* and *Fit Setup* windows to load the SPEC and PCM files, respectively. A pop-up advises the user what to do next.
 - h. Image_Load_DA_spectrum_refit
 - i. Looks up DA spec_file and sends a Notify to *Spectrum Display* to load it.
 - ii. Looks up the PCM file (starts assuming same name as DA matrix file) and sends a Notify to *Fit Setup* to load it.
 - iii. Pops up information instructions for next steps (fit, Generate DA).
 - i. Spectrum_display
 - i. Register these for new Notifys: "fit-setup-load" to pass to 'fit_setup' and "spectrum-load" to load a new spectrum.
 - j. OnNotify_Spectrum
 - i. Responds to a Notify, 'spectrum-load' to load a SPEC file.
 - k. Spectrum_load
 - i. Can pass a filename 'F1' now.
 - l. Spectrum_load_prep
 - i. If passed 'F' is present, use this and /skip_if_exists in 'file_requester'.
 - m. Fit_setup
 - i. Register this for new Notifys: "fit-setup-load" to load a PCM file.
 - ii. Responds to a Notify, 'fit-setup-load' to load a PCM.
 - iii. After a DA save, it will advise to also save PCM with same name.
 - n. Layer_setup

- i. After a YIELD save, it will advise to also save LCM with same name.
- o. Version 9.0**
- 2. Standards wizard
 - a. If the scan of files comes up with zero “On”, which means not found in “standards.csv”, then pop-up a warning to advise that the “resources” dir is probably incorrect.
 - b. Version 9.0
- 3. Depth wizard
 - c. Version 9.0
- 4. GUI Image Hotspots plugin
 - d. Added hotspots separation and extraction plugin

24 Apr, 2026

- 1. Main GeoPIXE
 - a. Define
 - i. Image, Stack: Add ‘energy_cal_file’
 - b. Write_geopixe_image
 - i. Version -58
 - ii. Write ‘energy_cal_file’ before has_flux, which gets skipped on /header read.
 - c. Read_geopixe_image
 - i. Cater for version -58
 - ii. Read ‘energy_cal_file’ before has_flux.
 - d. Image_detail
 - i. Add energy cal file
 - e. Evt
 - i. Add ‘energy_cal_file’ to *p.
 - 1. Set this when “Get” used and cal read (‘evt_getcal’).
 - 2. This also happens via Notify and Wizard actions.
 - ii. Set ‘energy_cal_file’ from template read (scan modes 0,2)
 - f. Evt_start
 - i. Copy EVT ‘(*p).energy_cal_file’ into new ‘(*pp).energy_cal_file’ after ‘da_evt’, etc.
- g. Version 9.0**

22 Apr, 2026

- 1. Main GeoPIXE
 - a. Evt
 - i. Wizard action notify ‘sort-image’ was missing setting these parameters passed in pdata, now added:
 - 1. Xrange, Yrange, Xsize, Ysize
- 2. Batch Wizard
 - a. Wizard_batch_process_blog
 - i. Added passing ‘Xrange, Yrange, Xsize, Ysize’ in ‘sort-image’ pdata to Evt.
 - b. Version 9.0

3. New “tag” added to GitHub for v8.9t.

8 Apr, 2026

- 1. XFM Image Table GUI plugin
 - a. Changed defaults to always output a regions CSV file, and optionally a file to a shared path, if enabled in the ‘geopixe.conf’ file under ‘custom’ with ‘name’ “XFM” and ‘enable’ equal 1.
 - b. Changed tab name to “XFM(AS)” to distinguish it from other XFM plugins.
- 2. Batch Wizard
 - a. If raw or analysis dir are changed, then clear table to force a re-scan.
 - b. Read raw and analysis before scan dir in case edited without <return>.
 - c. Version 8.9t

3. Main GeoPIXE

- a. Make the logging to files in cluster mode optional.
 - i. Use “cluster log 1” in ‘geopixe.conf’ to enable logging to ~/.geopixe/
- b. Geopixe_defaults
 - i. Add “cluster log” capability
 - ii. also add to default ‘geopixe.conf’ file.
- c. Cluster_client
 - i. Pass “log=” option to ‘parallel_Init’
- d. Parallel_client
 - i. Accept “log=” keyword in ‘parallel_Init’ and add it to the ‘args’ passed through the IDL bridge (to ‘spawn_bridge_object’), which calls ‘geopixe_parallel’.
- e. Parallel_worker – worker_init
 - i. Accept new log arg from ‘geopixe_parallel’.
- f. Geopixe_execute
 - i. Pass ‘cluster_debug=-2’ to ‘command’ indicate no logging.
- g. Da_evt, cut_evt, cube_evt, da_evt_tomo, da_evt_stack, spec_evt
 - i. Use ‘cluster_debug=-2’ to indicate no logging.
 - ii. If ‘log’ is not set, then use ‘gprint, active=0’ to disable gprints.
- h. Use explicit “group=event.top” or “group=(*pstate).tlb” in calls to ‘options_popup’
 - i. to prevent large default temporary parent base being used. In some OS the sizing of this to just 1x1 pixel to conceal it does not work.
 - ii. In batch and standards wizards, image_rgb_eventcb, image_eventcb, batch_sort, fit_setup.
- i. Version 8.9t

4. Geopixe_parallel

- a. If ‘args.log’ is not set, then use ‘gprint, active=0’ to disable gprints.
- b. Pass log arg to ‘worker_init’, ‘shared_memory_buffers’ and ‘geopixe_execute’.
- c. Veto ‘toc’ is log disabled.

2 Apr, 2026

1. Main GeoPIXE

- a. Go through and use ‘geopixe_scale()’ to scale all GUIs to default font
 - i. uses ‘sxy’ from ‘graphics_y_scale()’ in ‘startupp’.
- b. Correct_yield
 - i. Skip 1/Y weighting if Y is zero, as in “Back”.
- c. Version, 8.9s

31 Mar, 2026

1. Main GeoPIXE

- a. Ident2, periodic_table, state_button, file_requester, gimage, image_table, fit_setup, layer_setup, source_setup, pink_setup, spectrum_select, spectrum_display.
 - i. Adjust layout to respond to default font size changes.
- b. Source_calculate, pink_calculate
 - i. Return error=1 if input pointers bad or null
- c. Replace all ‘sxy’ in common with ‘geopixe_scale(relative=0)’
- d. Version, 8.9r

2. Wizard_batch

- a. Fixed ‘array’ mode for some devices (e.g. FalconX).
- b. Potentially, may still cancel a non-XY scan mode in a special template.
- c. Launch GeoPIXE when run standalone.
- d. Version, 8.9r

3. Wizard_standards

- a. Launch GeoPIXE when run standalone.

- b. Version, 8.9r
- 4. Wizard_depth
 - a. Launch GeoPIXE when run standalone.
 - b. Version, 8.9r
- 5. FalconX (merge) device object
 - a. Make it an “array” detector by default, unlike the simple FalconX device.

24 Mar, 2026

- 1. FalconX device object
 - a. Add code for a “Correct Y” option, to correct for wandering Y axis after turn-around.
 - i. Constrains Clear X border to at least 1 for this to work.
 - b. New fix to deal with glitches in data:
 - i. Glitches:
 - 1. Occasional X=0 when near X maximum turn-around
 - 2. Long periods showing X=0, for unknown reason.
 - ii. Fix:
 - 1. Restrict Y increment action to windows between [2,xmargin] only (and similar at X max margin). This ignores spurious X=0 values.
- 2. Fortran
 - a. Update function ‘FalconX_events5’ for FalconX with “Correct Y” option to mitigate against bad X values in scan stream. It helps ignore random x=0 and buzzing x=0,1.
 - b. Add glitch fix for FalconX_events5.
 - c. Fixed most compiler warnings. Only pedantry remains.
 - d. Version 57.

18-23 Mar, 2026

- 6. Main GeoPIXE
 - a. Fit_setup, evt
 - i. Adjust layout to fix Linux/Mac.
 - ii. Use frame=0 on Linux for widget_text, to avoid double frames.
 - iii. The way it is done here to allow relative graphics scaling for widgets if system font change effects widget sizes, is a model for updating other GUI routines.
 - 1. Use ‘geopixe_scale()’ function to scale size and offsets in widgets.
 - b. Os_type()
 - i. New function to return: “Win”, “Linux”, “Mac”, “Mac-old”, or with /arch set:
 - ii. “Win32”, “Win64”, “Linux32”, “Linux64”, “Mac-x86”, “Mac-arm”, “Mac-old”

	os_family	os	arch
Win	Windows	Win32	x86_64
Linux	unix	linux	x86_64
MAC	unix	darwin	x86_64
MAC	unix	darwin	arm64
Old MAC	MacOS		
 - c. Geopixe_scale()
 - i. New function to return relative graphics scaling for widgets if system font change effects widget sizes. See ‘fit_setup’ for usage. Scale (*now) = 1.0 in W11, 1.136 in Linux, 1.136 in MacOS.
 - d. Version, 8.9q
- 7. FalconX device object
 - a. Add code for a “Correct Y” option, to correct for wandering Y axis after turn-around.
 - i. Constrains Clear X border to at least 1 for this to work.

12-16 Mar, 2026

- 1. Widget scaling with system/OS change in GeoPIXE

- a. A new parameter 'sxy' (in common 'c_geopixe_scaling', using 'Graphics_y_scale()') is defined on startup, which gives a scaling of widgets from normal OS behaviour.
 - b. As a demonstration, 'Identify2' now uses this to scale widgets.
- 2. Main GeoPIXE
 - a. State_button
 - i. Retain=2 stops working under Linux (only) after a while. Buttons go black.
 - ii. Try retain=0, expose=1 on widget_draw and detect event.type = 3,4 to redraw.
 - b. Image_eventcb
 - i. Image_save_all_TIFF
 - 1. Need to define 'ipath' when 'F' is present.
 - c. Identify2, Periodic_table
 - i. Adjust layout to fix Linux/Mac.
 - ii. Use frame=0 on Linux for widget_text, to avoid double frames.
 - iii. Add code to veto tiny periodic table, only for Linux, due to display bug.
 - d. Cw_fslider2
 - i. Use frame=0, as Linux draws one anyway. This stops double frames!
 - e. Graphics_y_scale
 - i. To try and track changes in the pixel size of text in widgets, in different systems, this returns a scaling of character Y size relative to normal Win11 behaviour.
 - f. Startup
 - i. The normal GeoPIXE startup routine, that define paths such as 'geopixe_root', now defines 'sxy' (in common 'c_geopixe_scaling', using 'Graphics_y_scale()'), which gives a scaling of widgets from normal OS behaviour.
 - g. Version, 8.9p
- 3. FalconX device object
 - a. Trim_evt_files
 - i. Any Y needed for regions flags all input files with the relevant 'ext' number on.
 - ii. This caters for calls from the "FalconX (merge)" device, which has detector numbers ("_nn") as well in the filenames.
 - b. Add code for a "Correct Y" option, to correct for wandering Y axis after turn-around.
 - i. Constrains Y to only increment at the ends of scan lines.
 - ii. New droplist on Device tab.
 - iii. Calls new Fortran lib function 'FalconX_events5' only if Lib version is greater than or equal to 55.
- 4. Fortran
 - a. Merged in new Libs for MAC Apple Silicon machines, including embedded libgcc Fortran support.
 - b. New function 'FalconX_events5' for FalconX with "Correct Y" option.
 - c. Version 55.
- 5. Rebuild idl_query
 - a. To probe new MAC libs.

10 Mar, 2026

- 1. Main GeoPIXE
 - a. image_routines
 - i. plot_mark
 - 1. Draw mark/shape in XOR if corr_on and qc valid, else in Copy source.
 - 2. Always return to copy mode (3) after draw.
 - b. Image_eventcb
 - i. Clear_image_corr, Clear_All_Image_Marks
 - 1. Sends: **notify**, 'image-analyze-mark' to redraw (clear corr) on RGB window.
 - ii. OnNotify_Image
 - 1. Also sends **notify**, 'image-analyze-mark' to redraw (update) RGB display.

- c. Version, 8.9m

5 Mar, 2026

1. Main GeoPIXE
 - a. OnButton_image
 - i. Fix display of zoom view with hold of Middle mouse button (or scroll wheel).
 - ii. Handle edges of view better and show a central cross-hair.
 - b. Version, 8.9k

2 Mar, 2026

1. Main GeoPIXE
 - a. Image_routines
 - i. Analyze_image
 1. Has a new keyword /refine, to refine pixels already in 'qc' (from Association) by the applied new shape. It accepts pixels that are the overlap between 'qc' and the new shape's 'q' selection.
 2. Care was needed because, now, some points along the 'z' projection may have zero conc or charge values. This was done by keeping the original 'q' from the shape as 'q0' to provide the starting x,y and hence z for the profile.
 3. For a 'Traverse' (or 'Curve8') shape, the resulting spectra will only show the profile values selected by this overlap (and) of 'qc' and the traverse selection with error bars that reflect the reduced pixel count.
 - ii. Plot_mark
 1. Use 'device, set_graphics_function=6' (XOR) so shapes are always visible as Green complemented with existing colours.
 - b. OnButton_image
 - i. Interprets Modifier keys now (Shift, Alt, Control) and Scroll wheel changes.
 - ii. Use Control-Left mouse click to move the image. Control-Left click on a feature and drag to where you'd like that feature to be moved to. Nothing is drawn. On release the image is moved.
 1. Note: because the event.x, event.y are coordinates in the full virtual draw area, this makes it difficult to dynamically (while the mouse is moving) to determine change in screen coordinates and change the Viewport offsets, as these affect the X,Y event coordinates in a random way (probably reflecting the time delays in events rippling through the object hierarchy). Hence, a smooth drag effect was not possible.
 - iii. Use Control-Scroll wheel to increment the Zoom level in and out. The display zooms around the current centre.
 - c. Image_eventcb
 - i. image_analyze
 1. Has a new keyword /refine, to pass on to 'analyze_image'.
 - d. Gimage
 - i. New menu "Analyze→Further refine highlighted pixels within spline" to select the /refine option in 'image_analyze'.
 - ii. The existing function to just use the selected shape and ignore any highlighted pixels is now "Analyze→Include pixels within spline".
 - e. Version, 8.9j

26 Feb, 2026

1. Main GeoPIXE
 - a. Wizard_batch
 - i. Fixed layout for largr widget under Linux
 - b. Wizard_standards

- i. wizard_standards_callback_image_done
 - 1. Fixed use of 'pnew' return from 'evt' Notify, 'wizard-return', which now has a 'pfiles' pointer to the changes in file names (was changed for 'wizard_batch').
- c. Version, 8.9i

25 Feb, 2026

- 1. Fortran libs
 - a. The Fortran libs were missing additions for the FalconX since 2023. The Open Source version was older (v53).
 - b. This has been corrected. Make sure you have v54 (use idlquery).
- 2. Main GeoPIXE
 - a. Version, 8.9h

24 Feb, 2026

- 1. Main GeoPIXE
 - a. Layer_setup, cal, correct_yields, detector_setup, filter_setup
 - i. Add a "?" button to pop-up the Users Guide with help on this window

18 Feb, 2026

- 1. Main GeoPIXE
 - a. Gimage
 - i. Add query "buttons" with '?' to popup the users guide for this window.
 - ii. For these, use 'widget_text' instead of 'widget_button', as widget_button cannot be sized small enough (in 'map_help') under Windows when mapping it on/off.
 - b. Map_help
 - i. Add controls to resize the query buttons when help1/help2 mapped on/off.
 - ii. Changed 'scr_ysize_off' and 'xoff' for Help2. May need tweaks under Linux UI.
 - c. Spectrum_display, image_table, evt, fit_setup, ident2, image_history, interelement_operations, multi_image, corr, imageRGB
 - i. Add a "?" button to pop-up the Users Guide with help on this window
 - d. Update Users Guide.
 - e. Version, 8.9g

16 Feb, 2026

- 1. Main GeoPIXE
 - a. OnButton_Image_Table_Import_Regions
 - i. If element names are missing, use "0", "1", ...
 - ii. If all are missing, make n_el=1, el="0".
 - b. Geopixe_browser
 - i. Add buttons to launch instances for GeoPIXE Overview, Help Manual and Worked Examples.

9-11 Feb, 2026

- 1. Main GeoPIXE
 - a. Detector_map
 - i. Cater for more multi-detector spectra file label formats ("1 /E", "#1 /E", "Detector #1", "Detector 1", "Detector /1").
 - ii. Use 'size=1.2' to "Plot_maia_parameters" to make detector labels larger.
 - b. Plot_maia_parameters
 - i. Add 'size' keyword to be able to adjust !p.charsize from default size.
 - c. Geopixe_browser

- i. New embedded HTML browser in GeoPIXE to display help docs. Decodes any table-of-contents to make a table of HREF= which can be used (as keyword key='tag') to jump within the HTML page to the HREF key.
- d. Gimage, Spectrum_Display
 - i. Use the new browser window to display *Worked Examples* and *Maia 384 Help* HTML docs.
- e. Add a new "GeoPIXE Overview" doc and HTML.
- f. Version, 8.9f

3 Feb, 2026

- 1. Main GeoPIXE
 - a. Onbutton_image
 - i. Add code for middle mouse button
 - ii. Middle mouse button press-hold-moves now show a x5 (for zoom=0) magnifying glass view around cursor, offset to the above-right.
 - iii. It shows 20x20 pixels zoomed x5 (for zoom=0), regardless of 'zoom' setting for image with no smoothing/interpolation.
 - iv. Show magnification value relative to the current 'zoom' view.
 - v. Now make pixel area adapt to Draw widget Y size, getting larger for larger windows.
 - b. Image_eventcb
 - i. Postcreate_Image_Base
 - 1. Add 'movex', 'movey' (saved from previous motion step) and 'middle_button' state to pstate.
 - c. Read_geopixe_image
 - i. If the read element names are blank, give them names based on element index (e.g. "0", "1", ...).
 - d. Version, 8.9e
- 2. Geopixe_library
 - a. Add handling the arm64 libs for the MAC Apple Silicon. Will look for generic 'image_lib.dylib' first, then based on architecture: 'image_lib.arm64.dylib' or 'image_lib.64bit.dylib'.
 - b. More error messages to help with issues.
- 3. Idl_query_geopixe
 - a. Add output of current user \$HOME, geopixe_environment().
 - b. Add treatment of IDL 9.2 (based on guess for now).
- 4. Python_valid
 - a. Added IDL 9.2, based on a guess of valid python for now.

28 Jan, 2026

- 2. Main GeoPIXE
 - a. Detector_map
 - i. New window to display DA signal across a detector array. The signal is calculated by multiplying the DA matrix by the individual detector spectra across the array.
 - ii. Take care using detector_update, as it may return a different list order each call. Only use the returned lists initially to make droplist. Use it after that just to find the matching filename.
 - b. Plot_maia_parameter
 - i. If /wset_done then adjust plot region.
 - ii. Only load colour maps, etc. if west_done false.
 - c. Detector_setup
 - i. Fixed plot colours, which may get mixed up by other windows.

20 Jan, 2026

1. Main GeoPIXE
 - a. Plot_maia_parameters
 - i. Add /wset_done flag if window already open and wset set.

12 Jan, 2026

1. Main GeoPIXE
 - a. Image_eventcb
 - i. Image_colours
 1. Added definitions for “Inferno” and “Viridis” colour tables, still mapped onto 100 colours.
 - b. Gimage
 - i. Added menus for the new colours, under menu “Display→Colours”.
 - c. Corr/Association additions
 - i. Corr
 1. Added tabs for X and Y histograms and the new X,Y draw widgets.
 - ii. Corr_eventcb
 1. Postcreate_corr_base
 - a. added additions to pstate for X,Y histogram wids.
 2. OnRealize_CorrX, ...CorrY
 - a. added on-realize routines to set pstate for X,Y histogram wids.
 - iii. Corr_routines
 1. Draw_corrs
 - a. Added plots for X,Y histograms on the X,Y tabs draw areas.
 - b. Needed to detect image (*p).type and whether element/planes are “special_elements” or not.
 2. Set_corr_view
 - a. Change size of (*pstate).drawX, (*pstate).drawY when zoom level changes using “0”, “+”, “-“ buttons

11 Nov, 2025

1. Main GeoPIXE
 - a. Image_table_eventcb
 - i. OnButton_Image_Table_Import_Regions
 1. Was missing first ‘q’ of each row when reading subsequent rows of q.
 - b. Image_eventcb
 - i. Image_process_wizard
 1. When a wizard is opened, use ‘register_notify’ to register the following Notifies from anywhere: 'batch-operations-open', 'batch-rgb-open'.
 2. Any wizard can then use “notify, 'batch-operations-open’” and “notify, 'batch-RGB-open’” to make sure *Image* has its *Operations* and *RGB Image* windows open.
 3. Now moved to main *Image* window realize.
 - c. Gimage
 - i. Move these Register Notify to the main *Image* window (only for main *Image* window, not clones, with wGroup=0)
 - d. Interelement_operations
 - i. Refine action of “Auto” to set better starting Scales for Add, Multiply and Divide.
2. wizard_batch
 - a. In its Timer event code, call “notify, 'batch-operations-open’” and “notify, 'batch-RGB-open’” to make sure *Image* has its *Operations* and *RGB Image* windows open.
 - b. If they are closed, this will force them open again on next Timer loop.

28 Oct, 2025

1. Batch Wizard
 - a. wizard_batch_process_blog:
 - i. Seemed to lose 'output', fixed.
 - b. wizard_batch_process_setup:
 - i. Use 'file_requester(/skip_if_exists)' to find local path to 'blog' file to send to EVT.
 - ii. The 'pileup', 'throttle', 'DA' files will be fixed during processing and returned.
 - c. Clear processing table if blog or analysis paths are changed.
2. Main GeoPIXE
 - a. Evt
 - i. evt_getcal:
 1. Ignore blank or missing filename 'F'.

21 Oct, 2025

1. Batch Wizard
 - a. Changed the 'load' and 'save' flags in ':': 'load' = need to load any existing images (if not sorted afresh) so that corrections can be applied or exports done. 'save' = save the resulting images as a fresh image (or over-written, if 'over' set).
 - b. Needs to send (*p)[j].charge for devices that need it specified (i.e. no flux measure).
 - c. wizard_batch_process_blog
 - i. Do not create output filename here, as it's done in 'scan_dir_evt' already and user may want to edit it in table.
 - d. Notify to other windows when the raw (dpath) and analysis (path) paths change.
 - e. Resize issue
 - i. Needed to make sure that there were no explicit 'scr_xsize' or 'scr_ysize' specified on widget_bases between the top base in a tab and the widget_table. Otherwise, the table would not resize (just on Linux). Seems to be a bug/feature in IDL or Motif on Linux.
 - f. Version 8.9d
2. Standards Wizard
 - a. Version 8.9d
3. Depth Wizard
 - a. Version 8.9d
4. Main GeoPIXE
 - a. Image Notify events
 - i. Needs to "Notify, 'images-changed'" after 'image-corrections' and 'load-image' in Wizard actions, or if (*pd).save gets set in 'save-batch'.
 - b. File_requester
 - i. Accepts 'multi_char' keyword to set the character separating the numeric part of a file-name (defaults to "_").
 - c. Find_file2
 - i. Accepts 'multi_char' keyword to set the character separating the numeric part of a file-name (defaults to "_"). Called from 'file_requester'.
 - d. Evt
 - i. Wizard action ':': needs to call 'evt_start' with /notify (actually is the default).
 - ii. Add extra condition for setting /numeric on File_requester call for evt files:
 1. and (DevObj->multi_char() eq '.')
 - iii. evt_set_evt_file
 1. Enforce 'embed_detector' Dev Obj mode to use DevObj->multi_char() before detector number.
 - iv. Wizard actions: 'sort-setup' and 'sort-image'
 1. Set 'output' file BEFORE blog, as this sets the output path.
 - v. Wizard actions: 'sort-image'
 1. Call 'evt_set_evt_file' with /no_output as output is being set directly.

- e. Scan_dir_evt
 - i. Enforce 'embed_detector' Dev Obj mode to use DevObj->multi_char() before detector number.
- f. Version 8.9d

20 Oct, 2025

1. Batch Wizard

- a. wizard_batch_callback_image_done
 - i. Expect the 'pnew' returned from EVT to be a struct {files:sret, stats:{}}
 - ii. Add Linear to this return and to 'sort-setup' and 'sort-image' actions.
 - iii. Add stats for processed, clipped, valid, bad_xy, pass to table array (*pstate).presults
- b. wizard_batch_process_setup
 - i. Send a new action ('sort-setup') to EVT when a template sort DAI is opened to set initial settings, which a user may modify before starting processing. Do not send the default/template pdai settings later when processing loop is running.
 - ii. Needed to set the internal options for Device Obj in pstate list ((*pstate).pDevObj) to those in the loaded DAI file in ((*pstate).pdai).DevObj.
 - iii. Send these device options to evt in new struct tag 'device_options'.
- c. wizard_batch_update_table
 - i. Colour the active row (if (*pstate).busy) in table green.
- d. wizard_batch_process_blog
 - i. Set (*pstate).busy = 1 just before Notify 'wizard-action'.
- e. Add an 'Abort' button.
 - i. Stops next loop.
 - ii. Clears both busy and abort flags.
- f. New approach to testing for other Wizards and multiple windows.
 - i. When another wizard or multiple windows are detected, a message is placed in (*pstate).message.pwizard or (*pstate).message.pwindow.
 - ii. Only in the Timer event code are these popped up as Warnings, and message cleared, before the Timer is restarted, to avoid timer overrun.
 - iii. Set timer period to 20s.

2. Depth Wizard

- a. New approach to testing for other Wizards and multiple windows.
 - i. When another wizard or multiple windows are detected, a message is placed in (*pstate).message.pwizard or (*pstate).message.pwindow.
 - ii. Only in the Timer event code are these popped up as Warnings, and message cleared, before the Timer is restarted, to avoid timer overrun.
 - iii. Set timer period to 20s.
- b. Version 8.9c

3. Standards Wizard

- a. New approach to testing for other Wizards and multiple windows.
 - i. When another wizard or multiple windows are detected, a message is placed in (*pstate).message.pwizard or (*pstate).message.pwindow.
 - ii. Only in the Timer event code are these popped up as Warnings, and message cleared, before the Timer is restarted, to avoid timer overrun.
 - iii. Set timer period to 20s.
- b. Version 8.9c

4. Main

- a. Evt_event
 - i. The (*pd).pnew return is now a struct {files:sret, stats:{}}.
 - ii. Add new wizard action 'sort-setup'.
- b. Scan_dir_evt
 - i. Now also returns the Linearize filename if found in any DAIs.

- c. Wizard_window_count
 - i. Added extra tests to see if window ID is still valid, to detect any windows that may have closed.
 - ii. Test for null 'windows_open'.

13 Oct, 2025

1. Standards Wizard
 - a. Move test on looping to event return instead of in callback.
 - i. Use new "loop" tag in Define /wizard_notify.
 - b. A new convention:
 - i. Use new the "loop" tag in Define /wizard_notify to flag that this action is the last in the linked list and may be used to check for a loop increment.
 - ii. This is done in the event routine, so no need for a loop check in a callback routine.
 - c. Version 8.9a
2. Batch Wizard
 - a. Move test on looping to event return instead of in callback.
 - i. Use new "loop" tag in Define /wizard_notify.
 - b. A new convention:
 - i. Use new the "loop" tag in Define /wizard_notify to flag that this action is the last in the linked list and may be used to check for a loop increment.
 - ii. This is done in the event routine, so no need for a loop check in a callback routine.
 - c. Now implements all features of Batch-Sort, as a better organized replacement.
 - d. New features, not in Batch-Sort
 - i. Image operations and corrections are listed in a table and can be edited.
 - ii. RGB Exports are also listed in a table
 - iii. Both can be edited and added to.
 - e. Version 8.9c
3. Main
 - a. Define
 - i. /wizard_notify
 1. add struct tag "loop" (defaults to 0 [off]) to provide loop control in calling wizard program. Neater than having this in a callback routine.
 - b. Wizard_check_window_id
 - i. Needs to also check invalid window IDs (those that have been closed).
 - ii. Return a count of zero for only an invalid ID (0L).
 - c. Wizard_window_count
 - i. Return a count of zero for only an invalid ID (0L) open.
 - d. Evt
 - i. Wizard notify 'sort-image' now passes 'load' and 'skip' flags and returns the 'output' filename and 'charge'.
 - e. Image_rgbeventcb
 - i. OnNotify
 1. Add the wizard action 'save-rgb'.
 - f. ImageEventcb
 - i. OnNotify
 1. Add the wizard action 'set-display', 'image-corrections', 'save-batch'.
 - ii. Image_save
 1. Update (*pstate).file to match ((*pstate.p)).file
 - g. Image_processEventcb
 - i. OnNotify
 1. The wizard action for corrections has been moved to the Image window.
 2. Image Process window may not be needed to be opened now.
 - h. Version 8.9c

8 Oct, 2025

1. AS MEX H5 device object
 - a. Correct beam energy to keV.

7 Oct, 2025

1. Main
 - a. OnButton_Image_Process_Get
 - i. Most of the loop now moved into routine 'image_build_op'.
 - b. Gimage
 - i. Add menus for "shift odd columns +1" and -1, ...
 - c. Image_event
 - i. 'image-process' Notify event now uses 'image_do_operations', to apply incoming ops coming from the "Get" button in 'image_process'.
 - ii. Add a new 'wizard-action' Notify event 'set-display'
 1. This sets display parameters in (*p).options for image struct 'p' from Batch Wizard.
 - iii. Add a new 'wizard-action' Notify event 'image-corrections'
 1. Uses 'image_do_operations' to apply correction ops from Batch Wizard.
 - d. image_build_op
 - i. New routine to build a processing operation based on history.
 - e. Image_do_operation
 - i. To actually apply the ops.
 - f. Version 8.9b
2. Batch Wizard (draft)
 - a. New Wizard nearly ready to replace the *Batch Sort*.
 - b. Version 8.9a
3. AS MEX H5 device object
 - a. Force the PV list to be just ['i0','i1','i2','none'].

17 Sep, 2025

1. Main
 - a. Image_process
 - i. As this operations list is used for the "Get" to apply operations from a template image file, **the list MUST contain all operations used anywhere** (e.g. here or in main Gimage window menus). Otherwise, "Get" will not find them.
 - ii. Extend list to include some operations in Gimage menu that were not here, such as "shift odd columns +1", "Clear sides 1", some of the width=10 filters for Erode, Dilate, Gaussian smooth.
 - iii. A deficiency of the operations list is that it does not include extra keywords, such as /X, /Y, /side, etc. To accommodate these variants, new functions were added simply to add these keywords so they can be used in the operations list:
 1. Image_Process_Clear_sides, Image_Process_Shift_even_columns, Image_Process_Shift_odd_columns, Image_Process_Shift_even_rows, Image_Process_Shift_odd_rows
 - iv. Some things are still missing, such as the X and Y scaling menus.
 - v. Using keyword "return_list" in call will just return the processing commands list struct. Use to use this list elsewhere (e.g. in Wizard).
 - vi. Rearranged to put list definition at the top.
 - b. Image_Process_Shift_rows, Image_Process_Shift
 - i. Add "[el]" to History, as for any "*" operation on all planes.
 - c. OnButton_Image_Process_Get
 - i. In the loop for the normal process operations, added "if not start then skip_el=1" for "*" operations (applied to all element planes), so they get applied once (to all).

- ii. Use a case insensitive compare between operation retrieved from image file and the operations list in 'image_process'.
- d. Gimage
 - i. Add menus for "shift odd columns +1" and -1, ...
- e. Evt
 - i. For 'wizard-action' notify, command 'sort-image', now recognizes tags 'skip' (skip sort if DAI exists) and 'load' (load images if found). This is preparation for a *Batch Wizard* to replace *Batch_sort*.
- f. Scan_dir_evt
 - i. Added a return field in return struct 'p' called "dam" for the DAM file used (if it finds a DAI output file).
 - ii. Added 'dai_dir' keyword to be able to select a different dir for output DAI files.
- g. Image_event
 - i. 'image-process' Notify event now uses 'image_do_operations', to apply incoming ops coming from the "Get" button in 'image_process'.
 - ii. Add a new 'wizard-action' Notify event 'set-display'
 - 1. This sets display parameters in (*p).options for image struct 'p' from Batch Wizard.
 - iii. Add a new 'wizard-action' Notify event 'image-corrections'
 - 1. Uses 'image_do_operations' to apply correction ops from Batch Wizard.
- h. image_build_op
 - i. New routine to build a processing operation based on history.
- i. Image_do_operation
 - i. To actually apply the ops.
- j. Version 8.9b
- 2. Standards Wizard
 - a. Add skip=1 (skip if exists), load=1 (load after sort or if exists) tags to the 'pdata' struct sent to *Sort EVT* as a wizard command.
 - b. Version 8.9
- 3. Batch Wizard (draft)
 - a. New Wizard to replace the *Batch Sort*.
 - b. Version 8.9

9 Sep, 2025

- 1. Image_correct_zero
 - a. Testing of the neighbourhood of zero pixels (using "shift") breaks down for zeroes on image edges. This causing "wrapping" which is bad if the left/right or top/bottom edges are greatly contrasting. Used "extend_image" to extend the image 2 pixels in x,y (as used for various digital filters).
 - b. Also use "neighbours" count for good (non-zero) pixels surrounding these zero pixels for flux map correction, to match use for element images.
 - c. Tested, and works with Batch-Sort, as one of a set of "digital filters" applied to a training DAI.
- 2. Version 8.9a

26 Aug, 2025

- 1. AS MEX H5 device object
 - a. Draft for reading first MEX test HDF5 files.
- 2. Version 8.9

12 Aug, 2025

- 1. Fit_setup
 - a. Load_pcm_parameters

- i. Use 'set_widget_text' to set CUTs file widget, even if blank/none supplied.
- b. Fit_setup_do_fit
 - i. Kill bug that let sxrf_mono=1 remain for non SXRF cases.
- 2. Pixe_fit
 - a. Kill bug that let sxrf_mono=1 remain for non SXRF cases, such as PIXE.
- 3. Grow_tree
 - a. Use 'widget_control, root, /set_tree_visible' to make entire expanded folder visible in tree display (e.g. as used in "File_requester"), instead of positioned at the bottom.
- 4. File_requester_find
 - a. Pass file "find" pattern to 'file_requester_update_list'.
 - i. "Find" used to just show all files in the directory where the first match to the pattern occurred. Similarly, "More" would show all files in the next directory with a match. Now only files that satisfy the "Find" pattern are displayed in the list below.
 - b. Now following "Find", only files that match the requested pattern are displayed.
- 5. file_requester_update_list
 - a. Use the passed 'pattern', if supplied, to only list files that match the pattern.
- 6. Version 8.8z

5 Aug, 2025

- 1. Pixe_fit
 - a. A common problem with fitting SXRF spectra is the effect of the strong scatter peaks. The elastic peak may not be accurate (some beamlines have errors in known beam energy). The Compton peak may be poorly fitted initially until parameters are adjusted. These both skew the fit to the energy Cal parameters and often the Width parameters too (if enabled).
 - b. To avoid the fit to the elastic peak and Compton skewing the fit to the energy cal of a spectrum, 'pixe_fit' now limits 'e_high' to 85% of e_beam, if the yield is for SXRF (z1=0,a1=0), a mono beam (beam.continuum=0) and Cal is free.
 - c. Where 'pixe_fit' is called, it should be called as a prelim pass and then 'pixe_fit' should be called again, but with Cal OFF (see below for 'Fit_setup_do_fit').
- 2. Fit_setup
 - a. Fit_setup_do_fit
 - i. For SXRF (z1=0,a1=0), a mono beam (beam.continuum=0) and Cal is free:
 - 1. Calls 'pixe_fit' as usual first as a prelim, which will fit the spectrum with 'e_high' limited (see above) and fit the Cal and Width (if enabled) parameters.
 - 2. Then it calls 'pixe_fit' again with the Cal and Width parameters fixed, which will fit over the full E range with the Cal and Width preserved.
 - ii. This obviates the need to manually fit it twice (as discussed in the *Worked Examples* for SXRF), first limiting the E range to exclude the scatter peaks, and then again over the full E range with the Cal and Width fixed.
 - b. Fitting SXRF spectra is now (like PIXE) simply a matter of enabling Cal (and possibly Width) and clicking on *Fit*.
- 3. Version 8.8y

27 July, 2025

- 1. FalconX device
 - a. Flip_icr_raw
 - i. Mislabelled method as a Maia method.
- 2. Standards Wizard
 - a. Add a Device droplist to select the raw data device. Tested for "MAIA_DEVICE" and "FALCONX_MERGE_DEVICE".
 - b. Add storage in pstate for the array of available device objects.
 - c. Add event code and an OnRealize routine for the new device droplist.
 - d. Change from using (*pstate).DevObj to *(*pstate).pDevObj throughout.

22 July, 2025

1. EVT
 - a. evt_getcal
 - i. When comparing 'i' index (channel) to list of ADC #s found in file ('n'), needed to add the offset: (*pp[0]).DevObj->start_adc()
 - b. Use the test data for the following to sample a range of start-ADC and offsets:
 - i. Sandia-Primecore U48/Grid (Primecore U48)
 - ii. Uppsala-MPA3/Au_3 (MPA3)
 - iii. Madrid MPA4/Aug (MPA4)
 - iv. APS Regolith-82 (APS List)
 - v. Maia Rock3/111163 (CSIRO Maia)
 - vi. Lund/New 8 element (LUND VME MAC)
2. Image_table_eventcb
 - a. Load_image_table_table
 - i. Check to see if the filename of the current images match the filename of the images used to create the regions in the image table.
 - ii. If not, this means that an "Update: All" has not been done.
 - iii. Pop-up warning, advising of the need to do an "Update: All" before adding a new region to the table.

10 July, 2025

1. Image_table_eventcb
 - a. Load_image_table_table
 - i. Check to see if the elements in a new region sum (from current image) are present in the columns of the region table, as shown.
 - ii. If not, this means that an "Update: All" has not been done.
 - iii. Pop-up warning, advising of the need to do an "Update: All".

30 June, 2025

1. File_pcm_preview
 - a. Preview of PCM file contents for 'file_requester' as called from 'fit_setup'.
2. Fit_setup
 - a. Pass "file_pcm_preview" as preview routine name to 'file_requester' for PCM read.
3. Experimental_angles
 - a. Refined tests of sample-beam-detector (array) geometry to detect conditions like (i) detectors looking at back of sample, or (ii) at glancing angle and (iii) beam hitting back of sample.
4. Geo_array_yield, geo_yield2
 - a. Handle 'bad' error conditions properly, return error=1 and yield=0.0.
5. Blog browser
 - a. Process tag=57 (Report) records, which show blogd statistics.
6. Version 8.8x

24 June, 2025

1. Image_routines
 - a. Analyze_image
 - i. Use same approach as for "areas" on line profiles (traverse, project, project, Spline8, etc.) to detect non-elemental image planes and great these 'as is' in counts, such as for "Rate" and specials as listed in "special_elements" function.
 - ii. 'misc_special' is list of specials. 'nqell' is non-zero for these in 'where' statements testing 'el[i]' against 'misc_special'. In this case, use simple pixel-count version of 'hcharge' vector (called 'hcharge0').
 - iii. Now the traverse plot shows a sensible count rate versus distance.
2. Special_elements

- a. Add “c/s” as a special element as alternative to “Rate”.
- 3. File_lcm_preview
 - a. Preview of LCM file contents for ‘file_requester’ as called from ‘Layer_setup’.
- 4. Layer_setup
 - a. Pass “file_lcm_preview” as preview routine name to ‘file_requester’ for LCM read/write.
 - b. Add “file_yield_preview” for preview of output file too.
- 5. File_yield_preview
 - a. Add display of Alpha, Beta.

10 June, 2025

- 1. Image_table_eventcb
 - a. OnCellSelect_Image_Table
 - i. Try to fix error when doing regions for STIM and ion scattering, where el[2] index becomes illegal.
- 2. file_source_preview
 - a. Preview for file_requester for lab .source and .pink beam files.
 - b. Now called from layer_setup, source_setup, pink_setup, compare_soure, compare_pink, etc. in ‘file_requester’ args.
- 3. file_yield_preview
 - a. Preview for file_requester for yield calc .yield files.
 - b. Now called from fit_setup, layer_setup, compare_yields, etc. in ‘file_requester’ args.
- 4. Version 8.8w

3 June, 2025

- 1. Swap_bytes
 - a. Add recursive handling of Lists, Hashes, Ordered Hashes and Dictionaries.
 - b. Use ‘var_type(t)’ function for more detailed types.
- 2. Image_DA_preview
 - a. Used by ‘file_requester’ to provide preview data from a selected DA matrix file during file selection. This data (element list) is shown in the preview field of the requester.
- 3. Evt
 - a. File_requester called from the DA 'file_button' event now uses the preview routine option to select “image_DA_preview” as the preview routine.
- 4. Spectrum_DA_load
 - a. Uses the File_requester preview routine option to select “image_DA_preview” as the DA preview routine.
 - b. Set /image option on file_requester to make preview of spectrum “image” shown by default. This option (“image”) is a bit ambiguous.
- 5. Select_periodic
 - a. Correct “n_states” (was “n_state”) before ‘periodic_table’.
- 6. Version 8.8v

28 Apr, 2025

- 1. Add “Plot ALL regions” option to “Export→Image Plot” to draw ALL regions on export image plot.
 - a. Define
 - i. Add ‘ShowALLregions’ to /plot_options.
 - b. Save_plot_options
 - i. Increment to version -6 for extra plot_options data.
 - c. Load_plot_options
 - i. Handle version -5 as an old struct and add version -6 using define(/plot_options).
 - d. Plot_image_select
 - i. Add checkbox for “Plot ALL regions”.
 - e. Plot_images

- i. Detect ‘options.ShowALLregions’ true and loop through all regions (if found) and use ‘plot_mark’ for each.
- 2. Version 8.8u

8 Apr, 2025

- 1. Fix case sensitive filenames and dirs used in database build on Linux.
 - a. Fix filenames on PC to match case in routines:
 - i. alpha.txt, element.txt, isotope.txt, mass.txt, proton.txt
 - b. Fix case in routines:
 - i. build_ebel_data, init_xsect.
 - c. Fix case of some projects:
 - i. GUI plugins
- 2. Builder
 - a. Build_project
 - i. If search returns ‘ ’ then return.

1 Apr, 2025

- 1. Bug in device name shown in *Spectrum History* window for old files (pre about 2012).
 - a. Would display as Mpsys_device, when not so.
 - b. Read_spec
 - i. Type of old ‘device’ not declared properly (appears as Float). Now fixed as Integer. Seems default behaviour in IDL has changed at some time.
- 2. Bug with the selection of a ADC # in the *Energy Cal* window for a “Get” of that selected energy calibration.
 - a. Read_spec
 - i. Now form ‘find_offset’ for use in call to ‘get_spec’ to retrieve selected ADC # spectrum:
 - 1. $\text{find_offset} = \text{find} - 1 - \text{adc_offset_device}(\text{obj})$, clipped at zero,
 - a. where ‘find’ is the *Cal* Get droplist index (e.g. 0 for “any”, 1 for “0”, 2 for “1”, etc.).
 - b. The ‘adc_offset_device(obj)’ function returns 0 for devices where the ADC # start at 1, -1 for devices where the ADC # start at 0 and 2 for devices where the ADC # start at 3, etc. (i.e. “start ADC” -1).
 - ii. Tested OK for a range of device spec files with different Start ADC and offsets.
 - iii. Note that some old spec files have inconsistent ADC # shown in the “label” field.
- 3. Version 8.8t

27 Mar, 2025

- 1. Revisit Linux IDL display/resize bug
 - a. Background
 - i. In the main *gImage* window, when resized (either by dragging the window size or using the “+”, “-“ buttons) it sometimes displays the image offset in Y, with grey beneath and the top of the image truncated. This only happens when the whole image is visible and hence (normally) the scroll bars disappear.
 - ii. This only happens under Linux, and has persisted through IDL 8.8 to 9.1.
 - iii. And only if the Y scroll bar disappears.
 - iv. Attempts to use the viewport position controls fail to fix this.
 - v. Tests manually using the “tv” command, to draw an image into the Draw widget’s wid also show this offset, but not on a fresh window (using the “window” command).
 - b. Work-around
 - i. The previous work-around simply prevented the scroll bars from disappearing.
 - ii. The new work-around allows the X scroll bars to disappear, but not Y.
 - iii. It also adjusts this to the pixel level, to minimize the area of image hidden in Y.

2. Set_image_view
 - a. Add new offsets 'scr_xtrim' and 'scr_ytrim' to prevent Y scroll bars going in setting 'new.w', 'new.h'. These are zero except for Linux.
3. OnSize_image
 - a. Add new offsets 'scr_xtrim' and 'scr_ytrim' to prevent Y scroll bars going in setting 'w', 'h'. These are zero except for Linux.

24 Mar, 2025

1. Layer_setup
 - a. Problem arose if manual enter parameters into layer setup (not restore from LCM).
 - i. Then 'beam' not defined.
 - b. 'calculate-button' event:
 - i. Only assign beam.continuum and beam.energy if 'beam' is defined.
2. Geo_yield2
 - a. Move 'beam2' spectrum code inside the continuum==true if block.
3. Compare tests:
 - a. Tested (i) simple PIXE yield calc (single detector) – donuts2, and (ii) MM continuum yield calculation with Maia detector – rock-slab-poly2.
 - b. Used 'compare_yield' test: Results equal to reference yields.

24 Mar, 2025

1. Geopixe_default
 - a. Tests for valid "path data" and "path config" in '.geopixe/geopixe.conf' file only happen once now, reducing annoying popups.

14 Mar, 2025

1. Geopixe_default
 - a. Tests for valid "path data" and "path config" in '.geopixe/geopixe.conf' file.
 - b. Pops up a warning if these are not setup, suggests Edit of "geopixe.conf" file.
2. Strip_non_alphanumeric, strip_non_print
 - a. Extended to vector string arguments.

5 Mar, 2025

1. Maia_launch
 - a. maia_launch_version2
 - i. Add set *antialias.enable*, once and for all to enable antialiasing in the Maia FPGA pipeline to prevent aliasing using Linearization and Gain-trimming.
 - b. Version 8.8s
2. GeoPIXE
 - a. Version 8.8s

4 Mar, 2025

1. Plot_maia_parameters
 - a. This calls 'file_requester', which may use 'file_search2', which uses the 'progress' bar. The 'progress' bar will set a new window to draw the progress bar in.
 - b. Hence, in 'plot_maia_parameters', do not call 'file_requester' between opening a new window and plotting to it.
2. Pulser_FWHM_map_spectrum_plugin
 - a. Don't need to open window with 'window,0' as this is done in 'plot_maia_parameters'.

17 Feb, 2025

1. Petra P06 H5 Nexus device object (draft)

- a. Reads P06 tree of NXS files into spectra.
 - b. Get flux and dwell working, but no gain scales.
2. Scan_list
 - a. Updated tests of python and IDL versions in scan_list.
 - b. Fixed errors in bin/ scripts for this.
 - c. Changed it to make settings from 'geopixe.conf' take precedence, if found.
3. Maia_launch
 - a. Fixed bug in LED[3] used to flag all background processes running.

12 Feb, 2025

1. Petra P06 H5 Nexus device object (draft)
 - a. Added adding 'adc_*/value1, value2, ...', 'qbpm_*/value1, value2, ...' as PVs.
 - b. Added reading this PV in 'read_setup' for each data file.

4 Feb, 2025

1. Python_valid
 - a. Check python version against IDL for compatibility.

 IDL version	 Python version										
	2.7	3.4	3.5	3.6	3.7	3.8	3.9	3.10	3.11	3.12	
8.5	✓	✓									
8.5.1	✓	✓									
8.5.2	✓	✓	✓								
8.6	✓	✓	✓								
8.6.1	✓	✓	✓	✓							
8.7	✓	✓	✓	✓							
8.7.1	✓		✓	✓							
8.7.2	✓		✓	✓							
8.7.3	✓		✓	✓							
8.8				✓	✓	✓					
8.8.1				✓	✓	✓	✓				
8.8.2					✓	✓	✓	✓			
8.8.3					✓	✓	✓	✓			
8.9						✓	✓	✓			
9.0						✓	✓	✓	✓		
9.1							✓	✓	✓	✓	

NOTE: IDL versions prior to 8.5 do not support Python bridge functionality.

This fixes an error in doing these tests in Maia-Control.

2. Maia_control
 - a. Check python against IDL using 'python_valid()'.

27 Jan, 2025

1. File_requester
 - a. 'updir' was stopping one level short. Fixed.
2. Detector_update
 - a. If a detector is not found on path1 (geopixe_root), path2 (prefs.path.config) or the detector file's path, then popup file_requester (with updir=3 from local dir) to prompt for it, and append it to the list (at end, not alphabetically sorted).
3. Fit_setup
 - a. Only read detector once: pending after normal detector entry and done after yield detector entry.
 - b. As detector file is saved in PCM with no path, use the path for the PCM as a start (as well as config/detectors in 'detector_update').

- c. Make detector Layout behave similarly, inheriting the path for the detector file.
- 4. Deleted rogue SAV file
 - a. A plugin (FWHM map) had been compiled into the local project dir.
 - i. This SAV file then gets included in the next compile in that project (a nasty habit of IDL).
 - ii. It included 'resolve_all', which means it included ALL GeoPIXE routines into the plugin's SAV file.
 - iii. On running GeoPIXE, these SAV files get loaded and write over newer versions of many routines that have been compiled (into GeoPIXE.sav) since the plugin. This of course a really bad thing, and confusing for debugging.
 - b. Deleted the offending SAV file.
 - i. There should be NO SAV files in any plugin dir, only in the "geopixe" Runtime dir.
- 5. Version 8.8r.

20 Jan, 2025

- 1. maia_launch
 - a. Instead of just reporting an over-leakage event, it now takes action to set the bias back to minimum.
- 2. maia_launch_read_da_info
 - a. Removed illegal ref to *pl.

10 Jan, 2025

- 1. maia_launch
 - a. Corrected code to check compatibility between python and IDL.
 - b. Maia Version 8.8r
- 2. Idl_query
 - a. Added code to check compatibility between python and IDL.

8 Jan, 2025

- 1. maia_launch
 - a. The frame=0 option on widget_text used to have this behavior:
 - i. Ignored under Windows, frame drawn anyway.
 - ii. Seemed to draw a frame under Linux as well.
 - b. Now in v9.1 IDL
 - i. Windows does not draw a frame.
 - ii. Linux still does, weird.
 - c. Fixed by explicitly using frame=1 for widget_text
 - i. Status field, help field, blog number field.
 - ii. Under Linux, frame seems a bit wider now.
- 2. Idl_query
 - a. Lmgr2
 - i. Can't spawn "activate" in IDL v9, as it does not exist; skip.
- 3. Version 8.8q

7 Jan, 2025

- 1. Plot_maia_parameters
 - a. Add a call to "file_requester(/read, /skip_if_exists, updir=2, ...) to find the default layout file 'Maia_384C.csv' on a neighbouring path in the runtime distribution.
 - b. This is used in: 'Pulser_FWHM_map_spectrum_plugin', 'Peak_Stats_spectrum_plugin', 'Peak_Fit_Stats_spectrum_plugin' and compiled in main 'GeoPIXE.sav'. The latter ('Peak_Fit_Stats_spectrum_plugin') does supply an explicit filename.
 - c. Only need to recompile main GeoPIXE.
- 2. Merged develop branch, which had conflicts to fix:

- a. Firstly, I forgot I was in “develop” when upgrading the Workspace in IDL 9.1.
- b. No way to fix this except merging “develop” into main.
- c. There were duplicates: bat file to run IDLDE, GeoPIXE.sav.
- d. Deleted the sav files and fix bat, git Add and Commit.
- e. Did not fix new “No explicit project encoding” project warnings.

3 Dec, 2024

1. Plot_corr
 - a. Add options for /PNG (bit mapped) and /JPEG (true) plots for *Association* window following prescription in ‘plot_images’.
2. Plot_corr_select
 - a. Add options for /PNG and /JPEG plots for *Association* window.
3. Corr_export
 - a. Add options for /PNG and /JPEG plots for *Association* window.
4. Corr_event
 - a. Make /JPEG plot the default for call to ‘corr_export’.
5. Gimage
 - a. Add Test menu item to test Pink Beam sources, calling ‘compare_pink’.
6. Export_da2
 - a. Added more notes in software organization doc for binary export for DA real-time imaging.

20 Nov, 2024

1. Compare_yield
 - a. Test for New and Ref both array detectors, else flag error in output file.

11 Nov, 2024

1. Compare_fit
 - b. Add ability to deal with a PFR file with multiple rows (e.g. for ROI or individual array detectors).
 - c. Shows any models that differ by more than 0.1 % generally and 3% for fitted areas/concs.
 - d. Veto “Compton”, “elastic” and “sum” in comparisons.
2. Compare_source
 - a. Add ‘tol’ argument, defaults to 0.001.
3. Compare_pink
 - a. Add ‘tol’ argument, defaults to 0.001.
4. Compare_yields
 - a. Add ‘tol’ argument, defaults to 0.001.
5. Builder
 - a. Make sure !path is not cumulative as projects are processed.
 - b. Output ‘build.spro’ always to “main” dir.
6. Gimage
 - a. Add a “tests” menu for the ‘compare’ routines.

28 Oct, 2024

1. Compare_fit
 - e. New routine to compare fit results files (.PFR files) as a step towards a unit test.
 - f. Simply prints out any inconsistencies found to the ‘output’ file.
 - g. Also reports diffs for derived area, conc, MDL, etc.
2. Pixe_fit
 - a. The order of “state” and “e_beam” in the ‘ryield’ struct have been reversed at some stage (2 instances of ‘ryield’). But this effects the format in the PFR fit results file. Hence, newer PFR files read back with these switched.

- b. Fortunately, these parameters do not get used - they are for info only. However, the 'compare_fit' routine flagged them as inconsistent.
 - c. Hence, they have been switched back, so that new PFR files are consistent with old ones.
 - d. This will mean some instances of PFR file in between remain switched, which will be flagged harmlessly by 'compare_fit'.
- 3. Pixe_initial
 - a. For negative Z, and Compton line index, name "element", e.g. as "cIn".
 - b. But do these cIn lines inherit normal In rel-ints, rather than from beam lines?
 - i. Rel-ints for Comptons lines do come from beam lines. Good. However, the rel-int of the source lines is coming from normal rel-ints at the moment.
 - ii. Fixed this in 'select_element_lines'.
- 4. Sum_peaks
 - a. Use abs(z) to form el names for lines (to account for -Z used for Comptons).
- 5. Select_element_lines
 - a. Use -Z for Compton peaks from source lines (mark all changes with ;@10-24).
 - b. Add option (in line) to match lines for any element that is also in source, to source rel-ints.
 - i. Uses 'match_source_intensity' = 1 in code.
 - c. Do not change Continuum Beam Lines rel int here (done now in 'source_calculate').
- 6. Source_calculate
 - a. Calculate change to lines rel due to polycapillary (not in 'select_element_lines' now).
- 7. Version 8.8p

16-21 Oct, 2024

- 1. Compare_source
 - a. New routine to compare Lab source model results (.source files) as a step towards a unit test for the lab source modelling.
 - b. Checks beam.model should be "1".
 - c. Shows any results that differ by more than 0.1 %.
 - d. Simply prints out any inconsistencies found to the 'output' file.
 - e. Also reports diffs for derived source spectra.
- 2. Sig_change
 - a. Shows any results that differ by more than a 'tol' value, defaults to 1 ppm.
- 3. Source_calculate
 - a. Veto any input or interpolated polycapillary transmission table values less than zero.
- 4. Source_setup
 - a. Fix the mapping of polycapillary and monochromator widgets.
- 5. Compare_pink
 - a. New routine to compare Pink Beam source model results (.pink files) as a step towards a unit test for the pink beam modelling.
 - b. Checks beam.model should be "2".
 - c. Ignores polycapillary, for later.
 - d. Shows any results that differ by more than 0.1 %.
 - e. Simply prints out any inconsistencies found to the 'output' file.
 - f. Also reports diffs for derived pink beam spectra.
- 6. Compare_yields
 - a. Needs to switch between 'compare_source'; and 'compare_pink' depending on beam.model.
 - b. Tests for consistent beam.model.

7 Oct, 2024

- 1. /sec_fl in yield calculation - tidy up.
 - a. Geo_array_yield
 - i. Argument 'sec_fl' not used, remove
 - b. Results_properties

- i. Remove arg 'sec_fl' passed to geo_array_yield.
 - c. Geo_yield2
 - i. Tidy comments about 'sec_fl'.
- 2. Compare_yields
 - a. New routine to compare yield calculation results (.yield files) as a step towards a unit test for the yield modelling.
 - b. Shows any results that differ by more than 0.1 %.
 - c. Simply prints out any inconsistencies found to the 'output' file for the time being.
- 3. Geopixe_do_command
 - a. If first agv[0] is NOT a GCF file name, then assume a simple command execution, with three arguments: "command, files (string vector in stringify format), output".
 - b. This enables the test to be run in a script or workflow.
 - c. See test in BAT script: "Unit test Runtime GeoPIXE.bat".
- 4. Q_to_xyz
 - a. Routine to convert index vector 'q' into a 3D array to vectors of the indices for x,y,z in the array. Analogous to old 'q_to_xy' for a 2D array.
- 5. File_requester
 - a. Will now call 'startupp' if geopixe_root is not defined.

2 Oct, 2024

- 1. Make branch 'develop' for development and beta release.
 - a. This is identical with current 'main' at the moment.
- 2. Recommend to make other branches off 'develop' for feature additions and other fixes.

1 Oct, 2024

- 1. Export_DA2
 - a. Accepts keywords for pileup, throttle and linear, which can be set from fields in Evt window.
 - i. Linear is not used at present, as we don't have tools for realtime use of the Maia v2 Linearization functions.
 - b. Binary (dmx) mode changed:
 - i. Does not output individual detector E cals to the export file. These are supposed to be set elsewhere and should not be part of the DA matrix.
 - ii. Version now -2.
 - c. iThemba (dmm) mode changed:
 - i. Similar to DMX binary, but limits size of DA matrix (compressed if necessary).
 - ii. Does not output individual detector E cals to the export file. These are supposed to be set elsewhere and should not be part of the DA matrix.
 - iii. Version now -2.
 - d. Further work:
 - i. Does not export the *rGamma* matrix or *Pure* arrays. This is needed(?) to properly integrate contributions across an array (using selected channels) for quantitative estimation from regions/spectra, or at least for the spectra overlays.
- 2. EVT
 - a. Add "Exp" button next to DA matrix file fields to call 'export_DA2' to export the chosen DA matrix for use in a data acquisition system for realtime imaging and spectra analysis.
- 3. Fit_setup
 - a. Used to call 'export_DA' from "Export" button next to "Generate DA" button to output an expot file for use in a data acquisition system for realtime imaging and spectra analysis.
 - b. Now it calls 'Export_DA2', which does not include the pointers to spectra and does not output individual detector E cals to the export file. These are supposed to be set elsewhere and should not be part of the DA matrix. These files now have version = -2.

4 June, 2024

1. spectrum_display_eventcb
 - a. Spectrum_Menu_Clear_Cal
 - i. Only check second string in label for “/X” and “/Y”, not whole label, which may include path components with these sub-strings. Only want to test the post-fix tags.
2. wizard_standards
 - a. Allow “serial” to be blank, and match with a blank in “standards.csv” table.
 - b. Do not set “On” zero if serial is blank.
3. NSLS MARS Ge device
 - a. Swapped to big endian byte order for read in device.
4. Version 8.8n

3 June, 2024

1. Maia device
 - a. Added an options widget to adjust/correct a skew in X values, expressed as “correct X by one for every ‘n’ Y rows”, with this set via a droplist.
 - b. Read/write options now version -7 to cater for skew.x
 - i. This will require this new version Maia device to read DAI file.
 - c. ‘Read_buffer’ - corrects x1 by y1 (i.e. $x1 = x1 - \text{long}(y1 / \text{float}(\text{self.sort_options.skew.x}))$). This is done before any xoffset, so should work fine in cluster mode. Also done before any flip axis options, so applies to raw X1,Y1.
2. GUI Image Table XFM AS plugin
 - a. image_table_xfm_as_gui_plugin
 - i. Renamed this plugin from “image_table_xfm_as_gui_plugin” for the XFM beamline of the Australian Synchrotron.
 - ii. Writes a CSV table with region details to be loaded into the online run spreadsheet.
3. GUI Image Table XFM NSLS plugin
 - a. image_table_xfm_nsls_gui_plugin
 - i. Adapted this plugin from the AS version for the XFM beamline of the NSLS-II synchrotron, BNL, NY.
 - ii. Writes a CSV table with region details to be loaded into the online run spreadsheet.

31 May, 2024

1. Builder issue
 - a. Some plugins are missing routines. These used to be done as IDLDE build options, not supported in new ‘builder’.
 - b. Needed to resolve missing routines and save/routines a new SAV file.
 - c. Applies to: linearize2_spectrum_plugin, linearize_cuts_energies_spectrum_plugin, linearize_cuts_fit_offset_spectrum_plugin, linearize_cuts_spectrum_plugin, linearize_spectrum_plugin.
 - d. Need to add: *lmfit*.
 - e. Add a new place for miscellaneous resolves: ‘resolve_misc’.
2. Resolve_misc:
 - a. Resolve routines: *lmfit*.
 - b. Users who add plugins can also resolve their own added routines before saving a SAV file. But many basic ones can be added here, as this is not supported yet in builder.

19 May, 2024

1. Notes about /modal, /floating, blocking (File Requester and Progress)
 - a. Originally, ‘file_requester’ was setup as a normal modal widget, which blocks until it closes. It’s also floating, which means it sits in front of other windows.
 - i. Blocking is similar, keeping control in xmanager near the end of the main file requester program.

- ii. We don't want to set `no_block=1` on `xmanager`, to keep it modal.
 - iii. However, we should never set `no_block=0` on `xmanager`
 - 1. This does some weird stuff, like disable debugging.
 - 2. Simply, *omit* the `no_block` keyword to `xmanager` to achieve the same result. See 'file_requester' code.
- b. Then `file_requester` was changed to permit a progress bar popup while searching for a file match using "Find".
 - i. i.e. It was found that you could use `modal=0`, `floating=1` on the top base widget and *omit* `no_block` on `xmanager`.
- c. However, then `file_requester` could not work properly if called from another modal widget (e.g. 'flux_select').
 - i. In that case, we use another option `/within_modal` to remind `file_requester` to use `/modal` (and disable the Find).
 - ii. **Only use `/within_modal` when called from a modal widget.**
- 2. `File_requester`
 - a. New `/within_modal` option, if called from a modal popup (e.g. 'flux_select').
 - b. This means that the file "Find" does not work as the Progress window cannot function properly then.
- 3. `Flux_select`
 - a. As this is a modal popup, all calls from it to 'file_requester' use `/within_modal`.
- 4. `Spectrum_load_prep`
 - a. Call 'file_requester' for pileup, linearize and throttle with `'updir=3'` so that it looks in the local neighbourhood for a file match.
- 5. Version 8.8m.

15 May, 2024

- 1. Plugin: Cal by centroids
 - a. `peak_cal_cut_centroid_spectrum_plugin`
 - i. Use a common to save the 2 energies, so they appear next invocation.
- 2. `Write_source`, `write_pink`, `read_source`, `read_pink`
 - a. Only set 'file' in struct if file opened here, not if 'unit' passed.
- 3. `Fit_results/save_fit_results`
 - a. Write a new version -16 and write 'continuum' first, then 'model'
 - b. Then call either source or pink write.
- 4. `Read_fit_results`
 - a. New code for version -16, to read 'continuum' first, then 'model'.
 - b. Then call either source or pink read.
- 5. `Pink_calculate`
 - a. Use `file_requester(/skip_if_exists)` to search local tree and also along 'path' tree for a file match.

6 May, 2024

- 1. Continuum source
 - a. Moved back into 'main/xray' and 'main/' for 'source_setup'.
 - b. Delete "continuum_Source" plugin project.
- 2. Pink beam source
 - a. New pink beam routines in 'main/xray' and 'main/' for 'pink_setup'.
- 3. `Pink_setup`
 - a. New setup for a pink beam that parallel 'source_setup' for lab sources.
 - b. Uses FE beam spectrum and up to 4 mirrors, based on CXRO reflectivity data files.
 - c. Disable inline optics extras for now.
- 4. Define
 - a. New `/pink` for pink beam

- b. Set **model=1 for lab, model=2 for pink**, as was not used before.
- 5. Layer_setup
 - a. No source plugin load, fixed new droplist options for photon sources.
 - b. (*p).source is now a pointer to either a lab source or pink beam 'beam' struct
 - c. (*p).source → (*p).source in most places.
 - d. Cater for 'new-pink' Notify event, similar to new-source.
 - e. 'beam-mode' now just handles lab and pink in "else".
 - f. 'load-source' now handles cases of 6:lab, 7:pink beam.
 - g. 'new-source' launches 'source_setup' or 'pink_setup' according to beam.mode.
 - h. Add 'ppink' to pstate for notify to pink_setup.
- 6. Geo_yield2
 - a. At the end, add "rel_int[1:*,q] = 0.0" for the zero 'q' array, to avoid NaN 'rel_int' for elements where the yield drops to zero.
 - b. Some bad elements get through, despite 'zero', so add this to 'q' test:
 - i. $Q = \text{where}((\text{zero eq } 1) \text{ or } (\text{finite}(\text{rel_int}[1,*]) \text{ eq } 0))$
 - c. Catch all /0 conditions that affect: branch_ratio, ppm, mass_yield, total_yield, rel_int.
- 7. Geo_array_yield
 - a. Catch all /0 conditions that affect: rIntensity, enhance, rY.
- 8. Select_element_lines
 - a. Detect lack of "Lines" tag in 'beam' struct and set add_lines=0
- 9. Write_yield
 - a. Write beam.model before beam, if 'use_beam'.
 - b. New version -11
- 10. Read_yield
 - a. If version -11, after read 'use_beam', read 'model'.
 - b. If 'model = 2 then switch to a pink beam 'beam' struct.
- 11. Read_beam
 - a. Read a text file of energy versus beam or CXRO reflectivity data.
 - b. Has a 'skip=' option to skip header of CXRO files.
 - c. Has option 'remap_energy=' to remap E,data onto a given energy vector.
 - d. Clip output to >0
- 12. Pink_calculate
 - a. Just use FE beam * mirror and filter reflectivity/transmission, with no solid angle, etc. terms applied. Commented out for now.
 - b. Disable inline optics now, as this involves solid-angle considerations also.
 - c. Set e_beam, which is used to 'init_xrf' in 'get_lines':
 - i. $\text{pink.energy} = E[\text{max}(\text{where}(\text{spec gt } 1.0\text{e-}10))]$
 - d. Add pressure and temp args to 'transmit' like in 'source_tube_spectrum' called from 'source_calculate' to cater for spectra with P.T values.
- 13. Read_pink
 - a. Read a pink beam file, like read_source.
- 14. Write_pink
 - a. Write a pink beam file, like write_source.
- 15. fit_recalculate_yields
 - a. Add case to either 'source_calculate' or 'pink_calculate' based on beam.model
 - b. Note for non continuum beam these return passively.
- 16. Version 8.8k.

22 Apr, 2024

- 1. Maia Launch
 - a. Maia_launch_version2
 - i. Cater for 'number' zero for spectra, et2d, roi.
 - ii. Zero means the variable vanishes in Kandinski.

- b. `Maia_launch_initial`, `maia_launch_read_enable`, `maia_launch_read_groups`
 - i. Only set spectra parameters if number not zero
 - c. `Maia_launch`
 - i. Only setup groups shared memory is number > 0
 - ii. Catch anywhere `shrmem` referenced
 - d. `Maia_update_group_spectra`
 - i. Return if no shared mem
- 2. `Spawn_blog_parameters`
 - a. Pass in region enable, else veto spawn of region spectra
- 3. `Maia_setup`
 - a. `Maia_setup_event`, `maia_setup_apply_groups`
 - i. Only set spectra parameters if number not zero
- 4. `Maia_client_parameters`
 - a. Test for `(*pm).number.spectra`, roi and skip enable.
- 5. `Startupp`
 - a. Construct path to 'maia' and 'daq' subdirs correctly.
- 6. `pixe_fit`
 - a. Set default value for 'sum_deficit' to 0.5%
- 7. Version 8.8j

8 Apr, 2024

- 1. File-requester
 - a. `File_requester_preview`
 - i. Use `*( (*pstate).p ).pfile` (array) for files, rather than `(*pstate).file` (concatenated list).

14 Feb, 2024

- 1. Blog browse
 - a. Change format of output to correct a field width.
- 2. GitHub
 - a. Fresh load of GeoPIXE to local Git and to GeoPIXE on GitHub at URL:
 - b. <https://github.com/CSIRO-GeoscienceAnalytics/GeoPIXE> as branch "main".

27 Nov, 2023

- 1. Use *WinMerge* to view and merge changes across from GeoPIXE-source3 to *Open Source* (between Mar 27 and Nov 27). Take care to:
 - a. Not merge across differences due to licensing.
 - b. Watch for different path constructs, e.g. for Wizards.
- 2. Need to run all tests

24 Nov, 2023

- 1. GeoPIXE
 - a. `gImage`
 - i. Add menu for Export → Simple Image → Save as TIFF
 - ii. Call `Image_Save_GIF`, Event, /TIFF
 - b. `Image_Save_GIF`
 - i. Add /TIFF option
 - ii. For TIFF use 'write_tiff' to save as 32-bit float TIFF.

8 May, 2023

- 1. GeoPIXE
 - a. Removed modules with non CSIRO code, although the code had been supplied by the laboratories to enable an import object or plugin to be devised for their data and attribution was included.

- i. These include:
 - 1. Devices:
 - a. “APS LST”, “ESRF EDF”, “GSE-CARS MCA”, “Lund VME”, “NSLS MCA”, “NSLS NetCDF”.
 - 2. Plugins:
 - a. “Image Align”, “Image Combine Align”, “Image Shear Correct”.
 - 3. Background:
 - a. Bayes.
 - 4. These may be added to the GitHub repository by the labs concerned at a later time.
- 1. Builder
 - a. Add build for GUI plugins.
- 2. Eclipse “clean up”
 - a. Move .log and log files to “old/old-files-Open-Source” directory, from:
 - i. .metadata
 - ii. .metadata/.plugins/org.eclipse.ui.workbench
 - b. Move the following dirs with history to “old” as well:
 - i. .metadata/.plugins/org.eclipse.core.resources/.history
 - ii. .metadata/.plugins/org.eclipse.ltk.core.refactoring/.refactorings

21 Dec, 2022

- 1. builder (NEW)
 - a. Build a script “build.spro” to be used (use: “@build.spro”) to selectively build the SAV files, by categories ('all', 'plugin', 'back', 'spectrum', 'image', 'device', 'wizard', 'source', 'maia', 'daq', 'main', 'browse']).
 - i. This avoids issue with poor control of !PATH and using ‘.compile’ by file-name, rather than ‘resolve_routine’.
 - b. Does .full_reset_session for each project build to clear compiled routines.
 - i. But this makes it very slow if run from IDLDE.
 - c. !PATH built afresh for each project build to include whole “main” tree plus the project.
 - d. Build_project:
 - i. Does the fiddly work for builder.
 - e. Build_database
 - i. Does the database build part.
 - f. The following builds do a resolve_all:
 - i. Main, IDL Query, GeoPIXE update and Builder.
 - ii. IDL Query now does not need the make routine anymore.
 - iii. GeoPIXE update of a non-GUI version is not done yet.
- 2. projects:
 - a. Needed to enforce consistency in naming:
 - i. SAV file name constructed from project name, with additional options to tag a suffix to SAV filename.
 - ii. Build from Eclipse must match this SAV filename.
 - iii. Deleted some projects not needed for open source, such as junk tests, etc.
 - b. image_table_evt
- 3. Organization
 - a. The “builder” imposed some rules that needed to be enforced:
 - i. Plugins must start with “Back”, “Spectrum”, “Image” and end with “plugin”.
 - ii. Except “source” and “Wizards” plugins.
 - iii. Maia projects start with “Blog” or “Maia”.
 - iv. All Maia SAV end up in /maia, including maia_control.sav and maia_scan_list.sav.
 - v. All DAQ SAV end up in /daq, including daq_control.sav.
 - vi. All browsers start with “Browse”.

- vii. Some get renamed: mm_scan_list → maia_scan_list, GeoPIXE worker → GeoPIXE parallel, “ftp update” → “GeoPIXE update”.
 - viii. ‘misc’ compiles/builds include ‘geopixe_index’, ‘geopixe_update’, “builder”, ...
 - ix. Fake Blogs divided into ET2 and DA2 versions.
 - b. Database build
 - i. ‘make_database.pro’ has changed, so it gets called from ‘builder’.
 - c. Build
 - i. Use ‘builder’ (pops up index selection) to select which classes to build, which creates “build.spro” (note: this will be in “geopixe” for runtime execution and “main” for IDLDE execution). A pop-up reminds the user of “build.spro”, its path and the need to run “@build.spro” from the IDL command line after a “cd” to path.
 - ii. “@build.spro” from IDL command line to build (after “cd” to the dir). This is much faster than in IDLDE due to long lag after a full reset.
4. Version 8.7o.