

acc. to 29 CFR 1910.1200 App D

Tire Slick

Revision Date: 12/16/2024

SECTION 1: Identification

1.1 Product Identifier

Trade Name Tire Slick
Product Number 20-00064

1.2 Relevant Identified Uses

Relevant Identified Uses Tire Dressing

1.3 Details of the Supplier of the Safety Data Sheet

Car Wash Technologies 322 19th St SW Forest Lake, MN 55025 United States

Telephone: (651) 272-5459

1.4 Emergency Telephone Number

(651) 272-5459.

SECTION 2: Hazard(s) Identification

2.1 Classification of the Substance

Classification Acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

| Hazard Statement | Hazard Class | Category |
|------------------|-----------------------------------|----------|
| H318 | serious eye damage/eye irritation | 1 |

Employ good industrial hygiene practice

2.2 Label Elements



Labelling acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Signal Word **DANGER**

- Hazard Statements

H318 Causes serious eye damage.

- Precautionary Statements

P280 Wear eye protection/face protection.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing.

P310 Immediately call a poison center/doctor.

2.3 Other Hazards

Special danger of slipping by leaking/spilling product.

United States: en Page: 1 / 10

acc. to 29 CFR 1910.1200 App D

Tire Slick

Revision Date: 12/16/2024

SECTION 3: Composition/Information on Ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Description of the Mixture

| Name of Substance | CAS No | Wt% |
|------------------------|-------------|-----------|
| Water | 7732-18-5 | 50 - < 75 |
| Poly(dimethylsiloxane) | 63148-62-9 | 25 - < 50 |
| 2-Butoxyethanol | 111-76-2 | 5 – < 10 |
| Proprietary Solvents | Proprietary | 1-<5 |

SECTION 4: First-Aid Measures

4.1 Description of First-Aid Measures

General Notes

Do not leave affected person unattended. Remove victim out of the danger area. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

Following Inhalation

Provide fresh air. If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions.

Following Skin Contact

Wash with plenty of soap and water.

Following Eye Contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 15 minutes, holding the eyelids apart.

Following Ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

4.2 Most Important Symptoms and Effects, Both Acute and Delayed

Symptoms and effects are not known to date.

SECTION 5: Fire-Fighting Measures

5.1 Extinguishing Media

Suitable Extinguishing Media

Water spray, BC-powder, Carbon dioxide (CO2)

5.2 Special Hazards Arising from the Substance or Mixture

None.

5.3 Fire-Fighting Measures

In case of fire and/or explosion do not breathe fumes. Coordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

United States: en Page: 2 / 10

acc. to 29 CFR 1910.1200 App D

Tire Slick

Revision Date: 12/16/2024

SECTION 6: Accidental Release Measures

6.1 Personal Precautions, Protective Equipment and Emergency Procedures

For Non-Emergency Personnel

Remove persons to safety.

For Emergency Responders

Wear breathing apparatus if exposed to vapors/dust/aerosols/gases.

6.2 Environmental Precautions

Do not empty into drains, surface water or soil. If the product has entered a water course, sewer or soil, inform the responsible authority.

6.3 Methods and Material for Containment and Cleaning Up

Advice on How to Contain a Spill

Prevent entry to sewers and public waters. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

Advice on How to Clean Up a Spill

Collect spillage. Ensure good ventilation and exhaustion. Place in appropriate containers for disposal.

6.4 Reference to Other Sections

Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and Storage

7.1 Precautions for Safe Handling

Measures to Prevent Fire as well as Aerosol and Dust Generation

Use local and general ventilation. Use only in well-ventilated areas.

Advice on General Occupational Hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for Safe Storage, Including Any Incompatibilities

There Is No Additional Information.

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials" (Section 10).

SECTION 8: Exposure Controls/Personal Protection

8.1 Control Parameters

Occupational Exposure Limit Values (Workplace Exposure Limits)

| Coun try | Name of Agent | CAS No | Iden- tifier | TWA [ppm] | TWA [mg/m ³] | STEL [ppm] | STEL [mg/m ³] | Ceil- ing-C [ppm] | Ceil- ing-C [mg/m ³] | Nota- tion | Sourc e |
|-------------|-----------------|----------|-----------------|--------------|--------------------------------|---------------|---------------------------------|-------------------------|---|---------------|-------------------------|
| US | 2-butoxyethanol | 111-76-2 | TLV® | 20 | | | | | | | ACGIH® 2024 |
| US | 2-butoxyethanol | 111-76-2 | REL | 5 (10 h) | 24 (10 h) | | | | | Н | NIOSH REL |
| US | 2-butoxyethanol | 111-76-2 | PEL | 50 | 240 | | | | | Н | 29 CFR 1910.10 00 |

United States: en Page: 3 / 10

acc. to 29 CFR 1910.1200 App D

Tire Slick

Revision Date: 12/16/2024

| Occup | Occupational Exposure Limit Values (Workplace Exposure Limits) | | | | | | | | | | |
|-------------|--|----------|-----------------|--------------|--------------|---------------|---------------------------------|-------------------------|---|---------------|------------------|
| Coun try | Name of Agent | CAS No | Iden- tifier | TWA [ppm] | TWA [mg/m | STEL [ppm] | STEL [mg/m ³] | Ceil- ing-C [ppm] | Ceil- ing-C [mg/m ³] | Nota- tion | Sourc e |
| US | 2-butoxyethanol (EGBE) (glycol monobutyl ether) | 111-76-2 | PEL (CA) | 20 | 97 | | | | | Н | Cal/OSH A PEL |

Notation

Ceiling-C ceiling value is a limit value above which exposure should not occur

H absorbed through the skin

STEL short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period

(unless otherwise specified)

TWA time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-

weighted average (unless otherwise specified

Biological limit values

| Country | Name of Agent | Parameter | Nota- tion | Identifier | Value | Source |
|---------|-----------------|-------------------------|---------------|------------|----------|-------------|
| US | 2-butoxyethanol | Butoxyacetic acid (BAA) | hydr, crea | BEI® | 200 mg/g | ACGIH® 2024 |

Notation

crea creatinine hydr hydrolysis

8.2 Exposure Controls

Appropriate Engineering Controls

General ventilation.

Individual Protection Measures (Personal Protective Equipment)

Eye/Face Protection

Wear eye/face protection.

Skin Protection

- Hand Protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

- Body Protection

Wear suitable protective clothing.

- Other Protection Measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Respiratory Protection

In case of inadequate ventilation wear respiratory protection.

Environmental Exposure Controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

United States: en Page: 4 / 10

acc. to 29 CFR 1910.1200 App D

Tire Slick

Revision Date: 12/16/2024

SECTION 9: Physical and Chemical Properties

9.1 Information on Basic Physical and Chemical Properties

Appearance

| Physical State | Liquid |
|----------------|--------|
| Color | White |
| Foam Color | None |
| Fragrance | None |

Other safety parameters

| pH (value) | 7 |
|---|--------------------|
| Melting Point/Freezing Point | No Data Available |
| Initial boiling point and boiling range | No Data Available |
| Flash Point | >200 °F |
| Evaporation rate | No Data Available |
| Flammability (solid, gas) | No Data Available |
| Vapor pressure | No Data Available |
| Density | 1 g/ _{ml} |
| Solubility(ies) | No Data Available |

Viscosity

| Other Information | There Is No Additional Information |
|-----------------------|-------------------------------------|
| Oxidizing Properties | None |
| - Dynamic viscosity | 1,500 cP |
| - Kinematic viscosity | 1,500 ^{mm²} / _s |

SECTION 10: Stability and Reactivity

10.1 Reactivity

9.2

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials".

10.2 Chemical Stability

See below "Conditions to avoid".

10.3 Possibility of Hazardous Reactions

No known hazardous reactions.

10.4 Conditions to Avoid

There are no specific conditions known which have to be avoided.

United States: en Page: 5 / 10

acc. to 29 CFR 1910.1200 App D

Tire Slick

Revision Date: 12/16/2024

10.5 Incompatible Materials

Strong Oxidizers, Reducing Agents

10.6 Hazardous Decomposition Products

Hazardous combustion products: see section 5.

SECTION 11: Toxicological Information

11.1 Information on Toxicological Effects

Test data are not available for the complete mixture.

Classification Procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification Acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Acute Toxicity

Shall not be classified as acutely toxic.

Skin Corrosion/Irritation

Shall not be classified as corrosive/irritant to skin.

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or Skin Sensitization

Shall not be classified as a respiratory or skin sensitizer.

Germ Cell Mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Shall not be classified as carcinogenic.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans

| Name of Substance | CAS No | Classification | Number |
|-------------------|----------|----------------|--------|
| 2-butoxyethanol | 111-76-2 | 3 | |

Legend

Not classifiable as to carcinogenicity in humans

Reproductive Toxicity

Shall not be classified as a reproductive toxicant.

Specific Target Organ Toxicity - Single Exposure

Shall not be classified as a specific target organ toxicant (single exposure).

Specific Target Organ Toxicity - Repeated Exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration Hazard

Shall not be classified as presenting an aspiration hazard.

SECTION 12: Ecological Information

12.1 Toxicity

Shall not be classified as hazardous to the aquatic environment.

12.2 Persistence and Degradability

No Data Available.

United States: en Page: 6 / 10

acc. to 29 CFR 1910.1200 App D

Tire Slick

Revision Date: 12/16/2024

12.3 Bioaccumulative Potential

No Data Available.

12.4 Mobility in Soil

No Data Available.

12.5 Other Adverse Effects

No Data Available.

SECTION 13: Disposal Considerations

13.1 Waste Treatment Methods

Sewage Disposal-Relevant Information

Do not empty into drains. Avoid release to the environment.

Waste Treatment of Containers/Packages

Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

SECTION 14: Transport Information

14.1 UN Number, Proper Shipping Name, Class and Packing Group

NOT DOT REGULATED

14.2 Special precautions for user

There Is No Additional Information.

Transport of dangerous goods by road or rail (49 CFR US DOT) - Additional information

Not subject to transport regulations.

SECTION 15: Regulatory Information

15.1 Safety, Health and Environmental Regulations Specific for the Product in Question

National Regulations (United States)

Toxic Substance Control Act (TSCA) all ingredients are listed

Superfund Amendment and Reauthorization Act (SARA TITLE III)

- The List of Extremely Hazardous Substances and Their Threshold Planning Quantities (EPCRA Section 302, 304)

none of the ingredients are listed

- Specific Toxic Chemical Listings (EPCRA Section 313) none of the ingredients are listed

Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA)

- List of Hazardous Substances and Reportable Quantities (CERCLA section 102a) (40 CFR 302.4) none of the ingredients are listed

Clean Air Act

none of the ingredients are listed

United States: en Page: 7 / 10

acc. to 29 CFR 1910.1200 App D

Tire Slick

Revision Date: 12/16/2024

Right to Know Hazardous Substance List

- Cleaning Product Right to Know Act Substance List (CA-RTK)

| Name of Substance | CAS No | Functionality | Authoritative Lists |
|-------------------|----------|---------------|------------------------------------|
| 2-butoxyethanol | 111-76-2 | solvents | ATSDR Neurotoxicants OEHHA RELs |
| 2-butoxyethanol | | | CA TACs |

- Toxic or Hazardous Substance List (MA-TURA)

| Name of Substance | CAS No | DEP CODE | | De Minimis Concentration Threshold |
|-------------------|--------|----------|--|------------------------------------|
| 2-butoxyethanol | | 1022 | | 1.0 % |

- Hazardous Substances List (MN-ERTK)

| Name of Substance | CAS No | References | Remarks |
|-------------------|----------|------------|---------|
| 2-butoxyethanol | 111-76-2 | A, O | skin |

<u>Legend</u>

- A American Conference of Governmental Industrial Hygienists (ACGIH), "Threshold Limit Values for Chemical Substances and Physical Agents and Biological Exposure Indices for 1992-93", available from ACGIH
- Occupational Safety and Health Administration (OSHA), Safety and Health Standards, Code of Federal Regulations, title 29, part 1910, subpart Z, "Toxic and Hazardous Substances, 1990." General information: Minnesota Department of Labor and Industry, Occupational Safety and Health Division
- skin If a potential for absorption from skin contact merits special consideration, the word "skin" follows the substance name.

- Hazardous Substance List (NJ-RTK)

| Name of Substance | CAS No | Remarks | Classifications |
|-------------------|----------|---------|-----------------|
| 2-butoxyethanol | 111-76-2 | | CA F2 |
| 2-butoxyethanol | | | |

Legend

CA Carcinogenic

F2 Flammable - Second Degree

- Hazardous Substance List (Chapter 323) (PA-RTK)

| Name acc. to inventory | CAS No | Classification |
|------------------------|----------|----------------|
| ETHANOL, 2-BUTOXY- | 111-76-2 | |
| GLYCOL ETHERS | | E |

<u>Legend</u>

E Environmental hazard

United States: en Page: 8 / 10

acc. to 29 CFR 1910.1200 App D

Tire Slick

Revision Date: 12/16/2024

- Hazardous Substance List (RI-RTK)

| Name of Substance | CAS No | References |
|-------------------|----------|------------|
| 2-butoxyethanol | 111-76-2 | Т |
| 2-butoxyethanol | 111-76-2 | Т |

<u>Legend</u>

T Toxicity (ACGIH®)

California Environmental Protection Agency (Cal/EPA): Proposition 65 - Safe Drinking Water and Toxic Enforcement Act of 1987

none of the ingredients are listed

Industry or Sector Specific Available Guidance(s)

NPCA-HMIS® III

Hazardous Materials Identification System. American Coatings Association.

| Category | Rating |
|---------------------|--------|
| Chronic | / |
| Health | 2 |
| Flammability | 1 |
| Physical hazard | 0 |
| Personal protection | - |

NFPA® 704

National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States).

| Category | Degree of hazard |
|----------------|------------------|
| Flammability | 1 |
| Health | 2 |
| Instability | 0 |
| Special hazard | |

National inventories

| Country | Inventory | Status |
|---------|-----------|-------------------------------------|
| US | TSCA | all ingredients are listed (ACTIVE) |

<u>Legend</u>

TSCA Toxic Substance Control Act

SECTION 16: Other Information, Including Date of Preparation or Last Revision

OSHA Hazard Communication Standard (HCS), 29 CFR 1910.1200.

United States: en Page: 9 / 10

acc. to 29 CFR 1910.1200 App D

Tire Slick

Revision Date: 12/16/2024

Classification Procedure

Physical and chemical properties: The classification is based on tested mixture. Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Disclaimer

This information is based on the present state of our knowledge and does not constitute an assurance of product properties nor establishes contract legal rights. All data about health and safety are only for information. They should therefore not be construed as specifications. This SDS has been compiled and is solely intended for this product.

United States: en Page: 10 / 10