

Switching from In-Process to Standalone

1. Adjust your server startup scripts by removing SPM javaagent definition and adding parameters described on SPM Monitor - Standalone
2. Edit **properties** file of your system found in /spm/spm-monitor/conf/ directory (in case you are using Hadoop or HBase system which has multiple nodes, adjust properties files of nodes for which you want to change the mode). Set:
 - **SPM_MONITOR_IN_PROCESS**=“false”
 - **SPM_MONITOR_JMX_PARAMS** should be adjusted according to instructions on SPM Monitor - Standalone
3. Restart SPM Monitor:

```
sudo /etc/init.d/spm-monitor restart
```
4. restart your server

Switching from Standalone to In-Process

1. Add SPM javaagent definition to startup script of your server according to notes on <https://apps.sematext.com/ui/monitoring> (under in-process tab)
2. Edit **properties** file of your system found in /spm/spm-monitor/conf/ directory (in case you are using Hadoop or HBase system which has multiple nodes, adjust properties files of nodes for which you want to change the mode). Set:
 - **SPM_MONITOR_IN_PROCESS**=“true”
 - **SPM_MONITOR_JMX_PARAMS**=“”
3. Restart SPM monitor:

```
sudo /etc/init.d/spm-monitor restart
```
4. restart your server