


Integrantes:

Alejandro Rafael Guerrero Lozano

David Enrique López Juárez.

Creando instancia.



```
ubuntu@ip-172-31-81-131:~$ neofetch
.-/+oossssoo+/-.
`:+ssssssssssssssss+:`
-+ssssssssssssssssyyss+-
.oSSssssssssssssssdMMMnyssso.
/ssssssssssshdmNNmyNMMMMhsssss/
+ssssssssshmydMMMMMMNdddyssssss+
/ssssssssshNMMMyhyhyhNMMMNhssssss/
.sSSssssssdMMMNhssssssssshNMMMdssssss.
+ssssshhyNMMNysssssssssyNMMMyssssss+
ossyNMMNyMMhssssssssssshmmhssssso
ossyNMMNyMMhssssssssssshmmhssssso
+ssssshhyNMMNysssssssssyNMMMyssssss+
.sSSssssssdMMMNhssssssssshNMMMdssssss.
/ssssssssshNMMMyhyhyhNMMMNhssssss/
+ssssssssshmydMMMMMMNdddyssssss+
/ssssssssshdmNNmyNMMMMhsssss/
.oSSssssssssssssssdMMMnyssso.
-+ssssssssssssssssyyss+-
`:+ssssssssssssssss+:`
.-/+oossssoo+/-.

ubuntu@ip-172-31-81-131
-----
OS: Ubuntu 20.04.6 LTS x86_64
Host: HVM domU 4.11.amazon
Kernel: 5.15.0-1036-aws
Uptime: 1 min
Packages: 792 (dpkg), 6 (snap)
Shell: bash 5.0.17
Terminal: /dev/pts/0
CPU: Intel Xeon E5-2676 v3 (1) @ 2.400GHz
GPU: 00:02.0 Cirrus Logic GD 5446
Memory: 194MiB / 966MiB

ubuntu@ip-172-31-81-131:~$ node --version
v18.17.0
ubuntu@ip-172-31-81-131:~$
```

Práctica de la Lección

Una vez ingresado a la consola de la instancia ejecutar los siguientes comandos:

- Listar el contenido del directorio actual

```
ubuntu@ip-172-31-81-131:~$ ls
app-angular  express
ubuntu@ip-172-31-81-131:~$
```

- Ejecutar comando que indica la ruta de directorio actual.

```
+ ubuntu@ip-172-31-81-131: ~
ubuntu@ip-172-31-81-131:~$ pwd
/home/ubuntu
ubuntu@ip-172-31-81-131:~$
```

- Crear un directorio llamado workdir y cambiarse al directorio.

```
+ ubuntu@ip-172-31-81-131: ~/workdir
ubuntu@ip-172-31-81-131:~$ mkdir workdir
ubuntu@ip-172-31-81-131:~$ cd workdir/
ubuntu@ip-172-31-81-131:~/workdir$
```

- Crear un archivo llamado **welcome.txt** que tenga como contenido “Bienvenidos a Ubuntu”; despliega el contenido del archivo a través de línea de comandos.

```
+ ubuntu@ip-172-31-81-131: ~/workdir
GNU nano 4.8 welcome.txt
Bienvenidos a Ubuntu
+ ubuntu@ip-172-31-81-131: ~/workdir
ubuntu@ip-172-31-81-131:~/workdir$ cat welcome.txt
Bienvenidos a Ubuntu
ubuntu@ip-172-31-81-131:~/workdir$
```

- Ejecutar comando que instala la última versión de los paquetes

```
+ ubuntu@ip-172-31-81-131: ~/workdir
ubuntu@ip-172-31-81-131:~/workdir$ cat welcome.txt
Bienvenidos a Ubuntu
ubuntu@ip-172-31-81-131:~/workdir$ sudo apt update
Hit:1 http://us-east-1.ec2.archive.ubuntu.com/ubuntu focal InRelease
Hit:2 http://us-east-1.ec2.archive.ubuntu.com/ubuntu focal-updates InRelease
Hit:3 http://us-east-1.ec2.archive.ubuntu.com/ubuntu focal-backports InRelease
Hit:4 https://download.docker.com/linux/ubuntu focal InRelease
Hit:5 http://security.ubuntu.com/ubuntu focal-security InRelease
Reading package lists... Done
Building dependency tree
Reading state information... Done
All packages are up to date.
ubuntu@ip-172-31-81-131:~/workdir$
```

Creando aplicación de angular.

1. Crear un directorio de trabajo.

```
ubuntu@ip-172-31-81-131:~$ node --version
v18.17.0
ubuntu@ip-172-31-81-131:~$ mkdir app-angular
ubuntu@ip-172-31-81-131:~$ cd app-angular/
ubuntu@ip-172-31-81-131:~/app-angular$
```

2. Instalar Angular CLI

`npm install -g @angular/cli@latest`

```
ubuntu@ip-172-31-81-131:~/app-angular$ sudo npm install -g @angular/cli
added 240 packages in 11s
36 packages are looking for funding
  run `npm fund` for details
ubuntu@ip-172-31-81-131:~/app-angular$
```

3. Crear una nueva aplicación Angular

`ng new ejemplo --strict --style=scss --routing --skip-tests`

```
ubuntu@ip-172-31-81-131:~/app-angular$ ng new ejemplo --strict --style=scss --routing --skip-tests
Warning: This is a simple server for use in testing or debugging Angular applications
locally. It hasn't been reviewed for security issues.

Binding this server to an open connection can result in compromising your application or
computer. Using a different host than the one passed to the "--host" flag might result in
websocket connection issues. You might need to use "--disable-host-check" if that's the
case.

? Generating browser application bundles (phase: building)...
Warning: This is a simple server for use in testing or debugging Angular applications
locally. It hasn't been reviewed for security issues.

Binding this server to an open connection can result in compromising your application or
computer. Using a different host than the one passed to the "--host" flag might result in
websocket connection issues. You might need to use "--disable-host-check" if that's the
case.

? Generating browser application bundles (phase: building)...
```

4. Configurar la instancia EC2, seleccionar pestaña Seguridad y agregar las nuevas reglas

Detalles
Seguridad
Redes
Almacenamiento
Comprobaciones de estado
Monitoreo
Etiquetas

▼ Detalles de seguridad

Rol de IAM

-

ID del propietario

147750570083

Hora de lanzamiento

Fri Aug 04 20:

Grupos de seguridad

sg-071399a8893be581c (launch-wizard-7)

▼ Reglas de entrada

Q

Filtrar reglas

Nombre	ID de la regla del grupo d...	Intervalo de pu...	Protocolo	Origen
-	sgr-004f8c451cb933c0b	80	TCP	0.0.0.0/0
-	sgr-072ba9f740ee7309d	443	TCP	0.0.0.0/0
-	sgr-078d03b4c56beeeaf	4200	TCP	0.0.0.0/0
-	sgr-0cf6f5d60385ee469	22	TCP	0.0.0.0/0

5. Iniciar el servidor para conocer ejecución de la herramienta

`ng serve --host 0.0.0.0`

6. Copiar la IP pública de la instancia y pegarla en el navegador Web, acceder a través del protocolo HTTP y agregar el puerto 4200 de angular

Resumen de instancia de i-0c9183ff8af577de6 (backend-linux)
Información

ID de la instancia

i-0c9183ff8af577de6 (backend-linux)

Dirección IPv6

-

Tipo de nombre de anfitrión

Nombre de IP: ip-172-31-6-75.us-east-2.compute.internal

Responder al nombre DNS de recurso privado IPv4 (A)

Dirección IP asignada automáticamente

3.139.236.189 [IP pública]

Rol de IAM

-

IMDSv2

Optional

Dirección IPv4 pública

3.139.236.189 | dirección abierta

Estado de la instancia

En ejecución

Nombre DNS de IP privada (solo IPv4)

ip-172-31-6-75.us-east-2.compute.internal

Tipo de instancia

t2.micro

ID de VPC

vpc-06047a1607b56abb9

ID de subred

subnet-012d800bfb62e1e35

Direcciones IPv4 privadas

172.31.6.75

DNS de IPv4 pública

ec2-3-139-236-189.us-east-2.compute.amazonaws.com | dirección abierta

Direcciones IP elásticas

-


Hallazgo de AWS Compute Optimizer

Suscribirse a AWS Compute Optimizer para recibir recomendaciones.

Nombre del grupo de Auto Scaling

-

7. Abrir un navegador web e ingresar la dirección IP junto con su puerto



Referencia

Instalar las fuentes de configuración

```
sudo apt update
```

```
ubuntu@ip-172-31-81-131: ~$  
ubuntu@ip-172-31-81-131:~$ sudo apt update  
Hit:1 http://us-east-1.ec2.archive.ubuntu.com/ubuntu focal InRelease  
Hit:2 http://us-east-1.ec2.archive.ubuntu.com/ubuntu focal-updates InRelease  
Hit:3 http://us-east-1.ec2.archive.ubuntu.com/ubuntu focal-backports InRelease  
Hit:4 http://security.ubuntu.com/ubuntu focal-security InRelease  
Hit:5 https://download.docker.com/linux/ubuntu focal InRelease  
Reading package lists... Done  
Building dependency tree  
Reading state information... Done  
All packages are up to date.  
ubuntu@ip-172-31-81-131:~$ sudo apt install openssl  
Reading package lists... Done  
Building dependency tree  
Reading state information... Done  
openssl is already the newest version (1.1.1f-1ubuntu2.19).  
openssl set to manually installed.  
The following packages were automatically installed and are no longer required:  
gyp javascript-common libauthen-sasl-perl libc-ares2 libdata-dump-perl libdrm-amdgpu libdrm-intel1 libdrm-nouveau2 libdrm-radeon1 libencode-locale-perl  
libfile-basedir-perl libfile-desktopentry-perl libfile-listing-perl libfile-mimeinfo-perl libfont-afm-perl libfontenc1 libgl1 libgl1-mesa-dri  
libglapi-mesa libglvnd0 libglx-mesa0 libglx0 libhtml-form-perl libhtml-format-perl libhtml-parser-perl libhtml-tagset-perl libhtml-tree-perl  
libhttp-cookies-perl libhttp-daemon-perl libhttp-date-perl libhttp-message-perl libhttp-negotiate-perl libice6 libio-html-perl libio-socket-ssl-perl  
libio-stringy-perl libipc-system-simple-perl libis-inherits libjs-typedarray libjs-ps libjs-typedarray-to-buffer libllvm2 liblw-mediatypes-perl  
liblua5.2-1 libmailtools-perl libmdc-dbus-perl libnet-http-perl libnet-ntp-perl libnet-ssleay-perl libnode-dev libnode64 libpacaccess0  
libpython2-stdeb libpython2.7-minimal libpython2.7-stdeb libzensors-config libzensors4 libzms libzstd-dev libzstd-ixhash-perl libzstdate-perl  
libztny-perl libzuri-perl libzuri-dev libzuksan libzuysand-client0 libzwww-perl libzwww-robofilters-perl libxml-protocol-perl libxml-xcb1 libxaw7  
libxcb-dri2-0 libxcb-dri3-0 libxcb-glx0 libxcb-present0 libxcb-randr0 libxcb-shape0 libxcb-shm0 libxcb-sync1 libxcb-xfixes0 libxcursor0 libxcomposite1 libxcursor1  
libxf86d1 libxft2 libxi6 libxinera1 libxxkbfil1 libxnl-parser-perl libxnm1-twig-perl libxml-xpathengine-perl libxmms libxpm4 libxrandr2 libxrender1  
libxshmfence1 libxt6 libxtst6 libxxf86dgal libxxf86vm1 mesa-vulkan-drivers nodejs-doc perl-openssl-defaults python-pkg-resources python2  
python2-minimal python2.7 python2.7-minimal x11-common x11-utils x11-xserver-utils xdg-utils  
Use 'sudo apt autoremove' to remove them.  
0 upgraded, 0 newly installed, 0 to remove and 0 not upgraded.  
ubuntu@ip-172-31-81-131:~$
```

Instalar el servidor Web Nginx con el comando

```
sudo apt install nginx
```

```

ubuntu@ip-172-31-41-13:~$
E: The update command takes no arguments
ubuntu@ip-172-31-41-13:~$ sudo apt install nginx
Reading package lists... Done
Building dependency tree
Reading state information... Done

The following packages were automatically installed and are no longer required:
  g++-x86_64-linux-gnu libauthen-eas-perl libc-ares libdata-dump-perl libdrm-amdgpu libdrm-intel libdrm-nouveau libdrm-radeon libenco-de-local-perl
  libfile-basedir-perl libfile-desktopentry-perl libfile-listing-perl libfile-mimeinfo-perl libfont-afm-perl libfontconfig1 libgl1 libgl1-mesa-dr
  libglapi-mesa libgldm0 libglx-mesa0 libglx0 libhtml-form-perl libhtml-format-perl libhtml-parser-perl libhtml-tagset-perl libhtml-tree-perl
  libhttp-cookies-perl libhttp-daemon-perl libhttp-date-perl libhttp-message-perl libhttp-negotiate-perl liblbc6 libio-hdl-perl libio-socket-ssl-perl
  libio-stringy-perl libio-system-simple-perl libjs-inherits libjs-is-typedarray libjs-psl libjs-typedarray-to-buffer libllvm2 liblwp-mediatypes-perl
  libmailtools-perl libnet-dbus-perl libnet-http-perl libnet-httpclient-perl libnet-ssleay-perl libnet-ssleay-perl libnode-dev libnode64 libpbcaccess0
  libpython2-stdlib libpython2.7-minimal libpython2.7-stdlib libtensors-config libtensors5 libsm6 libssl-dev libtclix-shash-perl libtclimated-perl
  libtcl-tiny-perl libtcl-tty-perl libuv1-dev libuv1k1 libwayland-client0 libxaw-perl libxaw-rotoresutils libx11-protocol-perl libx11-xcb1 libxaw7
  libxcb-dri2-0 libxcb-dri3-0 libxcb-glx0 libxcb-present0 libxcb-randr0 libxcb-shape0 libxcb-shm0 libxcb-sync1 libxcb-fixes0 libxcomposit0 libxcursor0
  libxfixes3 libxft2 libxglx0 libxinerama0 libxkbfile0 libxkb-randr0 libxkb-tcl-perl libxkb-xpathengine0 libxkb-xpathengine0 libxkb2 libxrender2 libxrender0
  libxv0 libxv6 libxv6 libxv6 libxv6 libxv6 libxv6 libxv6 libxv6 libxv6 libxv6 libxv6 libxv6 libxv6 libxv6 libxv6 libxv6 libxv6 libxv6 libxv6 libxv6 libxv6
  python2-minimal python2.7 python2.7-minimal xii-common xii-utils xii-xserver-utils xdg-utils
Use 'sudo apt autoremove' to remove them.

The following additional packages will be installed:
  libgd3 libnginx-mod-http-image-filter libnginx-mod-http-xslt-filter libnginx-mod-mail libnginx-mod-stream nginx-common nginx-core
Suggested packages:
  libgd-tools fcgiwrap nginx-doc ssl-cert
The following NEW packages will be installed:
  libgd3 libnginx-mod-http-image-filter libnginx-mod-http-xslt-filter libnginx-mod-mail libnginx-mod-stream nginx-common nginx-core
0 upgraded, 9 newly installed, 0 to remove and 0 not upgraded.
Need to get 723 kB of archives.
After this operation, 2604 kB of additional disk space will be used.
Do you want to continue? [Y/n]


Get:1 http://us-east-1.ec2.archive.ubuntu.com/ubuntu focal-updates/main amd64 libgd3 amd64 2.2.1-5+ubuntu2.1 [118 kB]
Get:2 http://us-east-1.ec2.archive.ubuntu.com/ubuntu focal-updates/main amd64 nginx-common amd64 1.18.0-0ubuntu1.4 [37.7 kB]
Get:3 http://us-east-1.ec2.archive.ubuntu.com/ubuntu focal-updates/main amd64 libnginx-mod-http-image-filter amd64 1.18.0-0ubuntu1.4 [14.8 kB]
Get:4 http://us-east-1.ec2.archive.ubuntu.com/ubuntu focal-updates/main amd64 libnginx-mod-http-xslt-filter amd64 1.18.0-0ubuntu1.4 [13.0 kB]
Get:5 http://us-east-1.ec2.archive.ubuntu.com/ubuntu focal-updates/main amd64 libnginx-mod-mail amd64 1.18.0-0ubuntu1.4 [4.7 kB]
Get:6 http://us-east-1.ec2.archive.ubuntu.com/ubuntu focal-updates/main amd64 libnginx-mod-stream amd64 1.18.0-0ubuntu1.4 [62.9 kB]
Get:7 http://us-east-1.ec2.archive.ubuntu.com/ubuntu focal-updates/main amd64 nginx-core amd64 1.18.0-0ubuntu1.4 [425 kB]
Fetched 723 kB in 0s (15.8 MB/s)
Preconfiguring packages ...
Selecting previously unselected package libgd3:amd64.

```

Verificar el estado del servidor web

systemctl status nginx

Verificar qué se levantó de manera correcta el servidor web, ingresa la IP Pública de EC2



Ahora vamos a construir el proyecto test, ingresar el comando

ng build

```
ubuntu@ip-172-31-81-131: ~/app-angular/ejemplo
ubuntu@ip-172-31-81-131:~/app-angular/ejemplo$ ng build
✓ Browser application bundle generation complete.
✓ Copying assets complete.
✓ Index html generation complete.

Initial Chunk Files | Names | Raw Size | Estimated Transfer Size
main.1bec138984be6491.js | main | 204.54 kB | 55.94 kB
polyfills.65f68585fbb1ab6c.js | polyfills | 33.01 kB | 10.68 kB
runtime.55dc05f423a7eca3.js | runtime | 892 bytes | 507 bytes
styles.ef46db3751d8e999.css | styles | 0 bytes | -
| Initial Total | 238.42 kB | 67.11 kB

Build at: 2023-08-08T22:31:54.573Z - Hash: ce0887e27ead5c87 - Time: 10012ms
ubuntu@ip-172-31-81-131:~/app-angular/ejemplo$
```

Ingresar el comando para el listado de carpetas y archivos

ls -l

```
ubuntu@ip-172-31-81-131: ~/app-angular/ejemplo
ubuntu@ip-172-31-81-131:~/app-angular/ejemplo$ ls -l
total 476
-rw-r--r-- 1 root root 740 Aug 5 00:00 Dockerfile
-rw-r--r-- 1 ubuntu ubuntu 1061 Aug 4 23:21 README.md
-rw-r--r-- 1 ubuntu ubuntu 3468 Aug 4 23:21 angular.json
drwxrwxr-x 3 ubuntu ubuntu 4096 Aug 8 22:31 dist
drwxrwxr-x 560 ubuntu ubuntu 20480 Aug 4 23:22 node_modules
-rw-r--r-- 1 ubuntu ubuntu 426856 Aug 4 23:22 package-lock.json
-rw-r--r-- 1 ubuntu ubuntu 1038 Aug 4 23:21 package.json
drwxrwxr-x 4 ubuntu ubuntu 4096 Aug 4 23:21 src
-rw-r--r-- 1 ubuntu ubuntu 263 Aug 4 23:21 tsconfig.app.json
-rw-r--r-- 1 ubuntu ubuntu 901 Aug 4 23:21 tsconfig.json
-rw-r--r-- 1 ubuntu ubuntu 273 Aug 4 23:21 tsconfig.spec.json
ubuntu@ip-172-31-81-131:~/app-angular/ejemplo$
```

Para conocer la ruta de directorio actual ingresar comando

pwd

```
ubuntu@ip-172-31-81-131: ~/app-angular/ejemplo
ubuntu@ip-172-31-81-131:~/app-angular/ejemplo$ pwd
/home/ubuntu/app-angular/ejemplo
ubuntu@ip-172-31-81-131:~/app-angular/ejemplo$
```

Copiar la ruta y agregar la carpeta dist/test, por ejemplo:

`/home/ubuntu/workdir/test/dist/test`

Modificar el archivo de configuración de Nginx

`sudo nano /etc/nginx/sites-available/default`

```
+ ubuntu@ip-172-31-61-131: ~/app-angular/ejemplo
GNU nano 4.8 /etc/nginx/sites-available/default
#
# Self signed certs generated by the ssl-cert package
# Don't use them in a production server!
#
# Include snippets/snakeoil.conf;

root /home/ubuntu/app-angular/ejemplo;

# Add index.php to the list if you are using PHP
index index.html index.htm index.nginx-debian.html;

server_name _;

location / {
    # First attempt to serve request as file, then
```


Modificar línea: root `/var/www/html`; Por ruta: `/home/ubuntu/workdir/test/dist/test`

Reiniciar servidor seb con comando

`sudo systemctl restart nginx`

```
+ ubuntu@ip-172-31-61-131: ~/app-angular/ejemplo
ubuntu@ip-172-31-61-131:~/app-angular/ejemplo$ sudo systemctl restart nginx
ubuntu@ip-172-31-61-131:~/app-angular/ejemplo$
```

Ingresar nuevamente la IP de la dirección pública de EC2 en su navegador



Configuración HTTPS

Crear una carpeta llamada ssl

mkdir ssl

```
ubuntu@ip-172-31-81-131: ~/$ mkdir ssl
ubuntu@ip-172-31-81-131: ~/$ cd ssl/
ubuntu@ip-172-31-81-131: ~/ssl$
```

Instalar openssl

sudo apt install openssl

```
ubuntu@ip-172-31-81-131: ~/ssl$ sudo apt install openssl
Reading package lists... Done
Building dependency tree
Reading state information... Done
openssl is already the newest version (1.1.1f-1ubuntu2.19).
The following packages were automatically installed and are no longer required:
  gyp javascript-common libauthen-sasl-perl libc-ares2 libdata-dump-perl libdrm-amdgpu1 libdrm-intel1 libdrm-nouveau2 libdrm-radeon1 libencode-locale-perl
  libfile-basedir-perl libfile-desktopentry-perl libfile-listing-perl libfile-mimeinfo-perl libfont-afm-perl libfontenc1 libgl1 libgl1-mesa-dr1
  libglapi-mesa libglvnd0 libglx-mesa0 libglx0 libhtml-form-perl libhtml-format-perl libhtml-parser-perl libhtml-tagset-perl libhtml-tree-perl
  libhttp-cookies-perl libhttp-daemon-perl libhttp-date-perl libhttp-message-perl libhttp-negotiate-perl libice6 libio-html-perl libio-socket-ssl-perl
  libio-stringy-perl libipc-system-simple-perl libjs-inherits libjs-is-typedarray libjs-psl libjs-typedarray-to-buffer libllvm12 liblw-mediatypes-perl
  liblw-protocol-https-perl libmailtools-perl libnet-dbus-perl libnet-http-perl libnet-smtp-ssl-perl libnet-ssleay-perl libnode-dev libnode64 libpcaccess0
  libpython2-stdlib libpython2.7-minimal libpython2.7-stdlib libusbensors-config libusbosrs5 libamd libx11-dev libtie-ixhash-perl libtime-date-perl
  libtiny-perl liburi-perl libuv1-dev libvulkan1 libwayland-client0 libwww-perl libwww-robotrules-perl libx11-protocol-perl libx11-xcb1 libxaw7
  libxcb-dri2-0 libxcb-dri3-0 libxcb-glx0 libxcb-present0 libxcb-randr0 libxcb-shape0 libxcb-shm0 libxcb-sync1 libxcb-xf86vm0 libxcomposite1 libxcursor1
  libxfixes3 libxft2 libxi6 libxinerama1 libxkbfile1 libxml-parser-perl libxml-twig-perl libxml-xpathengine-perl libxmu6 libxrandr2 libxrender1
  libxshmfence1 libxt6 libxtst6 libxv1 libxxf86dga1 libxxf86vm1 mesa-vulkan-drivers nodejs-doc perl-openssl-defaults python-pkg-resources python2
  python2-minimal python2.7 python2.7-minimal x11-common x11-utils x11-xserver-utils xdg-utils
Use 'sudo apt autoremove' to remove them.
0 upgraded, 0 newly installed, 0 to remove and 0 not upgraded.
ubuntu@ip-172-31-81-131: ~/ssl$
```

Conocer versión de openssl

openssl version

```
ubuntu@ip-172-31-81-131: ~/ssl$ openssl version
OpenSSL 1.1.1f  31 Mar 2020
ubuntu@ip-172-31-81-131: ~/ssl$
```

Generar una clave privada llamada **clave-privada.key**

openssl genpkey -algorithm RSA -out clave-privada.key

```
ubuntu@ip-172-31-81-131: ~/ssl$ openssl version
OpenSSL 1.1.1f  31 Mar 2020
ubuntu@ip-172-31-81-131: ~/ssl$ openssl genpkey -algorithm RSA -out clave-privada.key
.....+++++
+++++
ubuntu@ip-172-31-81-131: ~/ssl$ ls
clave-privada.key
ubuntu@ip-172-31-81-131: ~/ssl$
```

Escribir comando para verificar qué se creo

Generar un certificado en base a la clave privada recién creada, responde a las interrogantes como en imagen de ejemplo

openssl req -new -key clave-privada.key -out cert.csr

```
ubuntu@ip-172-31-81-131: ~/ssl
ubuntu@ip-172-31-81-131:~/ssl$ openssl req -new -key clave-privada.key -out cert.csr
You are about to be asked to enter information that will be incorporated
into your certificate request.
What you are about to enter is what is called a Distinguished Name or a DN.
There are quite a few fields but you can leave some blank
For some fields there will be a default value,
If you enter '.', the field will be left blank.
-----
Country Name (2 letter code) [AU]:MX
State or Province Name (full name) [Some-State]:GTO
Locality Name (eg, city) []:DH
Organization Name (eg, company) [Internet Widgits Pty Ltd]:UTNG
Organizational Unit Name (eg, section) []:TIC'S
Common Name (e.g. server FQDN or YOUR name) []:DESWEB
Email Address []:alejandro02262@gmail.com

Please enter the following 'extra' attributes
to be sent with your certificate request
A challenge password []:linux123
An optional company name []:UTNG
ubuntu@ip-172-31-81-131:~/ssl$
```

Generar nuevamente certificado firmado

openssl x509 -req -days 365 -in /home/ubuntu/workdir/ssl/cert.csr -signkey /home/ubuntu/workdir/ssl/clave-privada.key -out /home/ubuntu/workdir/ssl/cert-auto.crt

```
139:0430150288:error:12000088:bio routines:bio_new_file:no such file:../crypto/bio/bss_file.c:70:
ubuntu@ip-172-31-81-131:~/ssl$ openssl x509 -req -days 365 -in /home/ubuntu/ssl/cert.csr -signkey /home/ubuntu/ssl/clave-privada.key -out /home/ubuntu/ssl/cert-auto.crt
Signature ok
subject=C = MX, ST = GTO, L = DH, O = UTNG, OU = TIC'S, CN = DESWEB, emailAddress = alejandro02262@gmail.com
Getting Private key
ubuntu@ip-172-31-81-131:~/ssl$
```

Unir ambos certificados para mayor seguridad

cat cert-auto.crt clave-privada.key > cert-completo.crt

```
-rw-rw-r-- 1 ubuntu ubuntu 1281 Aug  8 19:02 cert-auto.crt
-rw-rw-r-- 1 ubuntu ubuntu 2989 Aug  8 19:03 cert-completo.crt
-rw-rw-r-- 1 ubuntu ubuntu 1098 Aug  8 19:00 cert.csr
-rw----- 1 ubuntu ubuntu 1708 Aug  8 18:58 clave-privada.key
```

```
ubuntu@ip-172-31-81-131: ~/ssl
ubuntu@ip-172-31-81-131:~/ssl$ cat cert-auto.crt clave-privada.key > cert-completo.crt
ubuntu@ip-172-31-81-131:~/ssl$
```

Modificar archivo en servidor web Nginx

sudo nano /etc/nginx/sites-available/default

```
GNU nano 4.8 /etc/nginx/sites-available/default
# Please see /usr/share/doc/nginx-doc/examples/ for more detailed examples.
##

# Default server configuration
#
server {
    listen 80 default_server;
    listen [::]:80 default_server;

    # SSL configuration
    #
    listen 443 ssl default_server;
    ssl_certificate /home/ubuntu/ssl/cert-completo.crt;
    ssl_certificate_key /home/ubuntu/ssl/clave-privada.key;
    # listen [::]:443 ssl default_server;
    #
```


CTRL + S Guardar

CTRL + X Salir


Reiniciar nuevamente el servidor

sudo systemctl restart nginx

Abrir navegador web con la direccion: <https://44.201.171.30/>




Seleccionar configuración avanzada | Continuar a 18.233.156.132 (no seguro)




Instalar MySQL


Crear una nueva instancia donde se deposite la base de datos.



Abrir el puerto 3306 de EC2



Instalar la base de datos MySQL



```
ubuntu@ip-172-31-93-176:~$ sudo systemctl start mysql.service
ubuntu@ip-172-31-93-176:~$ sudo systemctl status mysql
● mysql.service - MySQL Community Server
   Loaded: loaded (/lib/systemd/system/mysql.service; enabled; vendor preset: enabled)
   Active: active (running) since Tue 2023-08-08 23:35:57 UTC; 26s ago
     Main PID: 2552 (mysqld)
    Status: "Server is operational"
       Tasks: 38 (limit: 1141)
      Memory: 355.5M
        CGroup: /system.slice/mysql.service
                └─2552 /usr/sbin/mysqld

Aug 08 23:35:56 ip-172-31-93-176 systemd[1]: Starting MySQL Community Server...
Aug 08 23:35:57 ip-172-31-93-176 systemd[1]: Started MySQL Community Server.
ubuntu@ip-172-31-93-176:~$
```

```
ubuntu@ip-172-31-93-176:~$ sudo mysql_secure_installation

Securing the MySQL server deployment.

Connecting to MySQL using a blank password.

VALIDATE PASSWORD COMPONENT can be used to test passwords
and improve security. It checks the strength of password
and allows the users to set only those passwords which are
secure enough. Would you like to setup VALIDATE PASSWORD component?

Press y|Y for Yes, any other key for No: y

There are three levels of password validation policy:

LOW      Length >= 8
MEDIUM  Length >= 8, numeric, mixed case, and special characters
STRONG Length >= 8, numeric, mixed case, special characters and dictionary file

Please enter 0 = LOW, 1 = MEDIUM and 2 = STRONG: 0

Skipping password set for root as authentication with auth_socket is used by default.
If you would like to use password authentication instead, this can be done with the "ALTER USER" command.
See https://dev.mysql.com/doc/refman/8.0/en/alter-user.html#alter-user-password-management for more information.

By default, a MySQL installation has an anonymous user,
allowing anyone to log into MySQL without having to have
a user account created for them. This is intended only for
testing, and to make the installation go a bit smoother.
You should remove them before moving into a production
environment.

Remove anonymous users? (Press y|Y for Yes, any other key for No) : Y
Success.

Normally, root should only be allowed to connect from
```

Crear la base de datos web_integral;

```
ubuntu@ip-172-31-93-176:~$ mysql -u aguerrero -p
Enter password:
Welcome to the MySQL monitor.  Commands end with ; or \g.
Your MySQL connection id is 8
Server version: 8.0.33-0ubuntu0.20.04.4 (Ubuntu)

Copyright (c) 2000, 2023, Oracle and/or its affiliates.

Oracle is a registered trademark of Oracle Corporation and/or its
affiliates. Other names may be trademarks of their respective
owners.

Type 'help;' or '\h' for help. Type '\c' to clear the current input statement.


mysql> CREATE DATABASE web_integral;
Query OK, 1 row affected (0.05 sec)

mysql> use web_integral;
Database changed
mysql>
```

Creando tabla de usuario.


```
mysql> CREATE TABLE tbl_usuario (  
->     Username VARCHAR(30) PRIMARY KEY,  
->     Password VARCHAR(250) NOT NULL,  
->     Role VARCHAR(20) NOT NULL  
-> );  
Query OK, 0 rows affected (0.04 sec)  
  
mysql> 
```

Configurar base de datos para acceso remoto



Instalar [DBeaver](#) para acceder a la BD

pasar los parámetros de conexión



Práctica de la lección

- Crear la base de datos de aplicación de ejemplo.

```
+
ubuntu@ip-172-31-93:~$ mysql -u aguerrero -p
Enter password:
Welcome to the MySQL monitor.  Commands end with ; or \g.
Your MySQL connection id is 8
Server version: 8.0.33-0ubuntu0.20.04.4 (Ubuntu)

Copyright (c) 2000, 2023, Oracle and/or its affiliates.

Oracle is a registered trademark of Oracle Corporation and/or its
affiliates. Other names may be trademarks of their respective
owners.

Type 'help;' or '\h' for help. Type '\c' to clear the current input statement.

mysql> CREATE DATABASE web_integral;
Query OK, 1 row affected (0.05 sec)


mysql> use web_integral;
Database changed
mysql>

mysql> CREATE TABLE tbl_usuario (
    ->     Username VARCHAR(30) PRIMARY KEY,
    ->     Password VARCHAR(250) NOT NULL,
    ->     Role VARCHAR(20) NOT NULL
    -> );
Query OK, 0 rows affected (0.04 sec)

mysql> 
```

- Montar el backend

Configurando backend




The screenshot shows the Visual Studio Code interface. On the left, the Explorer sidebar displays the project structure, including folders like `src`, `controllers`, and `models`. The main editor area shows the `src/config.ts` file, which contains database connection settings. The terminal window at the bottom shows the output of a command, displaying a list of files and directories.

```

src/config.ts
1  You have 20 segundos | 1 autor (you) | database > password
2  export default {
3    keys: {
4      secret: ')/X$5webintegral$6%/\'
5    },
6    database: {
7      host: '5.93.9.15',
8      port: 3306,
9      user: 'aguerero',
10     password: 'dicenwebintegral', // You have 1 segundo | Incremented changes
11     (property) connectionLimit: number
12     connectionLimit: 10, // Número máximo de conexiones en la pool
13   }
14 }
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
```

- Verificar funcionalidad con Postman



Creando contenedor Docker-Angular

```
GNU nano 4.8 Dockerfile
# Etapa 1: Compila y construye codebase de Angular
# Utilizar la última imagen oficial de Node
FROM node:latest as build

# Establecer el directorio de trabajo
WORKDIR /usr/local/app

# Agregar el código fuente al directorio app
COPY ./ /usr/local/app/

# Instalar las dependencias
RUN npm install

# Generar y correr la aplicación
RUN npm run build

# Etapa 2: Servidor Web with nginx


# Uso official nginx image as the base image
# Utilizar la imagen oficial nginx como imagen base
FROM nginx:latest
```

```
ubuntu@ip-172-31-81-131: /app-angular/ejemplo$ sudo docker build -t ejemplo:1.0.1 .
[+] Building 85.2s (13/13) FINISHED
--> [internal] load build definition from Dockerfile
--> [internal] load dockerfile /79B
--> [internal] load .dockerignore
--> [internal] transfer context: 20B
--> [internal] load metadata for docker.io/library/nginx:latest
--> [internal] load metadata for docker.io/library/node:latest
--> [build 1/5] FROM docker.io/library/node:latest@sha256:6461834718d49bwa180780aeb5f7378fa456bf3821775a2a8a700bcb05
--> CACHED [stage 1/2] FROM docker.io/library/nginx:latest@sha256:62f7ad18d42abeb66263d6d43c9703300a23a7773a58f6b15d7d41ca
--> [internal] load build context
--> [internal] transfer context: 1.80MB
--> CACHED [build 2/5] WORKDIR /usr/local/app
--> CACHED [build 3/5] COPY --> /usr/local/app/
--> CACHED [build 4/5] RUN npm install
--> [build 5/5] RUN npm run build
--> [internal] 2/2 COPY --> /usr/local/app/dist/ ejemplo /usr/share/nginx/html
--> exporting to image
--> exporting image
--> writing image sha256:805876c1bd5d1f46a9c2f6a0d426b74f6700a9c144579a21d0d80a4f0f1
--> saving to docker.io/library/ ejemplo:1.0.1
ubuntu@ip-172-31-81-131: /app-angular/ejemplo$
```

Ejecutando imagen.


```
ubuntu@ip-172-31-81-131: /app-angular/ejemplo$ sudo docker run -d -p 6080:80 ejemplo:1.0.1
7fe5b85a2e5b2cc8b0147e156180cf6fde955ab582ac31fc7babbfaa
ubuntu@ip-172-31-81-131: /app-angular/ejemplo$
```

Probando en la nube.




Práctica de la sesión

- Para contenedor recién ejecutado.



- Eliminar el contenedor recién ejecutado



- Eliminar la imagen

```

+
ubuntu@ip-172-31-81-131: ~
ubuntu@ip-172-31-81-131:~$ sudo docker images
REPOSITORY    TAG       IMAGE ID       CREATED        SIZE
myapp_node    1.0       2527bd28f4cf   3 days ago    1.11GB
ejemplo       1.0.1     bb907e6e1bd5   3 days ago    187MB
mysql         latest    54150e9955c4   5 days ago    577MB
ubuntu@ip-172-31-81-131:~$ sudo docker rmi bb907e6e1bd5
Untagged: ejemplo:1.0.1
Deleted: sha256:bb907e6e1bd591f46eae2f4ded4268d74f676dbd9e1845f9eb2e6d88aba6f6ff
ubuntu@ip-172-31-81-131:~$

```

- Listar todas las imágenes

```

ubuntu@ip-172-31-81-131:~$ sudo docker images
REPOSITORY    TAG       IMAGE ID       CREATED        SIZE
myapp_node    1.0       2527bd28f4cf   3 days ago    1.11GB
mysql         latest    54150e9955c4   5 days ago    577MB
ubuntu@ip-172-31-81-131:~$

```

Docker NodeJs


Ubicar un directorio de trabajo para alojar la aplicación.

Instalar express-generator, para mayor referencia véase [AQUI](#)

`npx express-generator`

Crear el proyecto

`express ejemplo-node`

A terminal window titled 'ubuntu@ip-172-31-81-131: ~ - express/ejemplo-node' shows the command 'npm start' being executed. The output indicates that 'ejemplo-node@0.0.0 start' is running and the server is listening on port 3000. The terminal is dark-themed with light blue text. The bottom of the window shows a Linux desktop environment with various icons and a system clock indicating '4 de ago 6:32 PM'.

Ingresar la URL <http://localhost:3000>

Parar el servidor Node

Ingresar `Ctrl+C`

Creando el contenedor Docker para Node

Crear un archivo **Dockerfile** en el directorio raíz del proyecto e ingresar las siguientes instrucciones

```
FROM node:latest as build
WORKDIR /usr/local/app
COPY package*.json /usr/local/app/
RUN npm install
COPY ./ /usr/local/app/
CMD [ "npm", "start" ]
```

```
+
ubuntu@ip-172-31-81-131: ~/express/ejemplo-node
GNU nano 4.8
FROM node:latest as build

WORKDIR /usr/local/app

COPY package*.json /usr/local/app/

RUN npm install

COPY ./ /usr/local/app/

CMD [ "npm", "start" ]
```

Crear la imagen


```
sudo docker build -t myapp_node:1.0 .
```

Ejecutar el contenedor

```
sudo docker run -p 3000:3000 myapp_node:1.0
```

```
ubuntu@ip-172-31-81-131:~/express/ejemplo-node$ sudo docker run -p 3000:3000 myapp_node:1.0
ejemplo-node@0.0.0 start
node ./bin/www
```

Agregando regla en aws



Docker MySQL

Extraer la imagen de mysql

docker pull mysql:latest

```
ubuntu@ip-172-31-81-131:~$ sudo docker pull mysql:latest
latest: Pulling from library/mysql
49bb46380fac: Pull complete
aab3066bbf8f: Pull complete
d6eef8c26cf9: Pull complete
0e908b1dcba2: Pull complete
480c3912a2fd: Pull complete
ef90fc42d4db: Pull complete
a2ffc585c753: Pull complete
e2ef842ff3d6: Pull complete
c6c990e874d7: Pull complete
a554d403eafe: Pull complete
Digest: sha256:6a5dbd2810c36048669639811461f27fee48d1e22039e5d31f4273a20d542f6
Status: Downloaded newer image for mysql:latest
docker.io/library/mysql:latest
ubuntu@ip-172-31-81-131:~$
```

Ejecutar el siguiente comando donde creará automáticamente la imagen con una contraseña y el volumen para almacenar la información

docker run --name mysql-demo -e MYSQL_ROOT_PASSWORD=demo -d -v mysql-demo:/var/lib/mysql mysql:latest

docker ps

```
ubuntu@ip-172-31-81-131:~$ sudo docker ps
CONTAINER ID   IMAGE          COMMAND                  CREATED        STATUS        PORTS                    NAMES
0d5f30607fea   mysql:latest   "docker-entrypoint.s..." 13 seconds ago Up 11 seconds   3306/tcp, 33060/tcp      mysql-demo
fb1665d1156d   myapp_node:1.0 "docker-entrypoint.s..." 5 minutes ago  Up 5 minutes   0.0.0.0:3000->3000/tcp, :::3000->3000/tcp  pe
062bfe5bb98e   ejemplo:1.0.1  "/docker-entrypoint.s..." 19 minutes ago Up 19 minutes   0.0.0.0:8080->80/tcp, :::8080->80/tcp      ga
llant_benz
```

Instalar cliente de MySQL

sudo apt install mysql-client -y

```
After this operation, 75.6 MB of additional disk space will be used.
Get:1 http://us-east-1.ec2.archive.ubuntu.com/ubuntu focal-updates/main amd64 mysql-client-core-8.0 amd64 8.0.33-0ubuntu0.20.04.4 [5176 kB]
Get:2 http://us-east-1.ec2.archive.ubuntu.com/ubuntu focal-updates/main amd64 mysql-common all 5.8+1.0.5ubuntu2 [7496 B]
Get:3 http://us-east-1.ec2.archive.ubuntu.com/ubuntu focal-updates/main amd64 mysql-client-8.0 amd64 8.0.33-0ubuntu0.20.04.4 [22.0 kB]
Get:4 http://us-east-1.ec2.archive.ubuntu.com/ubuntu focal-updates/main amd64 mysql-client all 8.0.33-0ubuntu0.20.04.4 [9356 B]
Fetched 5215 kB in 0s (11.4 MB/s)
Selecting previously unselected package mysql-client-core-8.0.
(Reading database ... 72211 files and directories currently installed.)
Preparing to unpack .../mysql-client-core-8.0_8.0.33-0ubuntu0.20.04.4_amd64.deb ...
Unpacking mysql-client-core-8.0 (8.0.33-0ubuntu0.20.04.4) ...
Selecting previously unselected package mysql-common.
Preparing to unpack .../mysql-common-5.8+1.0.5ubuntu2_all.deb ...
Unpacking mysql-common (5.8+1.0.5ubuntu2) ...
Selecting previously unselected package mysql-client-8.0.
Preparing to unpack .../mysql-client-8.0_8.0.33-0ubuntu0.20.04.4_amd64.deb ...
Unpacking mysql-client-8.0 (8.0.33-0ubuntu0.20.04.4) ...
Selecting previously unselected package mysql-client.
Preparing to unpack .../mysql-client-8.0.33-0ubuntu0.20.04.4_all.deb ...
Unpacking mysql-client (8.0.33-0ubuntu0.20.04.4) ...
Setting up mysql-common (5.8+1.0.5ubuntu2) ...
update-alternatives: using /etc/mysql/my.cnf.fallback to provide /etc/mysql/my.cnf (my.cnf) in auto mode
Setting up mysql-client-core-8.0 (8.0.33-0ubuntu0.20.04.4) ...
Setting up mysql-client-8.0 (8.0.33-0ubuntu0.20.04.4) ...
Setting up mysql-client (8.0.33-0ubuntu0.20.04.4) ...
Processing triggers for man-db (2.9.4-1) ...
```

Habilitar la extracción de instalación y versión de MySQL

which mysql

mysql --version

```
After this operation, 75.6 MB of additional disk space will be used.
Get:1 http://us-east-1.ec2.archive.ubuntu.com/ubuntu focal-updates/main amd64 mysql-client-core-8.0 amd64 8.0.33-0ubuntu0.20.04.4 [5176 kB]
Get:2 http://us-east-1.ec2.archive.ubuntu.com/ubuntu focal/main amd64 mysql-common all 5.8+1.0.5ubuntu2 [7496 B]
Get:3 http://us-east-1.ec2.archive.ubuntu.com/ubuntu focal-updates/main amd64 mysql-client-8.0 amd64 8.0.33-0ubuntu0.20.04.4 [22.0 kB]
Get:4 http://us-east-1.ec2.archive.ubuntu.com/ubuntu focal-updates/main amd64 mysql-client all 8.0.33-0ubuntu0.20.04.4 [9356 B]
Fetched 5215 kB in 0s (11.4 MB/s)
Selecting previously unselected package mysql-client-core-8.0.
(Reading database ... 72211 files and directories currently installed.)
Preparing to unpack .../mysql-client-core-8.0_8.0.33-0ubuntu0.20.04.4_amd64.deb ...
Unpacking mysql-client-core-8.0 (8.0.33-0ubuntu0.20.04.4) ...
Selecting previously unselected package mysql-common.
Preparing to unpack .../mysql-common_5.8+1.0.5ubuntu2_all.deb ...
Unpacking mysql-common (5.8+1.0.5ubuntu2) ...
Selecting previously unselected package mysql-client-8.0.
Preparing to unpack .../mysql-client-8.0_8.0.33-0ubuntu0.20.04.4_amd64.deb ...
Unpacking mysql-client-8.0 (8.0.33-0ubuntu0.20.04.4) ...
Selecting previously unselected package mysql-client.
Preparing to unpack .../mysql-client-8.0.33-0ubuntu0.20.04.4_all.deb ...
Unpacking mysql-client (8.0.33-0ubuntu0.20.04.4) ...
Setting up mysql-common (5.8+1.0.5ubuntu2) ...
update-alternatives: using /etc/mysql/my.cnf.fallback to provide /etc/mysql/my.cnf (my.cnf) in auto mode
Setting up mysql-client-core-8.0 (8.0.33-0ubuntu0.20.04.4) ...
Setting up mysql-client-8.0 (8.0.33-0ubuntu0.20.04.4) ...
Setting up mysql-client (8.0.33-0ubuntu0.20.04.4) ...
Processing triggers for man-db (2.9.1-1) ...
ubuntu@ip-172-31-81-131:~$ which mysql
/usr/bin/mysql
ubuntu@ip-172-31-81-131:~$ mysql --version
mysql Ver 8.0.33-0ubuntu0.20.04.4 for Linux on x86_64 ((Ubuntu))
ubuntu@ip-172-31-81-131:~$
```

Establecer comunicaci3n

mysql -u root -p

```
ubuntu@ip-172-31-81-131:~$ mysql -u root -p
Enter password:
ERROR 2002 (HY000): Can't connect to local MySQL server through socket '/var/run/mysqld/mysqld.sock' (2)
```

El comando de inspecci3n ayuda a asignar una direcci3n IP a la instancia del servidor MySQL:

docker inspect -f

'{{range NetworkSettings.Networks}}{{.IPAddress}}{{end}}' mysql-demo

```
ubuntu@ip-172-31-81-131:~$ mysql -h 172.17.0.4 -P 3306 --protocol=tcp -u root -p
Enter password:
Welcome to the MySQL monitor.  Commands end with ; or \g.
Your MySQL connection id is 8
Server version: 8.1.0 MySQL Community Server - GPL

Copyright (c) 2000, 2023, Oracle and/or its affiliates.

Oracle is a registered trademark of Oracle Corporation and/or its
affiliates. Other names may be trademarks of their respective
owners.

Type 'help;' or '\h' for help. Type '\c' to clear the current input statement.

mysql>
```

Proporcionar la direcci3n IP anterior en la opci3n de host del cliente, con el n3mero de puerto predeterminado y el tipo de protocolo como TCP:

mysql -h 172.17.0.2 -P 3306 --protocol=tcp -u root -p

```
ubuntu@ip-172-31-81-131: ~$ mysql -h 172.17.0.4 -P 3306 --protocol=tcp -u root -p
Enter password:
Welcome to the MySQL monitor.  Commands end with ; or \g.
Your MySQL connection id is 8
Server version: 8.1.0 MySQL Community Server - GPL

Copyright (c) 2000, 2023, Oracle and/or its affiliates.

Oracle is a registered trademark of Oracle Corporation and/or its
affiliates. Other names may be trademarks of their respective
owners.

Type 'help;' or '\h' for help. Type '\c' to clear the current input statement.

mysql>
```

Ingresar el siguiente comando para mostrar las base de datos
show databases;

```
mysql> show databases;
+-----+
| Database |
+-----+
| information_schema |
| mysql |
| performance_schema |
| sys |
+-----+
4 rows in set (0.14 sec)

mysql>
```

Crear una base de datos
create database automatiza;

```
mysql> create database automatiza;
Query OK, 1 row affected (0.03 sec)

mysql>
```

Cambiarse a la base de datos
use automatiza;

Crear una tabla llamada usuarios con los siguientes campos

Campo	Tipo de datos	Indices
username	varchar(30) PK	
password	varchar(20)	
email	varchar(80)	UNIQUE
telefono	varchar(10)	UNIQUE

```
mysql> create database automatiza;
Query OK, 1 row affected (0.03 sec)

mysql> use automatiza;
Database changed
mysql> CREATE TABLE usuarios (
  ->     username VARCHAR(30) PRIMARY KEY,
  ->     password VARCHAR(20),
  ->     email VARCHAR(80) UNIQUE,
  ->     telefono VARCHAR(10) UNIQUE
  -> );
Query OK, 0 rows affected (0.05 sec)

mysql> 
```

Ejecutar comando quit para salir de cliente mysql

quit

Para el contenedor

sudo docker stop mysql-demo

```
ubuntu@ip-172-31-81-131:~$ sudo docker stop mysql-demo
mysql-demo
ubuntu@ip-172-31-81-131:~$ 
```

Eliminar el contenedor

sudo docker rm mysql-demo

Creando un contenedor de red

docker network create network-mysql

Modificar archivo para crear contenedor y agregar comando

**--network network-mysql **