Anti-Spark Module User Manual

Model # AS60

The AS60 Anti-Spark Module is designed for power battery systems. It features a built-in power-on delay mechanism that effectively suppresses the sparking (inrush current) phenomenon that occurs when the battery is connected to the load. It significantly reduces the intensity of the spark, protecting connectors, controllers, and other electronic devices from repeated surges, thereby enhancing system safety and service life.

Product Features

•**Power-On Delay Mechanism:** Delays power-on after connection, suppressing instantaneous high-current surges and reducing sparking.

•**XT60 Standard Interface:** XT60 male input and XT60 female output, compatible with mainstream power devices.

•**Wide Voltage Support:** Compatible with 3S to 8S lithium battery packs (approx. 11.1V – 33.6V).

•**Dual Current Rating Options:** Available in 30A and 60A versions to meet different power requirements.

•**Plug-and-Play:** No external setup required; simply connect in series between the battery and the load.

autorotech.com

Structure Description

•**Input (XT60 Male):** Connects to the battery.

•**Output (XT60 Female):** Connects to the ESC, charger, or other load equipment.

•**Module Body:** Contains the built-in delay control circuit; no external power supply or setup required.

Precautions

•**Do Not Exceed Ratings:**
Ensure the system voltage does not exceed 8S (33.6V) and that the continuous current does not exceed the module's rated value. Failure to do so may cause overheating or damage.
•**Avoid Reverse Polarity:**
XT60 connectors are designed to prevent reverse insertion, but do not force reverse connection or modify the interface.
•**Avoid Moisture and High Temperature:**
The module contains electronic components and should not be used for extended periods in humid, high-temperature, or high-vibration environments.

autorotech.com

•Regular Inspection:

Before use, check the connectors for oxidation and the wires for damage to ensure proper contact.

•High-Power Application Suggestion:

When used in continuous 60A applications, ensure adequate ventilation and heat dissipation around the module.

Contact & Support

For technical support, contact: Autoro.service@hotmail.com

For commercial inquiries, contact: Autoro.sales@hotmail.com

Website: https://www.autorotech.com

autorotech.com

AUTORO