Autoro Product Catalog

Company: Zhuhai Baoge Technology Co., Ltd.

Document Version: V1.1

Update Date: 2026-10-08

Contact Information:

Technical Support: Autoro.service@hotmail.com

Cooperation Inquiries: Autoro.sales@hotmail.com

Official Website: https://www.autorotech.com

Address: 509, 5th Floor, Zone D, Shucai Wuliu Area, No.77 Huawei Road, Xiangzhou District, Zhuhai, China

autorotech.com

Table of Contents

Table of Contents 2
1 About This Catalog 3
    1.1 Brand Introduction 3
    1.2 Purpose 3
    1.3 Information Description 3
2 Product Classification Navigation 4
3 Product List 5
4 Product Selection Guide 11
    4.1 Selection by Application Scenario 11
5 Inquiry and Purchase Methods 12
    5.1 Cooperation Channels 12
    5.2 Service Support 12
6 Product Update Record 13
All rights reserved by Autoro. 14

autorotech.com

1 About This Catalog

1.1 Brand Introduction

Zhuhai Baoge Technology Co., Ltd. is a technology-driven enterprise focused on the R&D and manufacturing of high-end intelligent electric drive systems. Its brand, Autoro, leverages its independent R&D and technical optimizations based on the VESC architecture, committed to providing global users with high-performance, high-reliability electronic speed controller (ESC) systems and intelligent power solutions. Relying on the industrial and innovation resources of the Guangdong-Hong Kong-Macao Greater Bay Area, we promote the evolution and application of intelligent electric drive technology with sustained innovative vitality and pragmatic technical strength.

1.2 Purpose

To facilitate customers in quickly understanding Autoro's full range of products, core parameters, and cooperation channels, helping to efficiently match application needs.

1.3 Information Description

• Includes all products currently on sale; discontinued products are not listed.

• Product specifications are subject to the actual delivered product; customization support is available.

• Products can be quickly searched by classification, model, or parameter.

autorotech.com

2 Product Classification Navigation

Primary Classification	Secondary Classification	Number of Products	Key Features
Motor Drive & Speed Control System	VESC-based ESC (AESC Series)	8	High power, wide voltage adaptation, precise speed control; based on VESC architecture
	General DC Motor Driver	1	Wide voltage input, high output power, flexible control logic
Battery Management System	Multi-Channel Parallel Charging Management	1	Parallel charging for multiple batteries, safety monitoring
	Dual Power Automatic Transfer Switch	15	Dual power switching, high current capacity, system stability
	AC Dual Power Automatic Transfer Switch	1	Dual power switching
Safety Protection Components	Anti-Spark Module	1	Inrush current suppression, arc prevention, high safety factor
	Anti-Spark Switch	3	Inrush current suppression, arc prevention, high safety factor, switch control
Control & Communication Module	Wireless Communication Module	1	Remote control, multi-device compatibility, stable transmission
Accessories	Sensor Module	1	High compatibility, precise signal, easy installation
	Power Distributor	3	Multi-port distribution, high power capacity

autorotech.com

3 Product List

Product Model	Classification	Product Image	Core Specifications
Motor Drive & Speed Control System			
V4	VESC-based ESC (AESC Series)		Voltage: 3-12S(12-50.4V) Current: 50A cont. , 100A peak ERPM:100000
V6.7	VESC-based ESC (AESC Series)		Voltage: 3-12S(12-50.4V) Current: 50A cont. , 100A peak ERPM:150000
V4 Pro	VESC-based ESC (AESC Series)		Voltage: 4-12S(14-50.4V) Current: 80A cont. , 150A peak ERPM:100000
V6.7 Pro	VESC-based ESC (AESC Series)		Voltage: 4-12S(14-50.4V) Current: 80A cont. , 150A peak ERPM:150000
DV6.7	VESC-based ESC (AESC Series)		Voltage: 3-12S(12-50.4V) 50A cont. per channel (dual independent) ERPM:150000




autorotech.com

V75100	VESC-based ESC (AESC Series)		Voltage: 4-20S(14-84V) 100A cont. ERPM:150000 Full Metal Case Built-in Bluetooth module
V75100 Pro	VESC-based ESC (AESC Series)		Voltage: 4-20S(14-84V) 100A cont. ERPM:150000 Full Metal Case Built-in Bluetooth module Support light show and auxiliary cooling
V75100 mini	VESC-based ESC (AESC Series)		Voltage: 4-18S(14-75V) 80A cont. ERPM:150000
AM1000	General DC Motor Driver		Voltage:12-36V Max power：800W Control Logic Voltage: 3.3-12V
Battery Management System			
AB15	Multi-Channel Parallel Charging Management System		Voltage:2-8S LiPo/Li-ion Max Charging Current: 15A per channel (40A total) Max Balance Current: 2A Real-time Voltage Display
AB18	Dual Power Automatic Transfer Switch		Voltage:12-60V DC Max Output Current:18A Configurable Switching Voltage Real-time Voltage Display
AB19A	Dual Power Automatic Transfer Switch		Voltage:12-40V DC Max Output Current:50A Configurable Switching Voltage Real-time Voltage Display




autorotech.com

AB19B	Dual Power Automatic Transfer Switch		Voltage:12-72V DC Max Output Current:50A Configurable Switching Voltage Real-time Voltage Display
ABR19A	Dual Power Automatic Transfer Switch		Voltage:12-40V DC Max Output Current:50A Support remote control Real-time Voltage Display
ABR19B	Dual Power Automatic Transfer Switch		Voltage:12-72V DC Max Output Current:50A Support remote control Real-time Voltage Display
AB20A	Dual Power Automatic Transfer Switch		Voltage:3-30V DC Max Input Current: 10A per channel Max Output Current: 10A
AB20B	Dual Power Automatic Transfer Switch		Voltage: 3-30V DC Max Input Current: 20A per channel Max Output Current: 20A
AB20C	Dual Power Automatic Transfer Switch		Voltage:5-30V DC Max Input Current: 20A per channel Max Output Current: 20A Real-time Voltage Display



autorotech.com

AB20D	Dual Power Automatic Transfer Switch		Voltage:5-60V DC Max Input Current: 20A per channel Max Output Current: 20A Real-time Voltage Display
AB21A	Dual Power Automatic Transfer Switch		Voltage:5-30V DC Max Input Current: 40A per channel Max Output Current: 40A Real-time Voltage Display
AB21B	Dual Power Automatic Transfer Switch		Voltage:5-60V DC Max Input Current: 40A per channel Max Output Current: 40A Real-time Voltage Display
AB30	Dual Battery Automatic Transfer Switch		Voltage: 5-40V DC Max Input Current: 30A per channel Max Output Current: 60A(Peak 150A) Connector: XT30
AB50	Dual Battery Automatic Transfer Switch		Voltage: 5-40V DC Max Input Current: 50A per channel Max Output Current: 100A(Peak 200A) Connector: XT60
AB100	Dual Power Automatic Transfer Switch		Voltage:5-100V DC Max Input Current: 50 per channel Max Output Current: 100A(Peak 150A)

autorotech.com

AB200	Dual Power Automatic Transfer Switch		Voltage:5-100V DC Max Input Current: 80A per channel Max Output Current: 160A(Peak 200A)
AB220	AC Dual Power Automatic Transfer Switch		Voltage:100-240V AC Max Input Current: 10A
Safety Protection Components			
AS60	Anti-Spark Module		Voltage:3-8S Max Current: 30A / 60A Connector：XT60
AS100	Anti-Spark Switch		Voltage:2-20S (6-84V) Max Current: 100A Full Metal Case
AS200	Anti-Spark Switch		Voltage:2-20S (6-84V) Max Current: 200A Full Metal Case
ASR100	Anti-Spark Switch		Voltage:2-20S (6-84V) Max Current: 100A Full Metal Case Support remote control

autorotech.com

Control & Communication Module			
BT Nano	Wireless Communication Module		Voltage:3.3-5V Baud Rate:115200 Max Transmission Distance: 20m
Accessories			
AS5047P	Sensor Module		Voltage:3.3V / 5V Supports SPI / ABI / UVW
XT60 Hub	Power Distributor		1 to 4 Input Connector:XT60-M Output Connector:XT60-F
XT90 to XT60 Hub	Power Distributor		1 to 4 Input Connector:XT90-M Output Connector:XT60-F
XT60 to XT30 Hub	Power Distributor		1 to 4 Input Connector:XT60-M Output Connector:XT30-F

autorotech.com

4 Product Selection Guide

4.1 Selection by Application Scenario

Application Scenario	Recommended Product Models
High-performance electric skateboards, electric vehicles, underwater thrusters	V4、V6.7、V4 Pro、V6.7 Pro、DV6.7、V75100、V75100 Pro、V75100 mini
Small to medium power DC motor drive	AM1000
Parallel charging for multiple batteries (drones / energy storage)	AB15
Power switching for small to medium power devices	AB18、AB20、AB30、AB50
Power switching for high-power devices	AB100、AB200、AB19B、ABR19B、AB21B
Safety protection	AS60、AS100、AS200
Remote control / device interconnection	BT Nano
Power distribution / signal acquisition	XT60 Hub、T-Plug Hub、AS5047P

autorotech.com

5 Inquiry and Purchase Methods

5.1 Cooperation Channels

Email Contact:

• **Cooperation Inquiries:** Autoro.sales@hotmail.com
• **Technical Support:** Autoro.service@hotmail.com
• **In-person Meeting:** 509, 5th Floor, Zone D, Shucai Wuliu Area, No.77 Huawei Road, Xiangzhou District, Zhuhai, China (Appointment required)

5.2 Service Support

• **Customization Services:** Voltage, power, interface, function customization
• **Bulk Purchasing:** Tiered pricing + priority technical support
• **After-Sales Service:** 1-year warranty, product manuals, installation guidance

autorotech.com

6 Product Update Record

Update Date	Update Content
[2026-02-01]	Initial Release
[2025-10-08]	Add V75100 Pro/V75100 mini/ABR100

autorotech.com

CONTACT & SUPPORT

For technical support,contact : Autoro.service@hotmail.com

For business,contact : Autoro.sales@hotmail.com

Website : https://www.autorotech.com

DISCLAIMER & IMPORTANT NOTICE

This document is provided under the following terms:
1.Proprietary Information: All content,including text and graphics,constitutes Autoro's intellectual property.
2.Illustrative Purpose: Visual and textual materials serve as reference only. Technical specifications may be updated without notice.
3.Content Accuracy:Document content is subject to change without notice. Example scenarios use fictitious entities or data unless explicitly stated otherwise.
4.Product Evolution: Product specifications are subject to change without notice due to continuous product improvements.

All rights reserved by Autoro.

autorotech.com