



Autoro Product Catalog

Company: Zhuhai Baoge Technology Co., Ltd.

Document Version: V1.1

Update Date: 2026-08-06

Contact Information:

Technical Support: Autoro.service@hotmail.com

Cooperation Inquiries: Autoro.sales@hotmail.com

Official Website: <https://www.autorotech.com>

Address: 509, 5th Floor, Zone D, Shucai Wuliu Area, No.77 Huawei Road, Xiangzhou District,

Zhuhai, China

Table of Contents

Table of Contents	2
1 About This Catalog	3
1.1 Brand Introduction	3
1.2 Purpose	3
1.3 Information Description	3
2 Product Classification Navigation	4
3 Product List	5
4 Product Selection Guide	10
4.1 Selection by Application Scenario	10
5 Inquiry and Purchase Methods	11
5.1 Cooperation Channels	11
5.2 Service Support	11
6 Product Update Record	12
<i>All rights reserved by Autoro.</i>	13

1 About This Catalog

1.1 Brand Introduction

Zhuhai Baoge Technology Co., Ltd. is a technology-driven enterprise focused on the R&D and manufacturing of high-end intelligent electric drive systems. Its brand, Autoro, leverages its independent R&D and technical optimizations based on the VESC architecture, committed to providing global users with high-performance, high-reliability electronic speed controller (ESC) systems and intelligent power solutions. Relying on the industrial and innovation resources of the Guangdong-Hong Kong-Macao Greater Bay Area, we promote the evolution and application of intelligent electric drive technology with sustained innovative vitality and pragmatic technical strength.

1.2 Purpose

To facilitate customers in quickly understanding Autoro's full range of products, core parameters, and cooperation channels, helping to efficiently match application needs.


1.3 Information Description

- Includes all products currently on sale; discontinued products are not listed.
- Product specifications are subject to the actual delivered product; customization support is available.
- Products can be quickly searched by classification, model, or parameter.

2 Product Classification Navigation

Primary Classification	Secondary Classification	Number of Products	Key Features
Motor Drive & Speed Control System	VESC-based ESC (AESC Series)	7	High power, wide voltage adaptation, precise speed control; based on VESC architecture
	General DC Motor Driver	1	Wide voltage input, high output power, flexible control logic
Battery Management System	Multi-Channel Parallel Charging Management	1	Parallel charging for multiple batteries, safety monitoring
	Dual Power Automatic Transfer Switch	12	Dual power switching, high current capacity, system stability
	AC Dual Power Automatic Transfer Switch	1	Dual power switching
Safety Protection Components	Anti-Spark Module	1	Inrush current suppression, arc prevention, high safety factor
	Anti-Spark Switch	3	Inrush current suppression, arc prevention, high safety factor, switch control
Control & Communication Module	Wireless Communication Module	1	Remote control, multi-device compatibility, stable transmission
Accessories	Sensor Module	1	High compatibility, precise signal, easy installation
	Power Distributor	3	Multi-port distribution, high power capacity

3 Product List



Product Model	Product Image	Core Specifications
VESC-based ESC (AESC Series)		
V4		Voltage: 3-12S(12-50.4V) Current: 50A cont. , 100A peak ERPM:100000
V6.7		Voltage: 3-12S(12-50.4V) Current: 50A cont. , 100A peak ERPM:150000
V4 Pro		Voltage: 4-12S(14-50.4V) Current: 80A cont. , 150A peak ERPM:100000 Built-in anti-spark protection
V6.7 Pro		Voltage: 4-12S(14-50.4V) Current: 80A cont. , 150A peak ERPM:150000 Built-in anti-spark protection
DV6.7		Voltage: 3-12S(12-50.4V) 50A cont. per channel (dual independent) ERPM:150000 Built-in anti-spark protection

V75100		Voltage: 4-20S(14-84V) 100A cont. ERPM:150000 Full Metal Case Built-in Bluetooth module
V75100 Pro		Voltage: 4-20S(14-84V) 100A cont. ERPM:150000 Full Metal Case Built-in Bluetooth module COOL interface for 12V fan/pump ARGB interface for WS2812 LED effects
General DC Motor Driver		
AM1000		Voltage:12-36V Max power: 800W Control Logic Voltage: 3.3-12V
Multi-Channel Parallel Charging Management		
AB15		Voltage:2-8S LiPo/Li-ion Max Charging Current: 15A per channel (40A total) Max Balance Current: 2A Real-time Voltage Display
Dual Power Automatic Transfer Switch		
AB18		Voltage:12-60V DC Max Output Current:18A Configurable Switching Voltage Real-time Voltage Display
AB19		Voltage: 12-40V / 12-72V Max Output Current:50A Configurable Switching Voltage Real-time Voltage Display


ABR19		Voltage: 12–40V / 12–72V Max Output Current: 50A Real-time Voltage Display Remote source selection (main/backup switchable via remote)
AB20A		Voltage: 3-30V DC Max Input Current: 10A per channel Max Output Current: 10A
AB20B		Voltage: 3-30V DC Max Input Current: 20A per channel Max Output Current: 20A
AB20C		Voltage: 5-30V DC Max Input Current: 20A per channel Max Output Current: 20A Real-time Voltage Display
AB20D		Voltage: 5-60V DC Max Input Current: 20A per channel Max Output Current: 20A Real-time Voltage Display
AB21		Voltage: 5–30V / 5–60V Max Output Current: 50A Real-time Voltage Display
AB30		Voltage: 5-40V DC Max Input Current: 30A per channel Max Output Current: 60A(Peak 150A) Connector: XT30

AB50		Voltage: 5-80V DC Max Input Current: 50A per channel Max Output Current: 100A(Peak 200A) Connector: XT60
AB100		Voltage:5-100V DC Max Input Current: 50 per channel Max Output Current: 100A(Peak 150A)
AB200		Voltage:5-100V DC Max Input Current: 80A per channel Max Output Current: 160A(Peak 200A)
AC Dual Power Automatic Transfer Switch		
AB220		Voltage:100-240V AC Max Input Current: 10A
Anti-Spark Module		
AS60		Voltage:3-8S Max Current: 30A / 60A Connector: XT60


Anti-Spark Switch

AS100		Voltage: 2-20S (6-84V) Current: Continuous 100A (Peak 200A) Full Metal Case
ASR100		Voltage: 2-20S (6-84V) Max Output Current: 100A Full Metal Case Remote control ready (ON/OFF via dedicated remote) Two operating modes (Default / Vibration) – Vibration mode prevents accidental power-off by disabling the OFF button when motion is detected.
AS200		Voltage: 2-20S (6-84V) Current: Continuous 200A (Peak 400A) Full Metal Case

Wireless Communication Module

BT Nano		Voltage: 3.3-5V Baud Rate: 115200 Max Transmission Distance: 20m
---------	---	--

Sensor Module

AS5047P		Voltage: 3.3V / 5V Supports SPI / ABI / UVW
---------	---	--

Power Distributor

XT60 Hub		1 to 4 Input Connector:XT60-M Output Connector:XT60-F
XT90 to XT60 Hub		1 to 4 Input Connector:XT90-M Output Connector:XT60-F
XT60 to XT30 Hub		1 to 4 Input Connector:XT60-M Output Connector:XT30-F

4 Product Selection Guide

4.1 Selection by Application Scenario

Application Scenario	Recommended Product Models
High-performance electric skateboards, electric vehicles, underwater thrusters	V4、V6.7、V4 Pro、V6.7 Pro、DV6.7、V75100
Small to medium power DC motor drive	AM1000
Parallel charging for multiple batteries (drones / energy storage)	AB15
Power switching for small to medium power devices	AB18、AB20、AB30、AB50、AB19、ABR19、AB21
Power switching for high-power devices	AB100、AB200
Safety protection	AS60、AS100、AS200、ASR100
Remote control / device interconnection	BT Nano、ABR19、ASR100
Power distribution / signal acquisition	XT60 Hub、T-Plug Hub、AS5047P

5 Inquiry and Purchase Methods

5.1 Cooperation Channels

Email Contact:

- **Cooperation Inquiries:** Autoro.sales@hotmail.com
- **Technical Support:** Autoro.service@hotmail.com
- **In-person Meeting:** 509, 5th Floor, Zone D, Shucai Wuliu Area, No.77 Huawei Road, Xiangzhou District, Zhuhai, China (Appointment required)

5.2 Service Support

- **Customization Services:** Voltage, power, interface, function customization
- **Bulk Purchasing:** Tiered pricing + priority technical support
- **After-Sales Service:** 1-year warranty, product manuals, installation guidance

6 Product Update Record

Update Date	Update Content
[2026-02-01]	Initial Release
[2026-08-06]	Added V75100 Pro, AB19, ABR19, AB21, ASR100 models

autorotech.com



CONTACT & SUPPORT

For technical support, contact : Auroro.service@hotmail.com

For business, contact : Auroro.sales@hotmail.com

Website : <https://www.autorotech.com>

DISCLAIMER & IMPORTANT NOTICE

This document is provided under the following terms:

1. Proprietary Information: All content, including text and graphics, constitutes Auroro's intellectual property.
2. Illustrative Purpose: Visual and textual materials serve as reference only. Technical specifications may be updated without notice.
3. Content Accuracy: Document content is subject to change without notice. Example scenarios use fictitious entities or data unless explicitly stated otherwise.
4. Product Evolution: Product specifications are subject to change without notice due to continuous product improvements.

All rights reserved by Auroro.