Product Catalog

AESC			
Model	**SPEC**	**Image**	**Special Features**
V4	**Voltage: 3-12S(12-50.4V)** **Current: 50A cont. , 100A peak** **ERPM:100000**		**-**
V6.7	**Voltage: 3-12S(12-50.4V)** **Current: 50A cont. , 100A peak** **ERPM:150000**		**-**
V4 Pro	**Voltage: 4-12S(14-50.4V)** **Current: 80A cont. , 150A peak** **ERPM:100000**		**Built-in anti spark switch**
V6.7 Pro	**Voltage: 4-12S(14-50.4V)** **Current: 80A cont. , 150A peak** **ERPM:150000**		**Built-in anti spark switch**
DV6.7	**3-12S(12-50.4V)** **50A cont. per channel** **(dual independent)** **ERPM:150000**		**Dual motor sync**
V75100	**4-20S(14-84V)** **100A cont.** **ERPM:150000**		**Built-in Bluetooth module**
New models	**-**		***Continuously updated***

autoro tech.com

BMS

Model	SPEC	Image	Special Features
AB15	Supported Battery Types 2S to 8S LiPo Li ion Maximum Charging Current 15A per channel 40A total Maximum Balancing Current 2A Discharge Cut off Voltage 3.8V per cell Maximum Simultaneous Charging 4 batteries		Auto Cell Count Recognition 2S to 8S Real Time Voltage Display Charge Completion Alarm Discharge Completion Alarm
AB18	Voltage : 12~60V DC Max Output Current:18A cont.		Configuration switching voltage: Supported Real Time Voltage Display : Supported
AB20A	Maximum Input Voltage : 30V DC Input Current :10A cont. per channel Max Output Current:10A cont.		Reverse Current Protection : Supported Automatic Power Switching : Supported
AB20B	Maximum Input Voltage : 30V DC Input Current :20A cont. per channel Max Output Current:20A cont.		Reverse Current Protection : Supported Automatic Power Switching : Supported
AB20C	Maximum Input Voltage : 30V DC Input Current :20A cont. per channel Max Output Current:20A cont.		Reverse Current Protection : Supported Automatic Power Switching : Supported Real Time Voltage Display : Supported
AB20D	Maximum Input Voltage : 60V DC Input Current :20A cont. per channel Max Output Current:20A cont.		Reverse Current Protection : Supported Automatic Power Switching : Supported Real Time Voltage Display: Supported
AB50	Maximum Input Voltage : 80V DC Maximum Input Current : 50A per channel Maximum Output Current : Continuous 100A, Peak 200A		Maximum Input Voltage Differential : 20V DC Reverse Current Protection : Supported Automatic Power Switching : Supported

autorotech.com

AB100	**Maximum Input Voltage : 100V DC** **Maximum Input Current : 100A per channel** **Maximum Output Current : Continuous 200A, Peak 350A**		**Maximum Input Voltage Differential : 20V DC** **Reverse Current Protection : Supported** **Automatic Power Switching : Supported**
AB200	**Maximum Input Voltage : 100V DC** **Maximum Input Current : 200A per channel** **Maximum Output Current : Continuous 400A, Peak 500A**		**Maximum Input Voltage Differential : 20V DC** **Reverse Current Protection : Supported** **Automatic Power Switching : Supported**
XT60 Hub	**1-to-4 Power Splitter** **XT60**		**-**
T-Plug Hub	**1-to-6 Power Splitter** **T-Plug**		**-**
New models	**-**		***Continuously updated***

Switch

Model	SPEC	Image	Special Features
AS100	**Voltage: 2-20S(6-84V)** **Current: 100A cont. , 200A peak**		**Spark suppression for safe battery connection**
AS200	**Voltage: 2-20S(6-84V)** **Current: 200A cont. , 400A peak**		**Spark suppression for safe battery connection**
New models	**-**		***Continuously updated***

autorotech.com

Bluetooth			
Model	**SPEC**	**Image**	**Special Features**
BT Nano	**Input voltage: 3.3 - 5V** **Baud rate: 115200** **Compatible devices: Android/iPhone** **Range:20m**		**App: VESC Tool**
New models	**-**		***Continuously updated***

Other			
Model	**SPEC**	**Image**	**Special Features**
AS5047P Module	**Voltage:3.3V / 5V** **Support SPI/ABI/UVW**		**-**
New models	**-**		***Continuously updated***

autorotech.com