

macroeconomic_influence_on_hpi20260313

March 14, 2026

0.1 macroeconomic_influence_on_hpi.ipynb

0.1.1 1. Imports Library

```
[15]: # Imports Library
import pandas as pd
import matplotlib.pyplot as plt
import seaborn as sns
from pathlib import Path

import warnings
warnings.filterwarnings("ignore", category=Warning)
```

0.1.2 2. Load and Preprocess Ames House Price Index data

```
[16]: # Load Ames House Price Index data
df_hpi = pd.read_csv(Path("data/Ames House Price Index.csv"))
df_hpi.head(2)
```

```
[16]: observation_date  ATNHPIUS11180Q
0      1990-01-01      76.43
1      1990-04-01      76.58
```

```
[17]: # Preprocess df_hpi
# Rename to consistent column names
df_hpi = df_hpi.rename(columns={
    "observation_date": "Date",
    "ATNHPIUS11180Q": "HPI"
})

# Parse dates
df_hpi["Date"] = pd.to_datetime(df_hpi["Date"])

# Create YearQuarter column
df_hpi["YearQuarter"] = df_hpi["Date"].dt.to_period("Q")

# Ensure numeric
df_hpi["HPI"] = pd.to_numeric(df_hpi["HPI"], errors="coerce")
```

```
# Set index
df_hpi_q = df_hpi.set_index("YearQuarter").sort_index()

# Drop the original Date column if you only want to merge on Quarter
df_hpi_q = df_hpi_q.drop(columns=["Date"])

df_hpi_q.head()
```

```
[17]:          HPI
YearQuarter
1990Q1      76.43
1990Q2      76.58
1990Q3      78.72
1990Q4      78.86
1991Q1      81.22
```

0.1.3 3. Load and Preprocess CrimeRate, InterestRate, and UnemploymentRate dataset

1) Load and preprocess CrimeRate dataset

```
[18]: # Load CrimeRate data
df_crime = pd.read_csv(Path("data/Crime_Rate_lowa.csv"))
df_crime.head(2)
```

```
[18]:   Year  Population   Index  Violent  Property  Murder
0  1990    2776755  113871    8321    105550     54
1  1991    2795000  115546    8477    107069     57
```

```
[19]: # Calculate CrimeRate
df_crime["Index"] = df_crime["Index"].replace(',', ' ', regex=True).astype(int)
df_crime["Population"] = df_crime["Population"].replace(',', ' ', regex=True).
    ↪astype(int)
df_crime["CrimeRate"] = df_crime["Index"] / df_crime["Population"] * 1000
df_crime.head()
```

```
[19]:   Year  Population   Index  Violent  Property  Murder  CrimeRate
0  1990    2776755  113871    8321    105550     54  41.008659
1  1991    2795000  115546    8477    107069     57  41.340250
2  1992    2812000  111275    7816    103459     44  39.571479
3  1993    2814000  108239    9159     99080     66  38.464463
4  1994    2829000  103389    8914     94475     47  36.546129
```

```
[20]: # Preprocess df_crime

# Create mapping dictionary
```

```

yr_to_rate = df_crime.dropna(subset=["Year", "CrimeRate"]).
    ↪set_index("Year")["CrimeRate"]

# Build full quarterly PERIOD index
start_year = int(df_crime["Year"].min())
end_year = int(df_crime["Year"].max())

# Create range of Quarters
q_index = pd.period_range(start=f"{start_year}Q1", end=f"{end_year}Q4",
    ↪freq="Q")

# Map annual rates to quarters
df_crime_q = pd.DataFrame({"YearQuarter": q_index})
df_crime_q["Year"] = df_crime_q["YearQuarter"].dt.year
df_crime_q["CrimeRate"] = df_crime_q["Year"].map(yr_to_rate)

# Clean up
df_crime_q = df_crime_q.drop(columns=["Year"])
df_crime_q["CrimeRate"] = df_crime_q["CrimeRate"].round(6)

df_crime_q.head()

```

```

[20]:   YearQuarter  CrimeRate
0      1990Q1    41.008659
1      1990Q2    41.008659
2      1990Q3    41.008659
3      1990Q4    41.008659
4      1991Q1    41.340250

```

2) Load and preprocess InterestRate

```

[21]: # Load InterestRate data
df_mortgage = pd.read_csv(Path("data/Mortgage Rates USA.csv"))
df_mortgage.head(2)

```

```

[21]:   observation_date  MORTGAGE30US
0          1/5/1990           9.83
1          1/12/1990           9.80

```

```

[22]: # Preprocess mortgage df

# Rename to consistent column names
df_mortgage = df_mortgage.rename(columns={"observation_date": "Date",
    ↪"MORTGAGE30US": "MortgageRate"})
df_mortgage["Date"] = pd.to_datetime(df_mortgage["Date"], errors="coerce",
    ↪infer_datetime_format=True)
df_mortgage["MortgageRate"] = pd.to_numeric(df_mortgage["MortgageRate"],
    ↪errors="coerce")

```

```

# Create YearQuarter column
df_mortgage["YearQuarter"] = df_mortgage["Date"].dt.to_period("Q")

# Group by YearQuarter and take the mean
df_mortgage_q = df_mortgage.groupby("YearQuarter",
    ↪as_index=False)["MortgageRate"].mean()
df_mortgage_q["MortgageRate"] = df_mortgage_q["MortgageRate"].round(4)

df_mortgage_q.head()

```

```

[22]:   YearQuarter  MortgageRate
0      1990Q1         10.1315
1      1990Q2         10.3238
2      1990Q3         10.1031
3      1990Q4          9.9592
4      1991Q1          9.5008

```

3) Load and preprocess UnemploymentRate

```

[23]: # Load UnemploymentRate data
df_unemployment = pd.read_csv(Path("data/AMES Unemployment Rate.csv"))
df_unemployment.head()

```

```

[23]:   observation_date  AMES119URN
0      1990-01-01          4.2
1      1990-02-01          3.8
2      1990-03-01          3.4
3      1990-04-01          3.2
4      1990-05-01          3.5

```

```

[24]: # Preprocess unemployment df

# Rename to consistent column names
df_unemployment = df_unemployment.rename(columns={"observation_date": "Date",
    ↪"AMES119URN": "Unemployment"})
df_unemployment["Date"] = pd.to_datetime(df_unemployment["Date"],
    ↪errors="coerce")
df_unemployment["Unemployment"] = pd.
    ↪to_numeric(df_unemployment["Unemployment"], errors="coerce")

# Create YearQuarter column
df_unemployment["YearQuarter"] = df_unemployment["Date"].dt.to_period("Q")

# Group by YearQuarter and take the mean
df_unemployment_q = df_unemployment.groupby("YearQuarter",
    ↪as_index=False)["Unemployment"].mean()
df_unemployment_q["Unemployment"] = df_unemployment_q["Unemployment"].round(3)

```

```
# Check
df_unemployment_q.head()
```

```
[24]:   YearQuarter  Unemployment
0      1990Q1          3.800
1      1990Q2          3.500
2      1990Q3          4.000
3      1990Q4          4.200
4      1991Q1          4.467
```

4) Load and preprocess MedianIncome

```
[25]: # Load MedianIncome data
df_income = pd.read_csv(Path("data/Ames Median Household Income.csv"))
df_income.head()
```

```
[25]:   Year  MedianIncome
0  1984         19,860
1  1985         20,930
2  1986         22,460
3  1987         22,190
4  1988         24,310
```

```
[26]: # Preprocess MedianIncome df

# Clean & standardize
df_income = df_income.loc[:, ["Year", "MedianIncome"]].dropna()
df_income["Year"] = df_income["Year"].astype(int)
df_income["MedianIncome"] = (
    df_income["MedianIncome"].astype(str).str.replace(",", "", regex=True).
    ↪astype(float)
)

# Map: year to income
yr_to_income = df_income.set_index("Year")["MedianIncome"]

# Use the HPI period index to ensure alignment, or create new range
if "df_hpi_q" in globals():
    # Use the index from HPI (which is now YearQuarter periods)
    q_index = df_hpi_q.index
else:
    start_year = int(df_income["Year"].min())
    end_year = int(df_income["Year"].max())
    q_index = pd.period_range(f"{start_year}Q1", f"{end_year}Q4", freq="Q")

df_income_q = pd.DataFrame({"YearQuarter": q_index})
df_income_q["Year"] = df_income_q["YearQuarter"].dt.year
```

```

df_income_q["MedianIncome"] = df_income_q["Year"].map(yr_to_income)

df_income_q = df_income_q.drop(columns=["Year"]).sort_values("YearQuarter").
    ↪reset_index(drop=True)
df_income_q["MedianIncome"] = df_income_q["MedianIncome"].round(2)

# Check
df_income_q.head()

```

```

[26]:
YearQuarter  MedianIncome
0      1990Q1      27290.0
1      1990Q2      27290.0
2      1990Q3      27290.0
3      1990Q4      27290.0
4      1991Q1      28550.0

```

0.1.4 4. Merge all micro datasets with Ames HPI based on 'Date'

```

[27]: # Merge all datasets on Date
# Start with HPI as base. Reset index to make 'YearQuarter' a column for
    ↪merging if it's currently the index
df_q = df_hpi_q.reset_index()

# Merge CrimeRate
df_q = df_q.merge(df_crime_q, on="YearQuarter", how="left")

# Merge MortgageRate
df_q = df_q.merge(df_mortgage_q, on="YearQuarter", how="left")

# Merge Unemployment
df_q = df_q.merge(df_unemployment_q, on="YearQuarter", how="left")

# Merge MedianIncome
df_q = df_q.merge(df_income_q, on="YearQuarter", how="left")

# Clean
df_q_clean = df_q.dropna()

# Check
print("Merged dataset shape:", df_q_clean.shape)
df_q_clean.head()

# Save to CSV
output_filename = "Ames_Macro_Quarterly_Merged.csv"
output_path = Path("output/preprocess_csv") / output_filename

# Ensure the output directory exists

```

```

output_path.parent.mkdir(parents=True, exist_ok=True)

# Save the dataframe
df_q_clean.to_csv(output_path, index=False)
print(f"Successfully saved merged dataset to: {output_path}")

```

Merged dataset shape: (120, 6)
 Successfully saved merged dataset to:
 output\preprocess_csv\Ames_Macro_Quarterly_Merged.csv

```

[28]: # Alternative: Explicitly select the numeric columns you want to include
numeric_columns = ['HPI', 'CrimeRate', 'MortgageRate', 'Unemployment',
    ↳ 'MedianIncome']
correlation_matrix = df_q_clean[numeric_columns].corr()

# Create the heatmap
plt.figure(figsize=(8, 5))
ax = sns.heatmap(correlation_matrix, annot=True, fmt=".2f", cmap="coolwarm",
    ↳ vmin=-1, vmax=1,
                    linewidths=.5, cbar_kws={"shrink": .8})
plt.title("Quarterly Correlations: Ames HPI vs Macroeconomic Factors",
    ↳ fontsize=12)
plt.xticks(rotation=45, ha="right")
plt.yticks(rotation=0)
plt.tight_layout()

# Save the figure
out_path = Path("output") / "macroeconomic_correlation_heatmap.png"
out_path.parent.mkdir(parents=True, exist_ok=True)
plt.savefig(out_path, dpi=300, bbox_inches="tight")
plt.show()

```

