



Dense 3D Geometry Estimation

Enrique Dunn



ETH zürich



Microsoft

URCV

Large-scale 3D Modeling from Crowdsourced Data


Dense 3D Modeling

Unstructured Images



- A generalization of sparse 3D reconstruction

Sparse Model



SfM

MVS

Dense Model



COLMAP - 3D reconstruction pipeline:

<https://github.com/colmap/colmap>



ETH zürich




Microsoft URCV

Large-scale 3D Modeling from Crowdsourced Data

Dense 3D Modeling

- Goal: Reconstruct all observed scene surfaces that are compliant with available geometric SfM estimates and local image appearance



ETH zürich





Microsoft URCV

Large-scale 3D Modeling from Crowdsourced Data

3D Modeling Frameworks

- Globally Parameterized 3D Structure



Sample
Input Imagery

Tetrahedral
Lattice

Graph Cut
Optimization

Surface Model



ETH zürich




Microsoft URCV

3D Modeling Frameworks

- Globally Parameterized 3D Structure
- Locally Parameterized 3D Structure

Y Furukawa, J Ponce, Accurate, dense, and robust multiview stereopsis.
PAMI 2010.



3D Modeling Frameworks


- Globally Parameterized 3D Structure
- Locally Parameterized 3D Structure
- Mixed Parameterization



Sample
Input Imagery



Multiple
Depthmaps



Probabilistic Occupancy
Analysis

Multi-Layer
Heightmap



ETH zürich



Microsoft URCV


Crowd-Sourced Dense 3D

- Data Scale
 - Total Imagery



Herz-Jesu-P8 images

vs.



126K Registered images



ETH zürich



Microsoft

URCV

Large-scale 3D Modeling from Crowdsourced Data


Crowd-Sourced Dense 3D

- Data Scale
 - Total Imagery
 - Spatial extent



Herz-Jesu-P8 images

vs.



Towards City-Scale Registration



ETH zürich



Microsoft URCV

Crowd-Sourced Dense 3D

- Data Scale
- Content Diversity
 - Indoor/outdoor



**Inside Sistine Chapel
Vatican City**



**Outside Sistine Chapel
Vatican City**



ETH zürich



Microsoft URCV

Crowd-Sourced Dense 3D

- Data Scale
- Content Diversity
 - Indoor/outdoor
 - Static/Dynamic



ETH zürich




Microsoft URCV

Large-scale 3D Modeling from Crowdsourced Data

10

Crowd-Sourced Dense 3D

- Data Scale
- Content Diversity
- Heterogeneous Capture
 - Illumination
 - Viewpoint Bias
 - Resolution
 - Field of View



ETH zürich



Microsoft

URCV

Crowd-Sourced Dense 3D

- Data Scale **Efficiency**
- Content Diversity **Generality**
- Heterogeneous Capture **Robustness**




ETH zürich



Microsoft URCV

Large-scale 3D Modeling from Crowdsourced Data

Dense 3D Modeling



Initial
Reconstructed 3D Points

Densified
3D Points + Normals

Surface Approx.
Triangular 3D Mesh



Outline

- Multi-View Stereo
- Robust Depthmap Estimation
- Fusion and Surface Estimation



ETH zürich



Microsoft URCV

Large-scale 3D Modeling from Crowdsourced Data

Outline

- Multi-View Stereo
 - Building a Cost Volume
 - Plane Sweep
 - Patch Match
- Robust Depthmap Estimation
- Fusion and Surface Estimation



ETH zürich




Microsoft **URCV**

Large-scale 3D Modeling from Crowdsourced Data


Stereo Depth Estimation

- Basic Insight: Given a known imaging configuration, geometry estimation is reduced to pixel correspondence search.



Depthmap Estimation

- Goal: Determine a view-dependent depthfield (*i.e.* pixel-wise estimates) by leveraging the photo-consistency of a set of overlapping images.




ETH zürich



Microsoft URCV

Large-scale 3D Modeling from Crowdsourced Data

Depthmap Estimation



Projection into 3D space



3D point cloud



ETH zürich




Microsoft URCV


Large-scale 3D Modeling from Crowdsourced Data

Depthmap Estimation

- For each pixel p in image I determine a depth value, among a set D of depth hypotheses, most congruent with a set J of source images.




The correspondence cost profile



Pixel-wise Cost Evaluation

Depth Map




Ground Truth




Pixel Matching

reference image



Depth


Matching Cost



Pixel similarity: measured by color differences



Building a Cost Volume



ETH zürich



Microsoft


URCV

Large-scale 3D Modeling from Crowdsourced Data

Building a Cost Volume



*Cost aggregation:
cutting the cost volume.*




ETH zürich



Microsoft

URCV

Window-based Cost Evaluation



Fronto-Parallel Plane

Cost Volume




ETH zürich



Microsoft URCV


Large-scale 3D Modeling from Crowdsourced Data

Window-based Evaluation



Treat neighbors equally

Sum of Absolute
Differences (SAD)



ETH
Zurich







Microsoft

URCV


Large-scale 3D Modeling from Crowdsourced Data

Window-based Evaluation



- Color differences
- Spatial distances


Adaptive Weight
Yoon and Kweon, PAMI 2006



Microsoft URCV

Large-scale 3D Modeling from Crowdsourced Data

Window-based Evaluation




Adaptive Weight



Oriented Plane

Lu et al., CVPR 2013



Dept. of
Computer




Microsoft URCV

Large-scale 3D Modeling from Crowdsourced Data


Aggregated Photo-consistency

- Sum of Squared Differences (SSD)
- Normalized Cross Correlation (NCC)
- CENSUS Transform
- Rank Transform
- Mutual Information
- Learning-based Methods




Binocular vs. Multi-view Depthmaps

- Dense depth/normal reconstruction




Problem/Solution
Representation

- Multi-view correspondence search







Data Association
Strategies

Different Implementations



Plane Sweep Framework

- Hypothesis space is explored by “sweeping” a plane across the scene.



ETH zürich




Microsoft URCV

Plane Sweep: Plane-Induced Homography

Given: two cameras $P=K[I \ | 0]$ and $P' = K'[R \ | t]$, and
A plane $\pi=(n^T, d)^T$


The homography $x'=Hx$ is defined as

$$H = K'(R - tn^T/d)K^{-1}$$




Plane Sweep: Operation

3D scene



Hypothesis Plane

Overlaid Warped Images



SAD as similarity
(darker is higher similarity)



ETH zürich




Microsoft

URCV



Plane Sweep: Enhanced Robustness

- Aligning sweeping direction to surface orientation reduces photometric inconsistencies at correct depth



Plane Sweep: Computational Burden

```
Initialize Similarity Cost  
For Each Pixel  
    For Each Depth  
        For Each Source Image  
            Accumulate Similarity Cost
```



Plane Sweep Overview

- Pros:
 - + Flexible homography-based warping
 - + Controllable search resolution
- Cons:
 - Exhaustive Approach
 - Local/Greedy Search



ETH zürich



Microsoft **URCV**

Large-scale 3D Modeling from Crowdsourced Data

Patchmatch Stereo

- Randomized correspondence search

For Each Pixel

 Assign RandomDepth


For N iterations

 For Each Pixel


 Propagate Depth From Neighbor

 Sample new RandomDepth


 Update Depth



Sparse Search



Propagation Scheme



ETH zürich




Microsoft

URCV

Large-scale 3D Modeling from Crowdsourced Data

Propagation Scheme



ETH zürich



Microsoft URCV

Large-scale 3D Modeling from Crowdsourced Data

PatchMatch Overview

- Pros:
 - + Efficient Search Space Exploration/Sampling
Example required only $8N+1$ evaluations per pixel!!
 - + Good Empirical Convergence
- Cons:
 - Implicit regularization tends to over-smooth
 - Stochastic non-local search



Outline

- Multi-View Stereo
- Robust Depthmap Estimation
 - Data Association
 - Estimating Surface normals
 - Joint Inference
- Fusion and Surface Estimation



ETH zürich



Microsoft URCV


Large-scale 3D Modeling from Crowdsourced Data

Multi-view Data Association

How to robustly integrate photo-consistency measurements from multiple views?



Reference image



211 Source images (only 10 are shown)




ETH zürich



Microsoft URCV

Multi-view Data Association




ETH zürich



Microsoft URCV

Large-scale 3D Modeling from Crowdsourced Data

Multi-view Data Association



Reference image



ETH zürich




Microsoft

URCV

Large-scale 3D Modeling from Crowdsourced Data

Multi-view Data Association




ETH zürich



Microsoft URCV

Large-scale 3D Modeling from Crowdsourced Data

Multi-view Data Association



ETH zürich



Microsoft


URCV

Large-scale 3D Modeling from Crowdsourced Data

Multi-view Data Association Strategies

How to robustly integrate photo-consistency measurements from multiple views?


- Fixed Selection
 - Thresholding
 - Summary Statistics
(e.g. mean, median)
 - Rank Statistics
(e.g. Top-K)



Multi-view Data Association

How to robustly integrate photo-consistency measurements from multiple views?


- Geometry-based Selection
 - Camera Proximity
 - Shared Sparse Features



Multi-view Data Association

How to robustly integrate photo-consistency measurements from multiple views?

- Appearance-Based Selection
 - Global or Per-Pixel?



Pixel-level image selection



ETH zürich



Microsoft

URCV

Large-scale 3D Modeling from Crowdsourced Data

50

Pixel-level image selection



Pixel-level image selection



Pixel-level image selection








Image Selection vs Depth Estimation

Assume known 3D structure

Assume known image selection



Robustness of pixel-wise selection



ETH zürich





Microsoft URCV

Large-scale 3D Modeling from Crowdsourced Data



Multi-View Stereo

- Pixelwise Monte-Carlo view sampling
 - Visibility probability derived photometrically
 - Incorporate geometric selection priors
 - Triangulation angle prior





Multi-View Stereo

- Pixelwise Monte-Carlo view sampling
 - Visibility probability derived photometrically
 - Incorporate geometric selection priors
 - Triangulation angle prior
 - Incident angle prior




Multi-View Stereo

- Pixelwise Monte-Carlo view sampling
 - Visibility probability derived photometrically
 - Incorporate geometric selection
 - Triangulation angle prior
 - Incident angle prior
 - **Resolution prior**




Joint likelihood Estimation







- Generalized Expectation Maximization

- E-Step
 - Infer \mathbf{Z} using variational inference
- M-Step
 - Infer $\boldsymbol{\theta}, \mathbf{N}$ using PatchMatch sampling



Joint Inference

Image Selection



ETH zürich



Microsoft URCV


Large-scale 3D Modeling from Crowdsourced Data

Joint Inference

- Random depthmap initialization



Reference image



Random depthmap





ETH zürich



Microsoft URCV

Large-scale 3D Modeling from Crowdsourced Data

Joint Inference



ETH zürich





Microsoft URCV

Large-scale 3D Modeling from Crowdsourced Data

Joint Inference

Image Selection



ETH zürich





Microsoft

URCV

Large-scale 3D Modeling from Crowdsourced Data

Joint Inference




ETH zürich




Microsoft URCV

Large-scale 3D Modeling from Crowdsourced Data


Results vs. best-K Stereo




Completeness: percentage of pixels with errors less than 2 cm




Ground truth



Joint Estimation



K=3



K=10




ETH zürich



Microsoft URCV

Results



ETH zürich




Microsoft

URCV

Large-scale 3D Modeling from Crowdsourced Data

Results




ETH zürich



Microsoft URCV

Large-scale 3D Modeling from Crowdsourced Data

Results



ETH zürich



Microsoft URCV

Large-scale 3D Modeling from Crowdsourced Data

Outline

- Multi-View Stereo
- Robust Depthmap Estimation
- **Fusion and Surface Estimation**
 - Depthmap integration
 - Surface Approximation



ETH zürich




Microsoft URCV

Large-scale 3D Modeling from Crowdsourced Data

Depthmap Fusion

- Depthmaps as point clouds



ETH zürich




Microsoft URCV

Large-scale 3D Modeling from Crowdsourced Data

Depthmap Fusion


- Direct Aggregation



- Challenges
 - Error/inconsistency mitigation
 - Completeness

Depthmap Fusion

- Goal: Mitigate depthmap measurement errors by leveraging observation redundancies, to provide an aggregated and augmented 3D representation.



ETH zürich



Microsoft URCV

Large-scale 3D Modeling from Crowdsourced Data

Depthmap Fusion Approaches

- Depthmap Refinement:
 - Local analysis of relationships among 3D points
 - Filter cross-depthmap inconsistencies
- Depthmap Integration:
 - Global analysis based on auxiliary geometric structures
 - Robustly Estimate Surface Parameters



ETH zürich




Microsoft URCV

Large-scale 3D Modeling from Crowdsourced Data

73

Enforcing Depthmap Consistency

- In 3D Space



ETH zürich




Microsoft URCV

Large-scale 3D Modeling from Crowdsourced Data


Enforcing Depthmap Consistency

- Two-view Point Transfer




Enforcing Visibility Constraints


- Identify and penalize free space violations



(a) Visibility relations between points



(b) Stability calculation






(c) Support estimation

Merrel et al. ICCV 2007

Depthmap Filtering

- Filtering Result




ETH zürich



Microsoft URCV

Large-scale 3D Modeling from Crowdsourced Data

Results



ETH zürich



Microsoft URCV

Large-scale 3D Modeling from Crowdsourced Data

Results



ETH zürich



Microsoft URCV

Large-scale 3D Modeling from Crowdsourced Data

Results



ETH zürich



Microsoft URCV

Large-scale 3D Modeling from Crowdsourced Data

Poisson Surface Reconstruction






Figure from: Kazhdan et al. / Poisson Surface Reconstruction



Spatial Aggregation

- Volumetric Scene Representation
- Each pixel votes along its viewing ray
- Each voxel accumulates votes from all intersecting rays



Spatial Aggregation

- Volumetric Scene Representation
- Each pixel votes along its viewing ray
- Each voxel accumulates votes from all intersecting rays




Spatial Aggregation

- Volumetric Scene Representation
- Each pixel votes along its viewing ray
- Each voxel accumulates votes from all intersecting rays
- Binary Labeling Problem

Graph Cuts

Variational Methods




ETH zürich



Microsoft

URCV

Analyzing Adaptive Triangulations




Weakly Supported Surfaces

- Account for proximity to open-space boundaries

M Jancosek, T Pajdla

[Multi-view reconstruction preserving weakly-supported surfaces. CVPR 2011](#)





ETH zürich



Microsoft URCV

Multi-Layer Heightmaps

- Model transitions in space occupancy along independent 1D domains



Bayesian Inference
Dynamic Programming






ETH zürich



Microsoft URCV

Robust stereo fusion process

- Heightmap 2.5D representation
- Every heightmap pixel is treated independently




ETH zürich



Microsoft URCV

Robust stereo fusion process



- Enforces vertical facades
- One continuous surface, no holes
- Fast to compute, easy to store $O(n^2)$ instead of $O(n^3)$



ETH zürich




Microsoft URCV

Large-scale 3D Modeling from Crowdsourced Data

Layout

- Vertical direction
 - vanishing point
 - camera constraints (Szeliski 2005, Snavely et al. 2006)



Video





Photo Collections



ETH zürich



Microsoft URCV


Large-scale 3D Modeling from Crowdsourced Data

Vertical Surfaces


Gallup et al. 3DPVT 2010



Input Images




Input Depthmaps




Heightmap
(Top-Down View)

the brighter the higher



3D Model
Geometry



Textured
3D Model



Large-scale 3D Modeling from Crowdsourced Data




ETH zürich

Microsoft Research

N-Layer Heightmap

- Generalize to n-layer heightmap
- Each layer is a transition from full/empty or empty/full




- Compute layer positions with dynamic programming
- Use model selection (BIC) to determine number of layers

Probabilistic Occupancy

Introduced in robotics: Margaritis and Thrun 1998

Follows derivation of Guan et al. 2008



Random Variables

O – binary, occupancy of voxel

Z={Z_i} – continuous, depth measurements for i=1...k depth maps

$$P(O|Z)$$

$\underbrace{}$




ETH zürich



Microsoft URCV

Large-scale 3D Modeling from Crowdsourced Data

Probabilistic Occupancy





$$P(Z_i|O)$$

Measurement Model

$$\begin{aligned} P(Z_i|S, O) &= P(Z_i|S) = \begin{cases} \mathcal{N}(S, \sigma)|_{Z_i} & \text{if inliner} \\ \mathcal{U}(z_{min}, z_{max})|_{Z_i} & \text{if outlier} \end{cases} \\ &= \rho \mathcal{N}(S, \sigma)|_{Z_i} + (1 - \rho) \mathcal{U}(z_{min}, z_{max})|_{Z_i} \end{aligned}$$

Surface Formation Model

$$P(S|O) = \begin{cases} 1/(z_{max} - z_{min}) & \text{if } S < z_p - \epsilon \\ (1 - z_p/(z_{max} - z_{min})/\epsilon & \text{if } z_p - \epsilon \leq S \leq z_p \\ 0 & \text{if } S > z_p \end{cases}$$




ETH zürich




Microsoft URCV

Large-scale 3D Modeling from Crowdsourced Data


Probabilistic Occupancy



$$P(Z_i|O) = \int_{z_{min}}^{z_{max}} P(Z_i|S, O)P(S|O)dS$$



Probabilistic Occupancy



ETH zürich





Microsoft

URCV

Large-scale 3D Modeling from Crowdsourced Data

Heightmap Computation



$L(O_m | Z)$

cost of voxels 1...m being full

$$C(m) = \sum_{1}^m L(Z | O_m) + \sum_{m+1}^M L(Z | \neg O_m)$$

cost of voxels $m+1 \dots M$ being empty



ETH zürich





Microsoft

URCV

Large-scale 3D Modeling from Crowdsourced Data

Heightmap Computation



Heightmap Results



ETH zürich



Microsoft URCV

Large-scale 3D Modeling from Crowdsourced Data

Results



ETH zürich



Microsoft URCV

Large-scale 3D Modeling from Crowdsourced
Data

References

- Extensive Tutorial on MVS
 - Yasutaka Furukawa and Carlos Hernández (2015), "Multi-View Stereo: A Tutorial", Foundations and Trends® in Computer Graphics and Vision: Vol. 9: No. 1-2, pp 1-148.
<http://dx.doi.org/10.1561/0600000052>
- MVS Benchmarks
 - Middlebury MVS
[Steve Seitz • Brian Curless • James Diebel • Daniel Scharstein • Richard Szeliski](http://vision.middlebury.edu/mview/)
<http://vision.middlebury.edu/mview/>
 - The KITTI Vision Benchmark Suite
Andreas Geiger | Philip Lenz | Christoph Stiller | Raquel Urtasun
<http://www.cvlibs.net/datasets/kitti/>



ETH zürich



Microsoft **URCV**

Large-scale 3D Modeling from Crowdsourced
Data

Bibliography

- D Gallup, M Pollefeys, JM Frahm . 3d reconstruction using an n-layer heightmap. Joint Pattern Recognition Symposium, 2010
- Y Furukawa, J Ponce, Accurate, dense, and robust multiview stereopsis. PAMI 2010.
- SN Sinha, M Pollefeys. Multi-view reconstruction using photo-consistency and exact silhouette constraints: A maximum-flow formulation. ICCV 2005
- Multi-view reconstruction preserving weakly-supported surfaces M Jancosek, T Pajdla Computer Vision and Pattern Recognition (CVPR), 2011
- Johannes L. Schönberger, Enliang Zheng, Marc Pollefeys, Jan-Michael Frahm, “[Pixelwise View Selection for Unstructured Multi-View Stereo](#)”, [ECCV 2016](#)
- Jared Heinly, Johannes L. Schönberger, Enrique Dunn, Jan-Michael Frahm, “Reconstructing the World* in Six Days *(As Captured by the Yahoo 100 Million Image Dataset)”, [CVPR 2015](#)
- Johannes L. Schönberger, Jan-Michael Frahm, “[Structure-from-Motion Revisited](#)”, [CVPR 2016](#)



Thanks

Questions?



ETH zürich



Microsoft **URCV**

Large-scale 3D Modeling from Crowdsourced
Data