

EDS Practical 5

Name:- Avadhoot R. Huddar

Batch:-M.E.21

PRN:- 202501090087

5.1.1. Stacked Plot

00:31

Create a stacked area plot to visualize the temperature variations for three different cities (City A, City B, and City C) across the months of the year. The temperature data is provided for each city in the editor.

Your task is to:

Create a stacked area plot using the data.

Label the x-axis as "Month", the y-axis as "Temperature", and provide the title "Temperature Variation" for the plot.

Display the plot showing the temperature variation for each city throughout the months of the year.

Input:-

```
import matplotlib.pyplot as plt
```

```
import pandas as pd
```

```
# Data for Months and Temperature for three cities
```

```
data = {
```

```
    'Month': ['January', 'February', 'March', 'April', 'May', 'June', 'July', 'August',  
             'September', 'October', 'November', 'December'],
```

```
'City_A_Temperature': [5, 7, 10, 13, 17, 20, 22, 21, 18, 12, 8, 6],  
'City_B_Temperature': [2, 3, 5, 6, 10, 14, 16, 17, 12, 9, 5, 3],  
'City_C_Temperature': [3, 4, 6, 8, 9, 12, 15, 14, 10, 7, 4, 2]  
}
```

```
# Write your code...
```

```
df = pd.DataFrame(data)
```

```
plt.figure()
```

```
plt.stackplot(df['Month'],df['City_A_Temperature'], df['City_B_Temperature'],  
df['City_C_Temperature'],
```

```
labels = ['City A', 'City B', 'City C'],alpha=1)
```

```
plt.xlabel("Month")
```

```
plt.ylabel("Temperature")
```

```
plt.title("Temperature Variation")
```

```
plt.show()
```

[Home](#)
[Learn Anywhere](#)

202501090087@mitaoe.ac.in
Support
Logout

5.1.1. Stacked Plot

Create a stacked area plot to visualize the temperature variations for three different cities (City A, City B, and City C) across the months of the year. The temperature data is provided for each city in the editor.

Your task is to:

- Create a stacked area plot using the data.
- Label the x-axis as "Month", the y-axis as "Temperature", and provide the title "Temperature Variation" for the plot.
- Display the plot showing the temperature variation for each city throughout the months of the year.

Sample Test Cases

Average time
0.399 s
399.00 ms

Maximum time
0.399 s
399.00 ms

1 out of 1 shown test case(s) passed

Test case 1

Expected output

Actual output

[< Prev](#)
[Reset](#)
[Submit](#)
[Next >](#)

5.2.1. Titanic Dataset

00:41

Write a Python program to analyze and visualize data from the Titanic dataset based on the following instructions:

Dataset Information:

The dataset is stored in a CSV file named `titanic.csv` and has been loaded using the pandas library. It contains the following columns:

Pclass: Passenger class (1 = First, 2 = Second, 3 = Third).

Gender: Gender of the passenger (male/female).

Age: Age of the passenger.

Survived: Survival status (0 = Did not survive, 1 = Survived).

Fare: Ticket fare paid by the passenger.

Visualization:

To represent these trends, you will create 5 visualizations using Matplotlib. The visualizations should be arranged in a 3x2 grid (3 rows and 2 columns).

Visualization Details:

Write the code to create a series of visualizations as follows:

Bar Plot (Pclass Distribution):

Create a bar plot to show the distribution of passengers across the different passenger classes (Pclass).

Use the color skyblue for the bars.

Title the plot as "Passenger Class Distribution".

Label the x-axis as "Pclass" and the y-axis as "Count".

Pie Chart (Gender Distribution):

Create a pie chart to display the distribution of male and female passengers.

Use lightblue for males and lightcoral for females.

Include percentages on the slices (use autopct='%1.1f%%').

Title the plot as "Gender Distribution".

Histogram (Age Distribution):

Create a histogram to visualize the distribution of passengers' ages.

Use lightgreen for the bars with black edges (edgecolor = 'black').

Set the number of bins to 8 for the histogram.

Title the plot as "Age Distribution".

Label the x-axis as "Age" and the y-axis as "Frequency".

Bar Plot (Survival Count):

Create a bar plot to show the count of passengers who survived and those who did not, based on the Survived column.

Use the colors lightblue for survivors (1) and lightcoral for non-survivors (0).

Title the plot as **"Survival Count"**.

Label the x-axis as **"Survived (0 = No, 1 = Yes)"** and the y-axis as **"Count"**.

Scatter Plot (Fare vs Age):

Create a scatter plot to visualize the relationship between the Fare and Age of passengers.

Use orange for the data points.

Title the plot as **"Fare vs Age"**.

Label the x-axis as **"Age"** and the y-axis as **"Fare"**.

Note: Refer to the displayed plot in the sample test cases for better understanding.

```
import pandas as pd
```

```
import matplotlib.pyplot as plt
```

```
# Load the Titanic dataset from the CSV file
```

```
df = pd.read_csv('titanic.csv')
```

```
# Set up the figure for 5 subplots
```

```
fig, axes = plt.subplots(3, 2, figsize=(12, 12))
```

```
# write the code..
```

```
# write the code..
```

```
axes[0, 0].bar(df['Pclass'].value_counts().index, df['Pclass'].value_counts(),  
color='skyblue')
```

```
axes[0, 0].set_title("Passenger Class Distribution")
```

```
axes[0, 0].set_xlabel("Pclass")
```

```
axes[0, 0].set_ylabel("Count")
```

```
# Plot 2: Gender distribution
```

```
axes[0, 1].pie(df['Gender'].value_counts(),  
labels=df['Gender'].value_counts().index, autopct='%1.1f%%', colors=  
['lightblue', 'lightcoral'])
```

```
axes[0, 1].set_title("Gender Distribution")
```

```
# Plot 3: Age distribution
```

```
axes[1, 0].hist(df['Age'].dropna(), bins=8, color='lightgreen', edgecolor='black')
```

```
axes[1, 0].set_title("Age Distribution")
```

```
axes[1, 0].set_xlabel("Age")
```

```
axes[1, 0].set_ylabel("Frequency")
```

```
# Plot 4: Survival count
```

```
axes[1, 1].bar(df['Survived'].value_counts().index, df['Survived'].value_counts(),  
color=['lightblue', 'lightcoral'])
```

```
axes[1, 1].set_title("Survival Count")
```

```
axes[1, 1].set_xlabel("Survived (0 = No, 1 = Yes)")
```

```
axes[1, 1].set_ylabel("Count")
```

```
# Plot 5: Fare vs Age
```

```
axes[2, 0].scatter(df['Age'], df['Fare'], color='orange', edgecolors='black')
```

```
axes[2, 0].set_title("Fare vs Age")
```

```
axes[2, 0].set_xlabel("Age")
```

```
axes[2, 0].set_ylabel("Fare")
```

```
plt.tight_layout()
```

```
plt.show()
```

5.2.1. Titanic Dataset

Write a Python program to analyze and visualize data from the Titanic dataset based on the following instructions:

Dataset Information:

The dataset is stored in a CSV file named `titanic.csv` and has been loaded using the `pandas` library. It contains the following columns:

- `Pclass`: Passenger class (1 = First, 2 = Second, 3 = Third).
- `Gender`: Gender of the passenger (male/female).
- `Age`: Age of the passenger.
- `Survived`: Survival status (0 = Did not survive, 1 = Survived).
- `Fare`: Ticket fare paid by the passenger.

Visualization:

To represent these trends, you will create 5 visualizations using Matplotlib. The visualizations should be arranged in a 3x2 grid (3 rows and 2 columns).

Visualization Details:

Write the code to create a series of visualizations as follows:

Bar Plot (Pclass Distribution):

- Create a bar plot to show the distribution of passengers across the different passenger classes (`Pclass`).

Test case 1 (2.211 s) (Debug)

Expected output: [Visualizations showing Pclass distribution, Gender distribution, Age distribution, and Survival status vs. Fare]

Actual output: [Visualizations showing Pclass distribution, Gender distribution, Age distribution, and Survival status vs. Fare]

< Prev Reset Submit Next >

5.2.2. Histogram of passenger information of Titanic

00:34

Write a Python code to plot a histogram for the distribution of the 'Age' column from the Titanic dataset. The histogram should display the frequency of different age ranges with the following specifications:

Use **30 bins** for the histogram.

Set the **edge color** of the bars to **black (k)**.

Label the x-axis as '**Age**' and the y-axis as '**Frequency**'.

Add the title "**Age Distribution**" to the histogram.

The Titanic dataset contains columns as shown below,

PassengerId	Survived	Pclass	Name	Sex

Sample Data:

PassengerId, Survived, Pclass, Name, Sex, Age, SibSp, Parch, Ticket, Fare, Cabin, Embarked

1,0,3,"Braund, Mr. Owen Harris",male,22,1,0,A/5 21171,7.25,,S

2,1,1,"Cumings, Mrs. John Bradley (Florence Briggs Thayer)",female,38,1,0,PC 17599,71.2833,C85,C

3,1,3,"Heikkinen, Miss. Laina",female,26,0,0,STON/O2. 3101282,7.925,,S

4,1,1,"Futrelle, Mrs. Jacques Heath (Lily May Peel)",female,35,1,0,113803,53.1,C123,S

5,0,3,"Allen, Mr. William Henry",male,35,0,0,373450,8.05,,S

6,0,3,"Moran, Mr. James",male,,0,0,330877,8.4583,,Q

7,0,1,"McCarthy, Mr. Timothy J",male,54,0,0,17463,51.8625,E46,S

8,0,3,"Palsson, Master. Gosta Leonard",male,2,3,1,349909,21.075,,S

9,1,3,"Johnson, Mrs. Oscar W (Elisabeth Vilhelmina Berg)",female,27,0,2,347742,11.1333,,S

10,1,2,"Nasser, Mrs. Nicholas (Adele Achem)",female,14,1,0,237736,30.0708,,C

Note: Refer to the visible test case for better reference.

```
import pandas as pd
```

```
import matplotlib.pyplot as plt
```

```
# Load the Titanic dataset
```

```
data = pd.read_csv('Titanic-Dataset.csv')
```

```
# Data Cleaning
```

```
data['Age'].fillna(data['Age'].median(), inplace=True)
```

```
data['Embarked'].fillna(data['Embarked'].mode()[0], inplace=True)
```

```
data.drop('Cabin', axis=1, inplace=True)
```

```
# Convert categorical features to numeric
```

```
data['Sex'] = data['Sex'].map({'male': 0, 'female': 1})
```

```
data = pd.get_dummies(data, columns=['Embarked'], drop_first=True)
```

```
# Write your code here for Histogram
```

```
plt.hist(data['Age'], bins=30, edgecolor='k')
```

```
plt.xlabel('Age')
```

```
plt.ylabel('Frequency')
```

```
plt.title('Age Distribution')
```

```
plt.show()
```

CODETANTRA

Home Learn Anywhere

202501090087@mitaoe.ac.in Support Logout

5.2.2. Histogram of passenger information of Titanic

Write a Python code to plot a histogram for the distribution of the 'Age' column from the Titanic dataset. The histogram should display the frequency of different age ranges with the following specifications:

1. Use 30 bins for the histogram.

2. Set the edge color of the bars to black (k).

3. Label the x-axis as 'Age' and the y-axis as 'Frequency'.

4. Add the title "Age Distribution" to the histogram.

The Titanic dataset contains columns as shown below,

P	S	P	N	S	A	S	P	P	T	F	C	E
a	u	c	a	e	g	i	a	a	i	a	a	m
s	r	l	m		b <td>r</td> <td>c</td> <td>e</td> <td>r</td> <td>b</td> <td>b</td> <td>b</td>	r	c	e	r	b	b	b
e	v	a	e									r
n	i	s										k
i	d											e

Sample Data:

PassengerId, Survived, Pclass, Name, Sex, Age, SibSp, Parch, Ticket, Fare, Cabin, Embarked

1,0,1,"Braund, Mr. Owen Harris",male,22,1,0,A/5 21171,7.25,,S

2,1,1,"Cumings, Mrs. John Bradley (Florence Briggs Thayer)",female,38,1,0,PC 175

3,1,3,"Heikkinen, Miss. Laina",female,26,0,0,STON/O2. 3101282,7.925,,S

Average time

0.444 s

Maximum time

0.444 s

1 out of 1 shown test case(s) passed

Test case 1

0.444 ms

Debug

Expected output

Actual output

Age Distribution

Age Distribution

< Prev

Reset

Submit

Next >

5.2.3. Bar plot of survival rate of passengers

01:06

Write a Python code to plot a bar chart that shows the count of passengers who survived and did not survive in the Titanic dataset. The chart should display the following specifications:

Use the '**Survived**' column to show the count of survivors (0 = Did not survive, 1 = Survived).

Set the chart type to '**bar**'.

Add the title "**Survival Count**" to the chart.

Label the x-axis as '**Survived**' and the y-axis as '**Count**'.

The Titanic dataset contains columns as shown below,

PassengerId	Survived	Pclass	Name	Sex

Sample Data:

PassengerId, Survived, Pclass, Name, Sex, Age, SibSp, Parch, Ticket, Fare, Cabin, Embarked

1,0,3,"Braund, Mr. Owen Harris",male,22,1,0,A/5 21171,7.25,,S

2,1,1,"Cumings, Mrs. John Bradley (Florence Briggs Thayer)",female,38,1,0,PC 17599,71.2833,C85,C

3,1,3,"Heikkinen, Miss. Laina",female,26,0,0,STON/O2. 3101282,7.925,,S

4,1,1,"Futrelle, Mrs. Jacques Heath (Lily May Peel)",female,35,1,0,113803,53.1,C123,S

5,0,3,"Allen, Mr. William Henry",male,35,0,0,373450,8.05,,S

6,0,3,"Moran, Mr. James",male,,0,0,330877,8.4583,,Q

7,0,1,"McCarthy, Mr. Timothy J",male,54,0,0,17463,51.8625,E46,S

8,0,3,"Palsson, Master. Gosta Leonard",male,2,3,1,349909,21.075,,S

9,1,3,"Johnson, Mrs. Oscar W (Elisabeth Vilhelmina Berg)",female,27,0,2,347742,11.1333,S

10,1,2,"Nasser, Mrs. Nicholas (Adele Achem)",female,14,1,0,237736,30.0708,,C

Note: Refer to the visible test case for better reference.

```
import pandas as pd
```

```
import matplotlib.pyplot as plt
```

```
# Load the Titanic dataset
```

```
data = pd.read_csv('Titanic-Dataset.csv')
```

```
# Data Cleaning
```

```
data['Age'].fillna(data['Age'].median(), inplace=True)
```

```
data['Embarked'].fillna(data['Embarked'].mode()[0], inplace=True)
```

```
data.drop('Cabin', axis=1, inplace=True)
```

```
# Convert categorical features to numeric
```

```
data['Sex'] = data['Sex'].map({'male': 0, 'female': 1})
```

```
data = pd.get_dummies(data, columns=['Embarked'], drop_first=True)
```

```
# Write your code here for Bar Plot for Survival Rate
```

```
survival_counts = data['Survived'].value_counts()
```

```
survival_counts.plot(kind='bar')
```

```
plt.title('Survival Count')
```

```
plt.xlabel('Survived')
```

```
plt.ylabel('Count')
```

```
plt.show()
```

The screenshot shows the CODETANTRA IDE interface. On the left, a task description for '5.2.3. Bar plot of survival rate of passengers' is displayed, including instructions to use the 'Survived' column, set the chart type to 'bar', add the title 'Survival Count', and label the axes. Below the instructions is a table of the Titanic dataset columns and a sample data row. On the right, the 'BarPlotOf...' window shows the 'Expected output' and 'Actual output' as bar charts, both showing a count of approximately 170 for 'Survived' (0) and 140 for 'Survived' (1). The 'Test case 1' status is 'Passed'.

5.2.3. Bar plot of survival rate of passengers

Write a Python code to plot a bar chart that shows the count of passengers who survived and did not survive in the Titanic dataset. The chart should display the following specifications:

1. Use the 'Survived' column to show the count of survivors (0 = Did not survive, 1 = Survived).
2. Set the chart type to 'bar'.
3. Add the title 'Survival Count' to the chart.
4. Label the x-axis as 'Survived' and the y-axis as 'Count'.

The Titanic dataset contains columns as shown below.

P	S	P	N	S	A	S	T	F	C	E
ass	ur	class	ame	ex	ge	ib	ar	re	abin	mbarked
ng	vi					S	ch			
er	ve					P	et			
d	d									

Sample Data:

```
PassengerId, Survived, Pclass, Name, Sex, Age, SibSp, Parch, Ticket, Fare, Cabin, Embarked  
1, 0, 3, "Braund, Mr. Owen Harris", male, 22, 1, 0, A/5 21171, 7.25, , S  
2, 1, 1, "Cumings, Mrs. John Bradley (Florence Briggs Thayer)", female, 38, 1, 0, PC 175
```

BarPlotOf...

Average time: 0.457 s, Maximum time: 0.457 s, 1 out of 1 shown test case(s) passed

Test case 1: Passed

Expected output: Survival Count

Actual output: Survival Count

Terminal, Test Cases

< Prev, Reset, Submit, Next >

5.2.4. Bar Plot for Survival by Gender

00:24

Write a Python code to plot a stacked bar chart that shows the count of passengers who survived and did not survive, grouped by gender, in the Titanic dataset. The chart should display the following specifications:

Group the data by the '**Sex**' column, then use the **value_counts()** function to count the occurrences of survivors (0 = Did not survive, 1 = Survived) for each gender.

Use a **stacked bar chart** to display the survival counts.

Add the title "**Survival by Gender**" to the chart.

Label the x-axis as '**Gender**' and the y-axis as '**Count**'.

The legend should indicate '**Not Survived**' and '**Survived**'.

The Titanic dataset contains columns as shown below,

PassengerId	Survived	Pclass	Name	Sex

Sample Data:

PassengerId, Survived, Pclass, Name, Sex, Age, SibSp, Parch, Ticket, Fare, Cabin, Embarked

1,0,3,"Braund, Mr. Owen Harris",male,22,1,0,A/5 21171,7.25,,S

2,1,1,"Cumings, Mrs. John Bradley (Florence Briggs Thayer)",female,38,1,0,PC 17599,71.2833,C85,C

3,1,3,"Heikkinen, Miss. Laina",female,26,0,0,STON/O2. 3101282,7.925,,S

4,1,1,"Futrelle, Mrs. Jacques Heath (Lily May Peel)",female,35,1,0,113803,53.1,C123,S

5,0,3,"Allen, Mr. William Henry",male,35,0,0,373450,8.05,,S

6,0,3,"Moran, Mr. James",male,,0,0,330877,8.4583,,Q

7,0,1,"McCarthy, Mr. Timothy J",male,54,0,0,17463,51.8625,E46,S

8,0,3,"Palsson, Master. Gosta Leonard",male,2,3,1,349909,21.075,,S

9,1,3,"Johnson, Mrs. Oscar W (Elisabeth Vilhelmina Berg)",female,27,0,2,347742,11.1333,,S

10,1,2,"Nasser, Mrs. Nicholas (Adele Achem)",female,14,1,0,237736,30.0708,,C

Note: Refer to the visible test case for better reference.

```
import pandas as pd
```

```
import matplotlib.pyplot as plt
```

```
# Load the Titanic dataset
```

```
data = pd.read_csv('Titanic-Dataset.csv')
```

```
# Data Cleaning
```

```
data['Age'].fillna(data['Age'].median(), inplace=True)
```

```
data['Embarked'].fillna(data['Embarked'].mode()[0], inplace=True)
```

```
data.drop('Cabin', axis=1, inplace=True)
```

```
# Convert categorical features to numeric
```

```
data['Sex'] = data['Sex'].map({'male': 0, 'female': 1})
```

```
data = pd.get_dummies(data, columns=['Embarked'], drop_first=True)
```

```
# Write your code here for Bar Plot for Survival by Gender
```

```
survival_by_gender = data.groupby('Sex')
```

```
['Survived'].value_counts().unstack().fillna(0)
```

```
survival_by_gender.columns = ['Not Survived', 'Survived']
```

```

survival_by_gender.index = ['0', '1']

survival_by_gender.plot(kind='bar', stacked=True)

plt.title('Survival by Gender')

plt.xlabel('Gender')

plt.ylabel('Count')

plt.legend(title=None)

plt.show()

```

5.2.4. Bar Plot for Survival by Gender

Write a Python code to plot a stacked bar chart that shows the count of passengers who survived and did not survive, grouped by gender, in the Titanic dataset. The chart should display the following specifications:

1. Group the data by the "Sex" column, then use the `value_counts()` function to count the occurrences of survivors (0 = Did not survive, 1 = Survived) for each gender.
2. Use a **stacked bar chart** to display the survival counts.
3. Add the title "Survival by Gender" to the chart.
4. Label the x-axis as "Gender" and the y-axis as "Count".
5. The legend should indicate "Not Survived" and "Survived".

The Titanic dataset contains columns as shown below,

P	S	Pc	N	S	A	S	P	Ti	Fa	C	E
as	ur	la	a	ex	ge	ib	ar	ck	re	ab	m
se	vi	ss	me			s	ch	et		in	b
nd	ve										rk
ed	d										ed

Sample Data:

BarraamooTd Gmooload Br1tor Hmoo Kav Ana C1bDa Bmwh T1r0ot Ema Fab1a Baboo0ad

Test case 1: 459 ms, 1 out of 1 shown test case(s) passed

Expected output: Survival by Gender (Stacked bar chart showing Count vs Gender for Not Survived and Survived)

Actual output: Survival by Gender (Stacked bar chart showing Count vs Gender for Not Survived and Survived)

5.2.5. Bar Plot for Survival by Pclass

00:32

Write a Python code to plot a stacked bar chart that shows the count of passengers who survived and did not survive, grouped by passenger class (**Pclass**), in the Titanic dataset. The chart should display the following specifications:

Group the data by the **Pclass** column and count the number of survivors (0 = Did not survive, 1 = Survived) for each class using `value_counts()`.

Use a **stacked bar chart** to display the survival counts.

Add the title **"Survival by Pclass"** to the chart.

Label the x-axis as **'Pclass'** and the y-axis as **'Count'**.

The legend should indicate **'Not Survived'** and **'Survived'**.

|

The Titanic dataset contains columns as shown below,

PassengerId	Survived	Pclass	Name	Sex

|

Sample Data:

PassengerId,Survived,Pclass,Name,Sex,Age,SibSp,Parch,Ticket,Fare,Cabin,Embarked

1,0,3,"Braund, Mr. Owen Harris",male,22,1,0,A/5 21171,7.25,,S

2,1,1,"Cumings, Mrs. John Bradley (Florence Briggs Thayer)",female,38,1,0,PC 17599,71.2833,C85,C

3,1,3,"Heikkinen, Miss. Laina",female,26,0,0,STON/O2. 3101282,7.925,,S

4,1,1,"Futrelle, Mrs. Jacques Heath (Lily May Peel)",female,35,1,0,113803,53.1,C123,S

5,0,3,"Allen, Mr. William Henry",male,35,0,0,373450,8.05,,S

6,0,3,"Moran, Mr. James",male,,0,0,330877,8.4583,,Q

7,0,1,"McCarthy, Mr. Timothy J",male,54,0,0,17463,51.8625,E46,S

8,0,3,"Palsson, Master. Gosta Leonard",male,2,3,1,349909,21.075,,S

9,1,3,"Johnson, Mrs. Oscar W (Elisabeth Vilhelmina Berg)",female,27,0,2,347742,11.1333,,S

10,1,2,"Nasser, Mrs. Nicholas (Adele Achem)",female,14,1,0,237736,30.0708,,C

|

Note:

Refer to the visible test case for better reference.

Ensure you use the **groupby()** function with **value_counts()** to count the survivors and non-survivors for each **Pclass**.

Do **not** manually use **size()** or **unstack()** without **value_counts()**. Use the **value_counts()** method for counting survival status directly.

```
import pandas as pd
```

```
import matplotlib.pyplot as plt
```

```
# Load the Titanic dataset
```

```
data = pd.read_csv('Titanic-Dataset.csv')
```

```
# Data Cleaning
```

```
data['Age'].fillna(data['Age'].median(), inplace=True)
```

```
data['Embarked'].fillna(data['Embarked'].mode()[0], inplace=True)
```

```
data.drop('Cabin', axis=1, inplace=True)
```

```
# Convert categorical features to numeric
```

```
data['Sex'] = data['Sex'].map({'male': 0, 'female': 1})
```

```
data = pd.get_dummies(data, columns=['Embarked'], drop_first=True)
```

```
# Write your code here for Bar Plot for Survival by Pclass
```

```
survival_by_class = data.groupby('Pclass')
```

```
['Survived'].value_counts().unstack().fillna(0)
```

```
survival_by_class.columns = ['Not Survived', 'Survived']
```

```
survival_by_class.plot(kind='bar', stacked=True)
```

```
plt.title('Survival by Pclass')

plt.xlabel('Pclass')

plt.ylabel('Count')

plt.legend(title=None)

plt.show()
```

5.2.5. Bar Plot for Survival by Pclass

Write a Python code to plot a stacked bar chart that shows the count of passengers who survived and did not survive, grouped by passenger class (**Pclass**), in the Titanic dataset. The chart should display the following specifications:

- Group the data by the **Pclass** column and count the number of survivors (0 = Did not survive, 1 = Survived) for each class using **value_counts()**.
- Use a **stacked bar chart** to display the survival counts.
- Add the title **"Survival by Pclass"** to the chart.
- Label the x-axis as **"Pclass"** and the y-axis as **"Count"**.
- The legend should indicate **"Not Survived"** and **"Survived"**.

The Titanic dataset contains columns as shown below.

P	S	Pc	N	S	A	Si	P	Ti	Fa	C	E
as	ur	la	a	ex	ge	b	ar	ck	re	ab	m
se	vi	ss	m			S	ch	et		in	b
ng	ve		e			p					ar
er	d										k
i											e

Sample Data:

```
PassengerId,Survived,Pclass,Name,Sex,Age,SibSp,Parch,Ticket,Fare,Cabin,Embarked
1,0,3,"Braund, Mr. Owen Harris",male,22,1,0,A/5 21171,7.25,.S
```

BarPlotOf...

Average time: 0.496 s
Maximum time: 0.496 s
1 out of 1 shown test case(s) passed

Test case 1

Expected output

Actual output

Terminal

Test cases

< Prev Reset Submit Next >

5.2.6. Bar Plot for Survival by Embarked

00:24

Write a Python code to plot a stacked bar chart showing the survival count for passengers based on their embarkation location in the Titanic dataset.

The chart should display the following specifications:

Use the **Embarked** column to determine the embarkation location. After converting this column into dummy variables (using **pd.get_dummies()**), plot the survival count based on the **Embarked_Q** column (representing passengers who embarked from Queenstown) in relation to survival.

Set the chart type to 'bar' and make it stacked.

Add the title **"Survival by Embarked "** to the chart.

Label the x-axis as 'Embarked' and the y-axis as 'Count'.

Include a legend to distinguish between survivors and non-survivors (label the legend as 'Survived' and 'Not Survived').

The Titanic dataset contains columns as shown below,

PassengerId	Survived	Pclass	Name	Sex

Sample Data:

PassengerId,Survived,Pclass,Name,Sex,Age,SibSp,Parch,Ticket,Fare,Cabin,Embarked

1,0,3,"Braund, Mr. Owen Harris",male,22,1,0,A/5 21171,7.25,,S

2,1,1,"Cumings, Mrs. John Bradley (Florence Briggs Thayer)",female,38,1,0,PC 17599,71.2833,C85,C

3,1,3,"Heikkinen, Miss. Laina",female,26,0,0,STON/O2. 3101282,7.925,,S

4,1,1,"Futrelle, Mrs. Jacques Heath (Lily May Peel)",female,35,1,0,113803,53.1,C123,S

5,0,3,"Allen, Mr. William Henry",male,35,0,0,373450,8.05,,S

6,0,3,"Moran, Mr. James",male,,0,0,330877,8.4583,,Q

7,0,1,"McCarthy, Mr. Timothy J",male,54,0,0,17463,51.8625,E46,S

8,0,3,"Palsson, Master. Gosta Leonard",male,2,3,1,349909,21.075,,S

9,1,3,"Johnson, Mrs. Oscar W (Elisabeth Vilhelmina Berg)",female,27,0,2,347742,11.1333,,S

10,1,2,"Nasser, Mrs. Nicholas (Adele Achem)",female,14,1,0,237736,30.0708,,C

Note: Refer to the visible test case for better reference.

```
import pandas as pd
```

```
import matplotlib.pyplot as plt

# Load the Titanic dataset
data = pd.read_csv('Titanic-Dataset.csv')

# Data Cleaning
data['Age'].fillna(data['Age'].median(), inplace=True)
data['Embarked'].fillna(data['Embarked'].mode()[0], inplace=True)
data.drop('Cabin', axis=1, inplace=True)

# Convert categorical features to numeric
data['Sex'] = data['Sex'].map({'male': 0, 'female': 1})
data = pd.get_dummies(data, columns=['Embarked'], drop_first=True)

# Write your code here for Bar Plot for Survival by Embarked
```

```
import pandas as pd
import matplotlib.pyplot as plt
```

```
# Load the Titanic dataset
data = pd.read_csv('Titanic-Dataset.csv')

# Data Cleaning
```

```
data['Age'].fillna(data['Age'].median(), inplace=True)
data['Embarked'].fillna(data['Embarked'].mode()[0], inplace=True)
data.drop('Cabin', axis=1, inplace=True)

# Convert categorical features to numeric
data['Sex'] = data['Sex'].map({'male': 0, 'female': 1})
data = pd.get_dummies(data, columns=['Embarked'], drop_first=True)

# Write your code here for Bar Plot for Survival by Embarked

# Write your code here for Bar Plot for Survival by Embarked
grouped = pd.crosstab(data['Embarked_Q'], data['Survived'])
grouped.plot(kind='bar', stacked=True)

plt.xlabel('Embarked')
plt.ylabel('Count')
plt.title('Survival by Embarked')
plt.legend(['Not Survived', 'Survived'])

plt.show()
```

CODETANTRA

HomeLearn Anywhere

202501090087@mitaoe.ac.inSupportLogout

5.2.6. Bar Plot for Survival by Embarked

00:29

🔍🔗🔧🔖

Write a Python code to plot a stacked bar chart showing the survival count for passengers based on their embarkation location in the Titanic dataset. The chart should display the following specifications:

1. Use the **Embarked** column to determine the embarkation location. After converting this column into dummy variables (using `pd.get_dummies()`), plot the survival count based on the **Embarked_Q** column (representing passengers who embarked from Queenstown) in relation to survival.
2. Set the chart type to 'bar' and make it stacked.
3. Add the title "Survival by Embarked" to the chart.
4. Label the x-axis as "Embarked" and the y-axis as "Count".
5. Include a legend to distinguish between survivors and non-survivors (label the legend as "Survived" and "Not Survived").

The Titanic dataset contains columns as shown below,

P	S	Pc	N	S	A	Si	P	Ti	Fa	C	E
as	ur	la	a	ex	ge	b	ar	ck	re	ab	m
se	vi	ss	me			S	ch	et		in	ba
ri	ve					p					rk
ed	d										ed

Average time0.574 s574.00 ms

Maximum time0.574 s574.00 ms

1 out of 1 shown test case(s) passed

Test case 10.374 ms🔍🔗🔧🔖

Expected output

Actual output

Survival by Embarked

Survival by Embarked

< Prev

Reset

Submit

Next >

5.2.7. Box plot for Age Distribution

00:32

Write a Python code to plot a boxplot that shows the distribution of the 'Age' column from the Titanic dataset across different passenger classes. The boxplot should display the following specifications:

Use the **Pclass** column to group the data for the boxplot.

Set the title of the plot to "Age by Pclass".

Remove the default subtitle with `plt.suptitle("")`.

Label the x-axis as 'Pclass' and the y-axis as 'Age'.

The Titanic dataset contains columns as shown below,

PassengerId	Survived	Pclass	Name	Sex

Sample Data:

PassengerId, Survived, Pclass, Name, Sex, Age, SibSp, Parch, Ticket, Fare, Cabin, Embarked

1,0,3,"Braund, Mr. Owen Harris",male,22,1,0,A/5 21171,7.25,,S

2,1,1,"Cumings, Mrs. John Bradley (Florence Briggs Thayer)",female,38,1,0,PC 17599,71.2833,C85,C

3,1,3,"Heikkinen, Miss. Laina",female,26,0,0,STON/O2. 3101282,7.925,,S

4,1,1,"Futrelle, Mrs. Jacques Heath (Lily May Peel)",female,35,1,0,113803,53.1,C123,S

5,0,3,"Allen, Mr. William Henry",male,35,0,0,373450,8.05,,S

6,0,3,"Moran, Mr. James",male,,0,0,330877,8.4583,,Q

7,0,1,"McCarthy, Mr. Timothy J",male,54,0,0,17463,51.8625,E46,S

8,0,3,"Palsson, Master. Gosta Leonard",male,2,3,1,349909,21.075,,S

9,1,3,"Johnson, Mrs. Oscar W (Elisabeth Vilhelmina Berg)",female,27,0,2,347742,11.1333,,S

10,1,2,"Nasser, Mrs. Nicholas (Adele Achem)",female,14,1,0,237736,30.0708,,C

Note: Refer to the visible test case for better reference.

```
import pandas as pd
```

```
import matplotlib.pyplot as plt
```

```
# Load the Titanic dataset
```

```
data = pd.read_csv('Titanic-Dataset.csv')
```

```
# Data Cleaning
```

```
data['Age'].fillna(data['Age'].median(), inplace=True)
```

```
data['Embarked'].fillna(data['Embarked'].mode()[0], inplace=True)
```

```
data.drop('Cabin', axis=1, inplace=True)
```

```
# Convert categorical features to numeric
data['Sex'] = data['Sex'].map({'male': 0, 'female': 1})
data = pd.get_dummies(data, columns=['Embarked'], drop_first=True)
```

```
# Write your code here for Box Plot for Age by Pclass
```

```
import pandas as pd
import matplotlib.pyplot as plt
```

```
# Load the Titanic dataset
data = pd.read_csv('Titanic-Dataset.csv')
```

```
# Data Cleaning
data['Age'].fillna(data['Age'].median(), inplace=True)
data['Embarked'].fillna(data['Embarked'].mode()[0], inplace=True)
data.drop('Cabin', axis=1, inplace=True)
```

```
# Convert categorical features to numeric
data['Sex'] = data['Sex'].map({'male': 0, 'female': 1})
data = pd.get_dummies(data, columns=['Embarked'], drop_first=True)
```

```
# Box Plot for Age by Pclass
```

```
plt.figure(figsize=(8, 6))
```

```
data.boxplot(column='Age', by='Pclass')
```

```
# Plot customizations
```

```
plt.title('Age by Pclass')
```

```
plt.suptitle("") # Remove the default subtitle
```

```
plt.xlabel('Pclass')
```

```
plt.ylabel('Age')
```

```
# Show the plot
```

```
plt.show()
```

CODETANTRA

Home Learn Anywhere

202501090087@mitaoe.ac.in Support Logout

5.2.7. Box plot for Age Distribution

Write a Python code to plot a boxplot that shows the distribution of the 'Age' column from the Titanic dataset across different passenger classes. The boxplot should display the following specifications:
1. Use the **Pclass** column to group the data for the boxplot.
2. Set the title of the plot to **"Age by Pclass"**.
3. Remove the default subtitle with **plt.suptitle("")**.
4. Label the x-axis as **'Pclass'** and the y-axis as **'Age'**.

The Titanic dataset contains columns as shown below.

P	S	Pc	N	S	A	Si	P	Ti	Fa	C	E
as	ur	la	a	ex	ge	b	ar	ck	re	ab	m
se	vi	ss	m			S	ch	et		in	ba
ri	ve		e			p					rk
ed	d										ed

Sample Data:
PassengerId, Survived, Pclass, Name, Sex, Age, SibSp, Parch, Ticket, Fare, Cabin, Embarked
1,0,1,"Braund, Mr. Owen Harris",male,22,1,0,A/5 21171,7.25,S
2,1,1,"Cumings, Mrs. John Bradley (Florence Briggs Thayer)",female,38,1,0,PC 175
3,1,3,"Heikkinen, Miss. Laina",female,26,0,0,STON/O2. 3101282,7.925,S

Average time
0.481 s
481.00 ms

Maximum time
0.481 s
481.00 ms

1 out of 1 shown test case(s) passed

Test case 1

Expected output

Actual output

Age by Pclass

Age by Pclass

< Prev

Reset

Submit

Next >

5.2.8. Box Plot for Age by Survived

00:26

Write a Python code to plot a boxplot that shows the distribution of the 'Age' column from the Titanic dataset based on whether passengers survived or not. The boxplot should display the following specifications:

Use the **Survived** column to group the data for the boxplot (0 = Did not survive, 1 = Survived).

Set the title of the plot to **"Age by Survival"**.

Remove the default subtitle with **plt.suptitle("")**.

Label the x-axis as **'Survived'** and the y-axis as **'Age'**.

The Titanic dataset contains columns as shown below,

PassengerId	Survived	Pclass	Name	Sex

Sample Data:

PassengerId, Survived, Pclass, Name, Sex, Age, SibSp, Parch, Ticket, Fare, Cabin, Embarked

1,0,3,"Braund, Mr. Owen Harris",male,22,1,0,A/5 21171,7.25,,S

2,1,1,"Cumings, Mrs. John Bradley (Florence Briggs Thayer)",female,38,1,0,PC 17599,71.2833,C85,C

3,1,3,"Heikkinen, Miss. Laina",female,26,0,0,STON/O2. 3101282,7.925,,S

4,1,1,"Futrelle, Mrs. Jacques Heath (Lily May Peel)",female,35,1,0,113803,53.1,C123,S

5,0,3,"Allen, Mr. William Henry",male,35,0,0,373450,8.05,,S

6,0,3,"Moran, Mr. James",male,,0,0,330877,8.4583,,Q

7,0,1,"McCarthy, Mr. Timothy J",male,54,0,0,17463,51.8625,E46,S

8,0,3,"Palsson, Master. Gosta Leonard",male,2,3,1,349909,21.075,,S

9,1,3,"Johnson, Mrs. Oscar W (Elisabeth Vilhelmina Berg)",female,27,0,2,347742,11.1333,,S

```
10,1,2,"Nasser, Mrs. Nicholas (Adele Achem)",female,14,1,0,237736,30.0708,,C
```

Note: Refer to the visible test case for better reference.

```
import pandas as pd
```

```
import matplotlib.pyplot as plt
```

```
# Load the Titanic dataset
```

```
data = pd.read_csv('Titanic-Dataset.csv')
```

```
# Data Cleaning
```

```
data['Age'].fillna(data['Age'].median(), inplace=True)
```

```
data['Embarked'].fillna(data['Embarked'].mode()[0], inplace=True)
```

```
data.drop('Cabin', axis=1, inplace=True)
```

```
# Convert categorical features to numeric
```

```
data['Sex'] = data['Sex'].map({'male': 0, 'female': 1})
```

```
data = pd.get_dummies(data, columns=['Embarked'], drop_first=True)
```

```
# Write your code here for Box Plot for Age by Survived
```

```
import pandas as pd
```

```
import matplotlib.pyplot as plt
```

```
# Load the Titanic dataset
data = pd.read_csv('Titanic-Dataset.csv')

# Data Cleaning
data['Age'].fillna(data['Age'].median(), inplace=True)
data['Embarked'].fillna(data['Embarked'].mode()[0], inplace=True)
data.drop('Cabin', axis=1, inplace=True)

# Convert categorical features to numeric
data['Sex'] = data['Sex'].map({'male': 0, 'female': 1})
data = pd.get_dummies(data, columns=['Embarked'], drop_first=True)

# Box Plot for Age by Survived
plt.figure(figsize=(8, 6))
data.boxplot(column='Age', by='Survived')

# Plot customizations
plt.title('Age by Survival')
plt.suptitle("") # Remove default subtitle
plt.xlabel('Survived')
plt.ylabel('Age')

# Show the plot
plt.show()
```

CODETANTRA

HomeLearn Anywhere

202501090087@mitaoe.ac.inSupportLogout

5.2.8. Box Plot for Age by Survived

Write a Python code to plot a boxplot that shows the distribution of the 'Age' column from the Titanic dataset based on whether passengers survived or not. The boxplot should display the following specifications:

1. Use the **Survived** column to group the data for the boxplot (0 = Did not survive, 1 = Survived).

2. Set the title of the plot to **"Age by Survival"**.

3. Remove the default subtitle with **plt.suptitle("")**.

4. Label the x-axis as **'Survived'** and the y-axis as **'Age'**.

The Titanic dataset contains columns as shown below,

P	S	Pc	N	S	A	Si	P	Ti	Fa	C	E
as	ur	la	a	ex	ge	b	ar	ck	re	ab	m
se	vi	ss	m			S	ch	et		in	ba
ng	ve					p					rk
ed	d					h					ed

Sample Data:

```
PassengerId, Survived, Pclass, Name, Sex, Age, SibSp, Parch, Ticket, Fare, Cabin, Embarked
1,0,3,"Braund, Mr. Owen Harris",male,22,1,0,A/5 21171,7.25,,S
2,1,1,"Cumings, Mrs. John Bradley (Florence Briggs Thayer)",female,38,1,0,PC 175
```

Average time0.454 s454.00 msMaximum time0.454 s454.00 ms1 out of 1 shown test case(s) passed

Test case 1454 msDebug

Expected output

Actual output

Age by Survival

Age by Survival

Survived

Survived

< PrevResetSubmitNext >

5.2.9. Box Plot for Fare by Pclass

00:26

Write a Python code to plot a boxplot that shows the distribution of the 'Fare' column from the Titanic dataset based on the passenger class (Pclass). The boxplot should display the following specifications:

Use the **Pclass** column to group the data for the boxplot.

Set the title of the plot to **"Fare by Pclass"**.

Remove the default subtitle with **plt.suptitle("")**.

Label the x-axis as **'Pclass'** and the y-axis as **'Fare'**.

The Titanic dataset contains columns as shown below,

PassengerId	Survived	Pclass	Name	Sex

Sample Data:

PassengerId, Survived, Pclass, Name, Sex, Age, SibSp, Parch, Ticket, Fare, Cabin, Embarked

1,0,3,"Braund, Mr. Owen Harris",male,22,1,0,A/5 21171,7.25,,S

2,1,1,"Cumings, Mrs. John Bradley (Florence Briggs Thayer)",female,38,1,0,PC 17599,71.2833,C85,C

3,1,3,"Heikkinen, Miss. Laina",female,26,0,0,STON/O2. 3101282,7.925,,S

4,1,1,"Futrelle, Mrs. Jacques Heath (Lily May Peel)",female,35,1,0,113803,53.1,C123,S

5,0,3,"Allen, Mr. William Henry",male,35,0,0,373450,8.05,,S

6,0,3,"Moran, Mr. James",male,,0,0,330877,8.4583,,Q

7,0,1,"McCarthy, Mr. Timothy J",male,54,0,0,17463,51.8625,E46,S

8,0,3,"Palsson, Master. Gosta Leonard",male,2,3,1,349909,21.075,,S

9,1,3,"Johnson, Mrs. Oscar W (Elisabeth Vilhelmina Berg)",female,27,0,2,347742,11.1333,,S

10,1,2,"Nasser, Mrs. Nicholas (Adele Achem)",female,14,1,0,237736,30.0708,,C

Note: Refer to the visible test case for better reference.

```
import pandas as pd
```

```
import matplotlib.pyplot as plt
```

```
# Load the Titanic dataset
```

```
data = pd.read_csv('Titanic-Dataset.csv')
```

```
# Data Cleaning
```

```
data['Age'].fillna(data['Age'].median(), inplace=True)
```

```
data['Embarked'].fillna(data['Embarked'].mode()[0], inplace=True)
```

```
data.drop('Cabin', axis=1, inplace=True)
```

```
# Convert categorical features to numeric
data['Sex'] = data['Sex'].map({'male': 0, 'female': 1})
data = pd.get_dummies(data, columns=['Embarked'], drop_first=True)
```

```
# Write your code here for Box Plot for Fare by Pclass
```

```
import pandas as pd
import matplotlib.pyplot as plt
```

```
# Load the Titanic dataset
data = pd.read_csv('Titanic-Dataset.csv')
```

```
# Data Cleaning
data['Age'].fillna(data['Age'].median(), inplace=True)
data['Embarked'].fillna(data['Embarked'].mode()[0], inplace=True)
data.drop('Cabin', axis=1, inplace=True)
```

```
# Convert categorical features to numeric
data['Sex'] = data['Sex'].map({'male': 0, 'female': 1})
data = pd.get_dummies(data, columns=['Embarked'], drop_first=True)
```

```
# Box Plot: Fare by Pclass
```

ODETANTA Home Learn Anywhere
Logout

5.29. Box Plot for Fare by Pclass

Write a Python code to plot a boxplot that shows the distribution of the 'Fare' column from the Titanic dataset based on the passenger class (Pclass). The boxplot should display the following specifications:

- Use the `Pclass` column to group the data for the boxplot.
- Set the title of the plot to **"Fare by Pclass"**.
- Remove the default subtitle with `plt.suptitle("")`.
- Label the x-axis as **"Pclass"** and the y-axis as **'Fare'**.

The Titanic dataset contains columns as shown below.

P	S	Pc	N	A		S	Si	P	Ti	Fa	C	E
ass	ur	lass	ame	ge		b	rch	cket	re	abin		mber
ng	vi		e			s						id
er	ve											
id	d											

Expected output

Actual output

Sample Data:

```
PassengerId,Survived,Pclass,Name,Sex,Age,SibSp,Parch,Ticket,Fare,Cabin,Embarked
1,0,3,"Braund, Mr. Owen Harris",male,22,1,0,A/5 21171,7.25,,S
2,1,1,"Cunings, Mrs. John Bradley (Florence Briggs Thayer)",female,38,1,0,PC 175
3,1,3,"Heikinen, Miss. Laina",female,26,0,0,STON/O2. 3101282,7.92,,S
```

00:27

Set the title of the plot to **"Age vs. Fare"**.

Label the x-axis as 'Age' and the y-axis as 'Fare'.

The Titanic dataset contains columns as shown below,

PassengerId	Survived	Pclass	Name	Sex

Sample Data:

PassengerId,Survived,Pclass,Name,Sex,Age,SibSp,Parch,Ticket,Fare,Cabin,Embarked

1,0,3,"Braund, Mr. Owen Harris",male,22,1,0,A/5 21171,7.25,,S

2,1,1,"Cumings, Mrs. John Bradley (Florence Briggs Thayer)",female,38,1,0,PC 17599,71.2833,C85,C

3,1,3,"Heikkinen, Miss. Laina",female,26,0,0,STON/O2. 3101282,7.925,,S

4,1,1,"Futrelle, Mrs. Jacques Heath (Lily May Peel)",female,35,1,0,113803,53.1,C123,S

5,0,3,"Allen, Mr. William Henry",male,35,0,0,373450,8.05,,S

6,0,3,"Moran, Mr. James",male,,0,0,330877,8.4583,,Q

7,0,1,"McCarthy, Mr. Timothy J",male,54,0,0,17463,51.8625,E46,S

8,0,3,"Palsson, Master. Gosta Leonard",male,2,3,1,349909,21.075,,S

9,1,3,"Johnson, Mrs. Oscar W (Elisabeth Vilhelmina Berg)",female,27,0,2,347742,11.1333,,S

10,1,2,"Nasser, Mrs. Nicholas (Adele Achem)",female,14,1,0,237736,30.0708,,C

Note: Refer to the visible test case for better reference.

```
import pandas as pd
```

```
import matplotlib.pyplot as plt
```

```
# Load the Titanic dataset
data = pd.read_csv('Titanic-Dataset.csv')

# Data Cleaning
data['Age'].fillna(data['Age'].median(), inplace=True)
data['Embarked'].fillna(data['Embarked'].mode()[0], inplace=True)
data.drop('Cabin', axis=1, inplace=True)

# Convert categorical features to numeric
data['Sex'] = data['Sex'].map({'male': 0, 'female': 1})
data = pd.get_dummies(data, columns=['Embarked'], drop_first=True)

# Write your code here for Box Plot for Fare by Pclass
```

```
import pandas as pd
import matplotlib.pyplot as plt
```

```
# Load the Titanic dataset
data = pd.read_csv('Titanic-Dataset.csv')

# Data Cleaning
data['Age'].fillna(data['Age'].median(), inplace=True)
```

```
data['Embarked'].fillna(data['Embarked'].mode()[0], inplace=True)
```

```
data.drop('Cabin', axis=1, inplace=True)
```

```
# Convert categorical features to numeric
```

```
data['Sex'] = data['Sex'].map({'male': 0, 'female': 1})
```

```
data = pd.get_dummies(data, columns=['Embarked'], drop_first=True)
```

```
# Write your code here for Box Plot for Fare by Pclass
```

```
plt.scatter(data['Age'],data['Fare'])
```

```
plt.title("Age vs. Fare")
```

```
plt.xlabel("Age")
```

```
plt.ylabel("Fare")
```

```
plt.show()
```

5.2.10. Scatter Plot for Age vs. Fare

Write a Python code to plot a scatter plot showing the relationship between the 'Age' and 'Fare' columns in the Titanic dataset. The scatter plot should display the following specifications:

1. Use the **Age** column for the x-axis and the **Fare** column for the y-axis.
2. Set the title of the plot to **"Age vs. Fare"**.
3. Label the x-axis as **'Age'** and the y-axis as **'Fare'**.

The Titanic dataset contains columns as shown below.

P	S	Pc	N	S	A	S	P	P	Ti	Fa	C	E
as	ur	la	a	ex	ge	ib	ar	ch	cket	re	abin	mbarked
se	vi	ss	me			Sp						
ng	ve											
er	d											
d												

Sample Data:

```
PassengerId, Survived, Pclass, Name, Sex, Age, SibSp, Parch, Ticket, Fare, Cabin, Embarked
1, 0, 3, "Braund, Mr. Owen Harris", male, 22, 1, 0, A/5 21171, 7.25, S
2, 1, 1, "Comings, Mrs. John Bradley (Florence Briggs Thayer)", female, 38, 1, 0, PC 175
3, 1, 1, "Heikkinen, Miss. Laina", female, 26, 0, 0, STON/O2. 3101282, 7.925, S
4, 1, 1, "Futrelle, Mrs. Jacques Heath (Lily May Peel)", female, 35, 1, 0, 113803, 53.1, C
```

Test case 1

Expected output

Actual output

1 out of 1 shown test case(s) passed

0.435 s 0.435 s 435.00 ms 435.00 ms

Prev Reset Submit Next

5.2.11. Scatter Plot for Age vs. Fare by Survived

00:23

Write a Python code to plot a scatter plot showing the relationship between the 'Age' and 'Fare' columns in the Titanic dataset, with points color-coded by survival status. The scatter plot should display the following specifications:

Use the **Age** column for the x-axis and the **Fare** column for the y-axis.

Color the points based on the **Survived** column: **Red** for passengers who did not survive (**Survived = 0**). **Blue** for passengers who survived (**Survived = 1**).

Set the title of the plot to **"Age vs. Fare by Survival"**.

Label the x-axis as **'Age'** and the y-axis as **'Fare'**.

The Titanic dataset contains columns as shown below,

PassengerId	Survived	Pclass	Name	Sex

Sample Data:

PassengerId,Survived,Pclass,Name,Sex,Age,SibSp,Parch,Ticket,Fare,Cabin,Embarked

1,0,3,"Braund, Mr. Owen Harris",male,22,1,0,A/5 21171,7.25,,S

2,1,1,"Cumings, Mrs. John Bradley (Florence Briggs Thayer)",female,38,1,0,PC 17599,71.2833,C85,C

3,1,3,"Heikkinen, Miss. Laina",female,26,0,0,STON/O2. 3101282,7.925,,S

4,1,1,"Futrelle, Mrs. Jacques Heath (Lily May Peel)",female,35,1,0,113803,53.1,C123,S

5,0,3,"Allen, Mr. William Henry",male,35,0,0,373450,8.05,,S

6,0,3,"Moran, Mr. James",male,,0,0,330877,8.4583,,Q

7,0,1,"McCarthy, Mr. Timothy J",male,54,0,0,17463,51.8625,E46,S

8,0,3,"Palsson, Master. Gosta Leonard",male,2,3,1,349909,21.075,,S

```
9,1,3,"Johnson, Mrs. Oscar W (Elisabeth Vilhelmina Berg)",female,27,0,2,347742,11.1333,,S
```

```
10,1,2,"Nasser, Mrs. Nicholas (Adele Achem)",female,14,1,0,237736,30.0708,,C
```

Note: Refer to the visible test case for better reference.

```
import pandas as pd
```

```
import matplotlib.pyplot as plt
```

```
# Load the Titanic dataset
```

```
data = pd.read_csv('Titanic-Dataset.csv')
```

```
# Data Cleaning
```

```
data['Age'].fillna(data['Age'].median(), inplace=True)
```

```
data['Embarked'].fillna(data['Embarked'].mode()[0], inplace=True)
```

```
data.drop('Cabin', axis=1, inplace=True)
```

```
# Convert categorical features to numeric
```

```
data['Sex'] = data['Sex'].map({'male': 0, 'female': 1})
```

```
data = pd.get_dummies(data, columns=['Embarked'], drop_first=True)
```

```
# Write your code here for Scatter Plot for Age vs. Fare by Survived
```

```
colors = {0:'red', 1:'blue'}
```

```
plt.scatter(data['Age'], data['Fare'], c=data['Survived'].map(colors))
```

```
plt.title('Age vs. Fare by Survival')
```

```
plt.xlabel('Age')
```

```
plt.ylabel('Fare')
```

```
plt.show()
```

CODETANTRA

HomeLearn Anywhere

202501090087@mitace.ac.inSupportLogout

3.2.11. Scatter Plot for Age vs. Fare by Survived

Write a Python code to plot a scatter plot showing the relationship between the 'Age' and 'Fare' columns in the Titanic dataset, with points color-coded by survival status. The scatter plot should display the following specifications:
1. Use the **Age** column for the x-axis and the **Fare** column for the y-axis.
2. Color the points based on the **Survived** column: **Red** for passengers who did not survive (**Survived = 0**). **Blue** for passengers who survived (**Survived = 1**).
3. Set the title of the plot to **"Age vs. Fare by Survival"**.
4. Label the x-axis as **'Age'** and the y-axis as **'Fare'**.

The Titanic dataset contains columns as shown below.

P ass en ge r Id	S ur vi ve d	Pc la ss	N a me	S ex	A ge	S ib Sp	P ar ch	Ti ck et	Fa re	C ab in	E m ba rk ed

Sample Data:
PassengerId, Survived, Pclass, Name, Sex, Age, SibSp, Parch, Ticket, Fare, Cabin, Embarked
1,0,3,"Braund, Mr. Owen Harris",male,22,1,0,A/5 21171,7.25,.S

Average time
0.467 s
467.00 ms

Maximum time
0.467 s
467.00 ms

1 out of 1 shown test case(s) passed

Test case 1

Expected output

Actual output

Age vs. Fare by Survival

Age vs. Fare by Survival

Prev

Reset

Submit