



The picture can't be displayed.

Chapter 15 : Concurrency Control

Database System Concepts, 6th Ed.

©Silberschatz, Korth and Sudarshan

See www.db-book.com for conditions on re-use



Chapter 15: Concurrency Control

- Lock-Based Protocols
- Timestamp-Based Protocols
- Validation-Based Protocols
- Multiple Granularity
- Multiversion Schemes
- Insert and Delete Operations
- Concurrency in Index Structures



Lock-Based Protocols

- A lock is a mechanism to control concurrent access to a data item
- Data items can be locked in two modes:
 1. **exclusive** (X) *mode*. Data item can be both read as well as written. X-lock is requested using **lock-X** instruction.
 2. **shared** (S) *mode*. Data item can only be read. S-lock is requested using **lock-S** instruction.
- Lock requests are made to concurrency-control manager. Transaction can proceed only after request is granted.



Lock-Based Protocols (Cont.)

■ Lock-compatibility matrix

	S	X
S	true	false
X	false	false

- A transaction may be granted a lock on an item if the requested lock is compatible with locks already held on the item by other transactions.
- Any number of transactions can hold shared locks on an item,
 - but if any transaction holds an exclusive on the item no other transaction may hold any lock on the item.
- If a lock cannot be granted, the requesting transaction is made to wait till all incompatible locks held by other transactions have been released. The lock is then granted.



```
 $T_1$ : lock-X( $B$ );  
      read( $B$ );  
       $B := B - 50$ ;  
      write( $B$ );  
      unlock( $B$ );  
      lock-X( $A$ );  
      read( $A$ );  
       $A := A + 50$ ;  
      write( $A$ );  
      unlock( $A$ ).
```

Figure 15.2 Transaction T_1 .



```
T2: lock-S(A);  
    read(A);  
    unlock(A);  
    lock-S(B);  
    read(B);  
    unlock(B);  
    display(A + B).
```

Figure 15.3 Transaction T_2 .



```
T3: lock-x(B);  
    read(B);  
    B := B - 50;  
    write(B);  
    lock-x(A);  
    read(A);  
    A := A + 50;  
    write(A);  
    unlock(B);  
    unlock(A).
```

Figure 15.5 Transaction T_3 (transaction T_1 with unlocking delayed).



T_1	T_2	concurrency-control manager
lock-X(B)		grant-X(B, T_1)
read(B)		
$B := B - 50$		
write(B)		
unlock(B)		
	lock-S(A)	
		grant-S(A, T_2)
	read(A)	
	unlock(A)	
	lock-S(B)	
		grant-S(B, T_2)
	read(B)	
	unlock(B)	
	display($A + B$)	
lock-X(A)		grant-X(A, T_1)
read(A)		
$A := A - 50$		
write(A)		
unlock(A)		

Figure 15.4 Schedule 1.



```
T4: lock-S(A);  
    read(A);  
    lock-S(B);  
    read(B);  
    display(A + B);  
    unlock(A);  
    unlock(B).
```

Figure 15.6 Transaction T_4 (transaction T_2 with unlocking delayed).



Lock-Based Protocols (Cont.)

- Example of a transaction performing locking:

```
 $T_2$ : lock-S( $A$ );  
      read ( $A$ );  
      unlock( $A$ );  
      lock-S( $B$ );  
      read ( $B$ );  
      unlock( $B$ );  
      display( $A+B$ )
```

- Locking as above is not sufficient to guarantee serializability — if A and B get updated in-between the read of A and B , the displayed sum would be wrong.
- A **locking protocol** is a set of rules followed by all transactions while requesting and releasing locks. Locking protocols restrict the set of possible schedules.



Pitfalls of Lock-Based Protocols

- Consider the partial schedule

T_3	T_4
lock-x (B)	
read (B)	
$B := B - 50$	
write (B)	
	lock-s (A)
	read (A)
	lock-s (B)
lock-x (A)	

- Neither T_3 nor T_4 can make progress — executing **lock-S(B)** causes T_4 to wait for T_3 to release its lock on B , while executing **lock-X(A)** causes T_3 to wait for T_4 to release its lock on A .
- Such a situation is called a **deadlock**.
 - To handle a deadlock one of T_3 or T_4 must be rolled back and its locks released.



Pitfalls of Lock-Based Protocols (Cont.)

- The potential for deadlock exists in most locking protocols. Deadlocks are a necessary evil.
- **Starvation** is also possible if concurrency control manager is badly designed. For example:
 - A transaction may be waiting for an X-lock on an item, while a sequence of other transactions request and are granted an S-lock on the same item.
 - The same transaction is repeatedly rolled back due to deadlocks.
- Concurrency control manager can be designed to prevent starvation.



The Two-Phase Locking Protocol

- This is a protocol which ensures conflict-serializable schedules.
- Phase 1: Growing Phase
 - transaction may obtain locks
 - transaction may not release locks
- Phase 2: Shrinking Phase
 - transaction may release locks
 - transaction may not obtain locks
- The protocol assures serializability.
- It can be proved that the transactions can be serialized in the order of their **lock points** (i.e., the point where a transaction acquired its final lock).



T1

Lock S(A)

Lock X(B)

Unlock(A)

Unlock(B)

T2

Lock S(A)

Lock S(D)

Unlock(A)

Unlock (D)



The Two-Phase Locking Protocol (Cont.)

- Two-phase locking *does not* ensure freedom
 - Irrecoverability
 - Deadlocks
 - cascading roll backs
- To avoid this, follow a modified protocol called **strict two-phase locking**. Here a transaction must hold all its exclusive locks till it commits/aborts.
- **Rigorous two-phase locking** is even stricter: here *all* locks are held till commit/abort. In this protocol transactions can be serialized in the order in which they commit.



The Two-Phase Locking Protocol (Cont.)

- There can be conflict serializable schedules that cannot be obtained if two-phase locking is used.
- However, in the absence of extra information (e.g., ordering of access to data), two-phase locking is needed for conflict serializability in the following sense:

Given a transaction T_i that does not follow two-phase locking, we can find a transaction T_j that uses two-phase locking, and a schedule for T_i and T_j that is not conflict serializable.



Lock Conversions

- Two-phase locking with lock conversions:
 - First Phase:
 - can acquire a lock-S on item
 - can acquire a lock-X on item
 - can convert a lock-S to a lock-X (upgrade)
 - Second Phase:
 - can release a lock-S
 - can release a lock-X
 - can convert a lock-X to a lock-S (downgrade)
- This protocol assures serializability. But still relies on the programmer to insert the various locking instructions.



Automatic Acquisition of Locks

- A transaction T_i issues the standard read/write instruction, without explicit locking calls.
- The operation **read**(D) is processed as:
 - if** T_i has a lock on D
 - then**
 - read(D)
 - else begin**
 - if necessary wait until no other transaction has a **lock-X** on D
 - grant T_i a **lock-S** on D ;
 - read(D)
 - end**



Automatic Acquisition of Locks (Cont.)

- **write**(D) is processed as:
 - if T_i has a **lock-X** on D
 - then**
 - write(D)
 - else begin**
 - if necessary wait until no other trans. has any lock on D ,
 - if T_i has a **lock-S** on D
 - then**
 - upgrade** lock on D to **lock-X**
 - else**
 - grant T_i a **lock-X** on D
 - write(D)
 - end;**
 - All locks are released after commit or abort




Implementation of Locking

- A **lock manager** can be implemented as a separate process to which transactions send lock and unlock requests.
- **The lock manager replies to a lock request** by sending a lock grant messages (or a message asking the transaction to roll back, in case of a deadlock).
- The requesting transaction waits until its request is answered.
- The lock manager maintains a data-structure called a **lock table** to record granted locks and pending requests.
- The lock table is usually implemented as an in-memory hash table indexed on the name of the data item being locked.



Lock Table



- Black rectangles indicate granted locks, white ones indicate waiting requests
- Lock table also records the type of lock granted or requested
- New request is added to the end of the queue of requests for the data item, and granted if it is compatible with all earlier locks
- Unlock requests result in the request being deleted, and later requests are checked to see if they can now be granted
- If transaction aborts, all waiting or granted requests of the transaction are deleted
 - lock manager may keep a list of locks held by each transaction, to implement this efficiently




Graph-Based Protocols

- Graph-based protocols are an alternative to two-phase locking.
- Impose a partial ordering \rightarrow on the set $\mathbf{D} = \{d_1, d_2, \dots, d_h\}$ of all data items.
 - If $d_i \rightarrow d_j$ then any transaction accessing both d_i and d_j must access d_i before accessing d_j .
 - Implies that the set \mathbf{D} may now be viewed as a directed acyclic graph, called a *database graph*.
- The *tree-protocol* is a simple kind of graph protocol.



Tree Protocol



1. Only exclusive locks are allowed.
2. The first lock by T_i may be on any data item. Subsequently, a data Q can be locked by T_i only if the parent of Q is currently locked by T_i .
3. Data items may be unlocked at any time.
4. A data item that has been locked and unlocked by T_i cannot subsequently be relocked by T_i .



Graph-Based Protocols (Cont.)

- The tree protocol ensures conflict serializability as well as freedom from deadlock.
- Unlocking may occur earlier in the tree-locking protocol than in the two-phase locking protocol.
 - shorter waiting times, and increase in concurrency
 - protocol is deadlock-free, no rollbacks are required
- Drawbacks
 - Protocol does not guarantee recoverability or cascade freedom
 - ▶ Need to introduce commit dependencies to ensure recoverability
 - Transactions may have to lock data items that they do not access.
 - ▶ increased locking overhead, and additional waiting time
 - ▶ potential decrease in concurrency
- Schedules not possible under two-phase locking are possible under tree protocol, and vice versa.



Deadlock Handling

- Consider the following two transactions:

T_1 : write (X)
 write (Y)

T_2 : write(Y)
 write(X)

- Schedule with deadlock

T_1	T_2
lock-X on A write (A)	
	lock-X on B write (B)
wait for lock-X on B	wait for lock-X on A



Deadlock Handling

- System is deadlocked if there is a set of transactions such that every transaction in the set is waiting for another transaction in the set.
- **Deadlock prevention** protocols ensure that the system will *never* enter into a deadlock state. Some prevention strategies:
 - Require that each transaction locks all its data items before it begins execution (predeclaration).
 - Impose partial ordering of all data items and require that a transaction can lock data items only in the order specified by the partial order (graph-based protocol).




Multiple Granularity

- Allow data items to be of various sizes and define a hierarchy of data granularities, where the small granularities are nested within larger ones.
- Can be represented graphically as a tree (but don't confuse with tree-locking protocol)
- When a transaction locks a node in the tree *explicitly*, it *implicitly* locks all the node's descendents in the same mode.
- **Granularity of locking** (level in tree where locking is done):
 - **fine granularity** (lower in tree): high concurrency, high locking overhead
 - **coarse granularity** (higher in tree): low locking overhead, low concurrency



Example of Granularity Hierarchy



The levels, starting from the coarsest (top) level are:

- *database*
- *area*
- *file*
- *record*



Intention Lock Modes

- In addition to S and X lock modes, there are three additional lock modes with multiple granularity:
 - ***intention-shared*** (IS): indicates explicit locking at a lower level of the tree but only with shared locks.
 - ***intention-exclusive*** (IX): indicates explicit locking at a lower level with exclusive or shared locks
 - ***shared and intention-exclusive*** (SIX): the subtree rooted by that node is locked explicitly in shared mode and explicit locking is being done at a lower level with exclusive-mode locks.
- Intention locks allow a higher level node to be locked in S or X mode without having to check all descendent nodes.



Compatibility Matrix with Intention Lock Modes

- The compatibility matrix for all lock modes is:

	IS	IX	S	SIX	X
IS	true	true	true	true	false
IX	true	true	false	false	false
S	true	false	true	false	false
SIX	true	false	false	false	false
X	false	false	false	false	false



Multiple Granularity Locking Scheme

- Transaction T_i can lock a node Q , using the following rules:
 1. **The lock compatibility matrix** must be observed.
 2. **The root of the tree must be locked first**, and may be locked in any mode.
 3. **A node Q can be locked by T_i in S or IS mode** only if the parent of Q is currently locked by T_i in either IX or IS mode.
 4. **A node Q can be locked by T_i in X, SIX, or IX mode** only if the parent of Q is currently locked by T_i in either IX or SIX mode.
 5. **T_i can lock a node only if it has not previously unlocked** any node (that is, T_i is two-phase).
 6. **T_i can unlock a node Q** only if none of the children of Q are currently locked by T_i .
- Observe that locks are acquired in root-to-leaf order, whereas they are released in leaf-to-root order.



Timestamp-Based Protocols

- Unique value assigned to every transaction
- Tells order when transaction enters in system
- RTS
- WTS



Implementing TS

1. Use the value of the **system clock** as the timestamp; that is, a transaction's timestamp is equal to the value of the clock when the transaction enters the system.
2. Use a **logical counter** that is incremented after a new timestamp has been assigned; that is, a transaction's timestamp is equal to the value of the counter when the transaction enters the system.



Timestamp-Based Protocols

- Each transaction is issued a timestamp when it enters the system. If an old transaction T_i has time-stamp $TS(T_i)$, a new transaction T_j is assigned time-stamp $TS(T_j)$ such that $TS(T_i) < TS(T_j)$.
- The protocol manages concurrent execution such that the time-stamps **determine the serializability order**.
- In order to assure such behavior, the protocol maintains for each data Q two timestamp values:
 - **W-timestamp**(Q) is the largest time-stamp of any transaction that executed **write**(Q) successfully.
 - **R-timestamp**(Q) is the largest time-stamp of any transaction that executed **read**(Q) successfully.



Timestamp-Based Protocols (Cont.)

- The timestamp ordering protocol ensures that any conflicting **read** and **write** operations are executed in timestamp order.
- Suppose a transaction T_i issues a **read**(Q):
 1. If $TS(T_i) \leq \mathbf{W}$ -timestamp(Q), then T_i needs to read a value of Q that was already overwritten.
 - ▶ Hence, the **read** operation is rejected, and T_i is rolled back.
 2. If $TS(T_i) \geq \mathbf{W}$ -timestamp(Q), then the **read** operation is executed, and R-timestamp(Q) is set to **max**(R-timestamp(Q), $TS(T_i)$).



Timestamp-Based Protocols (Cont.)

- Suppose that transaction T_i issues **write**(Q).
 1. If $TS(T_i) < R\text{-timestamp}(Q)$, then the value of Q that T_i is producing was needed previously, and the system assumed that that value would never be produced.
 - ▶ Hence, the **write** operation is rejected, and T_i is rolled back.
 2. If $TS(T_i) < W\text{-timestamp}(Q)$, then T_i is attempting to write an obsolete value of Q .
 - ▶ Hence, this **write** operation is rejected, and T_i is rolled back.
 3. Otherwise, the **write** operation is executed, and $W\text{-timestamp}(Q)$ is set to $TS(T_i)$.



T_{25} : read(B);
read(A);
display($A + B$).

T_{26} : read(B);
 $B := B - 50$;
write(B);
read(A);
 $A := A + 50$;
write(A);
display($A + B$).



T_{25}	T_{26}
read(B)	read(B)
	$B := B - 50$
	write(B)
read(A)	read(A)
display($A + B$)	$A := A + 50$
	write(A)
	display($A + B$)

Figure 15.17 Schedule 3.



Example Use of the Protocol

A partial schedule for several data items for transactions with timestamps 1, 2, 3, 4, 5

T_1	T_2	T_3	T_4	T_5
				read (X)
read (Y)	read (Y)	write (Y) write (Z)		
				read (Z)
	read (Z) abort			
read (X)		write (W) abort	read (W)	
				write (Y) write (Z)



Correctness of Timestamp-Ordering Protocol

- The timestamp-ordering protocol guarantees serializability since all the arcs in the precedence graph are of the form:



Thus, there will be no cycles in the precedence graph.

- Timestamp protocol ensures freedom from deadlock as no transaction ever waits.
- But the schedule may not be cascade-free, and may not even be recoverable.



Recoverability and Cascade Freedom

- Problem with timestamp-ordering protocol:
 - Suppose T_i aborts, but T_j has read a data item written by T_i
 - Then T_j must abort; if T_j had been allowed to commit earlier, the schedule is not recoverable.
 - Further, any transaction that has read a data item written by T_j must abort
 - This can lead to cascading rollback --- that is, a chain of rollbacks
- Solution 1:
 - A transaction is structured such that its writes are all performed at the end of its processing
 - All writes of a transaction form an atomic action; no transaction may execute while a transaction is being written
 - A transaction that aborts is restarted with a new timestamp
- Solution 2: Limited form of locking: wait for data to be committed before reading it
- Solution 3: Use commit dependencies to ensure recoverability



Thomas' Write Rule

- Modified version of the timestamp-ordering protocol in which obsolete **write** operations may be ignored under certain circumstances.
- When T_i attempts to write data item Q , if $TS(T_i) < W\text{-timestamp}(Q)$, then T_i is attempting to write an obsolete value of $\{Q\}$.
 - Rather than rolling back T_i as the timestamp ordering protocol would have done, this **{write}** operation can be ignored.
- Otherwise this protocol is the same as the timestamp ordering protocol.
- Thomas' Write Rule allows greater potential concurrency.
 - Allows some view-serializable schedules that are not conflict-serializable.



Validation-Based Protocol

- Execution of transaction T_i is done in three phases.
 1. **Read and execution phase:** Transaction T_i writes only to temporary local variables
 2. **Validation phase:** Transaction T_i performs a "validation test" to determine if local variables can be written without violating serializability.
 3. **Write phase:** If T_i is validated, the updates are applied to the database; otherwise, T_i is rolled back.
- The three phases of concurrently executing transactions can be interleaved, but each transaction must go through the three phases in that order.
 - Assume for simplicity that the validation and write phase occur together, atomically and serially
 - ▶ i.e., only one transaction executes validation/write at a time.
- Also called as **optimistic concurrency control** since transaction executes fully in the hope that all will go well during validation



Validation-Based Protocol (Cont.)

- Each transaction T_i has 3 timestamps:
 - $\text{Start}(T_i)$: the time when T_i started its execution
 - $\text{Validation}(T_i)$: the time when T_i entered its validation phase
 - $\text{Finish}(T_i)$: the time when T_i finished its write phase
- Serializability order is determined by timestamp given at validation time, to increase concurrency.
 - Thus $\text{TS}(T_i)$ is given the value of $\text{Validation}(T_i)$.
- This protocol is useful and gives greater degree of concurrency if probability of conflicts is low.
 - because the serializability order is not pre-decided, and
 - relatively few transactions will have to be rolled back.



Validation Test for Transaction T_j

- If for all T_i with $TS(T_i) < TS(T_j)$ either one of the following condition holds:
 - **finish**(T_i) < **start**(T_j)
 - **start**(T_j) < **finish**(T_i) < **validation**(T_j) **and** the set of data items written by T_i does not intersect with the set of data items read by T_j .

then validation succeeds and T_j can be committed. Otherwise, validation fails and T_j is aborted.

- *Justification:* Either the first condition is satisfied, and there is no overlapped execution, or the second condition is satisfied and
 - the writes of T_j do not affect reads of T_i since they occur after T_i has finished its reads.
 - the writes of T_i do not affect reads of T_j since T_j does not read any item written by T_i .



Schedule Produced by Validation

- Example of schedule produced using validation

T_{25}	T_{26}
read (B)	read (B) $B := B - 50$ read (A) $A := A + 50$
read (A) $\langle \text{validate} \rangle$ display ($A + B$)	$\langle \text{validate} \rangle$ write (B) write (A)