

# ASSIGNMENT 2

Q1 Create 2 Public Docker Hub registries named

cloudethix\_master\_nginx\_yourname & cloudethix\_release\_nginx\_yourname.

- Clone below repository on your system.

<https://github.com/zembutsu/docker-sample-nginx.git>

- Initialize a local repository & copy the code from above repo to your local repository in master branch and then create below branches.

release

main

hotfix

- Once code is copied to local repository, from master branch update the index.html and add word "Cloudethix Master Branch Nginx" and build the docker image & add meaningful tags and push to Docker Hub registry cloudethix\_master\_nginx\_yourname.
- Also from release branch update the index.html and add word "Cloudethix Release Branch Nginx" and build the docker image & add meaningful tags and push to Docker Hub registry cloudethix\_release\_nginx\_yourname.
- Once Images are copied to Docker hub registries, switch to the main branch.
- In main branch create directory named kube/clusterIP & inside kube directory create file named master\_pod.yaml with pod name master\_nginx & with label master\_nginx & add image that you have pushed in Docker Hub registry cloudethix\_master\_nginx\_yourname.
- Also create a file release\_pod.yaml with pod name release\_nginx & with label release\_nginx & add image that you have pushed in Docker Hub registry cloudethix\_release\_nginx\_yourname.
- Create a file called cluster\_ip-service.yaml with service name cloudethix\_clusterip and with Type clusterIP.
- Then, select the pod with label release\_nginx in service.
- Create all these three resources in your k8s cluster.
- Now, access master\_nginx pod shell & curl the master\_nginx pod & check the result.
- Also try to curl release\_nginx pod with DNS name & check the result.
- Then curl the clusterip service with its name and check the result.
- Finally, create a GITHUB remote repository named cloudethix-k8s-yourname and push all the branches to the remote repository.
- Take all screenshots and create a well formatted document.

```
avej_lanjekar@AvejLanjekar:~ cloudethix-nginx$ git status
```

```
On branch master
```

```
No commits yet
```

```
Untracked files:
```

```
(use "git add <file>..." to include in what will be committed)
```

```
Dockerfile
```

```
LICENSE
```

```
README.md
```

```
default.conf
```

```
index.html
```

```
nothing added to commit but untracked files present (use "git add" to track)
```

```
avej_lanjekar@AvejLanjekar:~ cloudethix-nginx$ git add .
```

```
avej_lanjekar@AvejLanjekar:~ cloudethix-nginx$ git status
```

```
On branch master
```

```
No commits yet
```

```
Changes to be committed:
```

```
(use "git rm --cached <file>..." to unstage)
```

```
new file:   Dockerfile
```

```
new file:   LICENSE
```

```
new file:   README.md
```

```
new file:   default.conf
```

```
new file:   index.html
```

```
avej_lanjekar@AvejLanjekar:~ cloudethix-nginx$ git commit -m "initial commit  
adding all files"
```

```
[master (root-commit) 8e4394b] initial commit adding all files
```

```
5 files changed, 46 insertions(+)
```

```
create mode 100644 Dockerfile
```

```
create mode 100644 LICENSE
```

```
create mode 100644 README.md
```

```
create mode 100644 default.conf
```

```
create mode 100644 index.html
```

```
avej_lanjekar@AvejLanjekar:~ cloudethix-nginx$ git branch
```

```
* master
```

```
avej_lanjekar@AvejLanjekar:~ cloudethix-nginx$ git branch release
```

```
avej_lanjekar@AvejLanjekar:~ cloudethix-nginx$ git branch hotfix
```

```
avej_lanjekar@AvejLanjekar:~ cloudethix-nginx$ git branch main
```

```
avej_lanjekar@AvejLanjekar:~ cloudethix-nginx$ git branch
hotfix
main
* master
release
```

```
avej_lanjekar@AvejLanjekar:~ cloudethix-nginx$ ls
Dockerfile LICENSE README.md default.conf index.html
```

```
avej_lanjekar@AvejLanjekar:~ cloudethix-nginx$ vim index.html
```

```
avej_lanjekar@AvejLanjekar:~ cloudethix-nginx$ cat index.html
<html>
<body>
    <h1>Host: <!--#echo var="HOSTNAME" --></h1>
    Version: 1.1
    <h2>Cloudethix Master Branch Nginx</h2>
</body>
</html>
```

```
avej_lanjekar@AvejLanjekar:~ cloudethix-nginx$ docker build -t
cloudethix_master_nginx .
STEP 1/3: FROM nginx:alpine
STEP 2/3: COPY default.conf /etc/nginx/conf.d/
--> Using cache
0989e7142eba649abc4d95f1780a91bf1f19479e0fc6153f85667cfc7b500de5
--> 0989e7142eba
STEP 3/3: COPY index.html /usr/share/nginx/html/
COMMIT cloudethix_master_nginx
--> 7dd2f9352848
Successfully tagged localhost/cloudethix_master_nginx:latest
7dd2f93528487390cfb59c864cf86ca1ee436e51a9ce50b0a7c81d93810e4c81
```

```
avej_lanjekar@AvejLanjekar:~ cloudethix-nginx$ docker tag
cloudethix_master_nginx avejlanjekar45/cloudethix_master_nginx_avejlanjekar
```

```
avej_lanjekar@AvejLanjekar:~ cloudethix-nginx$ docker push
avejlanjekar45/cloudethix_master_nginx_avejlanjekar
Getting image source signatures
Copying blob 1ed8e39a7434 skipped: already exists
Copying blob 55afa1ecc21d skipped: already exists
Copying blob 8cdfe4f23778 skipped: already exists
Copying blob 0d62d88506ba skipped: already exists
Copying blob 0ea935727878 skipped: already exists
Copying blob d94291c26261 skipped: already exists
Copying blob 90a6a705d1fb done |
```

```
Copying blob da4dea1b00af skipped: already exists
Copying blob fb597529c916 skipped: already exists
Copying blob ba05887de274 skipped: already exists
Copying config 7dd2f93528 done |
Writing manifest to image destination
```

```
avej_lanjekar:~ cloudethix-nginx/kube/clusterIP$ cat cluster_ip-service.yml
apiVersion: v1
kind: Service
metadata:
  name: cloudethix-clusterip
  namespace: ns-1
spec:
  selector:
    app: release-nginx
  ports:
    - port: 80
      targetPort: 80
  type: ClusterIP
```

```
avej_lanjekar:~ cloudethix-nginx/kube/clusterIP$ kubectl get pods
```

| NAME          | READY | STATUS  | RESTARTS |
|---------------|-------|---------|----------|
| AGE           |       |         |          |
| master-nginx  | 1/1   | Running | 0        |
| 16m           |       |         |          |
| release-nginx | 1/1   | Running | 0        |
| 15m           |       |         |          |

```
avej_lanjekar:~ cloudethix-nginx/kube/clusterIP$ kubectl get service
```

| NAME                 | TYPE      | CLUSTER-IP   | EXTERNAL-IP | PORT(S) |
|----------------------|-----------|--------------|-------------|---------|
| AGE                  |           |              |             |         |
| cloudethix-clusterip | ClusterIP | 10.97.252.69 | <none>      | 80/TCP  |
| 17m                  |           |              |             |         |

```
avej_lanjekar:~cloudethix-nginx/kube/clusterIP$ kubectl exec -it master-nginx
-- sh
/ # curl http://localhost
<html>
<body>
  <h1>Host: master-nginx</h1>
  Version: 1.1
  <h2>Cloudethix Master Branch Nginx</h2>
</body>
</html>
/ #
/ #
```

```
avej_lanjekar@AvejLanjekar:~ cloudethix-nginx$ git status
On branch main
Changes not staged for commit:
  (use "git add <file>..." to update what will be committed)
  (use "git restore <file>..." to discard changes in working directory)
    modified:   index.html

Untracked files:
  (use "git add <file>..." to include in what will be committed)
    kube/

no changes added to commit (use "git add" and/or "git commit -a")

avej_lanjekar@AvejLanjekar:~ cloudethix-nginx$ git add .

avej_lanjekar@AvejLanjekar:~ cloudethix-nginx$ git status
On branch main
Changes to be committed:
  (use "git restore --staged <file>..." to unstage)
    modified:   index.html
    new file:   kube/clusterIP/cluster_ip-service.yml
    new file:   kube/master_pod.yaml
    new file:   kube/release_pod.yaml

avej_lanjekar@AvejLanjekar:~ cloudethix-nginx$ git commit -m " Adding all
files"
[main edb6da1] Adding all files
4 files changed, 40 insertions(+)
create mode 100644 kube/clusterIP/cluster_ip-service.yml
create mode 100644 kube/master_pod.yaml
create mode 100644 kube/release_pod.yaml

avej_lanjekar:~cloudethix-nginx$ git remote add origin
git@github.com:Avejlanjekar/cloudethix-k8s-Avejlanjekar.git

avej_lanjekar@AvejLanjekar:~ cloudethix-nginx$ git branch -M main

avej_lanjekar@AvejLanjekar:~ cloudethix-nginx$ git push -u origin main
Enumerating objects: 15, done.
Counting objects: 100% (15/15), done.
Delta compression using up to 8 threads
Compressing objects: 100% (15/15), done.
Writing objects: 100% (15/15), 2.21 KiB | 376.00 KiB/s, done.
Total 15 (delta 3), reused 0 (delta 0), pack-reused 0 (from 0)
```

```
remote: Resolving deltas: 100% (3/3), done.
To github.com:Avejlanjekar/cloudethix-k8s-Avejlanjekar.git
 * [new branch]      main -> main
branch 'main' set up to track 'origin/main'.
```

=====

==

Q2

In the main branch of your local repository create a directory kube/NodePort.

- Create below files from below url. Please make sure you will create NodePort service with port 30008 instead of loadbalancer.  
<https://kubernetes.io/docs/tasks/access-application-cluster/connecting-frontend-backend/>.  
backend-deployment.yaml  
backend-service.yaml  
frontend-deployment.yaml  
frontend-NodePort-service.yaml
- Once files are created , create all the resources in your k8s cluster.
- Access all public ips with port 30008 in the browser and then check the result.
- Finally, push all the latest code to the remote repository.

```
avej_lanjekar:~ cloudethix-nginx/kube/NodePort$ cat backend-deployment.yaml
apiVersion: apps/v1
kind: Deployment
metadata:
  name: backend
spec:
  selector:
    matchLabels:
      app: hello
      tier: backend
      track: stable
  replicas: 3
  template:
    metadata:
      labels:
        app: hello
        tier: backend
        track: stable
    spec:
      containers:
        - name: hello
```

```
    image: "gcr.io/google-samples/hello-go-gke:1.0"
    ports:
      - name: http
        containerPort: 80
```

```
avej_lanjekar:~ cloudethix-nginx/kube/NodePort$ cat backend-service.yaml
```

```
apiVersion: v1
kind: Service
metadata:
  name: hello
spec:
  selector:
    app: hello
    tier: backend
  ports:
    - protocol: TCP
      port: 80
      targetPort: http
```

```
avej_lanjekar:~ cloudethix-nginx/kube/NodePort$ cat frontend-deployment.yaml
```

```
apiVersion: apps/v1
kind: Deployment
metadata:
  name: frontend
spec:
  selector:
    matchLabels:
      app: hello
      tier: frontend
      track: stable
  replicas: 1
  template:
    metadata:
      labels:
        app: hello
        tier: frontend
        track: stable
    spec:
      containers:
        - name: nginx
          image: "gcr.io/google-samples/hello-frontend:1.0"
          lifecycle:
            preStop:
              exec:
                command: ["/usr/sbin/nginx", "-s", "quit"]
```

```
avej_lanjekar:~ cloudehthix-nginx/kube/NodePort$ cat frontend-NodePort-
service.yaml
apiVersion: v1
kind: Service
metadata:
  name: frontend
spec:
  selector:
    app: hello
    tier: frontend
  ports:
  - protocol: "TCP"
    port: 80
    targetPort: 80
    nodePort: 30008
  type: NodePort
```

```
avej_lanjekar:~ cloudehthix-nginx/kube/NodePort$ kubectl get deployments
```

| NAME                  | READY | UP-TO-DATE | AVAILABLE | AGE |
|-----------------------|-------|------------|-----------|-----|
| backend               | 3/3   | 3          | 3         | 21m |
| cloudehthix-configmap | 3/3   | 3          | 3         | 99m |
| flask-webapp          | 3/3   | 3          | 3         | 19h |
| frontend              | 0/1   | 1          | 0         | 20m |

```
avej_lanjekar:~ cloudehthix-nginx/kube/NodePort$ kubectl get svc
```

| NAME                  | TYPE      | CLUSTER-IP    | EXTERNAL-IP | PORT(S)      |
|-----------------------|-----------|---------------|-------------|--------------|
| cloudehthix-clusterip | ClusterIP | 10.97.252.69  | <none>      | 80/TCP       |
| frontend              | NodePort  | 10.102.240.80 | <none>      | 80:30008/TCP |
| hello                 | ClusterIP | 10.109.106.24 | <none>      | 80/TCP       |

```
avej_lanjekar@AvejLanjekar:~ cloudehthix-nginx/kube/NodePort$ minikube service
frontend -n ns-1 --url
http://127.0.0.1:42331
```

! Because you are using a Docker driver on linux, the terminal needs to be open to run it.

```
avej_lanjekar@AvejLanjekar:cloudethix-nginx$ git add .
avej_lanjekar@AvejLanjekar:cloudethix-nginx$ git status
On branch main
Your branch is up to date with 'origin/main'.
```



Changes to be committed:

(use "git restore --staged <file>..." to unstage)

```
modified:   Dockerfile
modified:   LICENSE
modified:   README.md
modified:   default.conf
modified:   index.html
new file:   kube/NodePort/backend-deployment.yaml
new file:   kube/NodePort/backend-service.yaml
new file:   kube/NodePort/frontend-NodePort-service.yaml
new file:   kube/NodePort/frontend-deployment.yaml
modified:   kube/clusterIP/cluster_ip-service.yml
modified:   kube/master_pod.yaml
modified:   kube/release_pod.yaml
```

avej\_lanjekar@AvejLanjekar:cloudethix-nginx\$ git commit -m "adding kube dir"

[main c248b0e] adding kube dir

12 files changed, 75 insertions(+)

mode change 100644 => 100755 Dockerfile

mode change 100644 => 100755 LICENSE

mode change 100644 => 100755 README.md

mode change 100644 => 100755 default.conf

mode change 100644 => 100755 index.html

create mode 100755 kube/NodePort/backend-deployment.yaml

create mode 100755 kube/NodePort/backend-service.yaml

create mode 100755 kube/NodePort/frontend-NodePort-service.yaml

create mode 100755 kube/NodePort/frontend-deployment.yaml

mode change 100644 => 100755 kube/clusterIP/cluster\_ip-service.yml

mode change 100644 => 100755 kube/master\_pod.yaml

mode change 100644 => 100755 kube/release\_pod.yaml

avej\_lanjekar@AvejLanjekar:cloudethix-nginx\$ git push origin main

Enumerating objects: 12, done.

Counting objects: 100% (12/12), done.

Delta compression using up to 8 threads

Compressing objects: 100% (9/9), done.

Writing objects: 100% (9/9), 1.27 KiB | 32.00 KiB/s, done.

Total 9 (delta 2), reused 0 (delta 0), pack-reused 0 (from 0)

remote: Resolving deltas: 100% (2/2), completed with 1 local object.

To github.com:Avejlanjekar/cloudethix-k8s-Avejlanjekar.git

edb6da1..c248b0e main -> main

=====

Q3 Create any 2 pods and assign them to different worker nodes with nodeName

property.

```
avej_lanjekar:~$ cat pod-1.yml
```

```
apiVersion: v1
```

```
kind: Pod
```

```
metadata:
```

```
  name: pod-1
```

```
  namespace: ns-1
```

```
spec:
```

```
  containers:
```

```
    - name: pod-1
```

```
      image: nginx
```

```
      ports:
```

```
        - containerPort: 80
```

```
  nodeName: minikube
```

```
avej_lanjekar:~$ cat pod-2.yml
```

```
apiVersion: v1
```

```
kind: Pod
```

```
metadata:
```

```
  name: pod-2
```

```
  namespace: ns-1
```

```
spec:
```

```
  containers:
```

```
    - name: pod-2
```

```
      image: nginx
```

```
      ports:
```

```
        - containerPort: 80
```

```
  nodeName: minikube-m02
```

```
avej_lanjekar@AvejLanjekar:~$ kubectl get pods -o wide
```

| NAME         |                | READY | STATUS          | RESTARTS | AGE   | IP          |
|--------------|----------------|-------|-----------------|----------|-------|-------------|
| NODE         | NOMINATED NODE |       | READINESS GATES |          |       |             |
| pod-1        |                | 1/1   | Running         | 0        | 2m43s | 10.244.0.30 |
| minikube     | <none>         |       | <none>          |          |       |             |
| pod-2        |                | 1/1   | Running         | 0        | 62s   | 10.244.1.22 |
| minikube-m02 | <none>         |       | <none>          |          |       |             |

=====

Que 4 →

- Label both worker nodes such as worker-0 node as cloudethix-k8s-00 & worker-1 node as cloudethix-k8s-01.
- Once nodes are labeled, create pod00.yaml file and schedule the pod on worker-0 node with nodeSelector property. Also create one more file named

pod01.yaml & schedule the pod on worker-1 node.

```
avej_lanjekar:~ kubectl label node minikube-m02 node-name=cloudethix-k8s-00
node/minikube-m02 labeled
```

```
avej_lanjekar:~ kubectl label node minikube-m03 node-name=cloudethix-k8s-01
node/minikube-m03 labeled
```

```
avej_lanjekar:~ kubectl get nodes -L node-name
```

| NAME         | STATUS | ROLES         | AGE | VERSION | NODE-NAME         |
|--------------|--------|---------------|-----|---------|-------------------|
| minikube     | Ready  | control-plane | 9d  | v1.35.1 |                   |
| minikube-m02 | Ready  | <none>        | 43h | v1.35.1 | cloudethix-k8s-00 |
| minikube-m03 | Ready  | <none>        | 21h | v1.35.1 | cloudethix-k8s-01 |

```
avej_lanjekar:~ cat pod00.yaml
```

```
apiVersion: v1
kind: Pod
metadata:
  name: pod-0
  namespace: ns-1
spec:
  nodeSelector:
    node-name: cloudethix-k8s-00
  containers:
    - name: pod-0
      image: nginx
      ports:
        - containerPort: 80
```

```
avej_lanjekar:~ cat pod01.yaml
```

```
apiVersion: v1
kind: Pod
metadata:
  name: pod-01
  namespace: ns-1
spec:
  nodeSelector:
    node-name: cloudethix-k8s-01
  containers:
    - name: pod-1-cont
      image: nginx
      ports:
        - containerPort: 80
```

```
avej_lanjekar:~ kubectl get pods -o wide
```

| NAME   | READY       | STATUS       | RESTARTS  |
|--------|-------------|--------------|-----------|
| AGE    | IP          | NODE         | NOMINATED |
|        |             |              | NODE      |
|        |             |              | READINESS |
|        |             |              | GATES     |
| pod-0  | 1/1         | Running      | 0         |
| 5m36s  | 10.244.1.22 | minikube-m02 | <none>    |
| pod-01 | 1/1         | Running      | 0         |
| 92s    | 10.244.3.9  | minikube-m03 | <none>    |

```
=====
=
```

Q5 Clone the below repo locally & create DaemonSet from directory

DaemonSet101.

<https://github.com/collabnix/kubelabs>

```
avej_lanjekar@AvejLanjekar:~ git clone
https://github.com/collabnix/kubelabs.git
Cloning into 'kubelabs'...
remote: Enumerating objects: 14031, done.
remote: Counting objects: 100% (707/707), done.
remote: Compressing objects: 100% (147/147), done.
remote: Total 14031 (delta 637), reused 560 (delta 560), pack-reused 13324
(from 5)
Receiving objects: 100% (14031/14031), 61.81 MiB | 4.16 MiB/s, done.
Resolving deltas: 100% (4181/4181), done.
Updating files: 100% (7374/7374), done.
```

```
avej_lanjekar@AvejLanjekar:~ ls
kubelabs
```

```
avej_lanjekar@AvejLanjekar:~ cd kubelabs/
```

```
avej_lanjekar@AvejLanjekar:~ ls
201          Gemfile          LICENSE
Secrets101   assets          kube101.md
AKS101       Gemfile.lock    LKE101
Security101  bluegreen       kubectl-for-docker.md
Autoscaler101  GitLab101      'Labels&Selectors'
ServiceCatalog101  bootstrap.sh  namespace.yaml
CONTRIBUTING.md  GitOps101     Labels-and-Selectors
ServiceMesh101    cka           nodejs.md
Chaos101         Helm101       Loft101
Services101      context       pods101
'Cheat Sheets'   IOT          Logging101
Shipa101         detect.md     pods101.png
ClusterNetworking101  Ingress101   ManagedKubernetes
```

|                      |                             |                          |
|----------------------|-----------------------------|--------------------------|
| SlidesReplicaSet101  | dockerdesktopformac         | portainer                |
| ConfigMaps101        | InitContainers101           | Monitoring101            |
| Slides_Services101   | dockervsk8s                 | portainer.yaml           |
| Cronjobs101          | JavaClient101               | MultiTenant101           |
| StatefulSets101      | gke-setup.md                | python                   |
| Cronjobs101.md       | Jenkins101                  | Network_Policies101      |
| Strimzi101           | golang                      | replicaset101            |
| DaemonSet101         | Jobs101                     | Observability101         |
| Terraform101         | helm                        | scripts                  |
| Deployment101        | Karpenter101                | Pods101_slides           |
| Weave-UI.png         | images                      | secerts_configmaps101    |
| Deployment101_slides | Keda101                     | RBAC101                  |
| _config.yml          | img                         | weave-pwk.md             |
| DevSpace101          | KubeSphere                  | README.md                |
| _config_dev.yml      | install                     | weave-service.png        |
| DisasterRecovery101  | Kubernetes_Architecture.md  | ReplicationController101 |
| _layouts             | intermediate                | weave.jpg                |
| EKS101               | Kubernetes_Intro_slides-1   | ResourceQuota101         |
| _site                | jekyll-theme-hacker.gemspec | weave.md                 |
| GKE101               | Kubezoo                     | Rollouts101              |
| ai                   | k3s                         |                          |
| Gateway101           | Kyverno101                  | Scheduler101             |
| api.md               | k8sworkshop.png             |                          |

```
avej_lanjekar@AvejLanjekar:~ cd DaemonSet101/
```

```
avej_lanjekar@AvejLanjekar:~ ls
README.md daemonset.yml
```

```
avej_lanjekar@AvejLanjekar:~ cat daemonset.yml
apiVersion: apps/v1
kind: DaemonSet
metadata:
  name: prometheus-daemonset
spec:
  selector:
    matchLabels:
      tier: monitoring
      name: prometheus-exporter
  template:
    metadata:
      labels:
        tier: monitoring
        name: prometheus-exporter
    spec:
      containers:
```

```
- name: prometheus
  image: prom/node-exporter
  ports:
    - containerPort: 80
```

```
avej_lanjekar@AvejLanjekar:~ kubectl apply -f daemonset.yml
daemonset.apps/prometheus-daemonset created
```

```
avej_lanjekar@AvejLanjekar:~ kubectl get ds
```

| NAME                 | DESIRED | CURRENT | READY | UP-TO-DATE | AVAILABLE |
|----------------------|---------|---------|-------|------------|-----------|
| NODE SELECTOR        | AGE     |         |       |            |           |
| prometheus-daemonset | 2       | 2       | 2     | 2          | 2         |
| <none>               | 32s     |         |       |            |           |

Q6 Create a static pod with name cloudethix-static in your k8s cluster. Refer below link.

<https://kubernetes.io/docs/tasks/configure-pod-container/static-pod>

```
avej_lanjekar@AvejLanjekar:~ minikube ssh
docker@minikube:~$ docker@minikube:~$ cd /etc/kubernetes
```

```
docker@minikube:/etc/kubernetes$ ls
addons  admin.conf  controller-manager.conf  kubelet.conf  manifests
scheduler.conf  super-admin.conf
```

```
docker@minikube:/etc/kubernetes$ cd manifests
```

```
docker@minikube:/etc/kubernetes/manifests$ cat cloudethix-static.yaml
```

```
apiVersion: v1
kind: Pod
metadata:
  name: cloudethix-static
  labels:
    app: cloudethix-static
spec:
  containers:
    - name: nginx
      image: docker.io/library/nginx:alpine
      ports:
        - containerPort: 80
```

```
docker@minikube:/etc/kubernetes/manifests$
```

```
docker@minikube:/etc/kubernetes/manifests$ ls
```

```
cloudethix-static.yaml  etcd.yaml  kube-apiserver.yaml  kube-controller-
manager.yaml  kube-scheduler.yaml
```

```
avej_lanjekar@AvejLanjekar:~ kubectl get pods -A
```

| NAMESPACE       | NAME                           | READY | STATUS  |
|-----------------|--------------------------------|-------|---------|
| cloudethix-avej | cloudethix-pod-9798fcf9d-5zsm9 | 1/1   | Running |
| 0               | 177m                           |       |         |
| cloudethix-avej | cloudethix-pod-9798fcf9d-t8wtq | 1/1   | Running |
| 0               | 177m                           |       |         |
| default         | cloudethix-static-minikube     | 1/1   | Running |
| 0               | 6m31s                          |       |         |

```
=====
=
```

Que 7 →

- Install Kubectl & kubens in your k8s cluste

```
avej_lanjekar@AvejLanjekar:~/kubernetes-Assignment/Repetition-
```

```
1/Assignment2/Q7$ sudo apt install kubectl -y
```

```
kubectl is already the newest version (0.9.5-2build1).
```

Summary:

Upgrading: 0, Installing: 0, Removing: 0, Not Upgrading: 62

```
avej_lanjekar@AvejLanjekar:~ kubectlx
```

```
avej-context
```

```
minikube
```

```
avej_lanjekar@AvejLanjekar:~ kubens
```

```
cloudethix-avej
```

```
default
```

```
ingress-nginx
```

```
kube-node-lease
```

```
kube-public
```

```
kube-system
```

```
ns-1
```

```
poc
```

```
repeat-1
```