# 后台接口API文档

## 说明

- 1. 协议为http
- 2. ip为47.94.234.136,端口80
- 3. 所有请求默认携带前缀 /server
- 4. 返回数据均为json,数据格式如下,code为自定义状态码,data为返回数据,msg代表错误提示信息

```
{
    code: INT,
    data: {},
    msg: STRING
}
```

5. 状态码 (code) 说明

code	说明
0	成功
1	未登录或登陆过期
2	未注册账号
3	账号或密码错误
4	账号已被注册
5	服务器错误
6	缺少参数
7	参数错误

6. 所有价格 (price) 的单位为分

## 用户模块

#### 说明

- 1. 该某块所有接口默认带有前缀/user
- 2. return中表示的为返回数据中data的数据格式

#### 获取注册验证码接口

url: /verificationCode

method: post

params:

```
email: string
```

return:

```
{
    status: 'success'
}
```

注册接口

*url:* /register

method: POST

params:

```
username: string,
email: string,
password: string, //最好转成sha256
code: int,
```

return:

```
{
    status: 'success'
}
```

登陆接口

url: /login

method: POST

params:

```
email: string,
password: string
```

```
{
    status: 'success'
}
```

## 获取个人信息

url: /userInfo/get

**method:** get

params:

```
null
```

#### return:

```
{
   username: string,
   email: string,
   imageUrl: string,
   birthday: data
}
```

## 修改个人信息

url: /userInfo/modify

**method:** post

params:

```
username: string,
birthday: string
```

#### return:

```
{
    status: 'success'
}
```

## 修改头像

url: /userInfo/upload

method: POST

params:

```
file: FILE
```

return:

```
{
    status: 'success'
}
```

获取收获地址

url: /address/get

method: GET

params:

```
null
```

#### return:

```
{
  address:[{
    id: int,
    name: string,
    phone: string,
    province: string,
    city: string,
    detail: string
}]
```

## 添加收获地址

url: /address/add

method: post

params:

```
name: string,
phone: string,
province: string,
```

```
city: string,
detail: string
```

```
{
    status: 'success'
}
```

## 修改收货地址

url: /address/modify

method: post

params:

```
id: int
name: string,
phone: string,
province: string,
city: string,
detail: string
```

#### return:

```
{
    status: 'success'
}
```

## 删除收获地址

url: /address/delete

method: POST

params:

```
id: int
```

```
{
    status: 'success'
```

## 用户商品模块

### 说明

- 1. 该某块所有接口默认带有前缀/food
- 2. return中表示的为返回数据中data的数据格式

### 根据分类获取商家

url: /shop/getByType

method: POST

params:

```
type: string
page: int, //从1开始
limit: int, //每页数量
```

#### return:

```
{
    shops: [{
        id: int,
            name: string,
            imageUrl: string,
            introduction: string,
        }]
}
```

#### 搜索商家

url: /shop/getByName

method: POST

params:

```
name: string
page: int, //从1开始
limit: int, //每页数量
```

```
{
    shops: [{
        id: int,
        name: string,
        imageUrl: string,
        introduction: string,
}]
```

商家详情

url: /shop/get

method: POST

params:

```
id: int
```

#### return:

```
{
    id: int,
    name: string,
    imageUrl: string,
    introduction: string,
    phone: string,
    address: string
    food: {
        'categoryName': [{
            id: int,
            name: string,
            price: int,
            imageUrl: string
        }]
    }
}
```

商家评论

url: /shop/common

method: POST

params:

```
id: int
```

```
{
   commons: [{
     usrname: string,
     text: string,
     imageUrl: string,
     rate: int,
     createdAt: timestamp
   }]
}
```

## 用户订单模块

### 说明

- 1. 该某块所有接口默认带有前缀/order
- 2. return中表示的为返回数据中data的数据格式
- 3. 订单转台码 (status) 说明

status	说明
0	订单创建
1	商家接单
2	商家派送
3	订单完成
4	用户取消
5	商家取消

#### 创建订单

url: /create

method: post

params:

```
foods:[{
    id: int,
    number: int
}]
addressId: int,
remark: string, //备注
```

```
{
    id: int// 订单id
}
```

获取订单

url: /get

method: post

params:

```
page: int, //从1开始
limit: int, //每页数量
```

return:

```
{
    orders: [{
        id: int,
        foods:[{
            id: int,
            name: string,
            price: int,
            imageUrl: string,
            number: int
        }]
        address:{
            name: string,
            phone: string,
            province: string,
            city: string,
            detail: string
        },
        status: int,
        createdAt: timestamp,
        remark: string, //备注
    }]
}
```

## 取消订单

url: /cancel

method: post

params:

```
id: int
```

return:

```
{
    id: int, //订单id
}
```

确认订单

url: /confirm

**method:** post

params:

```
id: int
```

return:

```
{
   id: int//订单id
}
```

评论图片上传

url: /common/upload

**method:** post

params:

```
file: FILE
```

```
{
    url: string
}
```

#### 对完成订单评论

url: /common

method: post

params:

```
id: int,
text: string,
imageUrl: string,
rate: int
```

return:

```
{
    id: int, //评论id
}
```

## 商家用户模块

###说明

- 1. 该某块所有接口默认带有前缀/shopUser
- 2. return中表示的为返回数据中data的数据格式

### 获取验证码

url: /verificationCode

method: POST

params:

```
email: string
```

#### return:

```
{
    email: string
}
```

#### 注册

url: /register

method: POST

params:

```
name: string,
email: string,
password: string, //sha256加密
code: int
address: string,
classification: string,
introduction: string
```

return:

```
{
    id: int, //用户id
}
```

登陆

url: /login

method: POST

params:

```
email: string,
password: string
```

return:

```
{
    id: int, //用户id
}
```

获取商店信息

url: /shop/get

method: GET

params:

null

```
{
    name: string,
    imageUrl: string,
    introduction: string,
    phone: string,
    address: string,
    classification: string,
    food: {
        'categoryName': [{
            id: int,
            name: string,
            price: int,
            imageUrl: string
        }]
    }
}
```

### 更新商店信息

url: /shop/modify

method: post

params:

```
name: string,
imageUrl: string,
introduction: string,
phone: string,
address: string,
classification: string,
food: {
    'categoryName': [{
        name: string,
        price: int,
        imageUrl: string
    }]
}
```

```
{
    status: 'success'
}
```

#### 上传图片

url: /shop/upload

method: POST

params:

```
file: FILE
```

#### return:

```
{
    url: string
}
```

#### 获取评论信息

url: /shop/common

method: GET

params:

```
null
```

#### return:

```
{
    commons: [{
        id: int,
        username: string,
        text: string,
        imageUrl: string,
        rate: int,
        createdAt: timestamp
    }]
}
```

## 商家订单模块

### 说明

- 1. 该某块所有接口默认带有前缀/shopOrder
- 2. return中表示的为返回数据中data的数据格式
- 3. 订单状态码 (status) 同订单系统中状态码

获取所有订单

*url:* /get

**method:** get

params:

```
null
```

return:

```
{
   orders: [{
        id: int,
        foods:[{
            id: int,
            name: string,
            price: int,
            imageUrl: string,
            number: int
        }]
        addressId: int,
        status: int,
        createdAt: timestamp,
        remark: string, //备注
    }]
}
```

确认接单

url: /confirm

method: post

params:

```
id: int
```

```
{
    id: int
}
```

送送订单
<b>rl:</b> /send
pethod: post
arams:
id: int
turn:
{     id: int }
Z消订单
<b>rl:</b> /cancel
pethod: post
arams:
id: int
turn:
{    id: int

}