

QAOA with ideal noise returns wrong result

<https://github.com/qiskit-community/qiskit-aqua/issues/1509>

ROW 59

QAOA with ideal noise returns wrong result #1509



Closed



iuliazidaru opened on Jan 18, 2021 · edited by iuliazidaru

Edits · ...

Information

- Qiskit Aqua version: qiskit-aqua: '0.8.1'
- Python version: 3.8.2
- Operating system: System: Darwin

What is the current behavior?

QAOA applied to the linear equation: minimize obj(x1 + x2+ x3 + ..x20) returns wrong result: 2

Steps to reproduce the problem

```
##%%

from qiskit.optimization import QuadraticProgram
def create_qubo_linear(num_variables):
    qubo = QuadraticProgram()
    for index in range(num_variables):
        qubo.binary_var('x' + str(index + 1))
    qubo.minimize(linear=[1] * num_variables,
                  quadratic={})
    return qubo

##%%

from qiskit.aqua import QuantumInstance
from qiskit.aqua import aqua_globals
from qiskit.optimization.algorithms import MinimumEigenOptimizer
from qiskit.aqua.algorithms import QAOA

SEED = 10598

def solve_qubo(qubo, device, optimiser, parameter_p):
    aqua_globals.random_seed = SEED
    quantum_instance = QuantumInstance(device, seed_simulator=SEED, seed_transpiler=SEED, shots=1024)
    qaoa_mes = QAOA(quantum_instance=quantum_instance, include_custom=True, optimizer=optimiser,
                    p=parameter_p)
    qaoa = MinimumEigenOptimizer(qaoa_mes)
    qaoa_result = qaoa.solve(qubo)
    return qaoa_result

##%%

from qiskit.aqua import aqua_globals
from qiskit.aqua.components.optimizers import SLSQP
from qiskit.providers.aer import QasmSimulator
from qiskit.providers.aer.noise import NoiseModel

def test_given_qubo_linear_then_qaoa_correct_result():
    # Arrange
    nbr_variables = 20
    qubo = create_qubo_linear(nbr_variables)
    noise_model = NoiseModel()
    ##device = QasmSimulator(method='matrix_product_state')
    ##device = QasmSimulator(method='density_matrix') # insufficient memory
    device = QasmSimulator(method='automatic', noise_model=noise_model)
    #device = Aer.get_backend('qasm_simulator')
    # Act
    result = solve_qubo(qubo, device, SLSQP(), 5)
    # Assert
    print(noise_model.is_ideal())
    print(result.fval)
    print(result.x)
    assert noise_model.is_ideal() == True
    assert result.fval == 0.0
    assert all([a == b for a, b in zip(result.x, [0] * nbr_variables)])

##%%

test_given_qubo_linear_then_qaoa_correct_result()

##%%
```



Assignees

No one assigned

Labels

No labels

Type

No type

Projects

No projects

Milestone

No milestone

Relationships

None yet

Development

No branches or pull requests

Notifications

Customize

Subscribe

You're not receiving notifications from this thread.

Participants



Zotero

```
import sys
print(sys.version)

#95%

import platform
uname = platform.uname()
print(f"System: {uname.system}")
print(f"Node Name: {uname.node}")
print(f"Release: {uname.release}")
print(f"Version: {uname.version}")
print(f"Machine: {uname.machine}")
print(f"Processor: {uname.processor}")

#95%
```

What is the expected behavior?

minimum value must be 0, and the solution 00000000000000000000

Suggested solutions

I replaced the problem in QAOA example <https://qiskit.org/textbook/ch-applications/qaoa.html> and the result looks good.

```
n = 20
V = np.arange(0,n,1)
E = []
```

[QAOA-algorithm.ipynb.zip](#)
[QAOA-bug.ipynb.zip](#)

This is related to : [#1434](#)

 iuliazidaru changed the title **QAOA with ideal noise return wrong result** **QAOA with ideal noise returns wrong result**
on Jan 25, 2021

In the above notebook just changing from SLSQP() to COBYLA(), I got the correct results.

Using

```
quantum_instance = QuantumInstance(QasmSimulator(method='automatic', noise_model=NoiseModel()),
                                   seed_simulator=aqua_globals.random_seed,
                                   seed_transpiler=aqua_globals.random_seed,
                                   shots=1024)
```

[illegible]

