

Unable to obtain FakeAlmaden model

<https://github.com/Qiskit/qiskit-aer/issues/1192>

ROW 65

Unable to obtain FakeAlmaden model #1192

New issue

Closed



haoqindeng opened on Mar 24, 2021

...

Informations

- Qiskit Aer version: 0.7.5
- Python version: 3.7.7
- Operating system: Windows Subsystem Linux 2

What is the current behavior?

We attempted to run the following code:

```
backend = FakeAlmaden()
fakealmaden_model = PulseSystemModel.from_backend(backend)
```



and we get the following error:

```
(vqe) haoqindeng@LAPTOP-CE39QN05: /mnt/c/Users/haoqi/OneDrive/Desktop/QCQ$ python qoc_test2.py line 45
Traceback (most recent call last):
  File "qoc_test2.py", line 46, in <module>
    fakealmaden_model = PulseSystemModel.from_backend(backend)
  File "/home/haoqindeng/miniconda3/envs/vqe/lib/python3.7/site-packages/qiskit/providers/aer/pulse/system_model.py", line 100, in from_backend
    return cls.from_config(config, subsystem_list)
  File "/home/haoqindeng/miniconda3/envs/vqe/lib/python3.7/site-packages/qiskit/providers/aer/pulse/system_model.py", line 110, in from_config
    hamiltonian = HamiltonianModel.from_dict(ham_string, subsystem_list)
  File "/home/haoqindeng/miniconda3/envs/vqe/lib/python3.7/site-packages/qiskit/providers/aer/pulse/system_model.py", line 120, in from_dict
    system.parse(subsystem_list)
  File "/home/haoqindeng/miniconda3/envs/vqe/lib/python3.7/site-packages/qiskit/providers/aer/pulse/system_model.py", line 130, in parse
    coef, token = self._tokenizer(ham, qubit_list)
  File "/home/haoqindeng/miniconda3/envs/vqe/lib/python3.7/site-packages/qiskit/providers/aer/pulse/system_model.py", line 140, in _tokenizer
    opr = gen_oper(name, idx, self.dim_osc, self.dim_qub)
  File "/home/haoqindeng/miniconda3/envs/vqe/lib/python3.7/site-packages/qiskit/providers/aer/pulse/system_model.py", line 150, in gen_oper
    return qobj.generators.tensor(opers)
  File "/home/haoqindeng/miniconda3/envs/vqe/lib/python3.7/site-packages/qiskit/providers/aer/pulse/qutip_extensions.py", line 160, in tensor
    return ten.tensor(list_qobj)
  File "/home/haoqindeng/miniconda3/envs/vqe/lib/python3.7/site-packages/qiskit/providers/aer/pulse/qutip_extensions.py", line 170, in tensor
    out.data = zcsr_kron(out.data, q.data)
  File "spmath.pyx", line 188, in qiskit.providers.aer.pulse.qutip_extensions.cy.spmath.zcsr_kron
  File "spmath.pyx", line 422, in qiskit.providers.aer.pulse.qutip_extensions.cy.spmath._safe_multiply
OverflowError: value too large
```



Steps to reproduce the problem

```
import qiskit
from qiskit import transpile, schedule as build_schedule
from qiskit.test.mock import FakeAlmaden
from qiskit import Aer, IBMQ, execute
from qiskit import QuantumCircuit
from qiskit.circuit import Gate

from qiskit import pulse
from qiskit.ignis.characterization.calibrations import rabi_schedules, RabiFitter

from qiskit.pulse import DriveChannel
from qiskit.compiler import assemble
from qiskit.qobj.utils import MeasLevel, MeasReturnType
# The pulse simulator
from qiskit.providers.aer import PulseSimulator

# Object for representing physical models
from qiskit.providers.aer.pulse import PulseSystemModel

# Mock Armonk backend
from qiskit.test.mock.backends.armonk.fake_armonk import FakeArmonk

# backend = qiskit.providers.aer.PulseSimulator()
backend = FakeAlmaden()
```



Assignees

No one assigned

Labels

bug

Type

No type

Projects

No projects

Milestone

No milestone

Relationships

None yet

Development

No branches or pull requests

Notifications

Customize

Subscribe

You're not receiving notifications from this thread.

Participants



```

from qiskit.pulse import DriveChannel
from qiskit.compiler import assemble
from qiskit.qobj.utils import MeasLevel, MeasReturnType
# The pulse simulator
from qiskit.providers.aer import PulseSimulator

# Object for representing physical models
from qiskit.providers.aer.pulse import PulseSystemModel

# Mock Armonk backend
from qiskit.test.mock.backends.armonk.fake_armonk import FakeArmonk

# backend = qiskit.providers.aer.PulseSimulator()
backend = FakeAlmaden()
print(backend.configuration().hamiltonian)
# schedule = build_schedule(transpiled_circ, backend)
circ = QuantumCircuit(2, 2)
circ.x(0)
circ.x(0)
circ.x(1)
circ.measure([0, 1], [0, 1])

schedule = build_schedule(circ, backend,
                          method="as_late_as_possible")
# schedule.draw(channels=[pulse.DriveChannel(0), pulse.DriveChannel(1)])

backend_sim = PulseSimulator()

qobj = assemble(schedule,
                 backend=backend_sim,
                 meas_level=1,
                 meas_return='avg',
                 shots=1)

print('line 45')
fakealmaden_model = PulseSystemModel.from_backend(backend)
print('line47')
sim_result = backend_sim.run(qobj, fakealmaden_model).result()

```

What is the expected behavior?

We should be able to run the code at the line:
 fakealmaden_model = PulseSystemModel.from_backend(backend)
 instead of getting the error above.

Suggested solutions

Don't know how. Any ideas?

[@taalexander](#)



[haoqindeng](#) added **bug** on Mar 24, 2021



[nonhermitian](#) on Mar 24, 2021

Contributor ...

You cannot build a sparse representation of a system model that big. That is what the error is indicating.



[haoqindeng](#) on Mar 24, 2021

Author ...

Our ultimate goal is to get the last line "sim_result = backend_sim.run(qobj, fakealmaden_model).result()" to work, but we are currently struck at error at "fakealmaden_model = PulseSystemModel.from_backend(backend)". Basically we are trying to extract a schedule of a circuit "circ" with FakeAlmaden backend, then use this schedule to construct a qobj and run it with fakealmaden_model.

If we cannot build a model that big, what do you suggest we could do to execute the qobj and obtain the results?

[@nonhermitian](#)

We should be able to run the code at the line:
`fakealmeden_model = PulseSystemModel.from_backend(backend)`
instead of getting the error above.

Suggested solutions

Don't know how. Any ideas?

[@taalexander](#)



haoqindeng added **bug** on Mar 24, 2021



nonhermitian on Mar 24, 2021

Contributor ...

You cannot build a sparse representation of a system model that big. That is what the error is indicating.



haoqindeng on Mar 24, 2021

Author ...

Our ultimate goal is to get the last line "`sim_result = backend_sim.run(qobj, fakealmeden_model).result()`" to work, but we are currently struck at error at "`fakealmeden_model = PulseSystemModel.from_backend(backend)`". **Basically we are trying to extract a schedule of a circuit "circ" with FakeAlmeden backend, then use this schedule to construct a qobj and run it with fakealmeden_model.**

If we cannot build a model that big, what do you suggest we could do to execute the qobj and obtain the results?

[@nonhermitian](#)



DanPuzzuoli on Mar 24, 2021

Contributor ...

Since it looks like you are only trying to run a schedule on the qubits 0 and 1, when constructing the `PulseSystemModel`, you can do:

```
fakealmeden_model = PulseSystemModel.from_backend(backend, subsystem_list=[0, 1])
```



This will tell the constructor to only construct the model for just qubits 0 and 1.



chriseclectic closed this as **completed** on Sep 15, 2021