

CompleteMeasFitter incorrectly imported in measurement_error_mitigation

<https://github.com/Qiskit/qiskit/issues/6980>

ROW 36

CompleteMeasFitter incorrectly imported in measurement_error_mitigation.py #6980

New Issue

Closed



omarshehab opened on Sep 3, 2021

Information

- Qiskit Terra version: 0.18.0
- Python version: 3.9.5 (default, May 18 2021, 12:31:01) [Clang 10.0.0]
- Operating system: Darwin

What is the current behavior?

I am currently seeing

```
QiskitError: 'Unknown fitter <qiskit.ignis.mitigation.measurement.fitters.CompleteMeasFitter object at 0x7fcbce6c40>'
```

error, when I pass an `qiskit.ignis.mitigation.measurement.fitters.CompleteMeasFitter` object as a value to the parameter `measurement_error_mitigation_cls` in the constructor of `QuantumInstance` and use the `QuantumInstance` object with `QuantumKernel.evaluate()`.

Steps to reproduce the problem

1. Generate the calibration circuits using `complete_meas_cal()`.
2. Execute the calibration circuits on target hardware (for this week ibm_toronto).
3. Calculate the calibration matrix using `CompleteMeasFitter()`.
4. Pass the calibration matrix calculated in step # 3 as a value for the parameter `measurement_error_mitigation_cls` while creating an instance of `QuantumInstance`. For simplicity, I am not overriding the default values for `cal_matrix_refresh_period` and `measurement_error_mitigation_shots`.
5. Use the `QuantumInstance` object in the standard QSVM pipeline.

What is the expected behavior?

It should not throw any runtime error.

Suggested solutions

`CompleteMeasFitter` incorrectly imported in `measurement_error_mitigation.py`. At line # 141 of `measurement_error_mitigation.py`, `CompleteMeasFitter` should be imported from `qiskit.ignis.mitigation.measurement.fitters` instead of `qiskit.ignis.mitigation.measurement`.



omarshehab added `bug` on Sep 3, 2021



TheGupta2012 on Sep 3, 2021

Contributor

May I work on this @omarshehab ?



Assignees

No one assigned

Labels

bug

Type

No type

Projects

No projects

Milestone

No milestone

Relationships

None yet

Development

No branches or pull requests

Notifications

Customize

Subscribe

You're not receiving notifications from this thread.

Participants





ShellyGarion on Sep 3, 2021

Member ...

I think that the following PR should handle this issue: [#6867](#)
(note that `qiskit-ignis` is going to be deprecated)



TheGupta2012 on Sep 3, 2021

Contributor ...

Okayy 🙌



[omarshehab](#) mentioned this on Sep 3, 2021

🔗 [Migrate measure mitigation from ignis for QuantumInstance #6867](#)



ShellyGarion on Sep 3, 2021

Member ...

PR [#6867](#) is part of the next release 0.19: <https://github.com/Qiskit/qiskit-terra/milestone/18>



woodsp-ibm on Sep 3, 2021

Member ...

Can you check with the latest version of qiskit - 0.18.1 (you say you have 0.18.0). The issue you describe was fixed

See https://qiskit.org/documentation/release_notes.html#bug-fixes

Fixed an issue where the QuantumInstance class would potentially try to use the CompleteMeasFitter class before it was imported resulting in an error. Fixed [#6774](#)



omarshehab on Sep 4, 2021

Author ...

[@woodsp-ibm](#) , I received the same error with Qiskit Terra 0.18.1.



jakelishman on Sep 4, 2021 - edited by jakelishman

Edits ▾ Member ...

It sounds like you're passing an instance, but the code wants the actual class (i.e. pass `CompleteMeasFitter` directly). The error you reported is consistent with the import having succeeded, but the wrong value having been passed.

(by the way, for reproducibility, it can be a little easier for us if you're able to provide a minimal complete block of code to read and copy/paste, rather than trying to interpret text)



omarshehab on Sep 4, 2021

Author ...

[@jakelishman](#) , I have attached the MWE code here.

[qsvm-readout-error-mitigation-mwe.ipynb.zip](#)



jakelishman on Sep 5, 2021

Member ...

That's not exactly a MWE, but I can see you are setting `measurement_error_mitigation_class` to an *instance* of `CompleteMeasFitter`, but it's meant to be the class (type). You need to pass `CompleteMeasFitter` to construct `QuantumInstance`, not a constructed instance of it.



woodsp-ibm on Sep 5, 2021

Member ...

If an example would be helpful for how to use it see this tutorial https://qiskit.org/documentation/tutorials/algorithms/03_vqe_simulation_with_noise.html#Performance-with-noise-and-measurement-error-mitigation



2

omarshehab on Sep 5, 2021

Author ...

@woodsp-ibm, I modified the statement to create `QuantumInstance` as follows.

```
noise_model = NoiseModel.from_backend(backend)
adhoc_backend = QuantumInstance(backend, shots=1024,
                                seed_transpiler=seed, optimization_level = 3, noise_model=noise_model, measure
```



Currently, I am getting the following error.

```
QiskitError: "The noise model is not supported on the selected backend ibmq_quito (<AccountProvider for
```



ShellyGarion on Sep 5, 2021

Member ...

@omarshehab - you cannot have a noise model with ibmq backend, only with Aer simulator:
`backend = Aer.get_backend('aer_simulator')`
the ibmq devices already have noise inside them :)
so, you should either choose an ibmq backend, or Aer simulator with a noise model
please look again at the tutorial suggested above.



jakelishman on Dec 14, 2021

Member ...

I'm closing this now, because I think that if there was a bug, it was fixed, and the other issues were due to problems with the usage. Please feel free to re-open this or another issue if that's not the case.



1

jakelishman closed this as completed on Dec 14, 2021