Chpt 5b, L5, 2h Results for Martin Freiwald

# Correct answer Question 1 Select the true statement regarding general aviation aircraft communication radios. The antennas are usually fin shaped and mounted below the cabin. The radios use a portion of the very high frequency (VHF) range from 118.0 MHz to 135.975 MHz. The range of transmission is not limited by obstruction, such as buildings, terrain, or the curve of the earth. Correct answer Question 2 Using the phonetic alphabet, what is the pronunciation of the following aircraft call sign: Cessna 649SP Cessna Nine Sierra Pap. Cessna 649 S P. Cessna SIX FOUR NINER Sierra Papa Wrong answer Question 3 What is the correct method of stating 10,500 MSL to ATC? One zero thousand, five hundred Ten point five Ten thousand, five hundred

Question 4

0/1 pts

Time Conversion Table				
To UTC (Zulu)				
Add 5 Hours				
Add 6 Hours				
Add 7 Hours				
Add 8 Hours				

NOTE: For daylight time, subtract one hour from the conversion time before converting to UTC (Zulu).

Refer to the time conversion table for the following two questions, if you depart an airport in the central standard time zone at 1300 and arrive in a city on the west coast two hours later what is your arrival time in Zulu?


1900





# Question 5 If you fly from a city in the Pacific Daylight Time zone to a city in the Central Daylight Time zone, and you leave at 0700 PDT with an estimated time enroute of three hours, what is your estimated time of arrival in Zulu? ○ 1700Z ○ 0300Z ○ 1100Z

Wmng answer



🔮 | Sales in the SWIII and business introduces on 122.5 MHz at 12 mHz and and give product reports to the multi-patient

### Correct answer

1 / 1 pts Question 7

Select the actions that you would take to comply with the following ATC clearance. "Cessna 52 Sierra, Runway 17, taxi via Bravo, hold short Runway 26 Right."

Taxi onto runway 17

Taxi along taxiway bravo toward runway 17, stopping at the hold line for runway 26 right and waiting for ATC clearance to cross runway 26 right.

Taxi on runway 17, crossing taxiway bravo, to runway 26 right, stopping at runway 26 right until cleared to proceed by ground control.

#### Correct answer


1 / 1 pts **Question 8** 

After landing at a tower controlled airport when should you contact ground control?

O After reaching a taxi way, that leads directly to the parking area

Prior to turning off the runway

Question 9
Select the correct procedure for lost communication used for landing at a Class D airspace primary airport.
A steady red light means the tower is closed
Join the airport traffic pattern and maintain visual contact with the tower for light gun signals
→ □ Set your transponder code to 7600
→ □ Acknowledge light gun signals by rocking your wings
Remain outside of Class D airspace until you have determined the flow of traffic
✓ ■ A steady green light indicates you are cleared to land
☐ You have the highest priority in landing
Acknowledge at night by blinking your landing or navigation lights
☐ All other pilots in the traffic pattern should make way for you



## Wrong answer

# Question 11

How often must the ELT battery be replaced or recharged if the batteries rechargeable?

- 12 Calendar months.
- After the ELT has been used for more the 30 minutes of cumulative use.
- → When half the useable life has been used or the ELT has been used for more than one cumulative hour.