

VER-MMVR

1-10

A01

A01

GENERAL

Operational Hours

ATS Hours / AD Hours: 1200-0500+, other times O/R.

Airport Information

RFF: CAT 6

PCN: RWY 18/36: 66/R/B/X/T 1700m / 5577ft

57/F/A/X/T 700m / 2296ft.

Operation

RWY Restriction

RWY 09/27 between RWY 18/36 and TWY C AVBL for ACFT up to code letter D as TWY to enter/exit RWY 18/36.

TWY Restriction

TWY D between stands 9 and 10 width 10.5m / 34ft.

Taxi/Parking

Enter/exit commercial platform by towing.

Warnings

Birds in vicinity of AD.

ARRIVAL

Speed

MAX IAS 250KT at or below 10100ft MSL within D30 VER VOR/DME.

MAX IAS 200KT at or below 3100ft MSL within D10 VER VOR/DME.

DEPARTURE

Take-off Minima

RWY		18/36	
All ACFT	ft - ft/SM	c300 - 1.0V	-


Speed

MAX IAS 250KT at or below 10100ft MSL within D30 VER VOR/DME.

MAX IAS 200KT at or below 3100ft MSL within D10 VER VOR/DME.


General Heriberto Jara **Veracruz** Mexico


AFC



127.800	1300-0100‡
120.400	1200-0500‡
118.500	1200-0500‡

RWY system:





VER-MMVR

SIDs RWY 36


SIDs RWY 18

SID

SID

SIDs RWY 36

SIDs RWY 18



Changes: Completely revised

© Lido 2016


VER-MMVR

SIDs RWY 36

SID

SIDs RWY 36

SID



Changes: Completely revised

© Lido 2016

18-AUG-2016

VER-MMVR**5-10****SIDs RWY 18**

AVTUX 2 / AXELI 2A / IMARA 2 / IPTAK 2 / LEXUR 2 / OTILO 2 / TAMVO 2 / URSOT 2
RWY 18 (186°)

	GS	120	150	180	210	240	270
6.0%	ft/MIN	800	1000	1100	1300	1500	1700

DESIGNATOR	ROUTING	ALTITUDES
	Runway 18	
AVTUX 2 120.400	intercept R185 VER - at D10 VER LT 160° intercept R176 VER to AVTUX	
AXELI 2A 120.400	intercept R185 VER - at D7 VER LT follow D10 VER arc - RT intercept R091 VER to AXELI	
IMARA 2 120.400	intercept R185 VER - at D7 VER LT follow D10 VER arc - RT intercept R104 VER to IMARA	
IPTAK 2 120.400	intercept R185 VER - at D7 VER LT follow D10 VER arc - RT intercept R119 VER to IPTAK	
LEXUR 2 120.400	intercept R185 VER - at D10 VER RT 195° intercept R188 VER to LEXUR	
OTILO 2 120.400	intercept R185 VER - at D7 VER LT follow D10 VER arc - RT intercept R154 VER to OTILO	
TAMVO 2 6.0% to 21000 120.400	intercept R185 VER - at D7 VER RT follow D10 VER arc - LT intercept R258 VER to TAMVO	
URSOT 2 6.0% to 21000 120.400	intercept R185 VER - at D7 VER RT follow D10 VER arc - LT intercept R266 VER to URSOT	

18-AUG-2016

VER-MMVR

5-20

SIDs RWY 18**SIDPT****VERACRUZ 3A**

RWY 18 (186°)

DESIGNATOR	ROUTING	ALTITUDES
	Runway 18	
VERACRUZ 3A VER 3A 120.400	intercept R185 VER - at D7 VER (MNM 1300 if DME U/S) LT (within D10 VER) direct VER	VER MNM 2500 (UJ18; OMPAN/ MID) VER MNM 2500 (UJ24; GOTAS/ CPE) VER MNM 2500 (V28/ UJ28; NOREL/ CME) VER MNM 2500 (V23/ UJ12; ELOGO/ VSA) VER MNM 2500 (V22/ A552/UA552; DUPLO/ MTT) VER MNM 2500 (V33/ UJ34; MISAS/ IZT) VER MNM 2500 (UJ70; ALESAS/ HUX) VER MNM 3500 (V29; OAX) VER MNM 14500 (UJ24; CUA) VER MNM 14500 (UJ12; PBC) VER MNM 10500 (V22/ UJ18; ALMET/ APN) VER MNM 7000 (V28/ V54/UJ28/UJ41; ONBAD/ REXES) VER MNM 2500 (V23/ A552/UJ34/UA552; AXORO/ NAU) VER MNM 2500 (V29; AMORA/ LIDAR)

Changes: Completely revised

18-AUG-2016

VER-MMVR**5-30****SIDs RWY 36****SIDPT**

AMORA 3 / AXELI 2B / AXORO 2 / BOLTA 2 / ETNAS 2 / ONBAD 2
RWY 36 (006°)

	GS	120	150	180	210	240	270
4.2%	ft/MIN	600	700	800	900	1100	1200

DESIGNATOR	ROUTING	ALTITUDES
	Runway 36	
AMORA 3 120.400	intercept R005 VER - at D10 VER LT 340° intercept R360 VER to AMORA	
AXELI 2B 120.400	intercept R005 VER - at D7 VER RT follow D10 VER arc - LT intercept R091 VER to AXELI	
AXORO 2 120.400	intercept R005 VER - at D7 VER LT follow D10 VER arc - RT intercept R328 VER to AXORO	
BOLTA 2 120.400	intercept R005 VER - at D7 VER RT follow D10 VER arc - LT intercept R068 VER to BOLTA	
ETNAS 2 120.400	intercept R005 VER - at D7 VER RT follow D10 VER arc - LT intercept R077 VER to ETNAS	
ONBAD 2 4.2% to 14000 120.400	intercept R005 VER - at D7 VER LT follow D10 VER arc - RT intercept R296 VER to ONBAD	

18-AUG-2016

VER-MMVR

5-40

SIDs RWY 36**VERACRUZ 3B**

RWY 36 (006°)

DESIGNATOR	ROUTING	ALTITUDES
	Runway 36	
VERACRUZ 3B VER 3B 120.400	intercept R005 VER - at D7 VER (MNM 1400 if DME U/S) LT (within D10 VER) direct VER	VER MNM 2500 (UJ18; OMPAN/MID) VER MNM 2500 (UJ24; GOTAS/CPE) VER MNM 2500 (V28/ UJ28; NOREL/CME) VER MNM 2500 (V23/ UJ12; ELOGO/VSA) VER MNM 2500 (V22/ A552/UA552; IPTAK/ MTT) VER MNM 2500 (V33/ UJ34; OTILO/IZT) VER MNM 2500 (UJ70; AVTUX/HUX) VER MNM 3500 (V29; LEXUR/OAX) VER MNM 14500 (UJ24; CUA) VER MNM 14500 (UJ12; PBC) VER MNM 10500 (V22/ UJ18; ALMET/APN) VER MNM 7000 (V28/ V54/UJ28/UJ41; REXES) VER MNM 2500 (V23/ A552/UJ34/UA552; NAU) VER MNM 2500 (V29; LIDAR)

Effective 01-MAR-2018

22-FEB-2018

VER-MMVR

Mexico Veracruz General Heriberto Jara

NIL

7-10

Transitions 18/36


IAC

IAC

General Heriberto Jara Veracruz Mexico

NIL

Transitions 18/36



Mexico Veracruz General Heriberto Jara

VOR DME Two 18

IAC

IAC

General Heriberto Jara **Veracruz** Mexico

VOR DME Two 18



7-30

VOR DME One 18

IAC


IAC

VOR DME One 18

[illegible]

		VOR DME					Circling TERPS
18							
C	ft - ft/SM 580	520 - 1.5V 580					600 - 1.5V 690
D	ft - ft/SM 580	520 - 1.75V 580					Not published

VOR DME Two 18



Mexico Veracruz General Heriberto Jara

General Heriberto Jara **Veracruz** Mexico

VOR DME One 36

IAC

VOR DME Two 36



18-AUG-2016

VER-MMVR

Mexico Veracruz General Heriberto Jara

7-60

VOR DME Two 36

IAC
IAC


General Heriberto Jara Veracruz Mexico

VOR DME Two 36

**VOR DME
Two 36
D 114.0 VER**

ATIS 127.800
APP 120.400
TWR 118.500

① Remain within D10 VER



60 H 45 x 2400		3.0° TDZ ---% 89 / 3hPa		HL-P1		3 4 5 6.1		3.00° D VER 005° RWY 006°	
R005 VER at D7 VER LT within D10 VER direct VER climb 2000		VER		D5 D6.1 D8 VER		1450 1200 1800			
GS 120 140 160		D5 VER 640 750 850		MAPt 2:30 2:09 1:53		MDA		DIST TO THR	
36		VOR DME						Circling TERPS	
C		ft - ft/SM ft		480 - 1.25V 560				600 - 1.5V 690	
D		ft - ft/SM ft		480 - 1.5V 560				700 - 2.25V 790	


Changes: Completely revised

18-AUG-2016


VER-MMVR

7-70

VOR 18



3.00° D VER 185° RWY 186°			5.7	5	4	3	(18)	3.0° 2400 x 45 60 H
			1800	1580	1270	950		68 / 2hPa TDZ ---% +0.3%



18	VOR					Circling TERPS
C	ft - ft/SM ft	600 - 1.5V 660				600 - 1.5V 690
D	ft - ft/SM ft	600 - 1.75V 660				700 - 2.25V 790


Changes: Nil

18-AUG-2016

VER-MMVR

7-80

VOR 36



Changes: Nil


VER-MMVR

NIL
MRC

MRC

MRC

NIL
MRC



Changes: new

© Lido 2014