

GENERAL**Operational Hours****ATS Hours:** RCO**AD OPS Hours:** MON-FRI 1200-2300±, SAT and SUN 1200-2100±, O/T PN.**Airport Information****RFF:** O/R**PCN:** O/R**Operation****Traffic Notes**

AD AVBL for ACFT wingspan below 52m / 171ft.

Aerodrome Level of Service

RWY 12/30: 2600R/0.5V

TWY Restriction

TWY B and APN 2: No winter maintenance.

ARRIVAL**Speed**

MAX IAS 250KT below 10000ft.

MAX IAS 200KT below 3000ft AGL within 10NM of AD.

Communication**COM Failure:** See CRAR Canada.**DEPARTURE****Take-off Minima**

| RWY | | 30 | |
|----------|------------|----------|----------------|
| All ACFT | ft - ft/SM | 0 - 0.5V | - |
| RWY | | 12 | |
| All ACFT | ft - ft/SM | 0 - 0.5V | No LT BLW 1300 |

Communication**COM Failure:** See CRAR Canada.

Effective 19-JUL-2018

12-JUL-2018

YCL-CYCL

2-10

Canada Charlo

AGC

AFC


AFC

AFC

Charlo Canada

AGC


AFC



Moncton Center 134.250

ATF 122.200 5NM 3100 ASL, ARCAL K

Landing RWY system:



Changes: FAT, VAR, AWY

Effective 19-JUL-2018

12-JUL-2018

YCL-CYCL

Canada Charlo

AGC

AGC

AGC


Charlo Canada

AGC

3-20

Moncton Center 134.250
ATF 122.200 5NM 3100 ASL, ARCAL K

| RWY | TORA | ASDA | TODA |
|-----|------|------|------|
| 12 | 1832 | 1832 | 1982 |
| 30 | 1832 | 1832 | 1982 |




Changes: VAR, QFU

| DEPARTURES | |
|------------|--|
| RWY | Routing |
| RWY 12 DEP | Departure: No LT below 1300 Visual Climb Over Airport: climb visual to 1200 (CAT C) / 1300 (CAT D) BPOC. |
| RWY | Notes |
| 12 | Trees to 219ft ASL, APRX 400ft past DER. |
| 30 | Power line to 271ft ASL, APRX 0.1NMpast DER. |
| | |


YCL-CYCL

7-10

RNAV (GNSS) 12



| | | | | | | | | |
|---------------|------|------|------|------|------|-----|--------|---------------------------------------|
| 3.00° RW12 | 7.9 | 6 | 5 | 4 | 3 | 2 | 12 | 60 HL |
| | 2700 | 2090 | 1770 | 1460 | 1140 | 820 | 732 | 1832 x 46 |
| | | | | | | | HL-P1R | THR 132 (5hPa) / TDZ 132 (---%) -0.3% |




| TERPS | 12 | RNAV GNSS LPV ZBF QNH 1) | RNAV GNSS LNAV ZBF QNH 1) | Circling 1) |
|-------|------------------|--------------------------|---------------------------|--------------------|
| C | ft - ft/SM ft | 340 - 1.0V 470 | 490 - 1.0V 620 | 650 - 2.0V 780 |
| D | ft - ft/SM ft | 340 - 1.0V 470 | 490 - 1.0V 620 | 730 - 2.25V 860 |

1) Use with Bathurst (CZBF) QNH

Changes: Track, FAT, ALT, VAR, MISAP text




RNAV (GNSS) 30



© Lido 2018

7-30

NDB A



| | | | | | | |
|--------------|------------------|--|--|--|--|---------------------------|
| 12/30 | | | | | | Circling 1) |
| C | ft - ft/SM ft | | | | | 650 - 2.0V 780 |
| D | ft - ft/SM ft | | | | | 730 - 2.25V 860 |

1) Use with Bathurst (CZBF) QNH

Changes: Track, FAT, VAR, MISAP text, Editorial