

GENERAL**Operational Hours****ATS Hours / AD Hours**

Summer: H24

Winter: H24 until OCT 31, from NOV 1 0630-2300 PS 1HR PPR

Airport Information**RFF:** CAT 9, 01 APR - 31 OCT

CAT 7, 01 NOV - 31 MAR, CAT 9 O/R MNM 3 days in advance

PCN: RWY 06/24: 131/F/AW/T, fist 104m / 341ft 104/R/B/W/T**Operation****Traffic Note**

AD not AVBL to code letter F ACFT.

Preferential RWY

RWY 24 when tail wind component does not exceed 10KT and the RWY surface is dry or wet with braking action good.

Low Visibility Procedure

LVP in force when RVR at or below 550m or when horizontal VIS is at or below 800m.

Only 1 ACFT will be allowed on manoeuvring area during LVP.

Follow-me O/R.

Exit RWY via:

RWY 24: TWY D or TWY H2.

RWY 06: TWY G or TWY H3.

Enter RWY via:

RWY 24: RWY holding position 24 in TWY H3.

RWY 06: RWY holding position 06 in TWY H2.

Standard Taxi Routes during LVP

Arrival:

RWY 24: proceed to Gate B via TWY D-C or TWY H2-C.

RWY 06: proceed to Gate A via TWY G-C or TWY H3-C.

Departure:

RWY 24: proceed to RWY holding position 24 via TWY A-C-H3.

RWY 06: proceed to RWY holding position 06 via TWY B-C-H2.

ACFT that have already landed will notify:

- RWY vacated
- TWY used

TWY Restriction

TWY H1, H4 width 19m / 62ft, MAX wingspan 36m / 118ft.

TWY E, F, APN A MAX wingspan 52m / 171ft.

ACFT with wingspan 52m / 171ft or above must enter/exit APN via gate B only.

GENERAL**Taxi/Parking**

Parking must be requested from 01 MAY - 15 OCT . This measure applies to ACFT with wingspan above 18m / 59ft and for stopovers of more than 3HR.

Follow-me mandatory for stands 19, 19A, 19B, 20, 20A, 20B, 25B and at those which the VDGS is out of service.

APU: Use of APU at stands with 400Hz current restricted to 2min after block-on and 5min prior off-block.
Exceptions:

- if stand is not equipped with AC power (400Hz) and mobile GPU not AVBL.
- if air condition is required and no ACU AVBL.

Engine Run-up Area

ENG test at medium or high PWR AVBL between 0630-2259†. ENG test will be accomplished at the locations indicated by TWR.

Warnings**IBA VOR/DME**

Limitations at 25NM:

VOR

R360-R050 at 5000ft or above

R280-R360 at 7000ft or above

Up to 5° deviation may occur on radials 3NM from VOR/DME at 4000ft.

Unusable: R299 beyond 18NM at 5000ft.

DME

R360-R050 at 5000ft or above

R090-R110 at 6000ft or above

R280-R360 at 7000ft or above

BAKAX1V

Possible signal loss on R057 IBA below FL80. Radar assistance will be provided.

Birds in vicinity of AD.

ARRIVAL**Speed**

MAX IAS 250KT at FL100 or below.

MAX IAS 210/220KT according to speed limitations over the WPT of standard ARR.

IAS 210KT at D12 ILS.

IAS 190KT at D9 ILS.

IAS 160KT at D4 ILS

or equivalent DIST from THR in case of DME ILS U/S.

ARRIVAL**Communication**

Notify ATC when ACFT wingspan 52m / 171ft or above in first COM.

COM-Failure**During MISAP****RWY 06 (ILS/LOC)**

At D2 IBA turn right (MAX IAS 230KT) to intercept and follow R077 IBA until D8 IBA. Turn left MT 007° to follow R052 IBA until BEBES. Turn left to proceed D20 IBA Arc until R256 IBA. Turn left to TILNO IAF.

RWY 06 (VOR)

At IBA DVOR/DME proceed R064 until D2 IBA, turn right (MAX IAS 230KT) to intercept and follow R077 IBA until D8 IBA. Turn left MT 007° to follow R052 IBA until BEBES. Turn left to proceed D20 IBA Arc until R256 IBA. Turn left to TILNO IAF.

RWY 24 (ILS/LOC/VOR Z)

Climb on MT 242° until D6 IBA. Turn right to intercept and follow R250 IBA direct to TILNO. Turn right to proceed D20 IBA Arc direct to BEBES.

During LVP

LDG ACFT hold PSN once ILS sensitive area is vacated. Wait for follow-me in order to be guided to stand.

If ATC taxi CLR is issued, continue on assigned route to CLR limit, hold PSN and wait for follow-me.

Arrival Procedure**Low Visibility Procedures**

At APN entry wait for follow-me.

CDA in use: 2200-2300‡ with PPR.

Reverse: Do not use more than idle reverse EXC for safety reasons 2200 - 0500‡.

Delay Information on APCH

ATC will not provide EAT information to ACFT HLDG on APCH, as long as the HLDG time does not exceed 10min.

DEPARTURE**Take-off Minima**

RWY		06/24	
All ACFT	ft - m/km	0 - 350R/350V	-

Communication**COM Failure****During LVP**

Continue by assigned taxi route to CLR limit, hold PSN and wait for follow-me in order to be guided to stand or HLDG bay.

DEPARTURE

Departure Procedure

Start-up/Push-back

When requesting start-up, report stand number and inform if crossbleed start required.

Notify ATC when ACFT wingspan 52m / 171ft or above in first COM.

Report to ATC when ACFT is ready for push-back.

ACFT must be ready for taxiing within 5min after receiving CLR.

Noise Abatement Procedures**RWY 06:**

- Reduce ENG PWR.
- Traffic bound for NW, do not turn left before D8 IBA.

RWY 24:

- Reduce ENG PWR.
- Traffic bound for NW, do not turn right before D8 IBA, from 2200-0500‡.

Departure Notes**RWY 06**

LAMPA 1F: Destination LEPA / LESJ only.

KABRE 1R: Destination LEMH only.

RWY 24

LAMPA 1E: Destination LEPA / LESJ only.

KABRE 1E: Destination LEMH only.

IBZ-LEIB


2-10

Spain Ibiza

AGC
AFC


Ibiza Spain

AGC
AFC



ATIS	119.800	HO
Palma CTL	134.825	
TWR	118.500	HO
GND	121.925	HO
CLR	121.375	Activity announced by ATIS

Landing RWY system:




Spain Ibiza

AGC

Ibiza Spain

AGC



05-OCT-2017

IBZ-LEIB

4-20


RNAV SIDs RWY 24

Spain Ibiza

ID Ibiza Spain

Ibiza Spain

RNAV SIDs RWY 24



05-OCT-2017

IBZ-LEIB

5-10

RNAV SIDs RWY 06

BAVER 2R / CONTINGENCY DEP / EPAMA 1F / INSUB 1F / KABRE 2R / LAMPA 2F / MENORCA 4F / XOSTA 2F
RWY 06 (062°)

	GS	120	150	180	210	240	270
4.6%	ft/MIN	600	700	900	1000	1200	1300
5.5%	ft/MIN	700	900	1100	1200	1400	1600

DESIGNATOR	ROUTING	ALTITUDES
	Runway 06	
BAVER 2R 5.5% to IB500 134.825 ①	IB500 [K250-] - IB510 [K250-] - IB511 [K250-] - IB512 - BAVER	IB500 MNM 2500 Initial climb 4000
CONTINGENCY DEP 4.6% to 3000 134.825 ①	076° - at 3000 turn following ATC instructions	
EPAMA 1F 5.5% to IB500 134.825 ①	IB500 [K250-] - IB501 [K250-] - IB502 [K250-] - EPAMA	IB500 MNM 2500 Initial climb 6000
INSUB 1F 5.5% to IB500 134.825 ①	IB500 [K250-] - IB510 - INSUB	IB500 MNM 2500 Initial climb 4000
KABRE 2R 5.5% to IB500 134.825 ①	IB500 [K250-] - IB520 [K250-] - LAMPA - KABRE	IB500 MNM 2500 Initial climb 6000
LAMPA 2F 5.5% to IB500 134.825 ①	IB500 [K250-] - IB520 [K250-] - LAMPA	IB500 MNM 2500 Initial climb 6000
MENORCA 4F MHN 4F 5.5% to IB500 134.825 ①	IB500 [K250-] - IB520 [K250-] - LAMPA - KABRE - MHN	IB500 MNM 2500 Initial climb 6000
XOSTA 2F 5.5% to IB500 134.825 ①	IB500 [K250-] - IB501 [K250-] - IB502 [K250-] - IB503 - XOSTA	IB500 MNM 2500 Initial climb 6000

① Caution: Close in obstacles: Tree 66ft, Spot 758ft

Changes: Speed RESTR

05-OCT-2017

IBZ-LEIB

5-20

RNAV SIDs RWY 24

BAVER 2E / CONTINGENCY DEP / EPAMA 1E / INSUB 1E / KABRE 2E / LAMPA 2E / MENORCA 4E
RWY 24 (242°)

	GS	120	150	180	210	240	270
4.6%	ft/MIN	600	700	900	1000	1200	1300
6.2%	ft/MIN	800	1000	1200	1400	1600	1700
6.5%	ft/MIN	800	1000	1200	1400	1600	1800

DESIGNATOR	ROUTING	ALTITUDES
	Runway 24	
BAVER 2E 6.2% to IB600 134.825 ①	IB600 [K250-] - IB605 [K250-] - BAVER	IB600 MNM 2100 Initial climb 6000
CONTINGENCY DEP 4.6% to 3000 134.825 ①	at 3000 turn following ATC instructions	
EPAMA 1E 6.2% to 4000 134.825 ①	IB600 [K230-] - IB601 [K230-] - EPAMA	IB600 MNM 2100 IB601 MNM 4000 Initial climb 6000
INSUB 1E 6.5% to IB610 134.825 ①	IB610 [K250-] - IB611 [K250-] - MOLAR - INSUB	IB610 MNM 2200 Initial climb 6000
KABRE 2E 6.5% to IB610 134.825 ①	IB610 [K250-] - IB611 [K250-] - MOLAR - KABRE	IB610 MNM 2200 Initial climb 6000
LAMPA 2E 6.5% to IB610 134.825 ①	IB610 [K250-] - IB611 [K250-] - MOLAR [K250-] - LAMPA	IB610 MNM 2200 Initial climb 6000
MENORCA 4E MHN 4E 6.5% to IB610 134.825 ①	IB610 [K250-] - IB611 [K250-] - MOLAR - KABRE - MHN	IB610 MNM 2200 Initial climb 6000

① Caution: Close in obstacles: Contour line 495ft, Spot 1247ft

Changes: Nil

IBZ-LEIB

5-30

RNAV SIDs RWY 24

XOSTA 2E

RWY 24 (242°)

	GS	120	150	180	210	240	270
6.2%	ft/MIN	800	1000	1200	1400	1600	1700

DESIGNATOR	ROUTING	ALTITUDES
	Runway 24	
XOSTA 2E 6.2% to IB600 134.825 ①	IB600 [K250-] - IB605 [K250-] - XOSTA	IB600 MNM 2100 Initial climb 6000

① Caution: Close in obstacles: Contour line 495ft, Spot 1247ft

Effective 17-AUG-2017

10-AUG-2017

IBZ-LEIB

6-10

RNAV STARs RWY 06

Spain Ibiza


RNAV STARs RWY 24

STAR

Ibiza Spain

RNAV STARs RWY 24

RNAV STARs RWY 06



10-AUG-2017

IBZ-LEIB

Spain Ibiza

7-20


ILS Y 06

IAC

IAC

Ibiza Spain

ILS Y 06



Changes: Nil


10-AUG-2017

BZ-LEIB

7-40

113 Y24

Iulza Spalii



Changes: OBST, TCH

05-0CT-2017


IBZ-LEIB

7-50

Spain Ibiza
LOC 24



IAC

LOC 24
LOC 06




Changes: Ni

Changes: Editorial



7-70

VOR 06




1) BTN 052° and 250° of RWY only

IBZ-LEIB

7-80

VOR 24




Changes: Completely revised

IBZ-LEIB

7-90

NDB 24



IBZ-LEIB

Spain Ibiza

NIL
MRC

Ibiza Spain

MR

8-10

