

GENERAL**Operational Hours****ATS Hours:** H24**AD ADMIN Hours:** SUN-THU 0500-1300**Airport Information****RFF:** CAT 7**PCN:** RWY 16/34: 59/F/A/X/T**Customs:** HO**Operation****Traffic Note**

Uncontrolled AD. 3HR PPR PN for non SKED FLT's.

Traffic Information Broadcast by ACFT (TIBA) must be followed daily 1600-0400, SAT H24.

All ACFT LDG or DEP requested to call TWR for assistance.

ARRIVAL**Communication**

Contact Fire and Rescue Service (FRS) on 133.500 15min before LDG.

Arrival Procedure**Non-standard GP intercept position on RWY 34**


GP intercepts RWY 34 at 320m / 1049ft after landing threshold.

Remaining LDG DIST beyond GP is 2740m / 8990ft.

DEPARTURE**Take-off Minima**

RWY		16/34	
1+2 ENG	ft - m/km	0 - 1.6V	Lower MIN by state permission
≥ 3 ENG		0 - 800V	

Additionally see CRAR.



D-ATIS 128.850
TWR 118.200 0400-1600 except SAT
GND 121.900 0400-1600 except SAT
TIBA 122.800

RWY	TORA	ASDA	TODA
16	3060	3120	3300
34	3060	3120	3360


ARP
N 25 17.2
E 049 29.2

ALAHSA
D 116.6 HSA


TWY A used as emergency RWY

VAR 2° E
MAG UP

AD ELEV 588



ILS DME 34






© Lido 2017

HOF-OEAH

7-20

ILS DME (RNAV) 34



34		Cat 1 DME ¹⁾	LOC DME ¹⁾	LOC DME ¹⁾			Circling ¹⁾
C	ft - m/km ft	200 - 800V 780	370 - 800V 940				920 - 4.4V 1500
D	ft - m/km ft	200 - 800V 780	370 - 1.2V 940	370 - 2.0V 940			920 - 4.8V 1500


1) Use with Al Ahsa (OEAH) QNH only

Changes: FREQ


HOF-OEAH

7-30

VOR DME 16



3.05°	10.6	9	8	7	5	4	16	3.0°	60 HL
D HSA								3060 x 45	
168°									
RWY 163°	3700	3170	2850	2530	1880	1560	HL-S	588 / 21hPa	TDZ ---% -0.1%



16	VOR DME					Circling
	1)					1)
C	ft - m/km ft	500 - 2.0V 1080				920 - 4.4V 1500
D	ft - m/km ft	500 - 2.4V 1080				920 - 4.8V 1500




1) Use with Al Ahsa (OEAH) QNH only

Changes: FREQ

HOF-OEAH

7-40

VOR DME 34



34	VOR DME ¹⁾	VOR DME ¹⁾				Circling ¹⁾
C	ft - m/km ft	450 - 1.2V 1020				920 - 4.4V 1500
D	ft - m/km ft	450 - 1.6V 1020	450 - 2.4V 1020			920 - 4.8V 1500

1) Use with Al Ahsa (OEAH) QNH only

Changes: FREQ