GENERAL

Operational Hours

ATS Hours: H24

AD ADMIN Hours: MON-FRI 0600-1430

Airport Information

RFF: CAT 9
Fuel: 0400-2200, other times O/R
PCN: RWY 05/23: 50/F/A/W/T

Operation

Traffic Note
HA2 IFR training simulation PROC omitted by intention.

TWY Restrictions
All wide body ACFT using TWY M to TWY G must taxi along CL of the TWY.

ACFT to avoid taxiing along the shoulder close to the RWY as ACFT are liable to sink.

TWYs A, B and H centre lights unserviceable, a follow-me will be AVBL for all night flights.

Parking
Stands 4, 5 and 6 have aerobridges with AGNIS.

Noise Abatement Procedure
Avoid built-up areas below 2500ft AGL.

Warnings

MIL OPS continually in force.

Do not overfly the city of Harare below 7000ft during hours of darkness.

Aerial mast height 45m / 148ft AGL erected at 5660m / 18570ft from RWY 23 end in TKOF climb area.

RWY 05/23 edge light are 120m / 394ft between TWYs H and K on both sides of the RWY due to some lights which are unserviceable.

Birds and animals in vicinity of AD.

ARRIVAL

Arrival Procedure

Inbound from N or NW may only leave 7000ft on either left base RWY 05 or CL RWY 23.

DEPARTURE

Take-off Minima

RWY		05/23	
All ACFT	ft - m/km	0 - 400V	HJ only
		0 - 800V	HN

Departure Procedure

Outbound to N or NW have to PROC via NZ NDB after TKOF 23 or maintain RWY track until passing 7500ft after TKOF 05.

Noise Abatement Procedure
TKOF on RWY 05 for left-hand-turnout must attain 2500ft AGL or D10 VHA before commencing turn.



ATIS	113.100	0400-1700
Info	125.100	
CTL	131.500	
APP	119.100	
Mugabe TWR	118.100	
GND	127.300	

Landing RWY system:



Changes: Navaid VHA, AWY, AD Code



Changes: AD Code

HRE-FVRG

7-10

ILS 05



LOC 3.00° D VHA	10.1	9	8	7	6	4
	7000	6650	6330	6010	5690	5050





GS	120	140	160
OL	640	740	850
-MAPt	1:42	1:28	1:17

05		Cat 1 1)	LOC				Circling
C	ft - m/km ft	200 - 1.0 **5000**	250 - 1.0 **5050**				Not published
D	ft - m/km ft	200 - 1.0 **5000**	250 - 1.0 **5050**				Not published

1) With EVS 650m, wo EVS use STD

Changes: Navaid VHA, ROD, Profile, MISAP text, AD Code



3.00° D VHA				7	6	5
				6000	*5690*	*5370*

05 M-S

3.0° 60 L 4725 x 46 420

THR 4793 (161hPa) / TDZ --- (---%) +0.6%



GS	120	140	160
D7 VHA	*640*	*740*	*850*
-D3.4 VHA	*1:48*	*1:33*	*1:21*
-VHA	*3:30*	*3:00*	*2:38*

05		VOR DME	VOR				Circling
C	ft - m/km ft	350 - 1.4 **5140**	540 - 2.2 **5330**				820 - 2.4V **5720**
D	ft - m/km ft	350 - 1.4 **5140**	540 - 2.2 **5330**				820 - 3.6V **5720**

Changes: Navaid VHA, DIST ALT table, ALT, AD Code

HRE-FVRG

7-30

VOR + NDB 05



3.00° D VHA	10.1	9	8	7	6	5
	7000	6650	6330	6010	5690	5370

05 M-S

3.0° 60 L
4725 x 46
420
THR 4793 (161hPa) / TDZ --- (---%) +0.6%



GS	120	140	160
D10.1 VHA	640	740	850
-MAPt	3:06	2:39	2:19

05		VOR NDB					Circling
C	ft - m/km ft	300 - 1.2 **5100**					Not published
D	ft - m/km ft	300 - 1.2 **5100**					Not published

Changes: Navaid VHA, Track, ROD, Editorial, AD Code





-0.6% TDZ --- (---%) / **THR 4887** (164hPa)

23

1	2	3	4	5	6	2.83° D VHA
5490	5800	6100	6400	6710	7000	



GS	120	140	160
D6 VHA	*600*	*700*	*800*
-MAPt	*3:00*	*2:34*	*2:15*

23		VOR DME					Circling
C	ft - m/km ft	480 - 2.2 **5360**					710 - 2.4V **5610**
D	ft - m/km ft	480 - 2.2 **5360**					710 - 3.6V **5610**

Changes: Navaid VHA, Track, MISAP text, AD Code

HRE-FVRG

7-50

NDB + NDB 05 / NDB 05







GS	120	140	160
D7.4 VHA	*640*	*740*	*850*
D3.9 VHA	*1:43*	*1:28*	*1:17*
D3.4 VHA	*2:00*	*1:43*	*1:30*

05		NDB NDB	NDB OL				Circling
C	ft - m/km ft	350 - 1.4 **5150**	540 - 2.2 **5330**				820 - 2.4V **5720**
D	ft - m/km ft	350 - 1.4 **5150**	540 - 2.2 **5330**				820 - 3.6V **5720**

Changes: Navaid VHA, Profile, MISAP text, AD Name



3.00° RW05					3.6	3
					6000	5810

05 — 3.0° — 60 L — 4725 x 46 — 420 — M-S — THR 4793 (161hPa) / TDZ --- (---%) — +0.6%



GS	120	140	160
D7 VHA -MAPt	*1:31*	*1:18*	*1:09*

05		NDB SI					Circling
C	ft - m/km ft	820 - 2.4 **5610**					820 - 2.4V **5720**
D	ft - m/km ft	820 - 3.6 **5610**					820 - 3.6V **5720**

Changes: Navaid VHA, MSA, Profile, MISAP text, AD Code