

15-FEB-2018

KCM-LTCN

1-10

AOI

AOI

GENERAL**Operational Hours****ATS Hours / AD ADMIN Hours:** See NOTAM**Airport Information****RFF:** CAT A7**PCN:** RWY 07/25: first 400m / 1312ft 105/R/C/W/T, rest of RWY 81/F/C/X/T**Customs:** Not published**Warnings****KHM NDB** unusable: 310°-070° beyond 4NM.**KHM VOR/DME** unusable: R310-070 beyond 4NM below 16000ft.

Vehicles on the road which is located 600m / 1970ft east of THR RWY 25 and within RWY 25 climbing line constitute moving obstacles.

Road traffic signalization lights which installed 200m-250m / 656ft-820ft away from APCH lights and located on the extension of THR RWY 25 APCH lights, can be confused with APCH lights.

Birds in vicinity of AD.

ARRIVAL**Speed**

MAX IAS 250KT within TMA at or below FL100 (refer to RFCs)

DEPARTURE**Take-off Minima**

RWY		07/25	
All ACFT	ft - m/km	0 - 400V	-

Speed

MAX IAS 250KT within TMA at or below FL100 (refer to RFCs)

ATC Slot, Clearance**Start-up:** For start-up PROCs see CRAR.**De-Icing**

See NOTAM

Effective 29-MAR-2018

22-MAR-2018

KCM-LTCN


Turkey Kahramanmaraş

AGC
AFC

Kahramanmaraş Turkey

AGC
AFC

2-10



Changes: APL, OBST, SUAs

Effective 29-MAR-2018

22-MAR-2018

KCM-LTCN

Turkey Kahramanmaraş

3-20

AGC

AGC


Kahramanmaraş Turkey

AGC

E036°57'

E036°58'

TWR 118.750
120.600
GND 121.550




RWY	TORA	ASDA	TODA
07	2300	2300	2450
25	2300	2300	2450

KAHRAMANMARAŞ
D 113.9 KHM 374

ARP
N 37 32.3
E 036 57.1

2300 x 45



COORDINATES
1, 2 N37 32.4 E036 58.0

07
071°
1618

ENGINE TEST
AREA

N37°32'
VAR 4° E
MAG UP
AD ELEV 1724

m 0 250 500
ft 0 500 1000 1500

Changes: Nil

15-MAR-2018

KCM-LTCN

Turkey Kahramanmaraş

RNAV SID RWY 25

4-10

RNAV SID RWY 07


SID

SID

Kahramanmaraş Turkey

RNAV SID RWY 25

RNAV SID RWY 07



15-MAR-2018

KCM-LTCN

Turkey Kahramanmaraş

4-20


RNAV SID RWY 25

SID

SID

Kahramanmaraş Turkey

RNAV SID RWY 25



REMP0 1R

RWY 07 (071°)

	GS	120	150	180	210	240	270
5.0%	ft/MIN	700	800	1000	1100	1300	1400

DESIGNATOR	ROUTING	ALTITUDES
	Runway 07	
REMP0 1R 5.0% to 6000 118.750 120.600	077° to DIKRU - RT 088° to ELKUM - RT 118° to BERET (MAX 270KT) - RT 208° to NARGU - RT 280° to INGAM - POPEN - RT 308° to REMPO - join the AWY FMS DIKRU [M077 ;R] - ELKUM [R] - BERET [K270- ;R] - NARGU [R] - INGAM - POPEN [R] - REMPO	ELKUM MNM 6000 NARGU MNM 9000 INGAM MNM 12000 ELKUM MNM 6000 NARGU MNM 9000 INGAM MNM 12000

REMP0 1A

RWY 25 (251°)

	GS	120	150	180	210	240	270
5.5%	ft/MIN	700	900	1100	1200	1400	1600

DESIGNATOR	ROUTING	ALTITUDES
	Runway 25	
REMP0 1A 5.5% to 11000	265° to CN101 (MAX 220KT) - RT direct REMPO FMS CN101 [M265 ;K220- ;R] - REMPO	

15-MAR-2018

KCM-LTCN

Turkey Kahramanmaraş

[RNAV STAR RWY 25]

6-10

RNAV STAR RWY 07


STAR

STAR

Kahramanmaraş Turkey

[RNAV STAR RWY 25]

RNAV STAR RWY 07



15-MAR-2018

KCM-LTCN

Turkey Kahramanmaraş

6-20


RNAV STAR RWY 25

STAR

STAR

Kahramanmaraş Turkey

RNAV STAR RWY 25



15-MAR-2018

KCM-LTCN


Turkey Kahramanmaraş

STARS

Kahramanmaraş Turkey

The logo consists of the word "NIL" in a white box with a black border, followed by the word "STARS" in a large, bold, black sans-serif font.

6-30



Effective 29-MAR-2018
22-MAR-2018

KCM-LTCN

Turkey Kahramanmaraş

RNAV (GNSS) 25

7-10

RNAV (GNSS) 07


IAC

IAC


Kahramanmaraş Turkey

RNAV (GNSS) 25

RNAV (GNSS) 07



07		RNAV GNSS LNAV GA 4.5%	RNAV GNSS LNAV GA 2.5%					Circling S of AD only
C	ft - m/km ft	610 - 2.8 2220	1190 - 5.0 2800					1680 - 5.0V 3400
D	ft - m/km ft	610 - 2.8 2220	1190 - 5.0 2800					1680 - 5.0V 3400



Changes: OBST, SUAs

Effective 29-MAR-2018

22-MAR-2018

KCM-LTCN


Turkey Kahramanmaraş

7-20

RNAV (GNSS) 25

Kahramanmaraş Turkey

RNAV (GNSS) 25



Effective 29-MAR-2018

22-MAR-2018


KCM-LTCN

7-30

Turkey Kahramanmaraş

VOR DME / NDB + DME

14



Changes: APL, OBST, SUAs

Effective 29-MAR-2018

22-MAR-2018


Turkey Kahramanmaraş

KCM-LTCN


7-40

VOR / NDB

IAC



07	83.0°	60 HL	60 HL	45 x 2000	300	720	25
HL-NF	THR 1618 (58hPa) / TDZ --- (---%)	+1.2%	-1.2%	TDZ --- (---%) / THR 1710 (61hPa)	HL-SF		



07/25		VOR	NDB	Circling S of AD only		
C	ft - m/km ft	Straight-in Not authorized	Straight-in Not authorized			1680 - 2.4V 3400
D	ft - m/km ft	Straight-in Not authorized	Straight-in Not authorized			1680 - 3.6V 3400

Changes: APL, OBST, SUAs