

**GENERAL****Operational Hours****ATS Hours:** See NOTAM**AD Operator Hours:** HO**Airport Information****RFF:** CAT 5, CAT 7 AVBL; NON SKED required CAT O/R**Fuel:** O/R**PCN:** RWY 12/30: 60/F/A/W/T**Customs:** HO 4HRs PN**Operation****Low Visibility Procedure**

OPS limited to one ACFT at the time on manoeuvring area when VIS below 550m-400m.

**RWY Restriction**

Turn pad AVBL on THR RWY 30 only.

**ARRIVAL****Communication****COM Failure****RNAV**

Follow STAR to the respective RWY and execute IAP and land.

**DEPARTURE****Take-off Minima**

RWY		30	
All ACFT	ft - m/km	0 - 400R/400V	-
RWY		12	
All ACFT	ft - m/km	0 - 400R/400V	MNM climb gradient 3.8% up to 1070

**Departure Procedure****Noise Abatement Procedure:** Turn right after TKOF RWY 12.**De-icing**

O/R

Effective 26-APR-2018

19-APR-2018

KAO-EFKS

2-10

Finland Kuusamo

AGC

AFC

AFC

AFC

Kuusamo Finland


AGC

AFC



D-ATIS 135.800  
TWR/AFIS 118.650 HR by NOTAM  
119.700 HR by NOTAM

Landing RWY system:



Changes: PROC, WPT ABURO added, MGA, SUAs, Editorial, FIR

Effective 26-APR-2018

19-APR-2018

KAO-EFKS

Finland Kuusamo

AGC


AGC

AGC

Kuusamo Finland

AGC

3-20



Changes: Nil

## DEPARTURES

	GS	120	150	180	210	240	270
3.8%	ft/MIN	500	600	700	900	1000	1100

RWY	Routing
OMNIDIRECTIONAL DEP	<b>RWY 12</b> 3.8% to 1070 RWY HDG - climb until MNM turning ALT <b>1360</b>
	<b>RWY 30</b> RWY HDG - climb until MNM turning ALT <b>1350</b>

RWY	Notes
12	Close-in obstacles exist.
30	1. Close-in obstacles exist. 2. Published close-in obstacles not considered in climb gradient.

Effective 26-APR-2018

19-APR-2018

KAO-EFKS

6-10

Finland Kuusamo

NIL

RNAV STARs


STAR

STAR

Kuusamo Finland

NIL

RNAV STARs





Changes: PROC, chart layout, WPT ABURO, OBST, Note, SUAs

## KAO-EFKS

7-10


ILS or LOC 12



12	Cat 1 DME <sup>1)</sup>	LOC DME				Circling
C	ft - m/km ft	200 - 550 1070	410 - 1.2 1270			960 - 2.4V 1820
D	ft - m/km ft	200 - 550 1070	410 - 1.2 1270			970 - 3.6V 1830

1) FD, AP or HGS required, else RVR 750m




Changes: ALT, MIN, OBST, SUAs



© Lido 2017

7-40

RNAV (GNSS) 30



30		RNAV GNSS VNAV 1) 2)	RNAV GNSS LNAV				Circling
C	ft - m/km ft	420 - 1.2 1280	480 - 1.5 1340				960 - 2.4V 1820
D	ft - m/km ft	420 - 1.2 1280	480 - 1.5 1340				970 - 3.6V 1830

1) Uncompensated BARO VNAV NA below -20°C (-4°F)

2) With EVS 800m

Changes: MIN