


Transit Networking

Solutions Engineering


MCNA Deployment: the Foundations






CLOUD ASSETS

- On the CoPilot you can create a new VPC/VNet/VCN.
- This feature is not only useful in a Greenfield deployment, but also if you need to add a new VPC/VNet/VCN on an existing environment, based on the architecture design.





Caveat: for the sake of simplicity, only the deployment in AWS is explained

CIDR 10.11.0.0/23




Creation of the Transit VPC

- The VPC CIDR range for a Transit VPC is from /16 to /23
- There is a specific reason why the Aviatrix Controller does not allow less than /23 prefix length for the Transit VPC (this will be discussed on the HPE lecture).



An IGW with the same name of the Transit VPC will be created and attached to the VPC, automatically



CIDR 10.11.0.0/23




The subnets' size can be customized




Creation of the Transit VPC

- The Aviatrix Controller will create 8 subnets, in two availability zones:
 - 4x Private subnets for the FW
 - 2x Public subnets for Ingress-Egress
 - 2x Public subnets for GW-FW-mgmt.
- All the subnets will have a /28 prefix length




CIDR 10.11.0.0/23





Creation of the Transit VPC

- 2x Routing Tables will be created:
 - Public RTB will encompass the 4 public subnets



Private RTB will encompass the 4 private subnets








CIDR 10.1.1.0/24




Creation of the Application/Spoke VPC

- The VPC CIDR range for a Spoke VPC is from /16 to /24
- An IGW with the same name of the Spoke VPC will be created and attached to the VPC, automatically






CIDR 10.1.1.0/24



Creation of the Application/Spoke VPC

- The Aviatrix Controller will create a pair of subnets, a public subnet and a private subnet, on each availability zone
- All the subnets will have a /28 prefix length




<u>Aviatrix Spoke VPC – Aviatrix Official Documentation</u>

CIDR 10.1.1.0/24





Creation of the Application/Spoke VPC

a Public RTB per each availability zone will encompass the corresponding subnet




 a Private RTB per each availability zone will encompass the corresponding subnet






Name Convention with Multiple Gateways

Cluster of Gateways




- If you create two or more Gateways, they will be encompassed inside a cluster.
- The name of the cluster will match the name of the first gateway.
- The second gateway will have the string "-1" appended to its name.
- The third gateway will have the string "-2" appended to its name.
 - •
 - •
- The sixteenth gateway will have the string "-14" appended to its name.




Greenfield Deployment (Transit Gateways deployment)

CIDR 10.11.0.0/23




- * The connection between the Transit Gateways is automatically created by the Controller.
- Best Practice: always deploy the Transit Gateway-1 (i.e the second gateway), and choose a different AZ.
- Only two Transit Gateways can be deployed per Transit VPC
- Aviatrix gateways are deployed in Public subnets

Transit Gateways Deployment through the CoPilot




Greenfield Deployment (Spoke Gateways deployment)

CIDR 10.1.1.0/24




- The connection between the Spoke Gateways is automatically created by the Controller.
- Best Practice: deploy the Spoke Gateway-1 (i.e the second gateway) on a different AZ.
- You can deploy up to 15 Spoke Gateways per each Spoke VPC
- Aviatrix gateways are deployed in Public subnets


Spoke Gateways Deployment through the CoPilot



Greenfield Deployment (Attachment deployment)




Deployment of the attachments through the CoPilot




Greenfield Deployment (Attachment deployment)


As soon as the Controller completes the deployment of the **attachments** between Spoke Gateways and Transit Gateways, it will also program the *three RFC1918 routes* in the route tables to point to the ENI of the Spoke Gateways.




■ Attachment = RFC1918 Routes Injection



Greenfield Deployment (Repeatable Design)






- The hub and spoke topology can be extended to another CSP or to another region within the same CSP
- In Azure all subnets are public by nature
- Aviatrix Controller creates "Private" subnets:
 - Aviatrix Controller programs a default route 0.0.0.0 pointing to the next hop type "None": in User Defined Route Table (UDR) for all private subnets it creates
 - > This will blackhole 0/0 traffic




Greenfield Deployment (Peering deployment)



The creation of the Transit Peering represents the last step for the completion of the MCNA.


	ransit Gateway: AVX-FR	ANKFUR	T-TRANSIT					
Name								
AVX-FR	RANKFURT-TRANSIT							
Cloud								
AWS								
Account			Region			VPC/VNet		
AWS-A	VIATRIX	*	eu-central-1		~	AVX-FRANKFURT-TRANSIT		
nstance S	Size		High Performance Encryption	en .				
c5n.lar	THE STATE OF THE S	× ×	O Off					
AZUKE	-WESTEUROPE-TRANSIT ×						Option	iai ×
nstanc	es							
+ Inst								
				Public IP				
	tance		v	Public IP 3.75.164.186			v	
+ Inst	Attach to Subnet		•				•	Ô






Advanced Transit Networking

AWS to on-Prem via ExpressRoute or vice versa



Single DX or ER can be used to communicate between On-Prem and multiple CSP resources






Initial environment in a brownfield scenario:

- Several Application VPCs that are connected to the TGW as attachments
- OnPrem connectivity (hybrid can be DX/IPSec)









- Initial environment in a brownfield scenario:
 - Several Application VPCs that are connected to the TGW as attachments
 - OnPrem connectivity (hybrid can be DX/IPSec)
- Deploy the Aviatrix Controller and CoPilot in a dedicated VPC, in a different AZ where there are no gateways deployed (best practice)






- Initial environment in a brownfield scenario:
 - Several Application VPCs that are connected to the TGW as attachments
 - OnPrem connectivity (hybrid can be DX/IPSec)
- Deploy the Aviatrix Controller and CoPilot in a dedicated VPC, in a different AZ where there are no gateways deployed (best practice)
- Deploy a Transit VPC and deploy a pair of Transit Gateways






- Initial environment in a brownfield scenario:
 - Several Application VPCs that are connected to the TGW as attachments
 - OnPrem connectivity (hybrid can be DX/IPSec)
- Deploy the Aviatrix Controller and CoPilot in a dedicated VPC, in a different AZ where there are no gateways deployed (best practice)
- Deploy a Transit VPC and deploy a pair of Transit Gateways
- Establish a back-to-back connection between the Transit Gateways and the TGW






- Initial environment in a brownfield scenario:
 - Several Application VPCs that are connected to the TGW as attachments
 - OnPrem connectivity (hybrid can be DX/IPSec)
- Deploy the Aviatrix Controller and CoPilot in a dedicated VPC, in a different AZ where there are no gateways deployed (best practice)
- Deploy a Transit VPC and deploy a pair of Transit Gateways
- Establish a back-to-back connection between the Transit Gateways and the TGW
- Deploy the Spoke Gateways inside the Application
 VPCs (this action will not change any routing)





- Initial environment in a brownfield scenario:
 - Several Application VPCs that are connected to the TGW as attachments
 - OnPrem connectivity (hybrid can be DX/IPSec)
- Deploy the Aviatrix Controller and CoPilot in a dedicated
 VPC, in a different AZ where there are no gateways
 deployed (best practice)
- Deploy a Transit VPC and deploy a pair of Transit Gateways
- Establish a back-to-back connection between the Transit Gateways and the TGW
- Deploy the Spoke Gateways inside the Application VPCs (this action will not change any routing)
- Remove the connections between the VPCs and the TGW and deploy the attachments between the Spoke Gateways and the Transit Gateways






- Initial environment in a brownfield scenario:
 - Several Application VPCs that are connected to the TGW as attachments
 - OnPrem connectivity (hybrid can be DX/IPSec)
- Deploy the Aviatrix Controller and CoPilot in a dedicated VPC, in a different AZ where there are no gateways deployed (best practice)
- Deploy a Transit VPC and deploy a pair of Transit Gateways
- Establish a back-to-back connection between the Transit Gateways and the TGW
- Deploy the Spoke Gateways inside the Application
 VPCs (this action will not change any routing)
- Remove the connections between the VPCs and the TGW and deploy the attachments between the Spoke Gateways and the Transit Gateways
- Deploy an Aviatrix Edge and then connect the Edge to the Transit Gateways. If you are not looking for HPE, you can also connect the WAN router as an IPSec connectivity to the Transit Gateways. Last but not least, remove the TGW.



Multi-Tier Transit (MTT)

- Improves operational simplicity by aggregating multiple Aviatrix Transits (no need for full mesh between transits)
- Additional failover option (pictured in the diagram)
- Allows for centralized firewall design for multiple Aviatrix-Transits in a single region, which allows intra-cloud traffic without any inspection
- To configure Multi-Tier Transit, go to Multi-cloud Transit -> Advanced Config. Select the Transit Gateway and enable the Multi-Tier Transit feature







Next: Lab 2 – (MCNA) Transit Networking