




# Transit Networking

ACE Technical Team


# MCNA Deployment: the Foundations



# Create VPC/VNet

## ☐ CLOUD ASSETS

- On the CoPilot you can create a new VPC/VNet/VCN.
- This feature is not only useful in a Greenfield deployment, but also if you need to add a new VPC/VNet/VCN on an existing environment, based on the architecture design.
- You can create two types of VPC/VnNet/VCN:
  - **Default** (i.e. Spoke)
  - **Transit + FireNet**




Create VPC/VNet

Name


AVX-FRANKFURT-TRANSIT

Cloud




Standard


AWS




Azure



GCP



OCI



Alibaba

Account

aws-account

Region

eu-central-1 (Frankfurt)

VPC CIDR

10.11.0.0/23

VPC Function

Transit + FireNet

Default

Transit + FireNet

Advanced Settings

Cancel

Save

# Cloud Assets: Managed VPC vs. Unmanaged VPC

- CoPilot shows VPC/VNets that were created in the CSP environment as well as those that were created as part of deploying Aviatrix resources such as those created during the deployment of your Controller, CoPilot, and gateways.
- A VPC/VNet can be marked as Aviatrix managed where:
  - **Aviatrix Managed = Yes** — Indicates an Aviatrix gateway is running in the VPC/VNet.
  - **Aviatrix Managed = No** — Indicates no Aviatrix gateways exist in the VPC/VNet.

Cloud Assets							
Virtual Machines							
VPC/VNets & Subnets							
<a href="#">+ VPC/VNet</a> <a href="#">Actions</a> <a href="#">Filter</a> <a href="#">Grid</a> <a href="#">Download</a> <a href="#">Search</a>							
<input type="checkbox"/> Name	Cloud	Region	IP Address CIDR	CSP Tags	SmartGroups	Aviatrix Managed	
<input type="checkbox"/> azure-west-us-spoke2	Azure ARM	westus	192.168.2.0/24	Aviatrix-Created-Resource: ..., <a href="#">+ 1 more</a>		Yes	
<input type="checkbox"/> gcp-us-central1-transit	GCP					Yes	
<input type="checkbox"/> gcp-us-central1-spoke1	GCP					Yes	
<input type="checkbox"/> aws-us-east-1-spoke1	AWS	us-east-1	10.0.12.0/24	Name: aws-us-east-1-spoke1, <a href="#">+ 1 more</a>		Yes	
<input type="checkbox"/> aws-us-east-2-spoke1	AWS	us-east-2	10.0.1.0/24	Name: aws-us-east-2-spoke1, <a href="#">+ 1 more</a>		Yes	
<input type="checkbox"/> azure-west-us-transit	Azure ARM	westus	192.168.10.0/23	Aviatrix-Created-Resource: ..., <a href="#">+ 1 more</a>		Yes	
<input type="checkbox"/> azure-west-us-spoke1	Azure ARM	westus	192.168.1.0/24	Aviatrix-Created-Resource: ..., <a href="#">+ 1 more</a>		Yes	
<input type="checkbox"/> aws-us-east-2-transit	AWS	us-east-2	10.0.10.0/23	Aviatrix-Created-Resource: ..., <a href="#">+ 1 more</a>		Yes	
<input type="checkbox"/> aws-us-east-1-transit	AWS	us-east-1	10.0.20.0/23	Name: aws-us-east-1-transit, <a href="#">+ 1 more</a>		Yes	
<input type="checkbox"/> vpc-574bab31	AWS	ap-southeast-1	172.31.0.0/16			No	
<input type="checkbox"/> vpc-3bf48952	AWS	ap-northeast-3	172.31.0.0/16			No	
<input type="checkbox"/> on-prem-partner1	AWS	us-east-1	172.16.1.0/24	Terraform: true, <a href="#">+ 2 more</a>		No	
<input type="checkbox"/> vpc-390a155e	AWS	sa-east-1	172.31.0.0/16			No	
<input type="checkbox"/> default	GCP					No	
<input type="checkbox"/> AviatrixVPC	AWS	us-east-1	172.16.0.0/16	aws:cloudformation:stack:..., <a href="#">+ 4 more</a>		No	

**Note:** If you create a VPC/Vnet by using cloud provider tools instead of Aviatrix tools (i.e. CoPilot UI), the VPC/Vnet will be marked as unmanaged even if an Aviatrix gateway is running in it

# Cloud Assets: Viewing virtual machines running in your Clouds

- CoPilot shows in a central location all the virtual machines running in your clouds for cloud accounts onboarded onto Aviatrix Controller.
- A VM can be marked as *Aviatrix managed* where:
  - **Aviatrix Managed = Yes** — Indicates the VM is behind an Aviatrix Gateway; that is running in a VPC/VNet where an Aviatrix gateway is deployed.
  - **Aviatrix Managed = No** — Indicates the VM is running in a VPC/VNet where no Aviatrix gateways exist.
  - **Aviatrix Managed = Gateways** — Indicates the VM is running an Aviatrix Gateway (Transit, Spoke, or Specialty/Other)

Cloud Assets							
Virtual Machines							
VPC/VNets & Subnets							
Actions							
Search							
<input type="checkbox"/>	Name	Cloud	Region	IP Address	Tags	SmartGroups	Aviatrix Managed
<input type="checkbox"/>	aviatrix-aws-us-east-1-transit	AWS	us-east-1	10.0.21.138, + 10 more	Controller: 54.161.179.60, HA: False, + 3 more		Gateways
<input type="checkbox"/>	aviatrix-aws-us-east-1-transit-hagw	AWS	us-east-1	10.0.21.196, + 1 more	Name: aviatrix-aws-us-east-1-transit-h..., + 4 more		Gateways
<input type="checkbox"/>	aviatrix-aws-us-east-1-spoke1-hagw	AWS	us-east-1	10.0.12.235, + 1 more	Aviatrix-Created-Resource: Do-Not-Del..., + 4 more		Gateways
<input type="checkbox"/>	aviatrix-aws-us-east-1-spoke1	AWS	us-east-1	10.0.12.135, + 10 more	Aviatrix-Created-Resource: Do-Not-Del..., + 4 more		Gateways
<input type="checkbox"/>	gcp-us-central1-transit	GCP	us-central1	172.16.10.2, + 1 more			Gateways
<input type="checkbox"/>	gcp-us-central1-transit-hagw	GCP	us-central1	172.16.10.3, + 1 more			Gateways
<input type="checkbox"/>	av-gw-azure-west-us-spoke2	Azure ARM	westus	104.40.57.73, + 1 more	Aviatrix-Created-Resource: Do-Not-Del..., + 3 more		Gateways
<input type="checkbox"/>	av-gw-azure-west-us-transit	Azure ARM	westus	192.168.10..., + 3 more	Type: gateway, Controller: 54.161.179.60, + 2 more		Gateways
<input type="checkbox"/>	av-gw-azure-west-us-transit-hagw	Azure ARM	westus	192.168.10..., + 3 more	Name: Aviatrix-av-gw-azure-west-us-tr..., + 3 more		Gateways
<input type="checkbox"/>	aws-us-east-1-spoke1-test2	AWS	us-east-1	10.0.12.60, + 1 more	Name: aws-us-east-1-spoke1-test2		Yes
<input type="checkbox"/>	aws-us-east-1-spoke1-test1	AWS	us-east-1	10.0.12.40, + 1 more	Name: aws-us-east-1-spoke1-test1		Yes
<input type="checkbox"/>	azure-west-us-spoke2-test1	Azure ARM	westus	104.40.65..., + 1 more	environment: bu2		Yes
<input type="checkbox"/>	aws-us-east-2-spoke1-test2	AWS	us-east-2	10.0.1.10	Name: aws-us-east-2-spoke1-test2, + 1 more		No
<input type="checkbox"/>	aws-us-east-2-spoke1-test1	AWS	us-east-2	10.0.1.100, + 1 more	Name: aws-us-east-2-spoke1-test1, + 1 more		No
<input type="checkbox"/>	AviatrixCoPilot	AWS	us-east-1	172.16.1.5, + 1 more	aws:cloudformation:stack-id: am:aws:..., + 4 more		No
<input type="checkbox"/>	AviatrixController	AWS	us-east-1	172.16.1.213, + 1 more	Name: AviatrixController, + 4 more		No
<input type="checkbox"/>	aws-cisco-csr	AWS	us-east-1	172.16.1.65, + 1 more	Name: aws-cisco-csr		No
<input type="checkbox"/>	gcp-us-central1-spoke1-test1	GCP	us-central1	172.16.1.100, + 1 more	environment: bu2		No

# Greenfield Deployment (VPC/VNet/VCN creation)

Caveat: for the sake of simplicity, only the deployment in AWS is explained

## Creation of the Transit VPC

CIDR 10.11.0.0/23



- The VPC CIDR range for a Transit VPC is from /16 to /23
- There is a specific reason why the Aviatrix Controller does not allow less than /23 prefix length for the Transit VPC (this will be discussed on the **HPE** lecture).



[AVXERR-TOOLS-0030] VPC/VNet CIDR size must be between 16 to 23. e.g. 10.0.0.0/20

- An IGW with the same name of the Transit VPC will be created and attached to the VPC, automatically

### Internet gateways (1/1) [Info](#)

Filter internet gateways

search: AVX-FRANKFURT-TRANSIT

Clear filters

<input checked="" type="checkbox"/>	Name	Internet gateway ID	State	VPC ID
<input checked="" type="checkbox"/>	AVX-FRANKFURT-TRANSIT	lgw-06d499f4d0f772915	Attached	vpc-01f51fa31db0c8458   AVX-FRANKFURT-TRANSIT

# Greenfield Deployment (VPC/VNet/VCN creation)


CIDR 10.11.0.0/23



## Creation of the Transit VPC

- The Aviatrix Controller will create 8 subnets, in two availability zones:
  - 4x Private subnets for the FW
  - 2x Public subnets for Ingress-Egress
  - 2x Public subnets for GW-FW-mgmt.
- All the subnets will have a /28 prefix length

## ❖ The subnets' size can be customized



**Subnets (8)** Info

Filter subnets

search: AVX-FRANKFURT-TRANSIT X Clear filters

<input type="checkbox"/>	Name	Subnet ID	IPv4 CIDR	Availability Zone
<input type="checkbox"/>	AVX-FRANKFURT-TRANSIT-Private-FW-north-eu-central-1a	subnet-04d1f3362661ae02a	10.11.0.16/28	eu-central-1a
<input type="checkbox"/>	AVX-FRANKFURT-TRANSIT-Private-FW-north-eu-central-1b	subnet-0a35db8130d9f9031	10.11.0.48/28	eu-central-1b
<input type="checkbox"/>	AVX-FRANKFURT-TRANSIT-Private-FW-south-eu-central-1a	subnet-06f4b955d965f1457	10.11.0.0/28	eu-central-1a
<input type="checkbox"/>	AVX-FRANKFURT-TRANSIT-Private-FW-south-eu-central-1b	subnet-0560c62d12c3ff59b	10.11.0.32/28	eu-central-1b
<input type="checkbox"/>	AVX-FRANKFURT-TRANSIT-Public-FW-ingress-egress-eu-central-1a	subnet-07818dd7b731a32a2	10.11.0.80/28	eu-central-1a
<input type="checkbox"/>	AVX-FRANKFURT-TRANSIT-Public-FW-ingress-egress-eu-central-1b	subnet-04094cc05bcd736a3	10.11.0.112/28	eu-central-1b
<input type="checkbox"/>	AVX-FRANKFURT-TRANSIT-Public-gateway-and-firewall-mgmt-e...	subnet-08228163bc8ca6f7d	10.11.0.64/28	eu-central-1a
<input type="checkbox"/>	AVX-FRANKFURT-TRANSIT-Public-gateway-and-firewall-mgmt-e...	subnet-002f879d78f686a57	10.11.0.96/28	eu-central-1b

[Aviatrix Transit VPC – Aviatrix Official Documentation](#)

# Greenfield Deployment (VPC/VNet/VCN creation)



CIDR 10.11.0.0/23



## Creation of the Transit VPC

- 2x Routing Tables will be created:
  - Public RTB will encompass the 4 public subnets
  - Private RTB will encompass the 4 private subnets

Destination	Target
0.0.0.0/0	<a href="#">lgw-06d499f4d0f772915</a>
10.11.0.0/23	local

Destination	Target
10.11.0.0/23	local

### Route tables (2) [Info](#)

Filter route tables

search: AVX-FRANKFURT-TRANSIT X

Clear filters

<input type="checkbox"/>	Name	Route table ID	Explicit subnet associations
<input type="checkbox"/>	AVX-FRANKFURT-TRANSIT-Public-rtb	<a href="#">rtb-0e5a22d0060c17eac</a>	<a href="#">4 subnets</a>
<input type="checkbox"/>	AVX-FRANKFURT-TRANSIT-Private-rtb	<a href="#">rtb-085cf49590ee4592d</a>	<a href="#">4 subnets</a>



# Greenfield Deployment (VPC/VNet/VCN creation)

CIDR 10.1.1.0/24

## Creation of the Application/Spoke VPC

- The VPC CIDR range for a Spoke VPC is from /16 to /24
- An IGW with the same name of the Spoke VPC will be created and attached to the VPC, automatically



Internet gateways (1/1) [Info](#)

Filter Internet gateways

search: AVX-FRANKFURT-SPOKE-PROD X Clear filters


<input checked="" type="checkbox"/>	Name	Internet gateway ID	State	VPC ID
<input checked="" type="checkbox"/>	AVX-FRANKFURT-SPOKE-PROD	lgw-0327c092c11fbd749	Attached	vpc-068d94ca168a85633   AVX-FRANKFURT-SPOKE-PROD

# Greenfield Deployment (VPC/VNet/VCN creation)

CIDR 10.1.1.0/24



❖ The subnets' size can be customized



## ❑ Creation of the Application/Spoke VPC

- The Aviatrix Controller will create a pair of subnets, a public subnet and a private subnet, on each availability zone
- All the subnets will have a /28 prefix length

Subnets (6) [Info](#)

Filter subnets

search: AVX-FRANKFURT-SPOKE-PROD X Clear filters

<input type="checkbox"/>	Name ▲	Subnet ID ▼	VPC ▼	IPv4 CIDR
<input type="checkbox"/>	AVX-FRANKFURT-SPOKE-PROD-Private-1-eu-central-1a	subnet-060df41c64a2c643a	vpc-068d94ca168a85633   AV...	10.1.1.0/28
<input type="checkbox"/>	AVX-FRANKFURT-SPOKE-PROD-Private-2-eu-central-1b	subnet-00bf95727955ec09b	vpc-068d94ca168a85633   AV...	10.1.1.16/28
<input type="checkbox"/>	AVX-FRANKFURT-SPOKE-PROD-Private-3-eu-central-1c	subnet-0bd05503b4b1f880c	vpc-068d94ca168a85633   AV...	10.1.1.32/28
<input type="checkbox"/>	AVX-FRANKFURT-SPOKE-PROD-Public-1-eu-central-1a	subnet-0b22457ff5b1a4895	vpc-068d94ca168a85633   AV...	10.1.1.48/28
<input type="checkbox"/>	AVX-FRANKFURT-SPOKE-PROD-Public-2-eu-central-1b	subnet-0c140dc3d0af1fa65	vpc-068d94ca168a85633   AV...	10.1.1.64/28
<input type="checkbox"/>	AVX-FRANKFURT-SPOKE-PROD-Public-3-eu-central-1c	subnet-06219ac03978942e3	vpc-068d94ca168a85633   AV...	10.1.1.80/28

# Greenfield Deployment (VPC/VNet/VCN creation)



CIDR 10.1.1.0/24



## Creation of the Application/Spoke VPC

- a Public RTB per each availability zone will encompass the corresponding subnet

Destination	Target
0.0.0.0/0	lgw-0327c092c11fbd749
10.1.1.0/24	local

- a Private RTB per each availability zone will encompass the corresponding subnet

Destination	Target
10.1.1.0/24	local


Route tables (6) [info](#)

search: AVX-FRANKFURT-SPOKE-PROD

<input type="checkbox"/>	Name	Route table ID	Explicit subnet associations
<input type="checkbox"/>	AVX-FRANKFURT-SPOKE-PROD-Private-1-eu-central-1a-rtb	rtb-0ca98234a5088dceb	subnet-060df41c64a2c643a / AVX-FRANKFURT-SPOKE-PROD-Private-1-eu-central-1a
<input type="checkbox"/>	AVX-FRANKFURT-SPOKE-PROD-Private-2-eu-central-1b-rtb	rtb-0cad721a70d6256d9	subnet-00bf95727955ec09b / AVX-FRANKFURT-SPOKE-PROD-Private-2-eu-central-1b
<input type="checkbox"/>	AVX-FRANKFURT-SPOKE-PROD-Private-3-eu-central-1c-rtb	rtb-04afaa976264662ac	subnet-0bd05503b4b1f880c / AVX-FRANKFURT-SPOKE-PROD-Private-3-eu-central-1c
<input type="checkbox"/>	AVX-FRANKFURT-SPOKE-PROD-Public-1-eu-central-1a-rtb	rtb-0c52cd5084b440f2d	subnet-0b22457ff5b1a4895 / AVX-FRANKFURT-SPOKE-PROD-Public-1-eu-central-1a
<input type="checkbox"/>	AVX-FRANKFURT-SPOKE-PROD-Public-2-eu-central-1b-rtb	rtb-0c973dec3847ae8ce	subnet-0c140dc3d0af1fa65 / AVX-FRANKFURT-SPOKE-PROD-Public-2-eu-central-1b
<input type="checkbox"/>	AVX-FRANKFURT-SPOKE-PROD-Public-3-eu-central-1c-rtb	rtb-099810bbea6608f17	subnet-06219ac03978942e3 / AVX-FRANKFURT-SPOKE-PROD-Public-3-eu-central-1c

# Name Convention with Multiple Gateways

## Cluster of Gateways



- ❖ If you create two or more Gateways, they will be encompassed inside a **cluster**.
- ❖ The name of the cluster will match the name of the first gateway.
- ❖ The second gateway will have the string “-1” appended to its name.
- ❖ The third gateway will have the string “-2” appended to its name.
- 
- 
- 
- ❖ The fifteenth gateway will have the string “-14” appended to its name.

CLUSTER


GW #1

GW #2

• AVX-FRANKFURT-DC-SPOKE	eu-central-1	vpc-04d947b7b73180e3c~~AVX-FRANKFURT-DC	
• AVX-FRANKFURT-DC-SPOKE	eu-central-1	vpc-04d947b7b73180e3c~~AVX-FRANKFURT-DC	192.168.0.48/28
• AVX-FRANKFURT-DC-SPOKE-1	eu-central-1	vpc-04d947b7b73180e3c~~AVX-FRANKFURT-DC	192.168.0.64/28

# Greenfield Deployment (Transit Gateways deployment)

CIDR 10.11.0.0/23



## Transit Gateways Deployment through the CoPilot

Create Transit Gateway

Name: AVX-FRANKFURT-TRANSIT

Cloud: ☒ AWS Standard ☐ Azure ☐ GCP ☐ OCI ☐ Alibaba

Account: AWS-AVIATRIX Region: eu-central-1 (Frankfurt) VPC/VNet: AVX-FRANKFURT-TRANSIT

Instance Size: c5n.large High Performance Encryption: ☐ Off

Peer To Transit Gateways:  Optional

Instances


	Attach to Subnet	Public IP
1	10.11.0.64/28	Allocate New Static Public IP
2	10.11.0.96/28	Allocate New Static Public IP

Cancel Save

- ❖ The connection between the Transit Gateways is automatically created by the Controller.
- ❖ **Best Practice:** always deploy the Transit Gateway-1 (i.e the second gateway), and choose a different AZ.
- ❖ Only 2 Transit Gateways can be deployed per Transit VPC
- ❖ Aviatrix gateways are deployed in Public subnets

# Greenfield Deployment (Spoke Gateways deployment)

CIDR 10.1.1.0/24



## Spoke Gateways Deployment through the CoPilot

The screenshot shows the 'Create Spoke Gateway' form in the AviaTriX CoPilot. The form includes the following fields and settings:


- Cloud:** AWS (Standard)
- Account:** AWS-AVIATRIX
- Region:** eu-central-1 (Frankfurt)
- VPC/VNet:** AVX-FRANKFURT-SPOKE-PROD
- Instance Size:** t3.micro
- High Performance Encryption:** Off
- Attach To Transit Gateway:** Optional
- Advanced Settings:**
  - BGP:** Off
- Instances:**
  - + Instance** button
  - Attach to Subnet:**
    - 1: 10.1.1.48/28
    - 2: 10.1.1.80/28
  - Public IP:**
    - 1: Allocate New Static Public IP
    - 2: Allocate New Static Public IP

Buttons for 'Cancel' and 'Save' are located at the bottom right.

- ❖ The connection between the Spoke Gateways is automatically created by the Controller.
- ❖ **Best Practice:** deploy the Spoke Gateway-1 (i.e the second gateway) on a different AZ.
- ❖ You can deploy up to **15** Spoke Gateways per each Spoke VPC
- ❖ AviaTriX gateways are deployed in Public subnets

# Greenfield Deployment (Attachment deployment)

## Deployment of the attachments through the CoPilot



### Edit Spoke Gateway: AVX-FRANKFURT-SPOKE-PROD

Name  
AVX-FRANKFURT-SPOKE-PROD

Cloud  
AWS

Account  
AWS-AVIATRIX

Region  
eu-central-1

VPC/VNet  
AVX-FRANKFURT-SPOKE-PROD

Instance Size  
t3.micro

High Performance Encryption  
Off

Attach To Transit Gateway  
AVX-FRANKFURT-TRANSIT

**Advanced Settings**

BGP  
Off

**Instances**

+ Instance

	Attach to Subnet	Public IP
1	10.1.1.48/28	3.72.194.207
2	10.1.1.80/28	18.192.199.249

Cancel Save

# Greenfield Deployment (Attachment deployment)

- As soon as the Controller completes the deployment of the **attachments** between Spoke Gateways and Transit Gateways, it will also program the *three RFC1918 routes* in the route tables to point to the ENI of the Spoke Gateways.


Routes	Subnet associations	Edge associations	Route propagation	Tags
Routes (4)				
Filter routes				
Destination		Target		
10.0.0.0/8		eni-08ac50fc16cd8c4a5		
10.1.1.0/24		local		
172.16.0.0/12		eni-08ac50fc16cd8c4a5		
192.168.0.0/16		eni-08ac50fc16cd8c4a5		

Route table for  
Private Subnet

Routes	Subnet associations	Edge associations	Route propagation	Tags
Routes (5)				
Filter routes				
Destination		Target		
0.0.0.0/0		igw-07c6ddedd190d12d3		
10.0.0.0/8		eni-08ac50fc16cd8c4a5		
10.1.1.0/24		local		
172.16.0.0/12		eni-08ac50fc16cd8c4a5		
192.168.0.0/16		eni-08ac50fc16cd8c4a5		


Route table for  
Public Subnet

## Attachment = RFC1918 Routes Injection






# Greenfield Deployment (Repeatable Design)



- ❑ The hub and spoke topology can be extended to another CSP or to another region within the same CSP
- ❑ In Azure all subnets are public by nature
- ❑ Aviatrix Controller creates “Private” subnets:
  - Aviatrix Controller programs a **default route 0.0.0.0 pointing to the next hop type “None”**: in User Defined Route Table (UDR) for all private subnets it creates
  - This will blackhole 0/0 traffic

# Greenfield Deployment (Peering deployment)



- The creation of the Transit Peering represents the last step for the completion of the **MCNA**.

Edit Transit Gateway: AVX-FRANKFURT-TRANSIT

Name  
AVX-FRANKFURT-TRANSIT

Cloud  
AWS

Account  
AWS-AVIATRIX

Region  
eu-central-1

VPC/VNet  
AVX-FRANKFURT-TRANSIT

Instance Size  
c5n.large

High Performance Encryption  
Off

Peer To Transit Gateways  
AZURE-WESTEUROPE-TRANSIT x Optional x


Instances

+ Instance

	Attach to Subnet	Public IP
1	10.11.0.64/28	3.75.164.186
2	10.11.0.96/28	3.127.251.156


Cancel Save

us-west-2




# Advanced Transit Networking

AWS to on-Prem via ExpressRoute or vice versa



Single DX or ER can be used to communicate between On-Prem and multiple CSP resources


# Typical Migration Deployment



## Initial environment in a brownfield scenario:


- Several Application VPCs that are connected to the TGW as attachments
- OnPrem connectivity (hybrid – can be DX/IPSec)

# Typical Migration Deployment




- ❑ **Initial environment in a brownfield scenario:**
  - Several Application VPCs that are connected to the TGW as attachments
  - OnPrem connectivity (hybrid – can be DX/IPSec)
- ❑ **Deploy the Aviatrix Controller and CoPilot in a dedicated VPC, in a different AZ where there are no gateways deployed (best practice)**

# Typical Migration Deployment



- ❑ **Initial environment in a brownfield scenario:**
  - Several Application VPCs that are connected to the TGW as attachments
  - OnPrem connectivity (hybrid – can be DX/IPSec)
- ❑ **Deploy the Aviatrix Controller and CoPilot in a dedicated VPC, in a different AZ where there are no gateways deployed (best practice)**
- ❑ **Deploy a Transit VPC and deploy a pair of Transit Gateways**


# Typical Migration Deployment



- ❑ **Initial environment in a brownfield scenario:**
  - Several Application VPCs that are connected to the TGW as attachments
  - OnPrem connectivity (hybrid – can be DX/IPSec)
- ❑ **Deploy the Aviatrix Controller and CoPilot in a dedicated VPC, in a different AZ where there are no gateways deployed (best practice)**
- ❑ **Deploy a Transit VPC and deploy a pair of Transit Gateways**
- ❑ **Establish a back-to-back connection between the Transit Gateways and the TGW**




# Typical Migration Deployment




- ❑ **Initial environment in a brownfield scenario:**
  - Several Application VPCs that are connected to the TGW as attachments
  - OnPrem connectivity (hybrid – can be DX/IPSec)
- ❑ **Deploy the Aviatrix Controller and CoPilot in a dedicated VPC, in a different AZ where there are no gateways deployed (best practice)**
- ❑ **Deploy a Transit VPC and deploy a pair of Transit Gateways**
- ❑ **Establish a back-to-back connection between the Transit Gateways and the TGW**
- ❑ **Deploy the Spoke Gateways inside the Application VPCs (this action will not change any routing)**

# Typical Migration Deployment



- ❑ **Initial environment in a brownfield scenario:**
  - Several Application VPCs that are connected to the TGW as attachments
  - OnPrem connectivity (hybrid – can be DX/IPSec)
- ❑ **Deploy the Aviatrix Controller and CoPilot in a dedicated VPC, in a different AZ where there are no gateways deployed (best practice)**
- ❑ **Deploy a Transit VPC and deploy a pair of Transit Gateways**
- ❑ **Establish a back-to-back connection between the Transit Gateways and the TGW**
- ❑ **Deploy the Spoke Gateways inside the Application VPCs (this action will not change any routing)**
- ❑ **Remove the connections between the VPCs and the TGW and deploy the attachments between the Spoke Gateways and the Transit Gateways (schedule a maintenance window)**


# Typical Migration Deployment



- ❑ **Initial environment in a brownfield scenario:**
  - Several Application VPCs that are connected to the TGW as attachments
  - OnPrem connectivity (hybrid – can be DX/IPSec)
- ❑ **Deploy the Aviatrix Controller and CoPilot in a dedicated VPC, in a different AZ where there are no gateways deployed (best practice)**
- ❑ **Deploy a Transit VPC and deploy a pair of Transit Gateways**
- ❑ **Establish a back-to-back connection between the Transit Gateways and the TGW**
- ❑ **Deploy the Spoke Gateways inside the Application VPCs (this action will not change any routing)**
- ❑ **Remove the connections between the VPCs and the TGW and deploy the attachments between the Spoke Gateways and the Transit Gateways (schedule a maintenance window)**
- ❑ **Deploy an Aviatrix Edge and then connect the Edge to the Transit Gateways. If you are not looking for HPE, you can also connect the WAN router with an IPSec connectivity to the Transit Gateways. Last but not least, remove the TGW.**

# Multi-Tier Transit (MTT)

- Improves operational simplicity by aggregating multiple Aviatrix Transits (no need for full mesh between transits)
- Additional failover option (pictured in the diagram)
- Allows for centralized firewall design for multiple Aviatrix-Transits in a single region, which allows intra-cloud traffic without any inspection
- To configure Multi-Tier Transit, go to Multi-cloud Transit -> Advanced Config. Select the Transit Gateway and enable the Multi-Tier Transit feature





Next: Lab 2 – (MCNA) Transit  
Networking