




Distributed Cloud Firewall

ACE Team

As Architected with Lift-and-Shift, Bolt-on, Data Center Era Products...






"Last Generation Firewalls"

In Reality...








What If... the architecture was built for cloud









Firewalling Functions were Embedded in the Cloud Network Everywhere...






Distribution of the Security Services into the Spokes





Impact of Failure – Centralized Architecture









Impact of Failure – Distributed Architecture





And, What If it was more than just firewalling...








Policy Creation Looked Like One Big Firewall ... A Distributed Cloud Firewall...





Where and How Policies Are Enforced Is Abstracted...



SmartGroups: Definition



- A firewall rule consists of two important initial elements (i.e. *L3 info*):
 - Source
 - Destination

What is a SmartGroup?

A SmartGroup identifies a group of resources that have similar policy requirements and are associated to the same logical container.

- The members of a SmartGroup can be classified using *different* methods:
 - CSP Tag
 - Subnets
 - VPC/Vnets
 - Kubernetes
 - Hostnames
 - External Connections (S2C)











Smart Groups Creation






- Controller polls the CSPs to retrieve inventory (about VPCs, instances etc.) every 15 minutes (can be modified)
- CoPilot queries Controller every 1 hour (can be modified)
- On-demand refresh of tags is available





Pre-defined Smart Groups






- Anywhere (0.0.0.0/0) → RFC1918 routes + Default Route (IGW)
- Public Internet → Default Route (IGW)

Enabling Distributed Cloud Firewall






- Enabling the Distributed Cloud Firewall without configured rules will deny all previously permitted traffic due to its implicit Deny All rule.
- To maintain consistency, a **Greenfield Rule** will be created to allow traffic that maintains the current state, facilitating the creation of custom rules for specific security needs.





The Greenfield-Rule Structure






- Source SmartGroups: Anywhere (0.0.0.0/0)
- **Destination SmartGroups:** Anywhere (0.0.0.0/0)
- **Protocol:** Any
- **Action:** Permit
- Can be **edited** and **deleted**
- It can be **moved** when new rules are created like any other rules
- If it is the only rule present in the rules base, it is allocated <u>above the</u> <u>implicit deny-all rule</u>

TLS Decryption: Basic TLS Connection







TLS Decryption: PKI/ KMS and Trust Bundle

Certificate Hierarchy

- Root
 - Intermediate
 - Server Cert (Leaf Cert)

Certificate Fields


- Issuer
- Validity
- Subject

Trusted Root CA Bundle


Used by the Client and/or Proxy Gateway to Identify/ Trust the Original Server Cert

Decryption CA Cert

Used by the Decryption/Proxy gateway to generate a new Proxy-Server Cert and Sign it with the Decryption CA Cert



TLS Decryption: Basic TLS Decryption




Signed by

Public CA



TLS Decryption: Decryption CA Cert






- Download the Decryption CA Bundle.
- Distribute the bundle across all the workloads.

Decrypt CA Certificates should be trusted by the **Source SmartGroup** virtual machines when TLS

Decryption is enabled for proxy.

Distributed Cloud Firewall Rule Types: Intra-rule vs. Inter-rule






INTRA-RULE: is defined within a Smart
Group, for dictating what kind of traffic is
allowed/prohibited among all the instances
that belong to that Smart Group

 INTER-RULE: is defined among Smart Groups, for dictating what kind of traffic is allowed/prohibited among two or more Smart Groups.

Micro-Segmention: SmartGroups, Intra-Rules and Inter-Rules



SmartGroup Nginx








ACE

AVIATRIX CERTIFIED
ENGINEER



- Micro-Segmentation: Combination of SmartGroups and DCF Rules
 - Rule changes are saved in **Draft** state.
 - When you apply a rule to a SmartGroup, please keep in mind that there is an **Invisible Hidden Deny** at the very bottom.
- To save the changes click on "Commit"
- **Discard** will trash the changes

× ×


Enforcement Logging

Cancel Save In Drafts

Rule is **stateful**, this means that the return traffic is allowed automatically 20

Network Segmentation & Distributed Cloud Firewall Rule together





Caveat:

same Network Domains: NO impact to the rule

- Network Segmentation and Distributed Firewalling are NOT mutually exclusive!
- Network Segmentation takes **precedence** over the extent of a SmartGroup





two different Network Domains: Inter-rule is impacted

Security Group (SG) Orchestration: Intra VPC/VNET Traffic Control




■ Enable the feature on the relevant VPC/VNet





Rule Enforcement





Enforcement ON


Policy is enforced in the Data Plane

Enforcement OFF

- Policy is NOT enforced in the Data Plane
- The option provides a Watch/Test mode
- Common use case is with deny rule
- Watch what traffic hits the deny rule before enforcing the rule in the Data Plane.

Rule Logging





Save In Drafts


Cancel

Rule Priority

DFW Engines At-a-Glance



- eBPF (extended Berkeley Packet Filter) Engine (L4) → Stateful Firewall Rule (forwarding path)
- WebProxy ATS (Apache Traffic Server) Engine (L7) → it is triggered whether WebGroups or TLS Decryption are required
- Suricata Engine (DPI) → Signature of the payload (only in IDS mode at the moment)







Next: Lab 11 – Distributed Cloud Firewall

