

GRRAS CSS Assessment

CSS 1-Hour Online Exam

Duration: 60 Minutes

Total Questions: 40 | Total Marks: 40 (1 Mark Each)

No Negative Marking

* Indicates required question

SECTION 1: STUDENT INFORMATION

Please fill in your academic details before proceeding to the assessment.

1. Full Name *

2. University Roll Number *

3. Email ID *

4. Mobile Number *

5. College / University Name *

6. Course / Technology *

7. Batch / Semester *

Skip to question 8

SECTION 2: ASSESSMENT QUESTIONS

40 Multiple-Choice Questions (Auto-Evaluated). Each question carries 1 mark. No negative marking.

8. 1. Consider this CSS declaration:

*

```
.box {  
  margin: 10px 20px 30px;  
}
```

Which of the following describes the correct margin mapping (top, right, bottom, left) applied to the .box element?

Mark only one oval.

- ☐ Top = 10px, Right = 20px, Bottom = 20px, Left = 30px
- ☐ Top = 10px, Right = 30px, Bottom = 10px, Left = 20px
- ☐ Top = 10px, Right = 10px, Bottom = 20px, Left = 30px
- ☐ Top = 10px, Right = 20px, Bottom = 30px, Left = 20px

9. 2. Which of the following selectors matches every <p> element that is placed immediately after an <h2> element, sharing the same parent container? *

Mark only one oval.

☐ h2 + p

☐ h2 > p

☐ h2 p

☐ h2 ~ p

10. 3. In a user profile card, long email addresses are overflowing out of their container cards on small screens. The developer wants to truncate the email with an ellipsis (...) if it is too long to fit on a single line. Which set of declarations must be applied to the text element? *

Mark only one oval.

☐ overflow: hidden; text-decoration: clip; width: auto;

☐ white-space: nowrap; overflow: hidden; text-overflow: ellipsis;

☐ display: inline-block; clip-path: inset(0);

☐ text-wrap: wrap; overflow: scroll; word-break: break-all;

11. 4. You want to create a CSS Grid layout with three columns: the first column takes up exactly 200px, the third column takes up exactly 100px, and the middle column fills all remaining available space dynamically. Which CSS declaration should you apply to the grid container? *

Mark only one oval.

- ☐ grid-template-columns: 200px auto 100px;
- ☐ grid-template-columns: 200px 1fr 100px;
- ☐ grid-template-columns: repeat(3, 1fr);
- ☐ grid-template-columns: 200px minmax(100px, 1fr);

12. 5. You are creating a responsive flexbox container of card components. You want cards to automatically wrap onto a new row instead of shrinking when they run out of horizontal space. Which property should you apply to the parent container? *

Mark only one oval.

- ☐ display: block;
- ☐ flex-wrap: wrap;
- ☐ flex-flow: row;
- ☐ align-content: space-around;

13. 6. In the CSS Box Model, which layer lies directly between the padding and the margin? *

Mark only one oval.

- ☐ Box-shadow
- ☐ Content
- ☐ Outline
- ☐ Border

14. 7. Which CSS Grid template columns property combination will produce a layout that automatically fits as many columns of at least 150px as possible into the container, and stretches them equally to fill any remaining container space? *

Mark only one oval.

- ☐ grid-template-columns: fit-content(150px) 1fr;
- ☐ grid-template-columns: repeat(auto-fill, 150px);
- ☐ grid-template-columns: repeat(3, minmax(150px, auto));
- ☐ grid-template-columns: repeat(auto-fit, minmax(150px, 1fr));

15. 8. You have a parent `<div>` containing three child `<div>`s that have been floated left (`float: left;`). The parent element's height collapses to 0px, causing elements below it to float upwards and break the layout. What is the modern, standard CSS solution to fix this 'float collapse' without adding empty helper elements to the HTML? *

Mark only one oval.

- ☐ Set position: absolute; on the parent container.
- ☐ Add display: inline; to the parent container.
- ☐ Add `<div style="clear:both;"></div>` inside the parent div.
- ☐ Set display: flow-root; on the parent container.

16. 9. A developer is building a modal popup. They set the backdrop z-index to 10 and the modal content container z-index to 20. However, the modal content still renders behind the header of the page, which has a z-index of 5. What is the most likely cause of this bug? *

Mark only one oval.

- ☐ The modal content's parent element has a z-index lower than 5 and has established its own stacking context.
- ☐ The modal backdrop has a higher z-index than the modal content.
- ☐ The browser does not support z-index values larger than 10.
- ☐ The header is positioned static and cannot have a z-index.

17. 10. In the standard W3C box model (box-sizing: content-box), if a <div> is configured with width: 200px; padding: 20px; border: 5px solid black; margin: 15px;, what is its total calculated layout width on the screen? *

Mark only one oval.

- ☐ 280px
- ☐ 225px
- ☐ 200px
- ☐ 250px

18. 11. Review the following CSS custom property (variable) definitions: *

```
:root {  
  --primary-color: #3498db;  
}  
.card {  
  --primary-color: #2ecc71;  
  color: var(--primary-color);  
}  
.card p {  
  color: var(--primary-color, #e74c3c);  
}
```

If we have a <div class="card"><p>Text</p></div>, what will be the color of the text in the <p> element?

Mark only one oval.

- ☐ The default browser color (black)
- ☐ #3498db (blue)
- ☐ #e74c3c (red)
- ☐ #2ecc71 (green)

19. 12. A web designer wants to implement fluid typography where the font size scales dynamically between 16px on small screens and 24px on large screens, but never goes below 16px or above 24px. Which CSS function achieves this without using media queries? *

Mark only one oval.

- ☐ font-size: fit-content(24px);
- ☐ font-size: clamp(16px, 2vw + 12px, 24px);
- ☐ font-size: calc(16px + 24px);
- ☐ font-size: minmax(16px, 24px);

20. 13. If you apply 'mix-blend-mode: multiply;' to an element, how will its colors react with the colors of its background layer? *

Mark only one oval.

- ☐ The pixels turn completely inverted relative to their background colors.
- ☐ The structural element isolates itself, ignoring parent container shapes completely.
- ☐ The component colors are multiplied by the backdrop colors, resulting in a darker appearance overall.
- ☐ The layer becomes perfectly transparent regardless of background color inputs.

21. 14. Which of the following is the correct HTML syntax to link an external CSS file? *

Mark only one oval.

- ☐ <link href="style.css" rel="style">
- ☐ <stylesheet>style.css</stylesheet>
- ☐ <link rel="stylesheet" type="text/css" href="style.css">
- ☐ <style src="style.css">

22. 15. If you want to make text bold, which CSS property must you use? *

Mark only one oval.

- ☐ font-variant
- ☐ font-style
- ☐ text-bold
- ☐ font-weight

23. 16. Which aspect-ratio declaration correctly sets an element to match a standard high-definition widescreen layout size profile? *

Mark only one oval.

- ☐ aspect-ratio: auto-scale(1.77);
- ☐ aspect-ratio: 4 / 3;
- ☐ aspect-ratio: 16 / 9;
- ☐ aspect-ratio: widescreen;

24. 17. Which CSS property controls the size of text? *

Mark only one oval.

- ☐ font-size
- ☐ font-style
- ☐ text-style
- ☐ text-size

25. 18. You want to center a box element both horizontally and vertically inside a parent container that has a height of 400px. Which combination of container styles is standard and most robust? *

Mark only one oval.

- ☐ display: flex; justify-content: center; align-items: center;
- ☐ display: block; vertical-align: middle;
- ☐ position: relative; top: 50%; transform: translateY(-50%);
- ☐ margin: 50px auto; text-align: center;

26. 19. How do you write a comment in a CSS file? *

Mark only one oval.

- ☐ # this is a comment
- ☐ /* this is a comment */
- ☐
- ☐ // this is a comment

27. 20. By default, HTML anchor tags (<a>) have an underline. Which CSS declaration removes this underline? *

Mark only one oval.

- ☐ decoration: none;
- ☐ font-style: plain;
- ☐ text-decoration: none;
- ☐ text-style: no-underline;

28. 21. What is the fundamental difference between the relative units em and rem? *

Mark only one oval.

- ☐ There is no difference; they are aliases for the same viewport-based size.
- ☐ em is relative to the font-size of the current/parent element, while rem is relative to the font-size of the root <html> element.
- ☐ em is relative to the viewport size, while rem is relative to the parent element font size.
- ☐ em is an absolute unit, while rem is a relative unit.

29. 22. What is the correct CSS property and value to set the list bullet style to square shapes? *

Mark only one oval.

- ☐ list-style-type: square;
- ☐ list-style: bullet(square);
- ☐ bullet-style: square;
- ☐ list-type: square;

30. 23. Which CSS selector is used to target a unique HTML element with the ID attribute "header"? *

Mark only one oval.

- ☐ *header
- ☐ .header
- ☐ header
- ☐ #header

31. 24. Which of the following CSS units is an absolute length unit? *

Mark only one oval.

- ☐ vh
- ☐ em
- ☐ px
- ☐ rem

32. 25. What does the 'will-change' property do in CSS? *

Mark only one oval.

- ☐ It automatically creates smooth transition effects for layout properties.
- ☐ It hints to the browser how an element is expected to change, allowing it to optimize rendering ahead of time.
- ☐ It locks an element's values to prevent accidental stylesheet overrides.
- ☐ It forces a JavaScript event listener to fire whenever properties mutate.

33. 26. A developer wants an image to completely fill its parent container (width: 300px; height: 200px) without stretching or losing its aspect ratio, cropping the image slightly if necessary. Which property and value should they use? *

Mark only one oval.

- ☐ width: 100%; height: 100%;
- ☐ object-fit: contain;
- ☐ background-size: cover;
- ☐ object-fit: cover;

34. 27. When styling a print version of a web page using @media print, you want to prevent a table header (<thead>) from being separated from its body rows across pages, and force a page break before each new main section (<section>). Which properties should you use? *

Mark only one oval.

- ☐ overflow: page; on the table, and margin-top: 100vh; on the section.
- ☐ break-inside: avoid; on the table, and break-before: always; on the section.
- ☐ page-break: avoid; on the table, and page-break-after: always; on the section.
- ☐ clear: both; on the table, and display: block; on the section.

35. 28. Which CSS pseudo-class matches an element only when a user navigates to it or selects it using the keyboard's 'Tab' key (for accessibility), rather than when clicking it with a mouse? *

Mark only one oval.

- ☐ :hover
- ☐ :focus-visible
- ☐ :active
- ☐ :focus

36. 29. What is the correct CSS declaration to create a semi-transparent white background with a blur filter behind it, commonly known as a 'glassmorphism' effect? *

Mark only one oval.

- ☐ background: rgba(255, 255, 255, 0.5); backdrop-filter: blur(10px);
- ☐ background: rgb(255, 255, 255, 0.5); filter: blur(10px);
- ☐ background-color: transparent; mix-blend-mode: overlay;
- ☐ background: hsl(0, 0%, 100%); opacity: 0.5;

37. 30. You want to create a CSS animation where an element pulses continuously. It should scale up to 1.1x size and back to 1.0x size, taking 2 seconds. Which property configures it to play forwards then backwards sequentially? *

Mark only one oval.

- ☐ animation-timing-function: ease-in-out;
- ☐ animation-direction: alternate;
- ☐ animation-fill-mode: both;
- ☐ animation-iteration-count: infinite;

38. 31. How does the browser resolve CSS rule conflicts when two selectors have the exact same specificity and source origin? *

Mark only one oval.

- ☐ It uses the rule that appears first in the stylesheet.
- ☐ It uses the rule that appears last in the stylesheet (overriding the earlier one).
- ☐ It prioritizes inline styles over stylesheet styles regardless of order.
- ☐ It ignores both rules and falls back to user-agent default styles.

39. 32. What is the primary benefit of using containment properties via 'contain: layout * paint;' on deep UI component structures?

Mark only one oval.

- ☐ It converts vector files into static raster image assets inside viewports.
- ☐ It locks security access limits around local cookies.
- ☐ It prevents text truncation inside input boxes automatically.
- ☐ It isolates the component subtrees so the browser can bypass layout and paint calculations for performance.

40. 33. A developer is building a page and wants the footer to stay stuck to the bottom * of the viewport even when the page content is short or when the user scrolls. Which CSS position configuration is best suited for this?

Mark only one oval.

- ☐ position: absolute; bottom: 0;
- ☐ position: relative; bottom: 0;
- ☐ position: static; vertical-align: bottom;
- ☐ position: fixed; bottom: 0; left: 0; right: 0;

41. 34. Which value of the display property hides an element from the page * completely, ensuring it occupies no layout space?

Mark only one oval.

- ☐ none
- ☐ hidden
- ☐ block
- ☐ invisible

42. 35. What is the default value of the position property in CSS? *

Mark only one oval.

- ☐ fixed
- ☐ absolute
- ☐ static
- ☐ relative

43. 36. Consider the following HTML structure and CSS:

*

```
<div class="container">  
  <div class="item">1</div>  
  <div class="item">2</div>  
</div>
```

```
.container {  
  display: flex;  
  flex-direction: row-reverse;  
}
```

What will be the visual layout order of the items on the screen, reading from left to right?

Mark only one oval.

- ☐ 2 above 1
- ☐ 2, then 1
- ☐ 1, then 2
- ☐ 1 above 2

44. 37. Which CSS property is used to change the background color of an element? *

Mark only one oval.

- ☐ bgcolor
- ☐ color
- ☐ background-image
- ☐ background-color

45. 38. How does setting the 'isolated' keyword on 'contain-intrinsic-size' impact container queries? *

Mark only one oval.

- ☐ It provides a reliable fallback placeholder size for elements subjected to content-visibility constraints.
- ☐ It forces flexbox containers to convert into strict grid definitions.
- ☐ It blocks cross-origin content rendering from loading inside iframes.
- ☐ It turns off media query support on mobile views completely.

46. 39. A developer applies text-transform: uppercase; to a username input field text. A user types 'john' and submits the form. How is this text displayed on screen, and what value is received by the backend database? *

Mark only one oval.

- ☐ Rendered as 'john', submitted to database as 'JOHN'
- ☐ Rendered as 'john', submitted to database as 'john'
- ☐ Rendered as 'JOHN', submitted to database as 'JOHN'
- ☐ Rendered as 'JOHN', submitted to database as 'john'

47. 40. How do you apply a CSS transition effect that animates only the background-color property for a duration of 0.5 seconds, using an 'ease-in-out' timing function? *

Mark only one oval.

- ☐ transition: color 500ms ease;
- ☐ transition: background-color 0.5s ease-in-out;
- ☐ transition-property: all 0.5s;
- ☐ animate: background-color 0.5s ease-in-out;

This content is neither created nor endorsed by Google.

Google Forms