

```
[ec2-user@ip-172-31-17-104 ~]$ cat /etc/resolv.conf
# This is /run/systemd/resolve/resolv.conf managed by man:systemd-resolved(8).
# Do not edit.
#
# This file might be symlinked as /etc/resolv.conf. If you're looking at
# /etc/resolv.conf and seeing this text, you have followed the symlink.
#
# This is a dynamic resolv.conf file for connecting local clients directly to
# all known uplink DNS servers. This file lists all configured search domains.
#
# Third party programs should typically not access this file directly, but only
# through the symlink at /etc/resolv.conf. To manage man:resolv.conf(5) in a
# different way, replace this symlink by a static file or a different symlink.
#
# See man:systemd-resolved.service(8) for details about the supported modes of
# operation for /etc/resolv.conf.

nameserver 172.31.0.2
search ec2.internal
[ec2-user@ip-172-31-17-104 ~]$ █
```

```
[ec2-user@ip-172-31-17-104 ~]$ ip route
default via 172.31.16.1 dev ens5 proto dhcp src 172.31.17.104 metric 512
172.31.0.2 via 172.31.16.1 dev ens5 proto dhcp src 172.31.17.104 metric 512
172.31.16.0/20 dev ens5 proto kernel scope link src 172.31.17.104 metric 512
172.31.16.1 dev ens5 proto dhcp scope link src 172.31.17.104 metric 512
[ec2-user@ip-172-31-17-104 ~]$
```

```
[ec2-user@ip-172-31-17-104 ~]$ ip link
1: lo: <LOOPBACK,UP,LOWER_UP> mtu 65536 qdisc noqueue state UNKNOWN mode DEFAULT group default qlen 1000
    link/loopback 00:00:00:00:00:00 brd 00:00:00:00:00:00
2: ens5: <BROADCAST,MULTICAST,UP,LOWER_UP> mtu 9001 qdisc mq state UP mode DEFAULT group default qlen 1000
    link/ether 0a:ff:d9:e9:a9:2d brd ff:ff:ff:ff:ff:ff
    altname enp0s5
    altname eni-0bf7df1e9f685aaa8
    altname device-number-0.0
[ec2-user@ip-172-31-17-104 ~]$
```

```
[ec2-user@ip-172-31-17-104 ~]$ ip -br addr
lo                UNKNOWN      127.0.0.1/8 ::1/128
ens5              UP          172.31.17.104/20 metric 512 fe80::8ff:d9ff:fee9:a92d/64
[ec2-user@ip-172-31-17-104 ~]$
```

```
[ec2-user@ip-172-31-17-104 ~]$ ip addr
1: lo: <LOOPBACK,UP,LOWER_UP> mtu 65536 qdisc noqueue state UNKNOWN group default qlen 1000
    link/loopback 00:00:00:00:00:00 brd 00:00:00:00:00:00
    inet 127.0.0.1/8 scope host lo
        valid_lft forever preferred_lft forever
    inet6 ::1/128 scope host noprefixroute
        valid_lft forever preferred_lft forever
2: ens5: <BROADCAST,MULTICAST,UP,LOWER_UP> mtu 9001 qdisc mq state UP group default qlen 1000
    link/ether 0a:ff:d9:e9:a9:2d brd ff:ff:ff:ff:ff:ff
    altname enp0s5
    altname eni-0bf7df1e9f685aaa8
    altname device-number-0.0
    inet 172.31.17.104/20 metric 512 brd 172.31.31.255 scope global dynamic ens5
        valid_lft 2893sec preferred_lft 2893sec
    inet6 fe80::8ff:d9ff:fee9:a92d/64 scope link proto kernel_ll
        valid_lft forever preferred_lft forever
[ec2-user@ip-172-31-17-104 ~]$
```

```
[ec2-user@ip-172-31-17-104 ~]$ hostname -I  
172.31.17.104  
[ec2-user@ip-172-31-17-104 ~]$
```