

AUTOMATIC WATER TAPS



SACRED AURA
TECHNOLOGIES

DESCRIPTION

AUTOMATIC WATER TAP – SPECIFICATION SHEET

- BODY MATERIAL: BRASS
- FINISH: CHROME-PLATED (HIGH-GLUSTRE, CORROSION-RESISTANT)
- INLET WATER PRESSURE: 1 BAR – 4.0 BAR (MINIMUM WORKING PRESSURE=1 BAR)
 - POWER SUPPLY:
 - AC 220 V, 50 HZ (MAINS)
 - BACKUP: 4×AA DURACELL BATTERIES (INSTALLED INTERNALLY)
 - SENSING RANGE: 9 CM – 20 CM (INFRARED PROXIMITY SENSOR)
 - TYPICAL FLOW RATE: 6 L/MIN (ADJUSTABLE)
- MOUNTING: STANDARD ½-INCH BSP THREAD, WALL-MOUNT OR DECK-MOUNT OPTIONS
 - OPERATING TEMPERATURE: 5°C – 45°C

NOTE: THE TAP AUTOMATICALLY SWITCHES TO BATTERY POWER IF THE AC SUPPLY IS INTERRUPTED, ENSURING UNINTERRUPTED OPERATION.



SACREDAURA
TECHNOLOGIES



RS. 4500

MODEL : SA AT 218



SACREDAURA
TECHNOLOGIES



RS. 9000

MODEL : SA AT 616



SACREDAURA
TECHNOLOGIES



RS. 9000
MODEL : SA AT 412



SACREDAURA
TECHNOLOGIES



RS. 9000

MODEL : SA AT 712



SACREDAURA
TECHNOLOGIES



RS. 7000

MODEL : SA AT 718



SACREDAURA
TECHNOLOGIES



RS. 9000
MODEL : SA AT 716



SACREDAURA
TECHNOLOGIES



RS. 9000

MODEL : SA AT 714



SACREDAURA
TECHNOLOGIES



RS. 9000
MODEL : SA AT 400



SACREDAURA
TECHNOLOGIES



RS. 7000

MODEL : SA AT 414



SACREDAURA
TECHNOLOGIES



RS. 9000
MODEL : SA AT 618



SACREDAURA
TECHNOLOGIES



RS. 9000
MODEL : SA AT 500



SACREDAURA
TECHNOLOGIES



RS. 9000

MODEL : SA AT 512



SACREDAURA
TECHNOLOGIES



RS. 9000
MODEL : SA AT 416