

# Sportsbook API M8

## Table Of Contents

Introduction.....	2
1. Request Format.....	2
2. Response Format.....	3
2.1 ErrCode and ErrText.....	3
3. Actions.....	4
3.1 create.....	4
3.2 update.....	5
3.3 update2.....	7
3.4 balance.....	9
3.5 deposit.....	10
3.6 withdraw.....	11
3.7 login.....	12
3.8 logout.....	13
3.9 check_payment.....	14
3.10 check_online.....	15
3.11 parlay.....	16
3.12 step.....	18
3.13 team.....	20
3.14 league.....	22
3.15 sportstype.....	24
3.16 match_count.....	26
3.17 fetch.....	27
3.18 fetch_result.....	29
3.19 mark_fetched.....	31
3.20 fetch2.....	32
3.21 fetch_result2.....	34
3.22 fetch_group.....	36
3.23 mark_fetched_group.....	38
3.24 group.....	39
3.25 check_ventran (For One Wallet use).....	41
4. Extra Information.....	42
4.1 Fetch Ticket Info.....	42
5. Update History.....	46

## Introduction

This document is to explain how to request action using Sportsbook API.

### 1. Request Format

http://<host>/api.aspx?secret=<secret>&action=<action>&agent=<agent>&username=<username>&...

#### 1.1 Request Parameter

Request	Description	Example
<host>	Host name	apiweb.mywinday.com
<secret>	Agent secret key	1245
<action>	Action that want to perform	create
<agent>	Agent name	hat
<username>	Username	test01

## 2. Response Format

Below is the print-screen for response format.

```
<?xml version="1.0" encoding="UTF-8"?>
<response>
  <errcode>ErrCode</errcode>
  <errtext>ErrText</errtext>
  <result>Result</result>
</response>
```

Parameter	Description
ErrCode	Error code
ErrText	Error text
Result	Display result when no errors

### 2.1 ErrCode and ErrText

ErrCode	Description
0	No error
Negative number / less than 0	General error (Refer 2.1.1)
Positive number / more than 0	Action specific error (Refer 2.1.2)

#### 2.1.1 General error (Negative number)

ErrCode	ErrText	Description
-1	System maintenance	Maintenance
-2	Invalid secret	Invalid secret key
-3	Ip address not allow	
-4	Invalid username (length 1-64, format A-Za-z0-9)	Invalid username
-5	Invalid action	
-7	Invalid agent	Invalid agent CompType
-8	Invalid username	Invalid username CompType
-11	Too many attempts, try again later!	
-12	Too many attempts, try again later!!	
-13	Too many attempts, try again later!!!	
-100		Invalid input
-101		Exception error

#### 2.1.2 Action specific error (Positive number)

Display the action specific error as ErrText.

Below is the print-screen for one of the action specific error.

```
<?xml version="1.0" encoding="UTF-8"?>
<response>
  <errcode>1</errcode>
  <errtext>Username exist</errtext>
  <result/>
</response>
```

### 3. Actions

#### 3.1 create

This action is to create member.

##### 3.1.1 Request Parameter

http://<host>/api.aspx?secret=<secret>&action=create&agent=<agent>&username=<username>

Parameter	Date Type	Description	Example
action	string	Action name	create
secret	string	Agent secret key	1245
agent	string	Agent name	hat
username	string	Username	test10

##### 3.1.2 Response XML (Example)

###### Success

Request example:

http://api.mywinday.com/api.aspx?secret=1245&action=create&agent=hat&username=test10

```
<?xml version="1.0" encoding="UTF-8"?>
<response>
  <errcode>0</errcode>
  <errtext/>
  <result>test10</result>
</response>
```

###### Error

Request example:

http://api.mywinday.com/api.aspx?secret=1245&action=create&agent=hat&username=test10

```
<?xml version="1.0" encoding="UTF-8"?>
<response>
  <errcode>1</errcode>
  <errtext>Username exist</errtext>
  <result/>
</response>
```

## 3.2 update

This action is to update member (max bets, limits and commissions settings).

### 3.2.1 Request Parameter

http://<host>/api.aspx?secret=<secret>&action=update&agent=<agent>&username=<username>&max1=1100&max2=1200&max3=1300&max4=1400&lim1=1000&lim2=1100&lim3=1200&lim4=1300&comtype=A&com1=0.1&com2=0.2&com3=0.3&com4=0.4&com5=0.5&com6=0.6&com7=0.7&com8=0.8&com9=0.0&suspend=0&max5=0&max6=0&max7=0

Parameter	Date Type	Description	Example
action	string	Action name	update
secret	string	Agent secret key	1245
agent	string	Agent name	hat
username	string	Username	test01
max1	double	Max Bet HDP/OU/OE	1100
max2	double	Max Single Bet Limit Parlay	1200
max3	double	Max Bet Correct Score	1300
max4	double	Max Bet Step	1400
max5	double	Max Bet 1D	0
max6	double	Max Bet 2D	0
max7	double	Max Bet 3D	0
lim1	double	Max Per Match HDP/OU/OE	1000
lim2	double	Mix Parlay Limit Per Combination	1100
lim3	double	Max Per Match Correct Score	1200
lim4	double	Step Limit Per Combination	1300
comtype	string	Choice of A,B,C,D,E,F,4,V for HDP/OU/OE	A
com1	double	Commission for HDP/OU/OE	0.1
com2	double	Commission for 1X2/Outright	0.2
com3	double	Commission for PAR/CS/TG	0.3
com4	double	Commission for Step (2 match)	0.4
com5	double	Commission for Step (3-4 match)	0.5
com6	double	Commission for Step (5-6 match)	0.6
com7	double	Commission for Step (7-8 match)	0.7
com8	double	Commission for Step (9-10 match)	0.8
com9	double	Commission for Step (11-12 match)	0.0
suspend	boolean	0: no suspend, 1:suspend	0

### 3.2.2 Response XML (Example)

#### Success

Request example:

http://api.mywinday.com/api.aspx?secret=1245&action=update&agent=hat&username=test01&max1=1100&max2=0&max3=0&max4=0&lim1=1000&lim2=0&lim3=0&lim4=0&comtype=A&com1=0.1&com2=0.2&com3=0.3&com4=0.4&com5=0.5&com6=0.6&com7=0.7&com8=0.8&com9=0.0&suspend=0&max5=0&max6=0&max7=0&max8=0&max9=0&lim5=1200&lim6=1200

```
<?xml version="1.0" encoding="UTF-8"?>
<response>
  <errcode>0</errcode>
  <errtext/>
  <result/>
</response>
```

### Error

Request example:

<http://api.mywinday.com/api.aspx?secret=1245&action=update&agent=hat&username=test01&max1=1100&max2=1000&max3=0&max4=0&lim1=1000&lim2=0&lim3=0&lim4=0&comtype=A&com1=0.1&com2=0.2&com3=0.3&com4=0.4&com5=0.5&com6=0.6&com7=0.7&com8=0.8&com9=0.0&suspend=0&max5=0&max6=0&max7=0&max8=0&max9=0&lim5=1200&lim6=1200>

```
<?xml version="1.0" encoding="UTF-8"?>
<response>
  <errcode>1</errcode>
  <errtext>EXCEED</errtext>
  <result/>
</response>
```

### 3.3 update2

This action is to update member (max bets, limits and commissions settings). Added max bet and match limit for P3D BSOE&AT/S and Perdana3D 3D.

#### 3.3.1 Request Parameter

http://<host>/api.aspx?secret=<secret>&action=update2&agent=<agent>&username=<username>&max1=1100&max2=1200&max3=1300&max4=1400&lim1=1000&lim2=1100&lim3=1200&lim4=1300&comtype=A&com1=0.1&com2=0.2&com3=0.3&com4=0.4&com5=0.5&com6=0.6&com7=0.7&com8=0.8&com9=0.0&suspend=0&max5=0&max6=0&max7=0&max8=0&max9=0&lim5=1200&lim6=1200

Parameter	Date Type	Description	Example
action	string	Action name	update2
secret	string	Agent secret key	1245
agent	string	Agent name	hat
username	string	Username	test01
max1	double	Max Bet HDP/OU/OE	1100
max2	double	Max Single Bet Limit Parlay	1200
max3	double	Max Bet Correct Score	1300
max4	double	Max Bet Step	1400
max5	double	Max Bet 1D	0
max6	double	Max Bet 2D	0
max7	double	Max Bet 3D	0
max8	double	Max Bet P3D BSOE&AT/S	0
max9	double	Max Bet P3D 3D	0
lim1	double	Max Per Match HDP/OU/OE	1000
lim2	double	Mix Parlay Limit Per Combination	1100
lim3	double	Max Per Match Correct Score	1200
lim4	double	Step Limit Per Combination	1300
lim5	double	Max Per Match P3D BSOE&AT/S	1200
lim6	double	Max Per Match P3D 3D	1200
comtype	string	Choice of A,B,C,D,E,F,4,V for HDP/OU/OE	A
com1	double	Commission for HDP/OU/OE	0.1
com2	double	Commission for 1X2/Outright	0.2
com3	double	Commission for PAR/CS/TG	0.3
com4	double	Commission for Step (2 match)	0.4
com5	double	Commission for Step (3-4 match)	0.5
com6	double	Commission for Step (5-6 match)	0.6
com7	double	Commission for Step (7-8 match)	0.7
com8	double	Commission for Step (9-10 match)	0.8
com9	double	Commission for Step (11-12 match)	0.0
suspend	boolean	0: no suspend, 1:suspend	0

#### 3.3.2 Response XML (Example)

##### Success

Request example:

http://api.mywinday.com/api.aspx?secret=1245&action=update2&agent=hat&username=test01&max1=1100&max2=0&max3=0&max4=0&lim1=100&lim2=0&lim3=0&lim4=0&comtype=A&com1=0.1&com2=0&com3=0&com4=0&com5=0&com6=0&com7=0&com8=0&com9=0.0&suspend=0&max5=0&max6=0&max7=0&max8=0&max9=0&lim5=0&lim6=0

```
<?xml version="1.0" encoding="UTF-8"?>
<response>
  <errcode>0</errcode>
  <errtext/>
  <result/>
</response>
```

### Error

Request example:

http://api.mywinday.com/api.aspx?secret=1245&action=update2&agent=hat&username=test01&max1=1100&max2=1000&max3=0&max4=0&lim1=100&lim2=0&lim3=0&lim4=0&comtype=A&com1=0.1&com2=0&com3=0&com4=0&com5=0&com6=0&com7=0&com8=0&com9=0.0&suspend=0&max5=0&max6=0&max7=0&max8=0&max9=0&lim5=0&lim6=0

```
<?xml version="1.0" encoding="UTF-8"?>
<response>
  <errcode>1</errcode>
  <errtext>EXCEED</errtext>
  <result/>
</response>
```



### 3.4 balance

This action is to check balance for member.

#### 3.4.1 Request Parameter

http://<host>/api.aspx?secret=<secret>&action=balance&agent=<agent>&username=<username>

Parameter	Data Type	Description	Example
action	string	Action name	balance
secret	string	Agent secret key	1245
agent	string	Agent name	hat
username	string	Username	test01

#### 3.4.2 Response XML (Example)

##### Success

Request example:

http://api.mywinday.com/api.aspx?secret=1245&agent=hat&username=test01&action=balance

```
<?xml version="1.0" encoding="UTF-8"?>
<response>
  <errcode>0</errcode>
  <errtext/>
  <result>100077.28</result>
</response>
```

##### Error

```
<?xml version="1.0" encoding="UTF-8"?>
<response>
  <errcode>1</errcode>
  <errtext>User not exist</errtext>
  <result/>
</response>
```

```
<?xml version="1.0" encoding="UTF-8"?>
<response>
  <errcode>4</errcode>
  <errtext>Casino online</errtext>
  <result/>
</response>
```

### 3.5 deposit

This action is to deposit a certain amount to member.

Please call action "balance" with no error before deposit.

#### 3.5.1 Request Parameter

http://<host>/api.aspx?secret=<secret>&action=deposit&agent=<agent>&username=<username>&serial=001&amount=100

Parameter	Data Type	Description	Example
action	string	Action name	deposit
secret	string	Agent secret key	1245
agent	string	Agent name	hat
username	string	Username	test01
serial	string	Reference number	001
amount	double	Amount	100

#### 3.5.2 Response XML (Example)

##### Success

Request example:

http://api.mywinday.com/api.aspx?secret=1245&agent=hat&username=test01&action=deposit&serial=022&amount=100

```
<?xml version="1.0" encoding="UTF-8"?>
<response>
  <errcode>0</errcode>
  <errtext/>
  <result>100527.285</result>
</response>
```

##### Error

Request example:

http://api.mywinday.com/api.aspx?secret=1245&agent=hat&username=test01&action=deposit&serial=001&amount=100

```
<?xml version="1.0" encoding="UTF-8"?>
<response>
  <errcode>2</errcode>
  <errtext>Serial exist</errtext>
  <result/>
</response>
```

### 3.6 withdraw

This action is to withdraw a certain amount from member.

Please call action "balance" with no error before withdraw.

#### 3.6.1 Request Parameter

http://<host>/api.aspx?secret=<secret>&action=withdraw&agent=<agent>&username=<user name>&serial=002&amount=50

Parameter	Data Type	Description	Example
action	string	Action name	withdraw
secret	string	Agent secret key	1245
agent	string	Agent name	hat
username	string	Username	test01
serial	string	Reference number	002
amount	double	Amount number	50

#### 3.6.2 Response XML (Example)

##### Success

Request example:

http://api.mywinday.com/api.aspx?secret=1245&agent=hat&username=test01&action=withdraw&amount=50&serial=011

```
<?xml version="1.0" encoding="UTF-8"?>
<response>
  <errcode>0</errcode>
  <errtext/>
  <result>100477.28</result>
</response>
```

##### Error

Request example:

http://api.mywinday.com/api.aspx?secret=1245&agent=hat&username=test01&action=withdraw&serial=002&amount=50

```
<?xml version="1.0" encoding="UTF-8"?>
<response>
  <errcode>2</errcode>
  <errtext>Serial exist</errtext>
  <result/>
</response>
```

### 3.7 login

This action is to sign in a member. The login url will be expired in 60 seconds.

#### 3.7.1 Request Parameter

http://<host>/api.aspx?secret=<secret>&action=login&agent=<agent>&username=<username>&lang=ENUS&accType=HK&ref=ref

Parameter	Data Type	Description	Example
action	string	Action name	login
secret	string	Agent secret key	1245
agent	string	Agent name	hat
username	string	Username	test01
lang	string	Language	EN-US, ZH-CN, KO-KR, TH-TH, VI-VN, ES-PA, ID-ID
accType	string	Odds type	MY, HK, ID, EU
ref	string	main domain for website (www.xxxx.com) (For mobile use)	

#### 3.7.2 Response XML (Example)

##### Success

Request example:

http://api.mywinday.com/api.aspx?secret=1245&agent=hat&username=test01&action=login  
&lang=EN-US&accType=HK

```
<?xml version="1.0" encoding="UTF-8"?>
<response>
  <errcode>0</errcode>
  <errtext></errtext>
  <result>
    <login>
      <weburl>
        <![CDATA[
          https://9q7r013d.mywinday.com/public/auth.aspx?us=1jm1test01&k=BF95AC45ACB1417481F25E76B018B89C&lang=EN-US&accType=HK&r=283966066&ref=
        ]]>
      </weburl>
      <weburlsecure>
        <![CDATA[
          https://9q7r013d.mywinday.com/public/auth.aspx?us=1jm1test01&k=BF95AC45ACB1417481F25E76B018B89C&lang=EN-US&accType=HK&r=283966066&ref=
        ]]>
      </weburlsecure>
      <mobiurl>
        <![CDATA[
          https://9q7r013dmobi.mywinday.com/public/auth.aspx?us=1jm1test01&k=BF95AC45ACB1417481F25E76B018B89C&lang=EN-US&accType=HK&r=283966066&ref=
        ]]>
      </mobiurl>
      <mobiurlsecure>
        <![CDATA[
          https://9q7r013dmobi.mywinday.com/public/auth.aspx?us=1jm1test01&k=BF95AC45ACB1417481F25E76B018B89C&lang=EN-US&accType=HK&r=283966066&ref=
        ]]>
      </mobiurlsecure>
    </login>
  </result>
</response>
```

##### Error

```
<?xml version="1.0" encoding="UTF-8"?>
<response>
  <errcode>2</errcode>
  <errtext>Invalid secret</errtext>
  <result/>
</response>
```

### 3.8 logout

This action is to sign out a member.

#### 3.8.1 Request Parameter

http://<host>/api.aspx?secret=<secret>&action=logout&agent=<agent>&username=<username>

Parameter	Data Type	Description	Example
action	string	Action name	logout
secret	string	Agent secret key	1245
agent	string	Agent name	hat
username	string	Username	test01

#### 3.8.2 Response XML (Example)

##### Success

Request example:

http://apiweb.mywinday.com/api.aspx?secret=1245&agent=hat&username=test01&action=logout

```
<?xml version="1.0" encoding="UTF-8"?>
<response>
  <errcode>0</errcode>
  <errtext/>
  <result/>
</response>
```

##### Error

```
<?xml version="1.0" encoding="UTF-8"?>
<response>
  <errcode>2</errcode>
  <errtext>Invalid secret</errtext>
  <result/>
</response>
```

### 3.9 check\_payment

This action is to check payment for member.

#### 3.9.1 Request Parameter

http://<host>/api.aspx?secret=<secret>&action=check\_payment&agent=<agent>&username=<username>&serial=001

Parameter	Data Type	Description	Example
action	string	Action name	check_payment
secret	string	Agent secret key	1245
agent	string	Agent name	hat
username	string	Username. Use empty string to check all user.	test01
serial	string	Reference number	001

#### 3.9.2 Response XML (Example)

##### Success

Request example:

http://api.mywinday.com/api.aspx?secret=1245&agent=hat&username=test01&action=check\_payment&serial=01

```
<?xml version="1.0" encoding="UTF-8"?>
<response>
  <errcode>0</errcode>
  <errtext/>
  <result>
    <payment>
      <username>hattest01</username>
      <amount>100</amount>
    </payment>
  </result>
</response>
```

##### Error

Request example:

http://apiweb.mywinday.com/api.aspx?secret=1245&agent=hat&username=test01&action=check\_payment&serial=019

```
<?xml version="1.0" encoding="UTF-8"?>
<response>
  <errcode>1</errcode>
  <errtext>No result</errtext>
  <result/>
</response>
```

### 3.10 check\_online

This action is to check online member.

#### 3.10.1 Request Parameter

http://<host>/api.aspx?secret=<secret>&action=check\_online&agent=<agent>&username=<username>

Parameter	Data Type	Description	Example
action	string	Action name	check_online
secret	string	Agent secret key	1245
agent	string	Agent name	hat
username	string	Username. Use empty string to check all user.	test01

#### 3.10.2 Response XML (Example)

##### Success

Request example:

http://api.mywinday.com/api.aspx?secret=1245&agent=hat&username=&action=check\_online

(List of Member Online)

```
<?xml version="1.0" encoding="UTF-8"?>
<response>
  <errcode>0</errcode>
  <errtext/>
  <result>tees,test,test01,test02,test04,test05</result>
</response>
```

(No Member Online)

```
<?xml version="1.0" encoding="UTF-8"?>
<response>
  <errcode>0</errcode>
  <errtext/>
  <result/>
</response>
```

##### Error

```
<?xml version="1.0" encoding="UTF-8"?>
<response>
  <errcode>2</errcode>
  <errtext>Invalid secret</errtext>
  <result/>
</response>
```

### 3.11 parlay

This action is to list out parlay ticket detail based on ticket id.

#### 3.11.1 Request Parameter

http://<host>/api.aspx?secret=<secret>&action=parlay&agent=<agent>&ticket\_id=PAR753983515&lang=ZH-CN

Parameter	Data Type	Description	Example
action	string	Action name	parlay
secret	string	Agent secret key	1245
agent	string	Agent name	hat
lang	string	[optional] Language. Default EN-US	EN-US, ZH-CN, ZH-TW, JA-JP, TH-TH, VI-VN, KO-KR
ticket_id	string	Ticket id	PAR753983515

#### 3.11.2 Response XML (Example)

##### Success

Request example:

http://api.mywinday.com/api.aspx?secret=1245&agent=hat&action=parlay&ticket\_id=PAR753983515



```

<?xml version="1.0" encoding="UTF-8"?>
<response>
  <errcode>0</errcode>
  <errtext></errtext>
  <result>
    <ticket>
      <parent>PAR753983515</parent>
      <id>24815741</id>
      <u>test01</u>
      <league>225</league>
      <home>10629</home>
      <away>10649</away>
      <status>N</status>
      <game>HDP</game>
      <odds>1.87</odds>
      <side>1</side>
      <info>+0</info>
      <half>0</half>
      <matchdate>07:00PM</matchdate>
      <runscore></runscore>
      <score>0-0</score>
      <res>D</res>
      <matchdatetime>2018-04-21 10:09:00</matchdatetime>
      <leaguename><![CDATA[    MAGNUM 1ST ]]></leaguename>
      <homename><![CDATA[MAGNUM {BIG} 1ST]]></homename>
      <awayname><![CDATA[MAGNUM {SMALL} 1ST]]></awayname>
    </ticket>
    .
    .
    .
  </result>
</response>

```

\* Refer 4.1.2 Parlay (PAR) for more information.

## Error

```

<?xml version="1.0" encoding="UTF-8"?>
<response>
  <errcode>2</errcode>
  <errtext>Invalid secret</errtext>
  <result/>
</response>

```

### 3.12 step

This action is to list out step ticket detail based on ticket id.

#### 3.12.1 Request Parameter

http://<host>/api.aspx?secret=<secret>&action=step&agent=<agent>&ticket\_id=PAS753983515&lang=ZH-CN

Parameter	Data Type	Description	Example
action	string	Action name	step
secret	string	Agent secret key	1245
agent	string	Agent name	hat
lang	string	[optional] Language. Default EN-US	EN-US, ZH-CN, ZH-TW, JA-JP, TH-TH, VI-VN, KO-KR
ticket_id	string	Ticket id	PAS753983515

#### 3.12.2 Response XML (Example)

##### Success

Request example:

http://api.mywinday.com/api.aspx?secret=1245&action=step&agent=hat&ticket\_id=PAS753986064

```

<?xml version="1.0" encoding="UTF-8"?>
<response>
  <errcode>0</errcode>
  <errtext></errtext>
  <result>
    <ticket>
      <parent>PAS753986064</parent>
      <id>1</id>
      <u>test03</u>
      <league>225</league>
      <home>10629</home>
      <away>10649</away>
      <status>N</status>
      <game>HDP</game>
      <odds>1.68</odds>
      <side>1</side>
      <info>+0</info>
      <half>0</half>
      <matchdate>07:00PM</matchdate>
      <runscore></runscore>
      <score>0-0</score>
      <res>D</res>
      <matchdatetime>2018-04-21 10:09:00</matchdatetime>
      <leaguename><![CDATA[    MAGNUM 1ST ]]></leaguename>
      <homename><![CDATA[MAGNUM {BIG} 1ST]]></homename>
      <awayname><![CDATA[MAGNUM {SMALL} 1ST]]></awayname>
    </ticket>
    .
    .
    .
  </result>
</response>

```

\* Refer 4.1.3 STEP (PAS) for more information.

## Error

```

<?xml version="1.0" encoding="UTF-8"?>
<response>
  <errcode>2</errcode>
  <errtext>Invalid secret</errtext>
  <result/>
</response>

```

### 3.13 team

This action is to display team name based on team id.

#### 3.13.1 Request Parameter

http://<host>/api.aspx?secret=<secret>&action=team&agent=<agent>&team\_id=1024

Parameter	Data Type	Description	Example
action	string	Action name	team
secret	string	Agent secret key	1245
agent	string	Agent name	hat
team_id	int	Team id	1024

#### 3.13.2 Response XML (Example)

##### Success

Request example:

http://api.mywinday.com/api.aspx?secret=1245&agent=hat&action=team&team\_id=1024

```

<?xml version="1.0" encoding="UTF-8"?>
<response>
  <errcode>0</errcode>
  <errtext></errtext>
  <result>
    <name>
      <lang>en-US</lang>
      <txt><![CDATA[Kashiwa Reysol]]></txt>
    </name>
    <name>
      <lang>zh-CN</lang>
      <txt><![CDATA[柏雷素尔]]></txt>
    </name>
    <name>
      <lang>zh-TW</lang>
      <txt><![CDATA[柏雷素尔]]></txt>
    </name>
    <name>
      <lang>ja-JP</lang>
      <txt><![CDATA[Kashiwa Reysol]]></txt>
    </name>
    <name>
      <lang>th-TH</lang>
      <txt><![CDATA[กาชิวา เรย์โซล]]></txt>
    </name>
    <name>
      <lang>vi-VN</lang>
      <txt><![CDATA[Kashiwa Reysol]]></txt>
    </name>
    <name>
      <lang>ko-KR</lang>
      <txt><![CDATA[Kashiwa Reysol]]></txt>
    </name>
  </result>
</response>

```

## Error

```

<?xml version="1.0" encoding="UTF-8"?>
<response>
  <errcode>2</errcode>
  <errtext>Invalid secret</errtext>
  <result/>
</response>

```

### 3.14 league

This action is to display team name league on league id.

#### 3.14.1 Request Parameter

http://<host>/api.aspx?secret=<secret>&action=league&agent=<agent>&league\_id=500

Parameter	Data Type	Description	Example
action	string	Action name	league
secret	string	Agent secret key	1245
agent	string	Agent name	hat
league_id	int	League id	500

#### 3.14.2 Response XML (Example)

##### Success

Request example:

http://api.mywinday.com/api.aspx?secret=1245&agent=hat&action=league&league\_id=500

```
<?xml version="1.0" encoding="UTF-8"?>
<response>
  <errcode>0</errcode>
  <errtext></errtext>
  <result>
    <name>
      <lang>en-US</lang>
      <txt><![CDATA[ MALAYSIA SABAH 88 4D]]></txt>
    </name>
    <name>
      <lang>zh-CN</lang>
      <txt><![CDATA[沙巴彩 4D]]></txt>
    </name>
    <name>
      <lang>zh-TW</lang>
      <txt><![CDATA[沙巴彩 4D]]></txt>
    </name>
    <name>
      <lang>ja-JP</lang>
      <txt><![CDATA[ MALAYSIA SABAH 88 4D]]></txt>
    </name>
    <name>
      <lang>th-TH</lang><txt>
      <![CDATA[ MALAYSIA SABAH 88 4D]]></txt>
    </name>
    <name>
      <lang>vi-VN</lang>
      <txt><![CDATA[ MALAYSIA SABAH 88 4D]]></txt>
    </name>
    <name>
      <lang>ko-KR</lang>
      <txt><![CDATA[ MALAYSIA SABAH 88 4D]]></txt>
    </name>
  </result>
</response>
```

## Error

```
<?xml version="1.0" encoding="UTF-8"?>
<response>
  <errcode>2</errcode>
  <errtext>Invalid secret</errtext>
  <result/>
</response>
```

### 3.15 sportstype

This action is to display sports type based on sportstype id.

#### 3.15.1 Request Parameter

http://<host>/api.aspx?secret=<secret>&action=sportstype&agent=<agent>&sportstype\_id=<sportstype\_id>

Parameter	Data Type	Description	Example
action	string	Action name	sportstype
secret	string	Agent secret key	1245
agent	string	Agent name	hat
sportstype_id	int	Game id	10

#### 3.15.2 Response XML (Example)

##### Success

Request example:

http://api.mywinday.com/api.aspx?secret=1245&agent=hat&action=sportstype&sportstype\_id=10

```
<?xml version="1.0" encoding="UTF-8"?>
<response>
  <errcode>0</errcode>
  <errtext></errtext>
  <result>
    <name>
      <lang>en-US</lang>
      <txt><![CDATA[Soccer - Outright]]></txt>
    </name>
    <name>
      <lang>zh-CN</lang>
      <txt><![CDATA[足球 - 優勝冠軍]]></txt>
    </name>
    <name>
      <lang>zh-TW</lang>
      <txt><![CDATA[Soccer - Outright]]></txt>
    </name>
    <name>
      <lang>ja-JP</lang>
      <txt><![CDATA[Soccer - Outright]]></txt>
    </name>
    <name>
      <lang>th-TH</lang>
      <txt><![CDATA[Soccer - Outright]]></txt>
    </name>
    <name>
      <lang>vi-VN</lang>
      <txt><![CDATA[Soccer - Outright]]></txt>
    </name>
    <name>
      <lang>ko-KR</lang>
      <txt><![CDATA[Soccer - Outright]]></txt>
    </name>
  </result>
</response>
```



## Error

```
<?xml version="1.0" encoding="UTF-8"?>
<response>
  <errcode>2</errcode>
  <errtext>Invalid secret</errtext>
  <result/>
</response>
```

### 3.16 match\_count

This action is to display match count.

#### 3.16.1 Request Parameter

http://<host>/api.aspx?secret=<secret>&action=match\_count&agent=<agent>

Parameter	Data Type	Description	Example
action	string	Action name	match_count
secret	string	Agent secret key	1245
agent	string	Agent name	hat

#### 3.16.2 Response XML (Example)

##### Success

Request example:

http://api.mywinday.com/api.aspx?secret=1245&agent=hat&action=match\_count

```
<?xml version="1.0" encoding="UTF-8"?>
<response>
  <errcode>0</errcode>
  <errtext/>
  <result>
    <count>
      <live>28</live>
      <Soccer>324</Soccer>
    </count>
  </result>
</response>
```

##### Error

```
<?xml version="1.0" encoding="UTF-8"?>
<response>
  <errcode>2</errcode>
  <errtext>Invalid secret</errtext>
  <result/>
</response>
```

### 3.17 fetch

This action is to display all fetch tickets. (Maximum 100 tickets)

#### 3.17.1 Request Parameter

http://<host>/api.aspx?secret=<secret>&action=fetch&agent=<agent>

Parameter	Data Type	Description	Example
action	string	Action name	fetch
secret	string	Agent secret key	1245
agent	string	Agent name	
lang	string	[optional] Language. Default EN-US	EN-US, ZH-CN, ZH-TW, JA-JP, TH-TH, VI-VN, KO-KR

#### 3.17.2 Response XML (Example)

##### Success

Request example:

http://api.mywinday.com/api.aspx?secret=1245&agent=hat&action=fetch

```

<?xml version="1.0" encoding="UTF-8"?>
<response>
  <errcode>0</errcode>
  <errtext></errtext>
  <result>
    <ticket>
      <fid>638</fid>
      <id>RAQ00001042</id>
      <t>2020-07-22 15:47:04.373</t>
      <u>999</u>
      <b>0.9</b>
      <w>-0.9</w>
      <a>0.9</a>
      <c>0</c>
      <ip></ip>
      <league>-52</league>
      <home>-52</home>
      <away>-52</away>
      <status>N</status>
      <game>RAQ</game>
      <odds>0</odds>
      <side></side>
      <info></info>
      <half>0</half>
      <trandate>2017-09-21 17:35:47</trandate>
      <workdate>2017-09-21 00:00:00</workdate>
      <matchdate></matchdate>
      <runscore></runscore>
      <score>0-0</score>
      <htscore>0-0</htscore>
      <flg></flg>
      <res>LA</res>
      <sportstype>116</sportstype>
      <oddstype></oddstype>
      <matchdatetime>2017-09-21 00:00:00</matchdatetime>
      <curcode>MYR</curcode>
      <leaguename><![CDATA[ACE333]]></leaguename>
      <homename><![CDATA[ACE333]]></homename>
      <awayname><![CDATA[ACE333]]></awayname>
      <groupid></groupid>
    </ticket>
    .
    .
    .
  </result>
</response>

```

\* Refer 4.1.1 Ticket for more information.

## Error

```

<?xml version="1.0" encoding="UTF-8"?>
<response>
  <errcode>2</errcode>
  <errtext>Invalid secret</errtext>
  <result/>
</response>

```

### 3.18 fetch\_result

This action is to display fetch tickets which already have result. (Maximum 100 tickets)

#### 3.18.1 Request Parameter

http://<host>/api.aspx?secret=<secret>&action=fetch\_result&agent=<agent>

Parameter	Data Type	Description	Example
action	string	Action name	fetch_result
secret	string	Agent secret key	1245
agent	string	Agent name	hat
lang	string	[optional] Language. Default EN-US	EN-US, ZH-CN, ZH-TW, JA-JP, TH-TH, VI-VN, KO-KR

#### 3.18.2 Response XML (Example)

##### Success

Request example:

http://api.mywinday.com/api.aspx?secret=1245&agent=hat&action=fetch\_result

```

<?xml version="1.0" encoding="UTF-8"?>
<response>
  <errcode>0</errcode>
  <errtext></errtext>
  <result>
    <ticket>
      <fid>638</fid>
      <id>RAQ00001042</id>
      <t>2020-07-22 15:47:04.373</t>
      <u>999</u>
      <b>0.9</b>
      <w>-0.9</w>
      <a>0.9</a>
      <c>0</c>
      <ip></ip>
      <league>-52</league>
      <home>-52</home>
      <away>-52</away>
      <status>N</status>
      <game>RAQ</game>
      <odds>0</odds>
      <side></side>
      <info></info>
      <half>0</half>
      <trandate>2017-09-21 17:35:47</trandate>
      <workdate>2017-09-21 00:00:00</workdate>
      <matchdate></matchdate>
      <runscore></runscore>
      <score>0-0</score>
      <htscore>0-0</htscore>
      <flg></flg>
      <res>LA</res>
      <sportstype>116</sportstype>
      <oddstype></oddstype>
      <matchdatetime>2017-09-21 00:00:00</matchdatetime>
      <curcode>MYR</curcode>
      <leaguename><![CDATA[ACE333]]></leaguename>
      <homename><![CDATA[ACE333]]></homename>
      <awayname><![CDATA[ACE333]]></awayname>
      <groupid></groupid>
    </ticket>
    .
    .
    .
  </result>
</response>

```

## Error

```

<?xml version="1.0" encoding="UTF-8"?>
<response>
  <errcode>2</errcode>
  <errtext>Invalid secret</errtext>
  <result/>
</response>

```

### 3.19 mark\_fetched

This action is to delete tickets.

#### 3.19.1 Request Parameter

http://<host>/api.aspx?secret=<secret>&action=mark\_fetched&agent=<agent>&fetch\_ids=<fetch\_ids>

Parameter	Data Type	Description	Example
action	string	Action name	mark_fetched
secret	string	Agent secret key	1245
agent	string	Agent name	hat
fetch_ids	string	Fetch id list	1234568598,1234568599

#### 3.19.2 Response XML (Example)

##### Success

Request example:

http://api.mywinday.com/api.aspx?secret=1245&agent=hat&action=mark\_fetched&fetch\_ids=1234568598,1234568599

```
<?xml version="1.0" encoding="UTF-8"?>
<response>
  <errcode>0</errcode>
  <errtext/>
  <result/>
</response>
```

##### Error

Request example:

http://api.mywinday.com/api.aspx?secret=1245&agent=hat&action=mark\_fetched&fetch\_ids=1239999999999

```
<?xml version="1.0" encoding="UTF-8"?>
<response>
  <errcode>100</errcode>
  <errtext>Invalid fetch_ids : 1239999999999</errtext>
  <result/>
</response>
```

### 3.20 fetch2

This action is to display all fetch tickets. (Maximum 500 tickets)

#### 3.20.1 Request Parameter

http://<host>/api.aspx?secret=<secret>&action=fetch2&agent=<agent>&lang=ZH-CN

Parameter	Data Type	Description	Example
action	string	Action name	fetch2
secret	string	Agent secret key	1245
agent	string	Agent name	hat
lang	string	[optional] Language. Default EN-US	EN-US, ZH-CN, ZH-TW, JA-JP, TH-TH, VI-VN, KO-KR

#### 3.20.2 Response XML (Example)

##### Success

Request example:

http://api.mywinday.com/api.aspx?secret=1245&agent=hat&action=fetch2



```

<?xml version="1.0" encoding="UTF-8"?>
<response>
  <errcode>0</errcode>
  <errtext></errtext>
  <result>
    <ticket>
      <fid>638</fid>
      <id>RAQ00001042</id>
      <t>2020-07-22 15:47:04.373</t>
      <u>999</u>
      <b>0.9</b>
      <w>-0.9</w>
      <a>0.9</a>
      <c>0</c>
      <ip></ip>
      <league>-52</league>
      <home>-52</home>
      <away>-52</away>
      <status>N</status>
      <game>RAQ</game>
      <odds>0</odds>
      <side></side>
      <info></info>
      <half>0</half>
      <trandate>2017-09-21 17:35:47</trandate>
      <workdate>2017-09-21 00:00:00</workdate>
      <matchdate></matchdate>
      <runscore></runscore>
      <score>0-0</score>
      <htscore>0-0</htscore>
      <flg></flg>
      <res>LA</res>
      <sportstype>116</sportstype>
      <oddstype></oddstype>
      <matchdatetime>2017-09-21 00:00:00</matchdatetime>
      <curcode>MYR</curcode>
      <leaguename><![CDATA[ACE333]]></leaguename>
      <homename><![CDATA[ACE333]]></homename>
      <awayname><![CDATA[ACE333]]></awayname>
      <groupid></groupid>
    </ticket>
    .
    .
    .
  </result>
</response>

```

\* Refer 4.1.1 Ticket for more information.

## Error

```

<?xml version="1.0" encoding="UTF-8"?>
<response>
  <errcode>2</errcode>
  <errtext>Invalid secret</errtext>
  <result/>
</response>

```

### 3.21 fetch\_result2

This action is to display fetch tickets which already have result. (Maximum 500 tickets)

#### 3.21.1 Request Parameter

http://<host>/api.aspx?secret=<secret>&action=fetch\_result2&agent=<agent>&lang=ZH-CN

Parameter	Data Type	Description	Example
action	string	Action name	fetch_result2
secret	string	Agent secret key	1245
agent	string	Agent name	hat
lang	string	[optional] Language. Default EN-US	EN-US, ZH-CN, ZH-TW, JA-JP, TH-TH, VI-VN, KO-KR

#### 3.21.2 Response XML (Example)

##### Success

Request example:

http://api.mywinday.com/api.aspx?secret=1245&agent=hat&action=fetch\_result2

```

<?xml version="1.0" encoding="UTF-8"?>
<response>
  <errcode>0</errcode>
  <errtext></errtext>
  <result>
    <ticket>
      <fid>638</fid>
      <id>RAQ00001042</id>
      <t>2020-07-22 15:47:04.373</t>
      <u>999</u>
      <b>0.9</b>
      <w>-0.9</w>
      <a>0.9</a>
      <c>0</c>
      <ip></ip>
      <league>-52</league>
      <home>-52</home>
      <away>-52</away>
      <status>N</status>
      <game>RAQ</game>
      <odds>0</odds>
      <side></side>
      <info></info>
      <half>0</half>
      <trandate>2017-09-21 17:35:47</trandate>
      <workdate>2017-09-21 00:00:00</workdate>
      <matchdate></matchdate>
      <runscore></runscore>
      <score>0-0</score>
      <htscore>0-0</htscore>
      <flg></flg>
      <res>LA</res>
      <sportstype>116</sportstype>
      <oddstype></oddstype>
      <matchdatetime>2017-09-21 00:00:00</matchdatetime>
      <curcode>MYR</curcode>
      <leaguename><![CDATA[ACE333]]></leaguename>
      <homename><![CDATA[ACE333]]></homename>
      <awayname><![CDATA[ACE333]]></awayname>
      <groupid></groupid>
    </ticket>
    .
    .
    .
  </result>
</response>

```

## Error

```

<?xml version="1.0" encoding="UTF-8"?>
<response>
  <errcode>2</errcode>
  <errtext>Invalid secret</errtext>
  <result/>
</response>

```

### 3.22 fetch\_group

This action is to display all fetch group tickets. (Maximum 100 tickets)

#### 3.22.1 Request Parameter

http://<host>/api.aspx?secret=<secret>&action=fetch\_group&agent=<agent>

Parameter	Data Type	Description	Example
action	string	Action name	fetch_group
secret	string	Agent secret key	1245
agent	string	Agent name	
lang	string	[optional] Language. Default EN-US	EN-US, ZH-CN, ZH-TW, JA-JP, TH-TH, VI-VN, KO-KR

#### 3.22.2 Response XML (Example)

##### Success

Request example:

http://api.mywinday.com/api.aspx?secret=1245&agent=hat&action=group

```

<?xml version="1.0" encoding="UTF-8"?>
<response>
  <errcode>0</errcode>
  <errtext></errtext>
  <result>
    <ticket>
      <fid>36</fid>
      <id>PAM4618561925</id>
      <t>2020-12-16 15:45:35.520</t>
      <u>test01</u>
      <b>55</b>
      <w>0</w>
      <a>0</a>
      <c>0</c>
      <ip>1.32.202.111</ip>
      <league>23854</league>
      <home>86464</home>
      <away>1024</away>
      <status>N</status>
      <game>PAM</game>
      <odds>68.036</odds>
      <side></side>
      <info></info>
      <half>0</half>
      <trandate>2020-12-16 15:45:35</trandate>
      <workdate>2020-12-16 00:00:00</workdate>
      <matchdate>06:00PM</matchdate>
      <runscore></runscore>
      <score></score>
      <htscore></htscore>
      <flg></flg>
      <res>P</res>
      <sportstype>2</sportstype>
      <oddstype></oddstype>
      <matchdatetime>2020-12-16 18:00:00</matchdatetime>
      <curcode>MYR</curcode>
      <leaguename><![CDATA[JAPAN J1 LEAGUE]]></leaguename>
      <homename><![CDATA[Sanfrecce Hiroshima]]></homename>
      <awayname><![CDATA[Kashiwa Reysol]]></awayname>
      <groupid></groupid>
    </ticket>
  </result>
</response>

```

\* Refer 4.1.1 Ticket for more information.

## Error

```

<?xml version="1.0" encoding="UTF-8"?>
<response>
  <errcode>2</errcode>
  <errtext>Invalid secret</errtext>
  <result/>
</response>

```

### 3.23 mark\_fetched\_group

This action is to delete tickets.

#### 3.23.1 Request Parameter

http://<host>/api.aspx?secret=<secret>&action=mark\_fetched\_group&agent=<agent>&fetch\_ids=<fetch\_ids>

Parameter	Data Type	Description	Example
action	string	Action name	mark_fetched_group
secret	string	Agent secret key	1245
agent	string	Agent name	hat
fetch_ids	string	Fetch id list	1234568598,1234568599

#### 3.23.2 Response XML (Example)

##### Success

Request example:

http://api.mywinday.com/api.aspx?secret=1245&agent=hat&action=mark\_fetched\_group&fetch\_ids=1234568598,1234568599

```
<?xml version="1.0" encoding="UTF-8"?>
<response>
  <errcode>0</errcode>
  <errtext/>
  <result/>
</response>
```

##### Error

Request example:

http://api.mywinday.com/api.aspx?secret=1245&agent=hat&action=mark\_fetched\_group&fetch\_ids=123999999999

```
<?xml version="1.0" encoding="UTF-8"?>
<response>
  <errcode>100</errcode>
  <errtext>Invalid fetch_ids : 123999999999</errtext>
  <result/>
</response>
```

### 3.24 group

This action is to display all fetch tickets under the group. (Maximum 100 tickets)

#### 3.24.1 Request Parameter

http://<host>/api.aspx?secret=<secret>&action=group&agent=<agent>&group\_id=<group\_id>

Parameter	Data Type	Description	Example
action	string	Action name	group
secret	string	Agent secret key	1245
agent	string	Agent name	
group_id	string	Group Id	PAM4618561925
lang	string	[optional] Language. Default EN-US	EN-US, ZH-CN, ZH-TW, JA-JP, TH-TH, VI-VN, KO-KR

#### 3.24.2 Response XML (Example)

##### Success

Request example:

http://api.mywinday.com/api.aspx?secret=1245&agent=hat&action=group&group\_id=PAM4618561925

```

<?xml version="1.0" encoding="UTF-8"?>
<response>
  <errcode>0</errcode>
  <errtext></errtext>
  <result>
    <ticket>
      <id>PAR4618561963</id>
      <u>test01</u>
      <b>5</b>
      <w>-0.6</w>
      <a>5</a>
      <c>0</c>
      <ip></ip>
      <league>23854</league>
      <home>7644</home>
      <away>5050</away>
      <status>N</status>
      <game>PAR</game>
      <odds>3.467</odds>\
      <side></side>
      <info></info>
      <half>0</half>
      <trandate>2020-12-16 15:45:35</trandate>
      <workdate>2020-12-16 00:00:00</workdate>
      <matchdate>06:00PM</matchdate>
      <runscore></runscore>
      <score>3-1</score>
      <htscore>0-1</htscore>
      <flg></flg>
      <res>WA</res>
      <sportstype>2</sportstype>
      <oddstype></oddstype>
      <matchdatetime>2020-12-16 18:00:00</matchdatetime>
      <curcode>MYR</curcode>
      <leaguename><![CDATA[JAPAN J1 LEAGUE]]></leaguename>
      <homename><![CDATA[Kawasaki Frontale]]></homename>
      <awayname><![CDATA[Urawa Red Diamonds]]></awayname>
      <groupid>PAM4618561925</groupid>
    </ticket>
    .
    .
    .
  </result>
</response>

```

\* Refer 4.1.1 Ticket for more information.

## Error

```

<?xml version="1.0" encoding="UTF-8"?>
<response>
  <errcode>2</errcode>
  <errtext>Invalid secret</errtext>
  <result/>
</response>

```



### 3.25 check\_ventran (For One Wallet use)

This action is to check transaction based on ventran id.

#### 3.25.1 Request Parameter

http://<host>/api.aspx?secret=<secret>&action=check\_ventran&agent=<agent>&ventran\_id=ABCD123456

Parameter	Data Type	Description	Example
action	string	Action name	check_ventran
secret	string	Agent secret key	1245
agent	string	Agent name	hat
ventran_id	string	Transaction id	02150451QXJYUM

#### 3.25.2 Response XML (Example)

##### Success

Request example:

http://api.mywinday.com/api.aspx?secret=1245&action=check\_ventran&agent=hat&ventran\_id=02150451QXJYUM

```
<?xml version="1.0" encoding="UTF-8"?>
<response>
  <errcode>0</errcode>
  <errtext></errtext>
  <result>75398687</result>
</response>
```

##### Error

```
<?xml version="1.0" encoding="UTF-8"?>
<response>
  <errcode>2</errcode>
  <errtext>Invalid secret</errtext>
  <result/>
</response>
```

## 4. Extra Information

### 4.1 Fetch Ticket Info

#### 4.1.1 Ticket

Parameter	Description
fid	Fetch Id (empty if not action=fetch)
id	Ticket Id
t	Last modified date time up to millisecond
u	Username
b	Bet Amount
w	Win Amount
a	Commission Amount  $a = \text{CommissionAmt} * 100$ $\text{CommissionAmt} = \text{BetAmt} * \text{ABS}(\text{WinRate}) / 100$
c	Commission % (value = 0.4 means 0.4%)
ip	IP address
league	League Id
home	Home Id
away	Away Id
status	N:Auto-Accept A:Accepted R:Reject C:Cancel RG:RejectGoal RP:RejectPenalty RR:RejectRedCard RA:RejectAbnormalBet
game	HDP,1X2,OU,OE,CSR,TG,FLG,HFT,DC,PAR,ORT, PAS
odds	Odds
side	1:Home/Over/Odd 2:Away/Under/Even X:Draw
info	Handicap, over/under, correct score, total goal ...etc
half	0:Full Time 1:First Half
trandate	Transaction date
workdate	Working date
matchdate	Match date
runscore	Running Score (empty if not running match)
score	Score (empty if not match over)
htscore	Half time score (empty if not match over & HFT)
flg	First/last goal result (empty if not match over & not FLG)
res	P:NotMatchOver WA:WinAll LA:LostAll WH:WinHalf LH:LostHalf D:Draw
sportstype	SportsType Id
oddstype	MY, HK, ID, EU
ventransid	VenTransId
matchdatetime	MatchDateTime
curcode	Currency Code
league name	League name
home name	Home team name
away name	Away team name
groupid	Group Id (empty if not parlay grouping)

## 4.1.2 Parlay (PAR)

Parameter	Description
parent	Parent ticket Id
id	Parlay Id
u	Username
league	League Id
home	Home Id
away	Away Id
status	N:Auto-Accept A:Accepted R:Reject C:Cancel
game	HDP,1X2,OU,OE,CSR,TG,FLG,HFT,PAR,ORT
odds	Odds
side	1:Home/Over/Odd 2:Away/Under/Even X:Draw
info	Handicap, over/under, correct score, total goal ...etc
half	0:Full Time 1:First Half
matchdate	Match date
runscore	Running Score (empty if not running match)
score	Score (empty if not match over)
res	P:NotMatchOver WA:WinAll LA:LostAll WH:WinHalf LH:LostHalf D:Draw
matchdatetime	MatchDateTime
leaguename	League name
homename	Home team name
awayname	Away team name

## 4.1.3 STEP (PAS)

Parameter	Description
parent	Parent ticket Id
id	Step Id
u	Username
league	League Id
home	Home Id
away	Away Id
status	N:Auto-Accept A:Accepted R:Reject C:Cancel
game	HDP,1X2,OU,OE,CSR,TG,FLG,HFT,PAR,ORT
odds	Odds
side	1:Home/Over/Odd 2:Away/Under/Even X:Draw
info	Handicap, over/under, correct score, total goal ...etc
half	0:Full Time 1:First Half
matchdate	Match date
runscore	Running Score (empty if not running match)
score	Score (empty if not match over)
res	P:NotMatchOver WA:WinAll LA:LostAll WH:WinHalf LH:LostHalf D:Draw
matchdatetime	MatchDateTime
leaguename	League name
homename	Home team name
awayname	Away team name

## 4.1.4 Reference

Type	Parameter	Description
HDP – Handicap	side	1=Home, 2=Away
	info	Handicap, minus means home give. Ex: +2.5, -0.75
1X2 – 1x2	side	1=Home 2=Away X=Draw
OU – Over / Under	side	1=Over, 2=Under
	info	Total goal
OE – Odds / Even	side	1=Odd, 2=Even
CSR – Correct Score	info	Correct score. Ex: 2-1, 0-0
TG – Total Goal	info	Total goal
FLG– First Goal / Last Goad	info	NG=No goal, HLG=Home last goal, ALG=Away last goal, HFG=Home first goal, AFG=Away first goal
	flg	First goal / last goal result
HFT – Half Time / Full Time	info	DD, DH, DA, HD, HH, HA, AD, AH, AA (D=Draw, H=Home, A=Away)
	htscore	Half time score
PAR – Parlay	Details in sub-tickets.	Details in sub-tickets.
ORT – Outright	league	Bet description, ex: NBA Champion
	home	Bet choice, ex: LA Lakers
Double Chance	info	X2, 1X, 12 (X=Draw, 1=Home, 2=Away)
PAS – STEP	Details in sub-tickets.	Details in sub-tickets.

## 5. Update History

### 5.1 Version July 24, 2019

5.1.1 Refer [3.2 Update](#)

5.1.1.1 Details

Add max5 = Max1D, max6 = Max2D, max7 = Max3D

### 5.2 Version March 05, 2019

5.2.1 Refer [4.1.1 Ticket](#)

5.2.1.1 Details

Add Danger status > RA

### 5.3 Version April 20, 2020

5.3.1 Refer [3.3 Update2](#)

5.3.1.1 Details

Add max8 = MaxLAA, max9 = MaxLAB, lim5 = MatchLimitLAA, lim6 = MatchLimitLAB  
(Perdana3D BSOE&AT/S and Perdana3D 3D)

5.3.2 Refer [3.7 Login](#)

5.3.2.1 Details

No longer need key in host URL.

HK

apiweb.mywinday.com / apissl.mywinday.com /  
apiweb2.mywinday.com / apissl2.mywinday.com  
changed to http://apid.mywinday.com

CN

apiwebcn.mywinday.com / apisslcn.mywinday.com  
changed to http://apir.mywinday.com

Example

http://apid.mywinday.com/api.aspx?secret=xxx&agent=xxxx&username=xxx&action=login&language=EN-US&accType=HK&ref=xxxx

http://apir.mywinday.com/api.aspx?secret=xxx&agent=xxxx&username=xxx&action=login&language=EN-US&accType=HK&ref=xxxx

5.3.3 Refer [3.13](#), [3.14](#), [3.15](#)

5.3.3.1 Details

Response data return with CDATA format.

### 5.4 Version August 3, 2020

5.4.1 Refer [3.20](#), [3.21](#)

5.4.1.1 Details

Add Action fetch2, fetch\_result2. Both actions are maximum 500 tickets.

### 5.5 Version January 19, 2021

5.5.1 Refer [3.22](#), [3.23](#), [3.24](#)

5.5.1.1 Details

Add Action fetch\_group, mark\_fetched\_group, group.