
ML Assignment 1: Perceptron

Anirudh Agrawal
2018A7PS0099H

Aviral Agarwal
2018A7PS0192H

Vikramjeet Das
2018A7PS0280H

1 Introduction

In this assignment, we implement Fischer's Linear Discriminant, it is used for supervised learning in solving classification problems. Given the data points in M dimensional space, we project all those points to D dimensions and then try to find out a discriminant function to classify our points using a threshold found by calculating the intersection point between the normal distribution followed by the projected points. In this assignment we were given data points in $3-D$ and we projected it to $1-D$ and found out the threshold.

2 Implementation

After solving the optimisation problem:

$$\max \frac{(W^T M_1 - W^T M_2)^2}{s_1^2 + s_2^2}$$

We get

$$W \propto S_W^{-1}(M_1 - M_2), \text{ where}$$

$$S_W = \sum_{k=1}^2 S_k, \text{ and}$$

$$S_k = \sum_{n \in c_k} (x_n - M_k)(x_n - M_k)^T$$

The threshold can be found by solving the quadratic equation $Ax^2 + Bx + C = 0$, where

$$A = -\frac{1}{\sigma_1^2} + \frac{1}{\sigma_2^2}$$

$$B = 2\left(\frac{\mu_1}{\sigma_1^2} - \frac{\mu_2}{\sigma_2^2}\right)$$

$$C = \frac{\mu_2^2}{\sigma_2^2} - \frac{\mu_1^2}{\sigma_1^2} + \log\left(\frac{\sigma_2^2}{\sigma_1^2}\right)$$

The algorithm can be roughly outlined as:

1. Find the individual means for different classes

2. Find S_W

3. Calculate unit vector W

4. Project all the points on to the unit vector by taking the dot product $W^T X$

5. Find the Normal distribution fitting the projected points

6. Find the **threshold** using the intersection point of the normal distribution.

3 Results

Figure 1 shows the original data plot in 3 dimensions along with the decision boundary (in green). All points above the green plane are classified as belonging to *class 1*, while those below the plane are classified as belonging to *class 0*. Figure 3 shows the data points projected to 1-dimension along with normal distributions fit on them and the threshold point.




Figure 1: Scatter plot of the original data in 3-dimensional space along with the decision boundary




Figure 2: Normal distribution fit to each projected cluster. The green line shows the threshold point

The threshold point in **1-D** is 8.122.

The discriminating plane in original dimensions(**3-D**) is : $0.148x_1 + 0.413x_2 - 22.636x_3 = 8.122$