

## CL-II 4 IR

July 22, 2025

```
[ ]: # Implement Agglomerative hierarchical clustering algorithm using  
# appropriate dataset.
```

```
[ ]: '''NAME:Aher Swami Sandip  
ROLL NO.01  
COURSE: AI&DS  
CLASS: BE  
SUB:Computer Laboratory-II (Information Retrival)'''
```

```
[18]: import pandas as pd  
import numpy as np  
import matplotlib.pyplot as plt  
from sklearn.decomposition import PCA  
from sklearn.cluster import AgglomerativeClustering  
from sklearn.preprocessing import StandardScaler, normalize  
from sklearn.metrics import silhouette_score  
import scipy.cluster.hierarchy as shc
```

```
[34]: #Step 2: Loading and Cleaning the data  
df=pd.read_csv("Customer_Data.csv")
```

```
[36]: X.head()
```

```
[36]:
```

	ID	Year_Birth	Education	Marital_Status	Income	Kidhome	Teenhome	\
0	1000	1978	PhD	Together	24342.06	1	0	
1	1001	1991	Master	Widow	51784.68	0	0	
2	1002	1968	Basic	Divorced	65007.28	2	1	
3	1003	1954	Graduation	Widow	52286.31	1	0	
4	1004	1982	PhD	Together	40979.04	1	0	

	Dt_Customer	Recency	MntWines	...	NumWebVisitsMonth	AcceptedCmp3	\
0	01-01-2012	38	373	...	1	1	
1	12-01-2012	90	64	...	8	1	
2	23-01-2012	73	145	...	3	0	
3	03-02-2012	89	223	...	2	1	
4	14-02-2012	18	238	...	1	1	

	AcceptedCmp4	AcceptedCmp5	AcceptedCmp1	AcceptedCmp2	Complain	\
--	--------------	--------------	--------------	--------------	----------	---

0	1	0	0	1	1
1	0	0	0	0	1
2	0	1	1	1	0
3	0	0	1	1	1
4	0	0	0	0	0

	Z_CostContact	Z_Revenue	Response
0	3	11	1
1	3	11	0
2	3	11	1
3	3	11	1
4	3	11	1

[5 rows x 25 columns]

```
[38]: # Handling the missing values
X.ffill(inplace=True)
```

```
[40]: X = df.select_dtypes(include=[float, int])
```

```
[42]: # Scaling the data so that all the features become comparable
scaler = StandardScaler()
X_scaled = scaler.fit_transform(X)
```


```
[44]: X.dropna(inplace=True)
```

```
[46]: # Normalizing the data so that the data approximately
# follows a Gaussian distribution
X_normalized = normalize(X_scaled)
```


```
[48]: # Converting the numpy array into a pandas DataFrame
X_normalized = pd.DataFrame(X_normalized)
```

```
[50]: #Step 4: Reducing the dimensionality of the Data
pca = PCA(n_components = 2)
X_principal = pca.fit_transform(X_normalized)
X_principal = pd.DataFrame(X_principal)
X_principal.columns = ['P1', 'P2']
```


```
[52]: #Step 5: Visualizing the working of the Dendrograms
plt.figure(figsize =(8, 8))
plt.title('Visualising the data')
Dendrogram = shc.dendrogram((shc.linkage(X_principal, method ='ward')))
```



```
[53]: #Step 6: Building and Visualizing the different clustering models for different
      ↪ values of k a) k = 2
ac2 = AgglomerativeClustering(n_clusters = 2)
# Visualizing the clustering
plt.figure(figsize =(6, 6))
plt.scatter(X_principal['P1'], X_principal['P2'],
c = ac2.fit_predict(X_principal), cmap ='rainbow')
plt.show()
```




```
[56]: ac3 = AgglomerativeClustering(n_clusters = 3)
plt.figure(figsize =(6, 6))
plt.scatter(X_principal['P1'], X_principal['P2'],
c = ac3.fit_predict(X_principal), cmap ='rainbow')
plt.show()
```




```
[58]: ac4 = AgglomerativeClustering(n_clusters = 4)


plt.figure(figsize =(6, 6))
plt.scatter(X_principal['P1'], X_principal['P2'],
c = ac4.fit_predict(X_principal), cmap ='rainbow')
plt.show()
```



```
[60]: ac5 = AgglomerativeClustering(n_clusters = 5)
plt.figure(figsize =(6, 6))
plt.scatter(X_principal['P1'], X_principal['P2'], c = ac5.
    ↪fit_predict(X_principal), cmap ='rainbow')
plt.show()
```



```
[62]: ac6 = AgglomerativeClustering(n_clusters = 6)
plt.figure(figsize =(6, 6))
plt.scatter(X_principal['P1'], X_principal['P2'],
c = ac6.fit_predict(X_principal), cmap ='rainbow')
plt.show()
```




```
[64]: #Step 7: Evaluating the different models and Visualizing the
      #results.
      k = [2, 3, 4, 5, 6]

      # Appending the silhouette scores of the different models to the list
      silhouette_scores = []
      silhouette_scores.append(
        silhouette_score(X_principal, ac2.fit_predict(X_principal)))
      silhouette_scores.append(
        silhouette_score(X_principal, ac3.fit_predict(X_principal)))
      silhouette_scores.append(
        silhouette_score(X_principal, ac4.fit_predict(X_principal)))
      silhouette_scores.append(
        silhouette_score(X_principal, ac5.fit_predict(X_principal)))
      silhouette_scores.append(
        silhouette_score(X_principal, ac6.fit_predict(X_principal)))
```



```
[66]: # Plotting a bar graph to compare the results
plt.bar(k, silhouette_scores)
plt.xlabel('Number of clusters', fontsize = 20)
plt.ylabel('S(i)', fontsize = 20)
plt.show()
```



```
[ ]:
```