


## PRODUCT PORTFOLIO – INDUSTRIAL SLC



**S330 Series 2.5" SSD**  
16 - 256GB SLC

SATA



**A270 Series mSATA**  
4 - 64GB SLC  
**A370 Series mSATA**  
8 - 64GB SLC



**F200 & F270 Series CFast**  
1 - 64GB SLC



**C300 Series CF: 128MB - 4GB SLC**  
**C400 Series CF: 128MB - 16GB SLC**  
**C500 Series CF: 2GB - 64GB SLC**  
**C670 Series CF: 4GB - 64GB SLC**

COMPACTFLASH



**D200 Series SD: 128MB - 8GB SLC**  
**D300 Series SD: 1GB - 32GB SLC**




**U300 Series uSD: 512MB - 16GB SLC**  
**U331 Series uSD: 128MB - 4GB SLC**  
**U331A Series uSD: 128MB - 4GB SLC**

SD/microSD



**B270 Series USB**  
128MB - 32GB SLC

USB



**E200 Series eUSB**  
1GB - 32GB SLC  
**E270 Series eUSB**  
128MB - 8GB SLC


## PRODUCT PORTFOLIO – UTILITY (MLC)



**Utility+ 2.5" SSD**  
64GB - 2TB



**Utility mSATA**  
32GB - 1TB  
**Utility+ mSATA**  
32GB - 512GB



**Utility+ M.2**  
2242 or 2280  
64GB - 512GB

SATA

Utility products are cost-effective, industrial-grade MLC solutions, with BOM control, life cycle management and include the support of Delkin's US-based applications and technical team.

Operating Temp Ranges for Utility/Utility+ Products by Form Factor:

Utility SATA:	0 to +70 °C
Utility SD/microSD:	-25 to +85 °C
All Utility+ (inc. eMMC)	-40 to +85 °C




**Utility & Utility+ SD**  
4GB - 128GB  
4 & 8GB pSLC



**Utility & Utility+ microSD**  
4GB - 128GB  
4 & 8GB pSLC

SD / microSD

**G530 Series eMMC**  
100 Ball - 14 x 18 x 1.4mm  
153 Ball - 11.5 x 13 x 1.0mm  
4 - 64GB MLC  
2 - 32GB pSLC



eMMC