FDC-320 with Arduino

Manual

How to operate the FDC-320 with Arduino controller

Reykjavík University

Torfi Þorgrímsson*

QUICK START

DOWNLOAD GIT

Run winget install Git.Git in cmd or powershell on Windows

Run sudo apt install git on Linux

MAKE SURE IT'S BEEN INCLUDED IN THE PATH ENVI-RONMENT VARIABLE

Sometimes on windows winget won't put the git/julia executable in the path variable. It seems to always put it in the start menu so you can find the executable there and add it's path to the PATH environment variable.

DOWNLOAD THE GITHUB REPOSITORY

git clone https://github.com/AwesomeQuest/fdc-320.git

The repo also has a copy of this manual in case you need another copy. Feel free to open an issue or send me an email if you have any problems.

INSTALL JULIA

WINDOWS

Run the following command in powershell or cmd

winget install JuliaLang.Julia

LINUX

Run the following command in your favorite shell

*torfit@gmail.c	om
-----------------	----

curl -fsSL https://install.julialang.org | sh

SETUP ENVIRONMENT

Then open a Julia REPL in the FDC-320 folder as follows

```
julia --project=.
```

And you should see something like this

Install the Serial port package.

```
julia> ]
(fdc-320) pkg> add LibSerialPort
```

Then include the file FDC3201ib.jl

```
julia> include("FDC320lib.jl")
```

QUERYING THE FDC-320

LIST AVAILABLE PORTS

Make sure the Arduino is plugged into your pc via USB. You check this with the following command.

```
julia> list_ports()
COM3

Description: Arduino Uno (COM3)
Transport type: SP_TRANSPORT_USB
```

This command lists all the valid USB port names and their description. The example above is for a windows machine, on linux the name has a different format but is functionally equivalent.

OPEN THE PORT

In order to use a USB port for serial communication you must "open" it first. This takes ownership of the port and makes sure no other processes can use it.

```
julia> port = LibSerialPort.open("COM3", 9600)
```

Here the first argument is the name of the port as shown by <code>list_ports()</code> and the second argument is the baud-rate. It is critical that the baud-rate be set the same as the Arduino, I have set it to 9600. The baud-rate of the FDC-320 is an internal setting and must be changed with the <code>setCommunicationBaudrate</code> function, then you must change the Arduino code to match.

MAKE A REQUEST

Now you can use the public API (Julia) to make requests to the FDC-320. Here is an example:

```
julia> get_ReadFlowrateActualFlowrate(port)
0.0f0
```

You can reference the FDC-300 manual pages 16-17 for the names of the available functions, each function either reads or writes to a register. In that table each register is marked either "Read only" (R), "Write only" (W), or "Read and write" (RW).

Each register gets one or two functions in the file FDC3201ib.jl corresponding to if the register is R, W, or RW. If the register is marked R it gets a function of the same name prefixed with "get", if it is marked with W the function prefix is "set". If the register is RW then it gets both a "get" and a "set" function.

When calling a "set" function it is important to call it with the right type. This type is annotated in the table in the FDC-300 manual as U16, U32, or Float, these correspond to UInt16, UInt32, and Float32 in Julia.

On a success the "set" function will return a 0

Here are a few examples of dos and don'ts for a set function. (The function returning θ means success)

```
julia> set_SetFlowrateActualFlowrate(port, 0.0f0)

julia> set_SetFlowrateActualFlowrate(port, 0.0e0)
ERROR: AssertionError: typeof(val) === regtypes[adr]
Stacktrace:
```

```
. . .
julia> set_SetFlowrateActualFlowrate(port, 0x01)
ERROR: AssertionError: typeof(val) === regtypes[adr]
Stacktrace:
julia> set_SetFlowrateActualFlowrate(port, Float32(0x01))
julia> set_SetFlowratePercentageMethod(port, 0x0001)
julia> set_SetFlowratePercentageMethod(port, 1)
ERROR: AssertionError: typeof(val) === regtypes[adr]
Stacktrace:
julia> set_SetFlowratePercentageMethod(port, 1.0)
ERROR: AssertionError: typeof(val) === reqtypes[adr]
Stacktrace:
julia> set_SetFlowratePercentageMethod(port, UInt16(1.0))
```

As you can see, it is only valid to call the set function with that function's appropriate type as defined in the table.

LOGGING DATA

In Julia it is most convenient to log data with the CSV.jl and DataFrames.jl packages. If you do not already have these installed you can do so as follows.

Go into Package mode by entering the] character.

```
julia> ]
(fdc-320) pkg> add CSV, DataFrames
```

Then you include them in your namespace with a using statement.

```
julia> using CSV, DataFrames
```

The following is a simple example of logging and saving data

```
julia> using Dates
julia> times = []; datas = [];
julia> for _ in 1:100
           push!(datas, get_ReadFlowrateActualFlowrate(port))
           push!(times, now())
       end
julia> CSV.write("test.csv", DataFrame(timescolumn=times,
datascolumn=datas))
"test.csv"
julia> CSV.read("test.csv", DataFrame)
100×2 DataFrame
      timescolumn
                                datascolumn
 Row I
       DateTime
                                Float64
       2025-08-07T12:16:43.107
   1
                                         0.0
   2
       2025-08-07T12:16:43.328
                                         0.0
  :
                                         :
  99
       2025-08-07T12:17:05.101
                                         0.0
       2025-08-07T12:17:05.316
                                        0.0
 100
                             96 rows omitted
```

READING TEMPERATURE AND HUMIDITY

The file FDC3201ib.jl also contains a function to read the Temperature and Humidity detected by a DHT22. It is used as follows.

```
julia> T,H = TH = readTandH(port)
(temperature = 24.1f0, humidity = 48.100002f0)

julia> T
24.1f0

julia> H
48.100002f0

julia> (T,H) === (TH.temperature, TH.humidity)
true
```

The function returns a NamedTuple which can either indexed into like an array or via field like a struct.

ARDUINO CODE AND WIRING

The Arduino is running the file reader/reader.ino and can be uploaded directly to the Arduino via the ArduinoIDE.




Figure 1: A wiring diagram of the Arduino, FDC, Multiplexer, and DHT22

If you need to replace the multiplexer board it is called "Multi USB RS232 RS485 TTL Converter SKU TEL0070".