

Unit – 4

# Deadlock

# Deadlock

- Permanent blocking of a set of processes that either compete for system resources or communicate with each other
- No efficient solution
- Involve conflicting needs for resources by two or more processes

# Deadlock




Figure 6.1 Illustration of Deadlock

# Reusable Resources

- Used by only one process at a time and not exhausted by that use.
- Processes obtain resources that they later release for reuse by other processes.
- Processors, I/O channels, main and secondary memory, devices, and data structures such as files, databases, and semaphores
- Deadlock occurs if each process holds one resource and requests the other

# Reusable Resources

## Process P

Step	Action
p <sub>0</sub>	Request (D)
p <sub>1</sub>	Lock (D)
p <sub>2</sub>	Request (T)
p <sub>3</sub>	Lock (T)
p <sub>4</sub>	Perform function
p <sub>5</sub>	Unlock (D)
p <sub>6</sub>	Unlock (T)



## Process Q

Step	Action
q <sub>0</sub>	Request (T)
q <sub>1</sub>	Lock (T)
q <sub>2</sub>	Request (D)
q <sub>3</sub>	Lock (D)
q <sub>4</sub>	Perform function
q <sub>5</sub>	Unlock (T)
q <sub>6</sub>	Unlock (D)

**Figure 6.4 Example of Two Processes Competing for Reusable Resources**

# Reusable Resources

- Space is available for allocation of 200Kbytes, and the following sequence of events occur



- Deadlock occurs if both processes progress to their second request

# Consumable Resources

- Created (produced) and destroyed (consumed)
- Interrupts, signals, messages, and information in I/O buffers
- Deadlock may occur if a Receive message is blocking
- May take a rare combination of events to cause deadlock

# Resource Allocation Graphs

- Directed graph that depicts a state of the system of resources and processes



(a) Resource is requested




(b) Resource is held




# Conditions for Deadlock

- Mutual exclusion
  - Only one process may use a resource at a time
- Hold-and-wait
  - A process may hold allocated resources while awaiting assignment of others
- No preemption
  - No resource can be forcibly removed from a process holding it
- Circular wait
  - A closed chain of processes exists, such that each process holds at least one resource needed by the next process in the chain

# Resource Allocation Graphs




(c) Circular wait



(d) No deadlock

# Resource Allocation Graphs



**Figure 6.6** Resource Allocation Graph for Figure 6.1b

# Possibility of Deadlock

- Mutual Exclusion
- No preemption
- Hold and wait

# Existence of Deadlock

- Mutual Exclusion
- No preemption
- Hold and wait
- Circular wait

# Deadlock Prevention

Restrain the ways request can be made

- **Mutual Exclusion** – not required for sharable resources; must hold for non-sharable resources
- **Hold and Wait** – must guarantee that whenever a process requests a resource, it does not hold any other resources
  - Require process to request and be allocated all its resources before it begins execution, or allow process to request resources only when the process has none
  - Low resource utilization; starvation possible

# Deadlock Prevention (Cont.)

- **No Preemption** –
  - If a process that is holding some resources requests another resource that cannot be immediately allocated to it, then all resources currently being held are released
  - Preempted resources are added to the list of resources for which the process is waiting
  - Process will be restarted only when it can regain its old resources, as well as the new ones that it is requesting
- **Circular Wait** – impose a total ordering of all resource types, and require that each process requests resources in an increasing order of enumeration

# Deadlock Avoidance

- A decision is made dynamically whether the current resource allocation request will, if granted, potentially lead to a deadlock
- Requires knowledge of future process requests



# Two Approaches to Deadlock Avoidance

- Do not start a process if its demands might lead to deadlock
- Do not grant an incremental resource request to a process if this allocation might lead to deadlock

# Resource Allocation Denial (Banker's Algorithm)

- Referred to as the banker's algorithm
- State of the system is the current allocation of resources to process
- Safe state is where there is at least one sequence that does not result in deadlock
- Unsafe state is a state that is not safe

# Determination of a Safe State

	R1	R2	R3		R1	R2	R3		R1	R2	R3
P1	3	2	2	P1	1	0	0	P1	2	2	2
P2	6	1	3	P2	6	1	2	P2	0	0	1
P3	3	1	4	P3	2	1	1	P3	1	0	3
P4	4	2	2	P4	0	0	2	P4	4	2	0
Claim matrix C				Allocation matrix A				C - A			
	R1	R2	R3		R1	R2	R3				
Resource vector R				Available vector V							

(a) Initial state

# Determination of a Safe State

	R1	R2	R3
P1	3	2	2
P2	0	0	0
P3	3	1	4
P4	4	2	2

Claim matrix C

	R1	R2	R3
P1	1	0	0
P2	0	0	0
P3	2	1	1
P4	0	0	2

Allocation matrix A

	R1	R2	R3
P1	2	2	2
P2	0	0	0
P3	1	0	3
P4	4	2	0

C - A

R1	R2	R3
9	3	6

Resource vector R

R1	R2	R3
6	2	3

Available vector V

(b) P2 runs to completion

# Determination of a Safe State

	R1	R2	R3
P1	0	0	0
P2	0	0	0
P3	3	1	4
P4	4	2	2

Claim matrix **C**

	R1	R2	R3
P1	0	0	0
P2	0	0	0
P3	2	1	1
P4	0	0	2

Allocation matrix **A**

	R1	R2	R3
P1	0	0	0
P2	0	0	0
P3	1	0	3
P4	4	2	0

**C - A**

R1	R2	R3
9	3	6

Resource vector **R**

R1	R2	R3
7	2	3

Available vector **V**

(c) **P1 runs to completion**

# Determination of a Safe State

	R1	R2	R3
P1	0	0	0
P2	0	0	0
P3	0	0	0
P4	4	2	2

Claim matrix **C**

	R1	R2	R3
P1	0	0	0
P2	0	0	0
P3	0	0	0
P4	0	0	2

Allocation matrix **A**

	R1	R2	R3
P1	0	0	0
P2	0	0	0
P3	0	0	0
P4	4	2	0

**C - A**

R1	R2	R3
9	3	6

Resource vector **R**

R1	R2	R3
9	3	4

Available vector **V**

(d) **P3 runs to completion**

# Determination of an Unsafe State

	R1	R2	R3
P1	3	2	2
P2	6	1	3
P3	3	1	4
P4	4	2	2

Claim matrix **C**

	R1	R2	R3
P1	1	0	0
P2	5	1	1
P3	2	1	1
P4	0	0	2

Allocation matrix **A**

	R1	R2	R3
P1	2	2	2
P2	1	0	2
P3	1	0	3
P4	4	2	0

**C - A**

R1	R2	R3
9	3	6

Resource vector **R**

R1	R2	R3
1	1	2

Available vector **V**

(a) Initial state

	R1	R2	R3
P1	3	2	2
P2	6	1	3
P3	3	1	4
P4	4	2	2

Claim matrix **C**

	R1	R2	R3
P1	2	0	1
P2	5	1	1
P3	2	1	1
P4	0	0	2

Allocation matrix **A**

	R1	R2	R3
P1	1	2	1
P2	1	0	2
P3	1	0	3
P4	4	2	0

**C - A**

R1	R2	R3
9	3	6

Resource vector **R**

R1	R2	R3
0	1	1

Available vector **V**

(b) **P1** requests one unit each of **R1** and **R3**

# Deadlock Avoidance

- Maximum resource requirement must be stated in advance
- Processes under consideration must be independent; no synchronization requirements
- There must be a fixed number of resources to allocate
- No process may exit while holding resources




# Deadlock Detection

- Allow system to enter deadlock state
- Detection algorithm
- Recovery scheme


# Single Instance of Each Resource Type

- Maintain *wait-for* graph
  - Nodes are processes
  - $P_i \rightarrow P_j$  if  $P_i$  is waiting for  $P_j$
- Periodically invoke an algorithm that searches for a cycle in the graph. If there is a cycle, there exists a deadlock
- An algorithm to detect a cycle in a graph requires an order of  $n^2$  operations, where  $n$  is the number of vertices in the graph

# Resource-Allocation Graph and Wait-for Graph



Resource-Allocation Graph



Corresponding wait-for graph

# Several Instances of a Resource Type

- **Available:** A vector of length  $m$  indicates the number of available resources of each type.
- **Allocation:** An  $n \times m$  matrix defines the number of resources of each type currently allocated to each process.
- **Request:** An  $n \times m$  matrix indicates the current request of each process. If  $Request[i_j] = k$ , then process  $P_i$  is requesting  $k$  more instances of resource type  $R_j$ .

# Detection Algorithm

1. Let *Work* and *Finish* be vectors of length *m* and *n*, respectively Initialize:

(a) *Work* = *Available*

(b) For  $i = 1, 2, \dots, n$ , if  $Allocation_i \neq 0$ , then  
 $Finish[i] = \text{false}$ ; otherwise,  $Finish[i] = \text{true}$

2. Find an index *i* such that both:

(a)  $Finish[i] == \text{false}$

(b)  $Request_i \leq Work$

If no such *i* exists, go to step 4

# Detection Algorithm (Cont.)

3.  $Work = Work + Allocation_i$

$Finish[i] = true$

go to step 2

4. If  $Finish[i] == false$ , for some  $i$ ,  $1 \leq i \leq n$ , then the system is in deadlock state. Moreover, if  $Finish[i] == false$ , then  $P_i$  is deadlocked

# Example of Detection Algorithm

- Five processes  $P_0$  through  $P_4$ ; three resource types A (7 instances), B (2 instances), and C (6 instances)
- Snapshot at time  $T_0$ :

	<u>Allocation</u>	<u>Request</u>	<u>Available</u>
	A B C	A B C	A B C
$P_0$	0 1 0	0 0 0	0 0 0
$P_1$	2 0 0	2 0 2	
$P_2$	3 0 3	0 0 0	
$P_3$	2 1 1	1 0 0	
$P_4$	0 0 2	0 0 2	

- Sequence  $\langle P_0, P_2, P_3, P_1, P_4 \rangle$  will result in  $Finish[i] = \text{true}$  for all  $i$

# Example (Cont.)

- $P_2$  requests an additional instance of type C

*Request*

	<i>A</i>	<i>B</i>	<i>C</i>
$P_0$	0	0	0
$P_1$	2	0	1
$P_2$	0	0	1
$P_3$	1	0	0
$P_4$	0	0	2

- State of system?
  - Can reclaim resources held by process  $P_0$ , but insufficient resources to fulfill other processes; requests
  - Deadlock exists, consisting of processes  $P_1$ ,  $P_2$ ,  $P_3$ , and  $P_4$



# Detection-Algorithm Usage

- When, and how often, to invoke depends on:
  - How often a deadlock is likely to occur?
  - How many processes will need to be rolled back?
    - one for each disjoint cycle
- If detection algorithm is invoked arbitrarily, there may be many cycles in the resource graph and so we would not be able to tell which of the many deadlocked processes “caused” the deadlock

# Recovery from Deadlock: Process Termination

- Abort all deadlocked processes
- Abort one process at a time until the deadlock cycle is eliminated
- In which order should we choose to abort?
  - Priority of the process
  - How long process has computed, and how much longer to completion
  - Resources the process has used
  - Resources process needs to complete
  - How many processes will need to be terminated
  - Is process interactive or batch?

## Recovery from Deadlock: Resource Preemption

- Selecting a victim – minimize cost
- Rollback – return to some safe state, restart process for that state
- Starvation – same process may always be picked as victim, include number of rollback in cost factor

# Advantages and Disadvantages

**Table 6.1 Summary of Deadlock Detection, Prevention, and Avoidance Approaches for Operating Systems [ISLO80]**

Approach	Resource Allocation Policy	Different Schemes	Major Advantages	Major Disadvantages
Prevention	Conservative; undercommits resources	Requesting all resources at once	<ul style="list-style-type: none"> <li>• Works well for processes that perform a single burst of activity</li> <li>• No preemption necessary</li> </ul>	<ul style="list-style-type: none"> <li>• Inefficient</li> <li>• Delays process initiation</li> <li>• Future resource requirements must be known by processes</li> </ul>
		Preemption	<ul style="list-style-type: none"> <li>• Convenient when applied to resources whose state can be saved and restored easily</li> </ul>	<ul style="list-style-type: none"> <li>• Preempts more often than necessary</li> </ul>
		Resource ordering	<ul style="list-style-type: none"> <li>• Feasible to enforce via compile-time checks</li> <li>• Needs no run-time computation since problem is solved in system design</li> </ul>	<ul style="list-style-type: none"> <li>• Disallows incremental resource requests</li> </ul>
Avoidance	Midway between that of detection and prevention	Manipulate to find at least one safe path	<ul style="list-style-type: none"> <li>• No preemption necessary</li> </ul>	<ul style="list-style-type: none"> <li>• Future resource requirements must be known by OS</li> <li>• Processes can be blocked for long periods</li> </ul>
Detection	Very liberal; requested resources are granted where possible	Invoke periodically to test for deadlock	<ul style="list-style-type: none"> <li>• Never delays process initiation</li> <li>• Facilitates online handling</li> </ul>	<ul style="list-style-type: none"> <li>• Inherent preemption losses</li> </ul>